

FCC PART 15.225



TEST REPORT

For

Maison Joseph Battat Ltd.

8430 Darnley Road, Montreal, Quebec, H4T 1M4, Canada

FCC ID: PN6RF1356BX1120

Report Type: Original Report	Product Name: Symphony in B.
Test Engineer: Sula Huang	
Report Number: RSZ111102801-00	
Report Date: 2011-11-14	
Reviewed By: EMC Manager	Merry Zhao 
Test Laboratory: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk "★" (Rev.2)

TABLE OF CONTENTS

GENERAL INFORMATION.....3

 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 3

 OBJECTIVE 3

 RELATED SUBMITTAL(S)/GRANT(S)..... 3

 TEST METHODOLOGY 3

 TEST FACILITY 3

SYSTEM TEST CONFIGURATION.....5

 JUSTIFICATION 5

 EUT EXERCISE SOFTWARE 5

 EQUIPMENT MODIFICATIONS 5

 BLOCK DIAGRAM OF TEST SETUP 5

SUMMARY OF TEST RESULTS6

FCC §15.203 - ANTENNA REQUIREMENT.....7

 APPLICABLE STANDARD 7

 ANTENNA CONNECTED CONSTRUCTION 7

FCC §15.225, §15.205 & §15.209 - RADIATED EMISSIONS TEST8

 APPLICABLE STANDARD 8

 MEASUREMENT UNCERTAINTY 8

 EUT SETUP 8

 EMI TEST RECEIVER SETUP 9

 CORRECTED AMPLITUDE & MARGIN CALCULATION 9

 TEST EQUIPMENT LIST AND DETAILS 9

 TEST RESULTS SUMMARY 9

 TEST DATA 10

FCC §15.225(E) - FREQUENCY STABILITY.....17

 APPLICABLE STANDARD 17

 TEST PROCEDURE 17

 TEST EQUIPMENT LIST AND DETAILS 17

 TEST DATA 17

FCC §15.215(C) – 20 DB BANDWIDTH TESTING19

 APPLICABLE STANDARD 19

 TEST PROCEDURE 19

 TEST EQUIPMENT LIST AND DETAILS 19

 TEST DATA 19

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The *Maison Joseph Battat Ltd.*'s product, model number: *BX1120* (FCC ID: *PN6RF1356BX1120*) or the "EUT" in this report is an *SYMPHONY IN B.*, which was measured approximately 38cm (L) x 24 cm (W) x 13 cm (H), rated input voltage: DC 9 V (6 AA,1.5 V Batteries).

** All measurement and test data in this report was gathered from production sample serial number: 1111001 (Assigned by BACL, Shenzhen). The EUT was received on 2011-10-28.*

Objective

This report is prepared on behalf of *Maison Joseph Battat Ltd.*, in accordance with Part 2-Subpart J, and Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The objective is to determine the compliance of the EUT with FCC rules, section 15.203, 15.205, 15.207, 15.209 and 15.225.

Related Submittal(s)/Grant(s)

No Related Submittals.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Lab Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp.(Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

EUT Exercise Software


N/A

Equipment Modifications

Some modifications were done for the EUT by Maison Joseph Battat Ltd.

1. Adding a core on the signal cable J1, J2, J3, J4, J5, and J6 near the main board.
2. Connection in parallel a ceramic capacitor (100Nf) between B pole and E pole on Q1.
3. Connection in series an inductance (100 μ H) on the C pole of Q2

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207	AC Line Conducted Emission	Not Applicable
§15.225 §15.209 §15.205	Radiated Emission Test	Compliance
§15.225(e)	Frequency Stability	Compliance
§15.215(c)	20 dB Emission Bandwidth	Compliance

Note: The EUT was operated by battery only, so AC line conducted emission was not applicable for the EUT.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Antenna Connected Construction

The EUT has a printed antenna on PCB, which complies with the Part 15.203. Please see EUT photo for details.

FCC §15.225, §15.205 & §15.209 - RADIATED EMISSIONS TEST

Applicable Standard

As per FCC Part 15.225

(a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.

(b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

(c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

(d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in §15.209.


Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Lab Corp. (Shenzhen) is ± 4.0 dB ($k=2$, 95% level of confidence).

The fundamental data was recorded in average detection mode: set the VBW AVE on, and then record the data.

EUT Setup



The radiated emission tests were performed in the 3-meter chamber a test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC Part Subpart C limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

According to FCC Rules, 47 CFR 15.33, the EUT emissions were investigated up to 1000 MHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

<i>Frequency Range</i>	<i>RBW</i>	<i>Video B/W</i>
9 kHz – 150 kHz	300 Hz	1 kHz
150 kHz – 30 MHz	10 kHz	30 kHz
30 – 1000 MHz	100 kHz	300 kHz

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corr. Ampl.}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-11	2011-11-10
HP	Amplifier	8447E	1937A01046	2011-08-02	2012-08-01
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2011-07-05	2012-07-04
ETS	Passive Loop Antenna	6512	00029604	2011-04-27	2012-04-26

* **Statement of Traceability:** Bay Area Compliance Lab Corp. (Shenzhen) attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209/FCC Part 15.225 with the worst margin reading of:

2.6 dB at 122.055500 **MHz** in the **Vertical** Polarization

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.9 kPa


The testing was performed by Sula Huang on 2011-11-02.

Test mode: Transmitting


1) Spurious Emissions below 30 MHz:

Indicated		Table Angle Degree	Antenna Height (m)	Detector PK/QP/Ave.	Correction Factor			Corrected Amplitude (dBµV/m) @3m	FCC Part 15.225\15.209	
Frequency (MHz)	Maximum Reading (dBµV) @3m				Ant. Factor (dB)	Cable Loss (dB)	Pre-Amp. Gain (dB)		Limit (dBµV/m) @3m	Margin (dB)
14.992	23.34	0	1.1	PK	31.8	0.2	0.0	55.34	69.5	14.16
26.540	24.07	0	1.1	PK	30.6	0.2	0.0	54.87	69.5	14.63
0.150	-1.10	0	1.1	QP	63.5	0.1	0.0	62.50	84.08	21.58



Please refer to the following plots for pre-scan:




Date: 2.NOV.2011 23:54:32




Date: 2.NOV.2011 23:56:03



Date: 3.NOV.2011 00:10:51



Date: 2.NOV.2011 23:56:57





Date: 2.NOV.2011 23:59:11

2) Fundamental:

Indicated			Table Angle Degree	Antenna Height (m)	Detector PK/QP/Ave	Correction Factor			Corrected Amplitude (dBµV/m) @3m	FCC Part 15.225	
Frequency Range (MHz)	Mark point (MHz)	Maximum Reading (dBµV) @3m				Ant. Factor (dB)	Cable Loss (dB)	Pre-Amp. Gain (dB)		Limit (dBµV/m) @3m	Margin (dB)
13.110-13.410	13.349	3.6	180	1.2	QP	31.8	0.20	0.0	35.6	80.5	44.9
13.410-13.553	13.553	30.1	180	1.1	QP	31.8	0.20	0.0	62.1	90.5	28.4
13.553-13.567	13.560	42.8	180	1.2	QP	31.8	0.20	0.0	74.8	124	49.2
13.567-13.710	13.567	27.1	180	1.1	QP	31.8	0.20	0.0	59.1	90.5	31.4
13.710-14.010	13.774	5.5	180	1.2	QP	31.8	0.20	0.0	37.5	80.5	43.0



Please refer to the following plots for final measurement:



Date: 2.NOV.2011 23:33:00





Att 10 dB AUTO RBW 9 kHz
MT 100 ms
PREAMP OFF



Date: 2.NOV.2011 23:37:21




Att 10 dB AUTO RBW 9 kHz
MT 100 ms
PREAMP OFF



Date: 2.NOV.2011 23:40:33

3) Spurious Emissions for 30 ~1000 MHz:



Frequency (MHz)	Corrected Amplitude (dBµV/m)	Antenna Height (cm)	Antenna Polarity (H/V)	Turntable Position (deg)	Correction Factor (dB)	Limit (dBµV/m)	Margin (dB)
122.055500	40.9	102.0	V	252.0	-12.3	43.5	2.6*
122.060250	39.7	102.0	V	208.0	-12.3	43.5	3.8*
49.417250	31.9	261.0	V	328.0	-17.0	40.0	8.1
328.356250	37.4	102.0	H	191.0	-11.6	46.0	8.6
262.362000	37.2	139.0	H	3.0	-13.2	46.0	8.8
196.968250	34.0	155.0	H	201.0	-14.5	43.5	9.5

*Within measurement uncertainty!

FCC §15.225(e) - FREQUENCY STABILITY

Applicable Standard

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to PC, than to an external AC power supply and loop antenna was connected to a f Spectrum Analyzer. The EUT was placed inside the temperature chamber.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the Spectrum Analyzer.

Frequency Stability vs. Voltage: An external variable AC power supply Source. The voltage was set to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the end point. The output frequency was recorded for each voltage.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-11	2011-11-10
WUHUAN	Temperature & Humidity Chamber	HTP205	20021115	2011-06-04	2012-06-03

* **Statement of Traceability:** Bay Area Compliance Lab Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.9 kPa

The testing was performed by Sula Huang on 2011-11-02.

Test Result: Pass

Test Mode: Transmitting

Power Supply (V _{DC})	Temperature (°C)	Measured Frequency (MHz)	Frequency Error	FCC Part 15.225 Limit
9	-20	13.55982	-0.0013%	± 0.01%
	-10	13.55984	-0.0012%	± 0.01%
	0	13.55982	-0.0013%	± 0.01%
	10	13.55984	-0.0012%	± 0.01%
	20	13.55950	-0.0037%	± 0.01%
	30	13.55984	-0.0012%	± 0.01%
	40	13.55986	-0.0010%	± 0.01%
	50	13.55988	-0.0009%	± 0.01%
Max. =10.35	20	13.55986	-0.0010%	± 0.01%
Min. = 7.65	20	13.55982	-0.0013%	± 0.01%

FCC §15.215(c) – 20 dB BANDWIDTH TESTING

Applicable Standard

Per FCC §15.215 (c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-11	2011-11-10
ETS	Passive Loop Antenna	6512	00029604	2011-04-27	2012-04-26

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.9 kPa

The testing was performed by Sula Huang on 2011-11-02.

Test Mode: Transmitting

20 dB Emission Bandwidth



Date: 2.NOV.2011 23:48:50

***** END OF REPORT *****