

SAR DATA SUMMARY – AirPrime FCC ID: PNF-PC3220P

Maximum Power: 25.0 dBm (conducted)

MEASUREMENT RESULTS Body SAR								
Notebook Host	Max. SAR (W/kg)		Separation Distance (cm) ^{‡‡}					
	Cellular CDMA	PCS	Lap (Touch) Configuration	Bystander 90° Configuration				
Fujitsu	1.34	1.26	1.0	1.5				
Panasonic	0.55	1.09	1.8	1.5				
Winbook	0.393	1.17	2.5	1.5				

NOTES:

1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration.

⊠ Conducted

⊠ DASY3

□ Head

□ Left Head

Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].

2. All modes of operation were investigated, and worst-case results are reported.

3.	Battery is fully charged for	all readings.	Standard Batteries are the only options.
----	------------------------------	---------------	--

- Power Measured
- 4. SAR Measurement System Phantom Configuration
- 5. SAR Configuration
- 6. Test Signal Call Mode
- 7. ^{‡‡}Test Configuration

□ With Holster

- Tissue parameters and temperatures are listed on the SAR plots. 8
- 9. Liquid tissue depth is 15.1 cm. \pm 0.1

PCTEST™ SAR REPORT	FCC CERTIFICATION	AIRPRIME	Reviewed by: Quality Manager
SAR Filename: SAR-221125617.PNF	 EUT TYPE: Dual-Band CDMA PCMCIA Modem Card	FCC ID: PNF-PC3220P	Page 1 of 1

□ EIRP

□ Right Head

- I Flat Phantom
- Body X

□ ERP

□ IDX

- **Base Station**
- ☑ Without Holster
- ⊠ Manu. Test Codes □