



ETS Dr.GenZ Taiwan PS Co., Ltd.

FCC Registration No.: 930600

Industry Canada filed test laboratory Reg. No. IC 5679

Accredited Testing Laboratory



A2LA Cert.No.: 2300.01

PTCRB Accredited Type Certification Test House

FCC

TEST - REPORT

FCC RULES PART 15 / SUBPART C

FCC ID: PNKDO-S105

Test report no.: W6M20511-6346-C-1





TABLE OF CONTENTS

1	GENERAL INFORMATION	3
1.1	NOTES	3
1.2	TESTING LABORATORY	3
1.2.1	Location	3
1.2.2	Details of accreditation status	3
1.3	DETAILS OF APPROVAL HOLDER	3
1.4	APPLICATION DETAILS	3
1.5	GENERAL INFORMATION OF TEST ITEM	3
1.6	TEST STANDARDS	3
2	TECHNICAL TEST	3
2.1	SUMMARY OF TEST RESULTS	3
2.2	TEST ENVIRONMENT	3
2.3	TEST EQUIPMENT LIST	3
3	TEST RESULTS (ENCLOSURE).....	3
3.1	PEAK OUTPUT POWER (TRANSMITTER)	3
3.2	EQUIVALENT ISOTROPIC RADIATED POWER	3
3.2.1	Transmitter	3
3.3	RF EXPOSURE COMPLIANCE REQUIREMENTS	3
3.4	TRANSMITTER RADIATED EMISSIONS IN RESTRICTED BANDS.....	3
3.5	SPURIOUS EMISSIONS (TX)	3
3.6	MINIMUM 6 DB BANDWIDTH	3
3.7	PEAK POWER SPECTRAL DENSITY.....	3
3.8	RADIATED EMISSIONS FROM RECEIVER SECTION	3
3.9	POWER LINE CONDUCTED EMISSION	3
	APPENDIX	3
	APPENDIX A.....	3
	APPENDIX B.....	3
	APPENDIX C.....	3
	APPENDIX D.....	3
	APPENDIX E.....	3
	APPENDIX F.....	3
	APPENDIX G.....	3
	APPENDIX H.....	3



Registration number: W6M20511-6346-C-1
FCC ID: PNKDO-S105

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has Passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems.

The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that is performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.

The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the ETS DR. GENZ TAIWAN PS CO., LTD.

Tester:

14.12.2005

Jay Chaing

Date

ETS-Lab.

Name

Signature

Technical responsibility for area of testing:

14.12.2005


Steven Chung

Date

ETS

Name

Signature



Registration number: W6M20511-6346-C-1
FCC ID: PNKDO-S105

1.2 Testing laboratory

1.2.1 Location

OATS
No.5-1, Shuang Sing Village,
LiShuei Rd., Wanli Township,
Taipei County 207, Taiwan (R.O.C.)

Company
ETS Dr.GenZ Taiwan PS Co., Ltd.
6F, NO. 58, LANE 188, RUEY-KUANG RD.
NEIHU, TAIPEI 114, TAIWAN R.O.C.
Tel : 886-2-66068877
Fax : 886-2-66068879

1.2.2 Details of accreditation status

Accredited testing laboratory

A2LA-registration number: 2300.01

FCC filed test laboratory Reg. No. 930600


Industry Canada filed test laboratory Reg. No. IC 5679

PTCRB Accredited Type Certification Test House

1.3 Details of approval holder

Name : ELANsat Technologies Inc.
Street : 5F, No.12, Innovation Rd.1, Hsinchu Science Park
Town : Hsinchu 300.
Country : Taiwan R.O.C.
Telephone : +886-3-563-5105
Fax : +886-3-563-5107

Contac : Ms. Erin Chu
Telephone : +886-3-563-5105



Registration number: W6M20511-6346-C-1
FCC ID: PNKDO-S105

1.4 Application details

Date of receipt of application : 22.11.2005
Date of receipt of test item : 22.11.2005
Date of test : from 23.11.2005 to 15.12.2005


1.5 General information of Test item

Type of test item : 2.4GHz Wireless Digital Audio
Model Number : DIO-T105
Hardware : 1.0
Software : 1.0
Serial number : without
Photos : see Annex

Technical data

Frequency band : 2.4 GHz – 2.4835 GHz
Frequency (ch A) : 2.410 GHz
Frequency (ch B) : 2.446 GHz
Frequency (ch C) : 2.473 GHz
Number of Channels : 8
Operation modes : duplex
Modulation Type : FSK

Fixed point-to-point operation : Yes / No
Type of Antenna : Inverted-F Antenna
Antenna gain of Antenna : 1.0 dBi
Antenna Power supply : Input power : 120 VAC
Output power : 9 VDC



Registration number: W6M20511-6346-C-1
 FCC ID: PNKDO-S105

Host device: none

Classification :

Fixed Device	<input checked="" type="checkbox"/>
Mobile Device (Human Body distance > 20cm)	<input type="checkbox"/>
Portable Device (Human Body distance < 20cm)	<input type="checkbox"/>

Transmitter

Unom

Power (ch A) : Conducted: 11.21 dBm
Power (ch B) : Conducted: 11.01 dBm
Power (ch C) : Conducted: 10.77 dBm


Manufacturer:
 (if applicable)

Name : ./.
 Street : ./.
 Town : ./.
 Country : ./.

Additional information: --

1.6 Test standards

Technical standard : FCC RULES PART 15 / SUBPART B / SUBPART C § 15.247



Registration number: W6M20511-6346-C-1
FCC ID: PNKDO-S105

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.



or

The deviations as specified in 2.5 were ascertained in the course of the tests performed.



2.2 Test environment

Temperature	: 23 °C
Relative humidity content	: 20 ... 75 %
Air pressure	: 86 ... 103 kPa
Details of power supply TX	: Input power : 120 VAC Output power : 9 VDC
Extreme conditions parameters	: --

Registration number: W6M20511-6346-C-1
FCC ID: PNKDO-S105

2.3 Test Equipment List

No.	Test equipment	Type	Serial No.	Manufacturer	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	11/8/2005
ETSTW-CE 002	PREREULATOR MODE DC POWER SUPPLY	S/N	S/N		
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW	
ETSTW-CE 004	ZWEILEITER-V-NETZNACHBILDUNG TWO-LINE V-NETWORK	ESH3-Z5	840731/011	R&S	11/8/2006
ETSTW-CE 005	Line-Impedance Stabilisation Network	NNBM 8126D	137	Schwarzbeck	11/3/2006
ETSTW-CE 006	IMPULS-BEGRENZER PULSE LIMITER	ESH3-Z2	100226	R&S	11/10/2006
ETSTW-CE 007	SPECTRUM ANALYZER 5GHz	FSB	849670/001	R&S	
ETSTW-CE 008	ABSORBING CLAMP	MDS 21	3469	ABSORPTIONS-MESSWANDLER-ZANGE	11/4/2006
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	5/10/2005
ETSTW-CE 010	Comb Generator-conducted	S/N	S/N	ETS	
ETSTW-CE 011	Power Line Conducted Emission Only	S/N	S/N	ETS	
ETSTW-CE 012	Dual-Phase-V-Network	NNB-2/16Z	03/10201	Telemeter	4/11/2006
ETSTW-CS 001	SIGNAL GENERATOR	SMX	849254/003	R&S	10/31/2005
ETSTW-CS 002	COUPLING AND DECOUPLING NETWORK	CDN S751	19263	SCHAFFNER	11/3/2005
ETSTW-CS 003	COUPLING AND DECOUPLING NETWORK	CDN T400	19820	SCHAFFNER	11/3/2005
ETSTW-CS 004	COUPLING AND DECOUPLING NETWORK	CDN M016	20053	SCHAFFNER	11/3/2005
ETSTW-CS 005	RF Power Amplifier	100A250A	306547	AR	11/3/2005
ETSTW-CS 006	Terminal 50Ω Load	50T-116 M	S/N	JFW	
ETSTW-CS 007	Terminal 50Ω Load	50T-116 F	S/N	JFW	
ETSTW-CS 008	6 dB Attenuator	HFP-5100-3/06 N M/F	2010876106		
ETSTW-RE 001	Controller	CD 1000	C01000/154/867/004/L	Heinrich Deisel	
ETSTW-RE 002	Function Generator	33220A	MY43004982	Agilent	11/3/2005
ETSTW-RE 003	EMI TEST RECEIVER	ESI	831438/001	R&S	11/16/2005
ETSTW-RE 004	EMI TEST RECEIVER	ESI	831459/012	R&S	11/9/2005
ETSTW-RE 005	EMI TEST RECEIVER	ESVS10	843207/020	R&S	11/1/2005
ETSTW-RE 008	Controller	HD100	C0100-L/047/6670703/L	Heinrich Deisel	
ETSTW-RE 009	Controller	HD100	100/341	Heinrich Deisel	
ETSTW-RE 010	PROGRAMMABLE LINEAR POWER SUPPLY	LPS-305	30503070181	MOTECH	
ETSTW-RE 011	PROGRAMMABLE LINEAR POWER SUPPLY	LPS-305	30503070165	MOTECH	
ETSTW-RE 012	TUNABLE BANDREJECT FILTER	D.C 0309	146	K&L	
ETSTW-RE 013	TUNABLE BANDREJECT FILTER	D.C 0036	397	K&L	
ETSTW-RE 014	DUAL TRACKING WITH 5V FIXED	GPC-3030D	S/N	GW	
ETSTW-RE 015	ANTENNA	HK116	841489/003	R&S	
ETSTW-RE 016	ANTENNA	HL223	848953/006	R&S	
ETSTW-RE 017	ANTENNA	HL025	352886/001	R&S	

Registration number: W6M20511-6346-C-1
FCC ID: PNKDO-S105

ETSTW-RE 018	ANTENNA	AT4560	27212	AR	11/7/2006
ETSTW-RE 019	ANTENNA , HORN	22240-25	121074	FM	
ETSTW-RE 020	MICROWAVE HORN ANTENNA	AT4002A	306915	AR	
ETSTW-RE 021	SWEEP GENERATOR	SWM05	835130/010	R&S	11/10/2005
ETSTW-RE 022	AMPLIFIER	8447D	2944A09837	Agilent	11/1/2005
ETSTW-RE 023	Shielded room	SR 1	S/N	Frankonia	
ETSTW-RE 024	Anechoic Chamber	CHC 1	S/N	Frankonia	
ETSTW-RE 025	Anechoic Chamber	CHC 2	S/N	Frankonia	
ETSTW-RE 026	Open Area Test Site	10m	S/N	ETS	
ETSTW-RE 027	Passive Loop Antenna	6512	34563	EMCO	6/29/2006
ETSTW-RE 028	Log-Periodic DipoleArray Antenna	3148	34429	EMCO	6/14/2006
ETSTW-RE 029	Biconical Antenna	3109	33524	EMCO	6/16/2006
ETSTW-RE 030	Double-Ridged Waveguide Horn Antenna	3117	35224	EMCO	5/4/2006
ETSTW-RE 031	Comb Generator-radiated	S/N	S/N	ETS	
ETSTW-RE 032	Millivoltmeter	URV 55	849086/013	R&S	11/17/2005
ETSTW-RE 033	4CH 1GHz 5GS/s DSO	WAVERUNNER 6100A	LCRY0604P14508	LeCory	
ETSTW-RE 034	Power Sensor	URV5-Z4	839313/006	R&S	11/17/2005
ETSTW-RE 035	1.5GHz Active Voltage Probe	HFP1500	2332	LeCory	
ETSTW-RE 036	100MHz High Voltage Diff Probe	ADP305	3305	LeCory	
ETSTW-RE 037	Log-Periodic DipoleArray Antenna	3148	00034546	EMCO	11/17/2006
ETSTW-RE 038	Log-Periodic DipoleArray Antenna	3148	00034547	EMCO	11/17/2006
ETSTW-RE 039	Biconical Antenna	3110B	41760	EMCO	11/17/2006
ETSTW-RE 040	Biconical Antenna	3110B	41761	EMCO	11/17/2006
ETSTW-RE 041	Anechoic Chamber	CHC 3	S/N	Frankonia	
ETSTW-RE 042	ANTENNA	HK116	100172	R&S	1/13/2007
ETSTW-RE 043	ANTENNA	HL223	100166	R&S	4/15/2006
ETSTW-RE 044	ANTENNA	HL050	100094	R&S	
ETSTW-RE 048	Triple Loop Antenna	HXYZ 9170	HXYZ 9170-134	Schwarzbeck	3/21/2007
ETSTW-RE 049	TRILOG Super Broadband test Antenna	VULB 9160	9160-3185	Schwarzbeck	5/18/2007
ETSTW-RE 050	Attenuator 10dB	50HF-010	S/N	JFW	
ETSTW-RE 051	Attenuator 6dB	50HF-006	S/N	JFW	
ETSTW-RE 052	Attenuator 3dB	50HF-003	S/N	JFW	
ETSTW-RE 053	Attenuator 3dB	50HF-003	S/N	JFW	
ETSTW-RE 054	Attenuator 3dB	50HF-003	S/N	JFW	
ETSTW-RE 055	SPECTRUM ANALYZER	FSU-26	200074	R&S	9/5/2006
ETSTW-EMI 001	HARMONICS 1000	HAR1000-1P	93	EMC-PARTNER	11/17/2005
ETSTW-EMS 001	Clamp BASELSTRASSE 160 CH-4242 LAUFEN	CN-EFT1000	354	EMC-PARTNER	11/1/2005
ETSTW-EMS 002	Frequency Converter	YF-6020	0308014		
ETSTW-EMS 003	EMC Immunity Test System	TRA2000IN6	579	EMC-PARTNER	11/1/2005
ETSTW-EMS 004	ESD generator minizap	ESD2000	016	EMC-PARTNER	11/1/2005



Registration number: W6M20511-6346-C-1
 FCC ID: PNKDO-S105

ETSTW-EMS 005	Attenuator (50Ω)	VERI50	051	EMC-PARTNER	8/30/2006
ETSTW-EMS 006	Attenuator (1 KΩ)	VERI1K	019	EMC-PARTNER	10/20/2006
ETSTW-EMS 007	20GΩ Divider	ESD-VERI-V	021	EMC-PARTNER	3/16/2006
ETSTW-EMS 008	Safety Test Solutions	ELT-400	E-0039	Narda	1/3/2006
ETSTW-EMS 009	Magnetic Field Antenna	MF1000-1	104	EMC-PARTNER	12/2/2006
ETSTW-EMS 010	Coupling De-coupling Network	CDN-UTP8	014	EMC-PARTNER	8/31/2006
ETSTW-EMS 011	Calibration Fixture	F-2031-CF-23MM	451	FCC	8/11/2006
ETSTW-EMS 012	EM Injection Clamp	F-2031-23MM	476	FCC	8/11/2006
ETSTW-RS 001	14" COLOR VIDEO MONITOR	TP-1480HR	P009799	TOPICA	
ETSTW-RS 002	14" COLOR VIDEO MONITOR	TP-1480HR	P009814	TOPICA	
ETSTW-RS 003	RF Power Amplifier	30S1G3	306933	AR	
ETSTW-RS 004	RF Power Amplifier	150W1000	307009	AR	11/18/2005
ETSTW-RS 005	Electric Field Probe Type 8.3	EMR-20	BN 2244/20	GW	9/3/2005
ETSTW-RS 006	SIGNAL GENERATOR	SML03	101551	R&S	11/15/2005
ETSTW-RS 007	AUDIO ANALYZER	UPA3	843458/029	R&S	11/15/2005
ETSTW-GSM 01	SIM Simulator	IT3	B2004-50106	ORGA	9/14/2006
ETSTW-GSM 02	Universal Radio Communication Tester	CMU 200	103489	R&S	
ETSTW-GSM 03	Agilent 8960 Test Set 1	E5515C	GB44052675	Agilent	7/13/2006
ETSTW-GSM 04	Agilent 8960 Test Set 2	E5515C	GB44052665	Agilent	7/13/2006
ETSTW-GSM 05	Agilent 8960 Test Set 3	E5515C	GB44052652	Agilent	7/16/2006
ETSTW-GSM 06	Agilent 8960 Test Set 4	E5515C	GB44052684	Agilent	7/15/2006
ETSTW-GSM 07	Agilent 8960 Test Set 5	E5515C	GB44052658	Agilent	7/13/2006
ETSTW-GSM 08	Agilent 8960 Test Set 6	E5515C	GB44052666	Agilent	7/15/2006
ETSTW-GSM 09	Controler PC	Dell GX 270	700F61J	Dell	
ETSTW-GSM 10	Combiner Wessex / Anite	B4605/100	053	Wessex / Anite	7/13/2006
ETSTW-GSM 11	GSM 850,900,1800,1900 Test system	TS8950G		R&S	10/31/2006
ETSTW-GSM 12	Acoustical Calibrator	4231	2463874	Brüel&Kjær	11/17/2005
ETSTW-GSM 13	Conditioning Amplifier	2690--0S2	2437856	Brüel&Kjær	
ETSTW-GSM 14	Telephone Test Head	4602B	2465324	Brüel&Kjær	
ETSTW-GSM 15	Mouth Simulator	4227	2462516	Brüel&Kjær	
ETSTW-GSM 16	TEMP.&HUMIDITY CHAMBER	GTH-120-40-1P-U	MAA0501002	GIANT FORCE	12/29/2005
ETSTW-GSM 17	ANTENNT COPLER	CMU-Z10	100988	R&S	
ETSTW-GSM 18	AUDIO ANALYZER	UPL16	100173	R&S	9/23/2006
ETSTW-GSM 19	Band Reject Filter	WRCTF824/ 849-822/851-40 /12+9SS	3	WI	
ETSTW-GSM 20	Band Reject Filter	WRCD1747/1748- 1743/1752-32/5SS	1	WI	
ETSTW-GSM 21	Band Reject Filter	WRCD1879.5/ 1880.5-1875.5/ 1884.5-32/5SS	3	WI	
ETSTW-GSM 22	Band Reject Filter	WRCT901.9/903. 1 -904.25-50/8SS	1	WI	
ETSTW-GSM 23	SPLITTER	4901.19.A	S/N	SUHNER	

Registration number: W6M20511-6346-C-1
FCC ID: PNKDO-S105

2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-2003 using a 50 μ H LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was according to ANSI STANDARD C63.4-2003 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The ambient temperature of the UUT was 23°C with a humidity of 40 %.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:


Freq (MHz)	METER READING + ACF + CABLE LOSS (to the receiver) = FS
33	20 dB μ V + 10.36 dB + 6 dB = 36.36 dB μ V/m @3m

The UUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table) and arranged according to ANSI C63.4-2003 Section 13.1.2. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

Measurements were made by ETS Dr.Genx Taiwan PS Co., Ltd. at the registered open field test site located at No.5-1, Shuang Sing Village, LiShuei Rd., Wanli Township, Taipei County 207, Taiwan (R.O.C.) The Registration Number: 930600.



Registration number: W6M20511-6346-C-1
FCC ID: PNKDO-S105

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

When the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The formula is as follows:

Average = Peak + Duty Factor


Duty Factor = $20 \log (\text{dwell time}/T)$

$T = 100\text{ms}$ when the pulse train period is over 100 ms or the period of the pulse train.

Modified Limits for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

ANTENNA & GROUND:

This unit use Inverted-F antenna. (see photos)




Registration number: W6M20511-6346-C-1
 FCC ID: PNKDO-S105

3 Test results (enclosure)

TEST CASE	Para. Number	Required	Test passed	Test failed
Peak Output Power	15.247(b)(3)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Equivalent radiated Power	15.247(b)(3)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Spurious Emissions radiated – Transmitter operating	15.247(c)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Band Edge Measurement	15.247(c)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Minimum 6 dB Bandwidth	15.247(a)(2)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Peak Power Spectral Density	15.247(d)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Radiated Emission from Digital Part And Receiver L.O.	15.109	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Power Line Conducted Emission	15.207	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

The follows is intended to leave blank.



Registration number: W6M20511-6346-C-1
 FCC ID: PNKDO-S105

3.1 Peak Output Power (transmitter)

FCC Rule: 15.247(b)(3)

This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.

The power was measured with modulation (declared by the applicant).

Test condition		Conducted Power		
		Channel A	Channel B	Channel C
		[dBm]	[dBm]	[dBm]
$T_{nom} = 23^{\circ}C$	$V_{nom} = 120\ V$	11.21	11.01	10.77
Measurement uncertainty		< 3 dB		


Test condition $T_{nom} = 23^{\circ}C, V_{nom} = 120\ V$	Signal Field strength TX highest power mode dB μ V/m
Frequency [MHz]	
2473	95.14
Measurement uncertainty	< 3 dB

Limits:

Frequency MHz	Power dBm
902 - 928	30
2400 – 2483.5	30
5725 – 5850	30

In case of employing transmitter antennas having antenna gain > 6 dBi and using fixed point-to-point operation consider §15.247 (b)(4)

Test equipment used: ETSTW-RE 003 , ETSTW-RE 012 , ETSTW-RE 017 , ETSTW-RE 024



Registration number: W6M20511-6346-C-1
 FCC ID: PNKDO-S105

3.2 Equivalent isotropic radiated power

FCC Rule: 15.247(b)(3)

EIRP = max. conducted output power + antenna gain
 EIRP = 11.21dBm + 1.0dBi
 = 12.21dBm

Limit: EIRP = +36 dBm for Antenna gain <6dBi

3.2.1 Transmitter

Integral Antenna:

At the transmitter the measurement was transacted with the modulation declared by the manufacturer and the maximum available output power of the EUT.

In this arrangement the EUT fulfils the requirements of the FCC rules § 15.247, subpart C, section b.

3.3 RF Exposure Compliance Requirements

The test sample is a WLAN access point intended for fixed installation.

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

$$S = \frac{PG}{4 \pi R^2}$$

S – Power Density

P – Output power ERP

R – Distance


D – Cable Loss

AG – Antenna Gain G = AG-D

Item	Unit	Value	Remarks
P	mW	13.213	Peak value
D	dB		
AG	dBi	1.3	
G		1.0	Calculated Value
R	cm	20	Assumed value
S	mW/cm ²	0.00342	Calculated value

Limits:

Limit for General Population / Uncontrolled Exposure	
Frequency (MHz)	Power Density (mW/cm ²)
1500 – 100.000	1,0



Registration number: W6M20511-6346-C-1
 FCC ID: PNKDO-S105

3.4 Transmitter Radiated Emissions in Restricted Bands

FCC Rules: 15.247 (c), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 1000 MHz.

For radiated emission tests, the analyzer setting was as followings:

Frequency \leq 1 GHz, RBW:100 kHz, VBW: 100 kHz (Peak measurements)

Frequency $>$ 1 GHz, RBW: 1 MHz, VBW: 1 MHz (Peak measurements)

Frequency $>$ 1 GHz , RBW:1 MHz , VBW: 100Hz (Average measurements)

Limits.

For frequencies below 1GHz:

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above	500	54.0

For frequencies above 1GHz (Average measurements).

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.


Duty cycle correction = $20 \log (\text{dwell time} / 100\text{ms})$

No duty cycle correction was added to the reading.

$54.0\text{dB } \mu \text{V/m} + 20 \text{ dB} = 74 \text{ dB } \mu \text{V/m}$

Remarks: see attached diagrams

Test equipment used: ETS 0125, ETS 0271



Registration number: W6M20511-6346-C-1
 FCC ID: PNKDO-S105

3.5 Spurious Emissions (tx)

Spurious emission was measured with modulation (declared by manufacturer).

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))

FCC Rule: 15.247(c), 15.35

For out of band emissions that are close to or that exceed the 20 dB attenuation requirement described in the specification, radiated measurements were performed at a 3 m separation distance to determine whether these emissions complied with the general radiated emission requirement.

Limits:

For frequencies below 1GHz:

Max. reading – 20 dB

95.14dB μ V/m- 20 dB= 75.14dB μ V/m

Guidance on Measurement of DSSS Systems:

“If the emission is pulsed, modify the unit for continuous operation, use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.”

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty Cycle correction = 20 log (dwell time/100ms)

For frequencies above 1GHz (Peak measurements).

Limit = max. aver. Reading-20dB+20dB(because Peak detector is used)

75.14dB μ V/m

For frequencies above 1GHz (Average measurements).

Max. reading – 20dB

No duty cycle correction was added to the reading

95.14dB μ V/m- 20 dB= 75.14dB μ V/m

Remarks: see attached diagrams

Test equipment used: ETSTW-RE 003 , ETSTW-RE 012 , ETSTW-RE 015 , ETSTW-RE 016 , ETSTW-RE 017 , ETSTW-RE 024

Registration number: W6M20511-6346-C-1

FCC ID: PNKDO-S105

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance with point 2.3.

Calculation of test results:

Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.


The peak and average spurious emission plots was measured with the average limits.

In the Table being listed the critical peak and average value and exhibit the compliance with the above calculated Limits.

If in the column's correction factor states a value then the max. Field strength in the same row is corrected by a value gained from the "Duty-Cycle Correction Factor".

Summary table with radiated data of the test plots

Freq	Frequency Marker [MHz]	Polarization	Corrected Reading [dBuV/m]	Compliance Limit [dBuV/m]	Detector	BW [MHz]	Margin
1	135.611222	V	36.53	43.5	PK	0.1	6.97
1	169.338677	V	29.15	43.5	PK	0.1	14.35
2	225.651303	V	28.11	75.14	PK	0.1	47.03
2	270.541082	V	26.93	46	PK	0.1	19.07
3	2395.190381	V	48.08	75.14	PK	1	27.06
4	4817.635271	V	51.88	54	PK	1	2.12
4	7230.460922	V	53.55	75.14	PK	1	21.59
5	9643.286573	V	51.38	75.14	PK	1	23.76
1	135.611222	H	31.37	43.5	PK	0.1	12.13
1	169.338677	H	27.31	43.5	PK	0.1	16.19
2	225.651303	H	27.25	75.14	PK	0.1	47.89
2	270.541082	H	27.68	46	PK	0.1	18.32
3	2394.388778	H	46.48	75.14	PK	1	28.66
4	4817.635271	H	50.25	54	PK	1	3.75
5	9635.270541	H	48.12	75.14	PK	1	27.02
1	135.611222	V	36.22	43.5	PK	0.1	7.28
1	169.339	V	30.33	43.5	PK	0.1	13.17
2	225.651	V	27.43	75.14	PK	0.1	47.71
2	270.541	V	27.14	46	PK	0.1	18.86
4	4889.780	V	53.60	54	PK	1	0.4
5	9787.575	V	49.68	75.14	PK	1	25.46
1	135.611	H	31.82	43.5	PK	0.1	11.68
1	169.339	H	29.11	43.5	PK	0.1	14.39



Registration number: W6M20511-6346-C-1
 FCC ID: PNKDO-S105

2	225.651	H	26.71	75.14	PK	0.1	48.43
2	270.541	H	28.74	46	PK	0.1	17.26
4	4889.775	H	52.93	54	PK	1	1.07
5	9779.559	H	48.75	75.14	PK	1	26.39
1	135.611	V	36.43	43.5	PK	0.1	7.07
1	169.339	V	29.33	43.5	PK	0.1	14.17
2	225.651	V	28.38	75.14	PK	0.1	46.76
2	270.541	V	27.82	46	PK	0.1	18.18
3	2487.640	V	51.28	54	PK	1	2.72
4	4945.892	V	52.83	54	PK	1	1.17
4	6781.563	V	52.05	75.14	PK	1	23.09
1	135.611	H	31.54	43.5	PK	0.1	11.96
1	169.339	H	28.29	43.5	PK	0.1	15.21
2	225.651	H	27.94	75.14	PK	0.1	47.2
2	270.541	H	29.47	46	PK	0.1	16.53
2	284.970	H	23.91	46	PK	0.1	22.09
3	2487.640	H	48.96	54	PK	1	5.04
4	4945.892	H	51.58	54	PK	1	2.42

Freq. – Frequency Range:


- 1: 30 - 200 MHz
- 2: 200 - 1000 MHz
- 3: 1 - 4 GHz
- 4: 4 - 8 GHz
- 5: 8 - 12 GHz
- 6: 12 - 17 GHz
- 7: 17 - 26.5 GHz

All not in the table noted test results are more than 20 dB below the relevant limits.
 All other not noted test polts do not contain significant test results in relation to the limits.

TEST RESULT (Transmitter): The unit DOES meet the FCC requirements.

Comment: see attached diagrams

Test equipment used: ETSTW-RE 003, ETSTW-RE 015, ETSTW-RE 016, ETSTW-RE 017, ETSTW-RE 024



Registration number: W6M20511-6346-C-1
 FCC ID: PNKDO-S105

3.6 Minimum 6 dB Bandwidth

The analyzer ResBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK reading was taken, two markers were set 6 dB below the maximum level on the right and the left side of the emission. The 6 dB bandwidth is the frequency difference between the two markers.


Test conditions		6 dB Bandwidth		
		Channel A	Channel B	Channel C
$T_{nom} = 23^{\circ}C$	$V_{nom} = 120 V$	1.474358974 MHz	1.442307692 MHz	1.538461538 MHz
Measurement uncertainty		< 10 Hz		

Limits:

Frequency Range MHz	Limits
902-928	min 500 kHz
2400-2483.5	min 500 kHz
5725-5850	min 500 kHz

Test equipment used: ETSTW-CE 003 , ETSTW-RE 003

Comment: see attached diagram



Registration number: W6M20511-6346-C-1
 FCC ID: PNKDO-S105

3.7 Peak Power Spectral Density

Peak Power Spectral density is a measured at low, middle and high channel.
 The peak output power is measured with a measurement bandwidth of 10 MHz and displayed on diagram together with Peak Power Spectral Density result which was measured with a bandwidth of 3 kHz, appreciate frequency span and sweep time.

Test conditions		Peak Power Spectral Density (3 kHz)		
		Channel A [dBm]	Channel B [dBm]	Channel C [dBm]
$T_{nom} = 23^{\circ}C$	$V_{nom} = 120 V$	1.04	0.75	-0.86
Measurement uncertainty		< 3 Hz		

Limits:

Frequency Range MHz	dBm
902-928	8
2400-2483,5	8
5725-5850	8

Test equipment used: ETSTW-CE 003 , ETSTW-RE 003

Comment: see attached diagram



Registration number: W6M20511-6346-C-1
 FCC ID: PNKDO-S105

3.8 Radiated Emissions from Receiver Section

FCC Rule: 15.109

Summary table with radiated data of the test plots


(Digital - Audio Mode)

Polarization	Frequency Marker (MHz)	C.R. (dBuv)	C.F. (dB)	Detector AV/QP	T.R. (dBuV/m)	C.L. (dBuV/m)	Margin (dB)	Azimuth (degree)	A.H. (cm)
1-V	135.4637024	30.75	3.42	PK	34.17	43.5	9.33	83	156
	169.33066132	25.79	3.44	PK	29.23	43.5	14.27	82	192

Polarization	Frequency Marker (MHz)	C.R. (dBuv)	C.F. (dB)	Detector AV/QP	T.R. (dBuV/m)	C.L. (dBuV/m)	Margin (dB)	Azimuth (degree)	A.H. (cm)
1-H	135.451528	28.91	3.52	PK	32.43	43.5	11.07	134	126

Polarization	Frequency Marker (MHz)	C.R. (dBuv)	C.F. (dB)	Detector AV/QP	T.R. (dBuV/m)	C.L. (dBuV/m)	Margin (dB)	Azimuth (degree)	A.H. (cm)
2-V	225.651303	20.55	3.33	PK	23.88	46	22.12	173	163
	270.541082	23.63	4.7	PK	28.33	46	17.67	232	243

Polarization	Frequency Marker (MHz)	C.R. (dBuv)	C.F. (dB)	Detector AV/QP	T.R. (dBuV/m)	C.L. (dBuV/m)	Margin (dB)	Azimuth (degree)	A.H. (cm)
2-H	225.651303	23.01	3.33	PK	26.34	46	19.66	154	232
	270.541082	27.75	4.7	PK	32.45	46	13.55	286	184



Registration number: W6M20511-6346-C-1
 FCC ID: PNKDO-S105

(Digital - USB Mode)

Polarization	Frequency Marker (MHz)	C.R. (dBuv)	C.F. (dB)	Detector AV/QP	T.R. (dBuV/m)	C.L. (dBuV/m)	Margin (dB)	Azimuth (degree)	A.H. (cm)
1-V	60.551102	30.56	-1.02	QP	29.54	40	10.46	118	324
	76.663326	28.99	-0.87	QP	28.12	40	11.88	0	283

Polarization	Frequency Marker (MHz)	C.R. (dBuv)	C.F. (dB)	Detector AV/QP	T.R. (dBuV/m)	C.L. (dBuV/m)	Margin (dB)	Azimuth (degree)	A.H. (cm)
1-H	79.03006012	32.41	0.06	PK	32.47	40	7.53	301	238
	165.204408	35.05	3.47	PK	38.52	45.5	6.98	100	111

Polarization	Frequency Marker (MHz)	C.R. (dBuv)	C.F. (dB)	Detector AV/QP	T.R. (dBuV/m)	C.L. (dBuV/m)	Margin (dB)	Azimuth (degree)	A.H. (cm)
2-V	256.112224	25.43	4.3	PK	29.73	46	16.27	284	144
	661.723447	21.96	13.64	PK	35.60	46	10.40	172	286

Polarization	Frequency Marker (MHz)	C.R. (dBuv)	C.F. (dB)	Detector AV/QP	T.R. (dBuV/m)	C.L. (dBuV/m)	Margin (dB)	Azimuth (degree)	A.H. (cm)
2-H	225.651303	26.01	3.33	PK	29.34	46	16.66	76	135
	624.849699	26.94	7.69	PK	34.63	46	11.37	184	175


- Note**
- 1. Correction Factor = Antennal factor + Cable loss + Preampifier gain**
 - 2. Test Result = Correction reading + Correction Factor**
 - 3. P = Peak , QP = Qusai Peak**
 - 4. C.R.=Corrected Reading; C.F.= Correction Factor; T.R.= Test Result; C.L.=Compliance Limit; A.H.=Antenna Height**

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of Emission (MHz)	Field Strength (microvolts/meter)	Field Strength (dBmicrovolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

Test equipment used: ETSTW-RE 015, ETSTW-RE 016, ETSTW-RE 017, ETSTW-CS 001, ETSTW-RE 026, ETSTW-RE 003, ETSTW-RE 025

Comment: see attached diagram



Registration number: W6M20511-6346-C-1
 FCC ID: PNKDO-S105

3.9 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.


Frequency	Level (dBμV)	
	quasi-peak	average
150 kHz	lower limit line	Lower limit line

Measurement Result: “_ Fin AV”

(Audio mode)

Frequency Marker [MHz]	Type	Corrected Reading [dBuV]	Compliance AVLimit [dBuV]	BW [MHz]	Margin(AV)
0.46	N	6.4	47.1	0,01	40.70
0.77	N	4.5	46	0,01	41.50

Frequency Marker [MHz]	Type	Corrected Reading [dBuV]	Compliance AVLimit [dBuV]	BW [MHz]	Margin(AV)
0.45	L1	3.7	47.4	0,01	43.70
0.81	L1	2.9	46	0,01	43.10



Registration number: W6M20511-6346-C-1
 FCC ID: PNKDO-S105

Measurement Result: “_ Fin QP”

(Audio mode)

Frequency Marker [MHz]	Type	Corrected Reading [dBuV]	Compliance QPLimit [dBuV]	BW [MHz]	Margin(QP)
0.46	N	30.5	57.1	0,01	26.60
0.77	N	24.4	56	0,01	31.60


Frequency Marker [MHz]	Type	Corrected Reading [dBuV]	Compliance QPLimit [dBuV]	BW [MHz]	Margin(QP)
0.45	L1	20.9	57.4	0,01	36.50
0.81	L1	14.3	56	0,01	41.70

Measurement Result: “_ Fin AV”

(USB mode)

Frequency Marker [MHz]	Type	Corrected Reading [dBuV]	Compliance AVLimit [dBuV]	BW [MHz]	Margin(AV)
0.970	N	34.7	46	0,01	11.30
1.070	N	36.8	46	0,01	9.20
1.460	N	35.1	46	0,01	10.90
1.850	N	32.8	46	0,01	13.20
9.330	N	19.0	50	0,01	31.00

Frequency Marker [MHz]	Type	Corrected Reading [dBuV]	Compliance AVLimit [dBuV]	BW [MHz]	Margin(AV)
1.070	L1	37.9	46	0,01	8.10
1.360	L1	36.7	46	0,01	9.30
1.460	L1	38.5	46	0,01	7.50
1.850	L1	36.6	46	0,01	9.40
9.400	L1	26.0	50	0,01	24.00



Registration number: W6M20511-6346-C-1
 FCC ID: PNKDO-S105

Measurement Result: “_ Fin QP”

(USB mode)

Frequency Marker [MHz]	Type	Corrected Reading [dBuV]	Compliance QPLimit [dBuV]	BW [MHz]	Margin(QP)
0.970	N	36.1	56	0,01	19.90
1.070	N	38.6	56	0,01	17.40
1.460	N	36.0	56	0,01	20.00
1.850	N	35.5	56	0,01	20.50
9.330	N	25.5	60	0,01	34.50


Frequency Marker [MHz]	Type	Corrected Reading [dBuV]	Compliance QPLimit [dBuV]	BW [MHz]	Margin(QP)
1.070	L1	40.1	56	0,01	15.90
1.360	L1	38.6	56	0,01	17.40
1.460	L1	39.2	56	0,01	16.80
1.850	L1	38.0	56	0,01	18.00
9.400	L1	34.2	60	0,01	25.80

Limits:

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi Peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Test equipment used: ETSTW-CE 004, ETSTW-CE 001, ETSTW-RE 023

Comment: see attached diagram



Registration number: W6M20511-6346-C-1
FCC ID: PNKDO-S105

Appendix

- A Peak Output Power
- B Spurious Emissions radiated
- C Band Edge Measurement
- D Minimum 6dB Bandwidth
- E Peak Power Spectral Density
- F Radiated Emissions from Receiver Section
- G Power Line Conducted Emission
- H Pictures



Registration number: W6M20511-6346-C-1
FCC ID: PNKDO-S105


Appendix A

Peak Output Power

The measurement diagram are wideband pre-scan results; only for reference.



Ref 20 dBm * Att 35 dB * RBW 2 MHz Marker 1 [T1] 11.21 dBm
* VBW 2 MHz 2.409326923 GHz
* SWT 500 ms




Max Output Power Low Channel

Date: 19.NOV.2005 11:40:39



Ref 20 dBm *Att 35 dB *RBW 2 MHz Marker 1 [T1] 11.01 dBm
*VBW 2 MHz *SWT 500 ms 2.445310897 GHz




Max Output Power Middle Channel

Date: 19.NOV.2005 11:09:08



Ref 20 dBm *Att 35 dB *RBW 2 MHz Marker 1 [T1] 10.77 dBm
*VBW 2 MHz 2.472310897 GHz
*SWT 500 ms




Max Output Power High Channel

Date: 19.NOV.2005 11:06:17

Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 1
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.409GHz, Emax: 94.16dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 1
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.409GHz, Emax: 92.61dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 5
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.446GHz, Emax: 93.72dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 5
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.446GHz, Emax: 94.21dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 8
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.474GHz, Emax: 95.14dBµV/m, RBW: 1MHz



Carrier power (Field Strength)

FCC RULES PART 15, SUBPART C

EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 8
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL025
Freq: 2.472GHz, Emax: 93.87dBµV/m, RBW: 1MHz





Registration number: W6M20511-6346-C-1
FCC ID: PNKDO-S105

Appendix B


Spurious Emissions radiated

The measurement diagram are wideband pre-scan results; only for reference.

Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 1
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 135.611MHz, Emax: 36.53dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 1
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 135.611MHz, Emax: 31.37dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 1
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 865.331MHz, Emax: 36.13dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 1
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 987.174MHz, Emax: 36.11dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 1
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.395GHz, Emax: 48.08dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 1
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.394GHz, Emax: 46.48dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 1
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.230GHz, Emax: 53.55dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 1
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.904GHz, Emax: 52.75dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 1
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 9.643GHz, Emax: 51.38dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 1
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.824GHz, Emax: 48.89dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 1
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.820GHz, Emax: 52.99dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 1
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.832GHz, Emax: 53.37dB μ V/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 1
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 24.354GHz, Emax: 51.43dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 1
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 25.239GHz, Emax: 51.67dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 5
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 135.611MHz, Emax: 36.22dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 5
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 135.611MHz, Emax: 31.82dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 5
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 987.174MHz, Emax: 35.87dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 5
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 982.365MHz, Emax: 36.61dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 5
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 3.870GHz, Emax: 45.63dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 5
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 3.870GHz, Emax: 45.49dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 5
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 4.890GHz, Emax: 53.60dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 5
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.992GHz, Emax: 53.10dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 5
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 9.788GHz, Emax: 49.68dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 5
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.743GHz, Emax: 48.80dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 5
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.856GHz, Emax: 53.39dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 5
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.772GHz, Emax: 53.04dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 5
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 26.330GHz, Emax: 51.09dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 5
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 26.313GHz, Emax: 51.04dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 8
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 135.611MHz, Emax: 36.43dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 8
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HK 116
Freq: 135.611MHz, Emax: 31.54dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 8
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 919.840MHz, Emax: 36.75dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 8
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247
Comment 1: Dist.: 3m, Ant.: HL 223,
Freq: 993.587MHz, Emax: 36.03dBµV/m, RBW: 100kHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 8
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.488GHz, Emax: 51.28dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 8
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 2.489GHz, Emax: 49.15dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 8
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 4.946GHz, Emax: 52.83dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 8
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 7.880GHz, Emax: 53.03dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 8
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.904GHz, Emax: 48.75dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 8
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 11.936GHz, Emax: 48.68dBμV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 8
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.699GHz, Emax: 53.09dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 8
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, ampl.+HP.
Freq: 17.832GHz, Emax: 53.17dBµV/m, RBW: 1MHz



Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 8
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 25.921GHz, Emax: 51.01dBµV/m, RBW: 1MHz




Spurious emissions Field Strength

FCC RULES PART 15, SUBPART C

EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 CH 8
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to §15.247, peak detector
Comment 1: Dist.: 3m, Ant.: HL025, amplif.
Freq: 26.296GHz, Emax: 51.35dBµV/m, RBW: 1MHz






Registration number: W6M20511-6346-C-1
FCC ID: PNKDO-S105

Appendix C

Band Edge Measurement




Bandedge Low Channel

Date: 19.NOV.2005 11:27:50



Ref 20 dBm *Att 35 dB *RBW 100 kHz Marker 1 [T1] -45.19 dBm
*VBW 100 kHz *SWT 500 ms 2.48350000 GHz

1 PK
MAXH



Center 2.4835 GHz

4 MHz/

Span 40 MHz

Bandedge Range High Channel

Date: 19.NOV.2005 11:26:36



Registration number: W6M20511-6346-C-1
FCC ID: PNKDO-S105

Appendix D


Minimum 6dB Bandwidth



*RBW 100 kHz Marker 1 [T1] 10.06 dBm
*VBW 300 kHz
*SWT 500 ms 2.409935897 GHz

Ref 20 dBm *Att 35 dB

1 PK
MAXH



A

LVL

Center 2.41 GHz

2 MHz/

Span 20 MHz

6dB Bandwidth Low Channel


Date: 19.NOV.2005 11:35:25



*RBW 100 kHz Marker 1 [T1] 9.96 dBm
*VBW 300 kHz
*SWT 500 ms 2.409967949 GHz

Ref 20 dBm *Att 35 dB

1 PK
MAXH



A

LVL

6dB Bandwidth Middle Channel


Date: 19.NOV.2005 11:33:42



*RBW 100 kHz Marker 1 [T1] 9.66 dBm
*VBW 300 kHz
*SWT 500 ms 2.472935897 GHz

Ref 20 dBm *Att 35 dB

1 PK
MAXH



A

LVL

Center 2.473 GHz

2 MHz/

Span 20 MHz

6dB Bandwidth High Channel
Date: 19.NOV.2005 11:25:10



Registration number: W6M20511-6346-C-1
FCC ID: PNKDO-S105

Appendix E

Peak Power Spectral Density




*RBW 3 kHz Marker 1 [T2]
*VBW 100 kHz 1.04 dBm
*SWT 500 s 2.409939904 GHz

Ref 20 dBm

*Att 35 dB

1 PK
VIEW

2 PK
MAXH



LVL

Center 2.41 GHz

150 kHz/

Span 1.5 MHz

Power Density Low Channel

Date: 19.NOV.2005 11:41:59




*RBW 3 kHz Marker 1 [T2]
*VBW 100 kHz 0.75 dBm
*SWT 500 s 2.445947115 GHz

Ref 20 dBm

*Att 35 dB

1 PK
VIEW

2 PK
MAXH



Center 2.446 GHz

150 kHz/

Span 1.5 MHz

Power Density Middle Channel

Date: 19.NOV.2005 11:10:00




*RBW 3 kHz Marker 1 [T2]
*VBW 100 kHz -0.86 dBm
*SWT 500 s 2.472930288 GHz

Ref 20 dBm *Att 35 dB

1 PK
VIEW

2 PK
MAXH



Center 2.473 GHz

150 kHz/

Span 1.5 MHz

Power Density High Channel
Date: 19.NOV.2005 11:07:17



Registration number: W6M20511-6346-C-1
FCC ID: PNKDO-S105

Appendix F


Radiated Emissions from Receiver Section

The measurement diagram are wideband pre-scan results; only for reference.

Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 AUDIO mode
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:135.611MHz Emax:33.45dBµV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 AUDIO mode
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:135.611MHz Emax:31.96dBµV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 AUDIO mode
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq:913.427MHz Emax:36.56dBµV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 AUDIO mode
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (AC/DC adaptor)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq:881.363MHz Emax:36.10dBµV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 USB mode
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:60.661MHz Emax:36.30dBµV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 USB mode
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HK 116
Freq:168.317MHz Emax:39.24dBµV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B


EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 USB mode
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq:913.427MHz Emax:35.96dBµV/m RBW: 100 kHz



Field Strength under normal conditions

FCC RULES PART 15, SUBPART B

EUT: 2.4GHz Wireless Digital Audio
MODEL NO.: DIO-T105 USB mode
Approval Holder: ELANSat Technologies Inc.
Test Site / Operator: ETS / Dennis
Temperature/Voltage: Temp.: 24.9°C/ Unom.: 120 VAC (power on pc)
Test Specification: according to subpart B
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.
Freq:969.539MHz Emax:36.32dBµV/m RBW: 100 kHz





Registration number: W6M20511-6346-C-1
FCC ID: PNKDO-S105

Appendix G


Power Line Conducted Emission

The measurement diagram are wideband pre-scan results; only for reference.

EMI voltage test in the ac-mains according to FCC Part 15

Class B


EUT: 2.4GHz Wireless Digital Audio AUDIO mode
 Approval Holder: ELANSat Technologies Inc.
 Operating Condition: Unom : 120VAC (AC/DC ADAPTOR) , Tnom : 23 °C
 Test Site: ETS
 Operator: Patrick
 Test Specification: V-network: ESH3-Z5 N
 Comment: model: DIO-T105 mode: active



EMI voltage test in the ac-mains according to FCC Part 15

Class B


EUT: 2.4GHz Wireless Digital Audio AUDIO mode
 Approval Holder: ELANSat Technologies Inc.
 Operating Condition: Unom : 120VAC (AC/DC ADAPTOR) , Tnom : 23 °C
 Test Site: ETS
 Operator: Patrick
 Test Specification: V-network: ESH3-Z5 L1
 Comment: model: DIO-T105 mode: active



EMI voltage test in the ac-mains according to FCC Part 15

Class B

EUT: 2.4GHz Wireless Digital Audio USB mode
 Approval Holder: ELANSat Technologies Inc.
 Operating Condition: Unom : 120VAC (power on pc) , Tnom : 23 °C
 Test Site: ETS
 Operator: Pann
 Test Specification: V-network: ESH3-Z5 N
 Comment: model: DIO-T105 mode: active



EMI voltage test in the ac-mains according to FCC Part 15

Class B

EUT: 2.4GHz Wireless Digital Audio USB mode
Approval Holder: ELANSat Technologies Inc.
Operating Condition: Unom : 120VAC (power on pc) , Tnom : 23 °C
Test Site: ETS
Operator: Pann
Test Specification: V-network: ESH3-Z5 N
Comment: model: DIO-T105 mode: active

MEASUREMENT RESULT: "_fin AV"


11/24/05 1:10PM

Frequency MHZ	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
1.070000	36.80	10.0	46	9.2	---	---

EMI voltage test in the ac-mains according to FCC Part 15

Class B

EUT: 2.4GHz Wireless Digital Audio USB mode
 Approval Holder: ELANSat Technologies Inc.
 Operating Condition: Unom : 120VAC (power on pc) , Tnom : 23 °C
 Test Site: ETS
 Operator: Pann
 Test Specification: V-network: ESH3-Z5 L1
 Comment: model: DIO-T105 mode: active



EMI voltage test in the ac-mains according to FCC Part 15


Class B

EUT: 2.4GHz Wireless Digital Audio USB mode
Approval Holder: ELANSat Technologies Inc.
Operating Condition: Unom : 120VAC (power on pc) , Tnom : 23 °C
Test Site: ETS
Operator: Pann
Test Specification: V-network: ESH3-Z5 L1
Comment: model: DIO-T105 mode: active

MEASUREMENT RESULT: "_fin AV"

11/24/05 11:58AM

Frequency MHZ	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
1.070000	37.70	10.0	46	8.3	---	---
1.360000	36.60	10.1	46	9.4	---	---
1.460000	38.50	10.1	46	7.5	---	---
1.850000	36.80	10.1	46	9.2	---	---



Registration number: W6M20511-6346-C-1
FCC ID: PNKDO-S105

Appendix H

Pictures