
FCC Test Report

Report No.: AGC02931180506FE10A

FCC ID : POD-MDUV390
PRODUCT DESIGNATION : DMR Digital Transceiver
BRAND NAME : TYT
MODEL NAME : MD-UV390G, MD-UV390
APPLICANT : TYT ELECTRONICS CO., LTD
DATE OF ISSUE : Jan. 15, 2021
STANDARD(S) : FCC Part 90 Rules
: FCC Part 22 Rules
REPORT VERSION : V 1.1

Attestation of Global Compliance (Shenzhen) Co., Ltd



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Jan. 15, 2021	Invalid	Re-certification Report
V1.1	1 st	Jan. 15, 2021	Valid	Updated model name

Note: The original test report Ref. No. (AGC02931180506FE10) (dated 2018-11-28), was modified on 2021-01-15 to include the following changes and additions for:

- Increase the main test model MD-UV390G.
 - Add GPS module, change some resistance and capacitance.
- The DMR Digital Transceiver shut down the channel of 25KHz.
Re-evaluate the radiated spurs of all powers of VHF and UHF

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



TABLE OF CONTENTS

1. GENERAL INFORMATION.....	4
2.PRODUCT INFORMATION.....	5
2.1 PRODUCT TECHNICAL DESCRIPTION	5
2.2 TEST FREQUENCY LIST	6
2.3 RELATED SUBMITTAL(S) / GRANT (S)	7
2.4 TEST METHODOLOGY	7
2.5 CALCULATION OF EMISSION INDICATORS	7
2.6 SPECIAL ACCESSORIES	8
2.7 EQUIPMENT MODIFICATIONS.....	8
3. TEST ENVIRONMENT.....	9
3.1 ADDRESS OF THE TEST LABORATORY	9
3.2 TEST FACILITY.....	9
3.3 ENVIRONMENTAL CONDITIONS	10
3.4 MEASUREMENT UNCERTAINTY	10
3.5 LIST OF EQUIPMENTS USED	11
4.SYSTEM TEST CONFIGURATION	12
4.1 EUT CONFIGURATION	12
4.2 EUT EXERCISE	12
4.3 CONFIGURATION OF TESTED SYSTEM.....	12
4.4 EQUIPMENT USED IN TESTED SYSTEM.....	12
4.5 SUMMARY OF TEST RESULTS.....	13
5.DESCRPTION OF TEST MODES.....	14
6. SPURIOUS RATIATED EMISSION	15
6.1 PROVISIONS APPLICABLE	15
6.2 MEASUREMENT PROCEDURE.....	15
6.3 MEASUREMENT SETUP	16
8.4 MEASUREMENT RESULTS	17
APPENDIX I: PHOTOGRAPHS OF TEST SETUP	54
APPENDIX II: PHOTOGRAPHS OF TEST EUT.....	55

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



1. GENERAL INFORMATION

Applicant	TYT Electronics Co., Ltd.
Address	Block 39-1, Optoelectronics-information industry base, Nan'an, Quanzhou, Fujian, China.
Manufacturer	TYT Electronics Co., Ltd.
Address	Block 39-1, Optoelectronics-information industry base, Nan'an, Quanzhou, Fujian, China.
Factory	TYT Electronics Co., Ltd.
Address	Block 39-1, Optoelectronics-information industry base, Nan'an, Quanzhou, Fujian, China.
Product Designation	DMR Digital Transceiver
Brand Name	TYT
Test Model	MD-UV390G
Series Model(s)	MD-UV390
Difference Description	MD-UV390G supports GPS, MD-UV390 does not have GPS.
Deviation from Standard	None
Date of Test	Dec. 27, 2020~Jan. 14, 2021
Test Result	Pass

WE HEREBY CERTIFY THAT:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI/TIA-603-E-2016. The sample tested as described in this report is in compliance with the FCC Rules Part 22 and 90. The test results of this report relate only to the tested sample identified in this report.

Prepared By



Donjon Huang
(Project Engineer)

Jan. 14, 2021

Reviewed By



Calvin Liu
(Reviewer)

Jan. 15, 2021

Approved By



Forrest Lei
Authorized Officer

Jan. 15, 2021

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



2.PRODUCT INFORMATION

2.1 PRODUCT TECHNICAL DESCRIPTION

Hardware Version	UV-V2.1-171109	
Software Version	V1.06	
Power Supply	DC 7.4V by battery 2200mAh	
Adapter Information	Input:100-240V, 50/60Hz, 0.6A Output: DC 12V 500mAh	
Communication Type	Voice / Data	
Operation Frequency Range	From 136MHz to 174MHz--VHF From 400MHz to 480MHz--UHF	
Modulation Type	Analog Voice:	FM
	Digital Voice/Digital Data:	4FSK
Digital Type	DMR	
Channel Separation	Analog Voice:	12.5 KHz
	Digital Voice/Digital Data:	12.5 KHz
Support Data Rate	9600bps	
Rated Output Power	UHF/VHF:1W/5W (It was fixed by the manufacturer, any individual can't arbitrarily change it.)	
Antenna Designation	Detachable Antenna	
Antenna Gain	1.5dBi	

Note:

1. The product has the same digital working characters when operating in both two digitized voice/data mode. So only one set of test results for digital modulation modes are provided in this test report.
2. This equipment is capable of supporting a minimum data rate of 4800 bits per second per 6.25 kHz of channel bandwidth. DMR interphone's bandwidth is 12.5 kHz, and it has a double time slot, one is the speech time slot, one is the data time slot, just language sequence is satisfied with 4800 bps/6.25 kHz BW.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



2.2 TEST FREQUENCY LIST

Operation mode	Channel Separation	Operation Frequency Range	Test channel	Test Frequency
Analog/ Digital	12.5 KHz	400-470MHz	Bottom	406.125 MHz
	12.5 KHz	400-470MHz	Middle	453.2125 MHz
	12.5 KHz	400-470MHz	Middle	454.025 MHz
	12.5 KHz	400-470MHz	Middle	458.2125 MHz
	12.5 KHz	400-470MHz	Top	479.975 MHz
Analog/ Digital	12.5 KHz	136-174MHz	Bottom	136.025 MHz
	12.5 KHz	136-174MHz	Middle	151.850 MHz
	12.5 KHz	136-174MHz	Middle	155.025 MHz
	12.5 KHz	136-174MHz	Middle	161.610 MHz
	12.5 KHz	136-174MHz	Top	173.975 MHz

Note:

In section KDB 634817 D01 Sections II) (f) (1) and (2):

Test at least one frequency in each band for each rule part applied under and ensure the device is capable of operating on the frequency under each rule part. This requirement may result in testing on multiple frequencies. Testing on one frequency may be acceptable if multiple listed bands for a rule part with a continuous frequency range are split to remove a conflict with other rules and the technical requirements in the split bands are the same. Additional requirements for RF exposure may apply.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



2.3 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for FCC ID: **POD-MDUV390**, filing to comply with Part 2, Part 22, and Part 90 of the Federal Communication Commission rules.

2.4 TEST METHODOLOGY

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 22	Public Mobile Services
2	FCC 47 CFR Part 90	Private Land Mobile Radio Services
3	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
4	ANSI/TIA-603-E	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
5	KDB 971168 D01	KDB 971168 D01 Power Meas License Digital Systems v03r01
6	KDB 579009 D03	KDB 579009 D03 Applications Part 90 Refarming Bands v01
7	KDB 634817 D01	KDB 634817 D01 Freq Range Listing for Grants v04r01

2.5 CALCULATION OF EMISSION INDICATORS

FCC Rules and Regulations Part 2.202: Necessary Bandwidth and Emission Bandwidth

For FM Mode (Channel Spacing: 12.5kHz)

Emission Designator 11K0F3E

In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation.

$$BW = 2(M+D) = 2*(3.0 \text{ kHz} + 2.5 \text{ kHz}) = 11 \text{ kHz} = 11K0$$

F3E portion of the designator represents an FM voice transmission.

Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.

For FM Mode (Channel Spacing: 25kHz)

Emission Designator 16K0F3E

In this case, the maximum modulating frequency is 3.0 kHz with a 5.0 kHz deviation.

$$BW = 2(M+D) = 2*(3.0 \text{ kHz} + 5.0 \text{ kHz}) = 16 \text{ kHz} = 16K0$$

F3E portion of the designator represents an FM voice transmission.

Therefore, the entire designator for 25 kHz channel spacing FM mode is 16K0F3E.

For Digital Mode (Channel Spacing: 12.5 kHz)

Emission Designator 7K60F1D and 7K60F1W

The 99% energy rule was used for digital mode. It basically states that 99% of the modulation energy falls within X kHz, in this case, 7.60 kHz.

F1D and F1W portion of the designator indicates digital information.

Therefore, the entire designator for 12.5 kHz channel spacing digital mode is 7K60F1D and 7K60F1W.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



2.6 SPECIAL ACCESSORIES

Not available for this EUT intended for grant.

2.7 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>



3. TEST ENVIRONMENT

3.1 ADDRESS OF THE TEST LABORATORY

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



3.3 ENVIRONMENTAL CONDITIONS

	NORMAL CONDITIONS	EXTREME CONDITIONS
Temperature range (°C)	15 - 35	-20 - 50
Relative humidity range	20 % - 75 %	20 % - 75 %
Pressure range (kPa)	86 - 106	86 - 106
Power supply	--	--

Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.

3.4 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Test Items	Measurement Uncertainty
Frequency stability	$\pm 0.5\%$
Transmitter power conducted	$\pm 0.8\text{dB}$
Transmitter power Radiated	$\pm 1.3\text{dB}$
Conducted spurious emission 9kHz-40 GHz	$\pm 2.7\text{dB}$
Conducted Emission	$\pm 3.2\text{ dB}$
Radiated Emission below 1GHz	$\pm 3.9\text{ dB}$
Radiated Emission above 1GHz	$\pm 4.8\text{ dB}$
Occupied Channel Bandwidth	$\pm 2\%$
FM deviation	$\pm 2\%$
Audio level	$\pm 0.98\text{dB}$
Low Pass Filter Response	$\pm 0.65\text{dB}$
Modulation Limiting	0.42 %
Transient Frequency Behavior	6.8 %

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



3.5 LIST OF EQUIPMENTS USED

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	May 15, 2020	May 14, 2021
EXA Signal Analyzer	Aglient	N9020A	W1312-60196	Aug. 21, 2020	Aug. 20, 2021
EXA Signal Analyzer	Aglient	N9020A	MY52090123	Sep. 03, 2020	Sep. 02, 2021
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Sep.16, 2019	Sep.15, 2021
preamplifier	ChengYi	EMC184045SE	980508	Sep. 21, 2019	Sep. 20, 2021
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	May. 17, 2019	May. 16, 2021
Broadband Preamplifier	SCHWARZBECK	BBV 9718	9718-205	Jun. 09, 2020	Jun. 08, 2021
HORN ANTENNA	EM	EM-AH-10180	/	Feb.28, 2020	Feb.27, 2021
SIGNAL GENERATOR	AGILENT	E4421B	MY43351603	Jun. 09, 2020	Jun. 08, 2021
SIGNAL GENERATOR	R&S	SMT03	A0304261	Jun. 09, 2020	Jun. 08, 2021
ANTENNA	SCHWARZBECK	VULB9168	VULB9168-494	Jan. 08, 2021	Jan. 07, 2023
ANTENNA	SCHWARZBECK	VULB9168	D69250	Sep.20, 2019	Sep.19, 2021
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Jun. 11, 2020	Jun. 10, 2021
Modulation Domain Analyzer	HP	53310A	3121A02467	Jul. 03, 2020	Jul. 02, 2021
Small environmental tester	ESPEC	SH-242	--	Sep. 03, 2020	Sep. 02, 2022
RF Communication Test Set	HP	8920B	--	Jun. 09, 2020	Jun. 08, 2021
Attenuator	Weinachel Corp	58-30-33	ML030	Oct. 26, 2020	Oct. 25, 2021
RF Cable	R&S	1#	--	Each time	N/A
RF Cable	R&S	2#	--	Each time	N/A
Fliter-UHF	Microwave	N25155M2	498705	May 11, 2020	May 10, 2021
Fliter-VHF	Microwave	N26460M1	498703	May 11, 2020	May 10, 2021

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



4.SYSTEM TEST CONFIGURATION

4.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission’s requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT EXERCISE

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 CONFIGURATION OF TESTED SYSTEM

Fig. 2-1 Configuration of Tested System



Table 2-1 Equipment Used in Tested System

4.4 EQUIPMENT USED IN TESTED SYSTEM

The Following Peripheral Devices And Interface Cables Were Connected During The Measurement:

- Test Accessories Come From The Laboratory
- Test Accessories Come From The Manufacturer

Item	Equipment	Model No.	Identifier	Note
1	DMR Digital Transceiver	MD-UV390G	FCC ID: POD-MDUV390	EUT

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



4.5 SUMMARY OF TEST RESULTS

Item	FCC Rules	Description Of Test	Result
1	§90.210&22.359& 2.1053	Spurious Ratiated Emission	Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: <http://cn.agc-cert.com/>



5. DESCRIPTION OF TEST MODES

The EUT (**Two-way radio**) has been tested under normal operating condition. (The top channel, the middle channel and the bottom channel) are chosen for testing at each channel separation.

NO.	TEST MODE DESCRIPTION	CHANNEL SEPARATION
1	TX Bottom channel-UHF	12.5 kHz
2	TX Middle channel-UHF	12.5 kHz
3	TX Middle channel-UHF	12.5 kHz
4	TX Top channel-UHF	12.5 kHz
5	TX Bottom channel-VHF	12.5 kHz
6	TX Middle channel-VHF	12.5 kHz
7	TX Middle channel-VHF	12.5 kHz
8	TX Middle channel-VHF	12.5 kHz
9	TX Top channel-VHF	12.5 kHz

Note:

1. Only the result of the worst case was recorded in the report, if no other cases.
2. The battery is full-charged during the test.
3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
4. For Conducted Test method, a temporary antenna connector is provided by the manufacture.
5. Manufacturers use computer PC programming software to switch and operate frequency points, refer to the instructions for details

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



6. SPURIOUS RADIATED EMISSION

6.1 PROVISIONS APPLICABLE

According to FCC §2.1053 §22.359 and §90.210, the power of each unwanted emission shall be less than Transmitted Power as specified below for transmitters designed to operate with each channel separation.

Emission Mask D -for 12.5 kHz Channel Separation:

- (1) On any frequency removed from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 : Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (f_d in kHz) f_0 of more than 5.625 kHz but no more than 12.5 kHz: At least $7.27(f_d - 2.88 \text{ kHz})$ dB
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (f_d in kHz) f_0 of more than 12.5 kHz: At least $50 + 10 \log(P)$ dB or 70 dB, whichever is lesser attenuation.

According to FCC §22.359:

- (a) *Out of band emissions.* The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

6.2 MEASUREMENT PROCEDURE



- (1) On a test site, the EUT shall be placed on a turntable, and in the position closest to the normal use as declared by the user.
- (2) The test antenna shall be oriented initially for vertical polarization located 3m from the EUT to correspond to the transmitter.
- (3) The output of the antenna shall be connected to the measuring receiver and either a peak or quasi-peak detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
- (4) The transmitter shall be switched on; if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
- (5) The test antenna shall be raised and lowered through the specified range of height until the measuring receiver detects a maximum signal level.
- (6) The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- (7) The test antenna shall be raised and lowered again through the specified range of height until the measuring receiver detects a maximum signal level.
- (8) The maximum signal level detected by the measuring receiver shall be noted.
- (9) The measurement shall be repeated with the test antenna set to horizontal polarization.
- (10) Replace the antenna with a proper Antenna (substitution antenna).
- (11) The substitution antenna shall be oriented for vertical polarization and, if necessary, the length of the substitution antenna shall be adjusted to correspond to the frequency of transmitting.
- (12) The substitution antenna shall be connected to a calibrated signal generator.
- (13) If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- (14) The test antenna shall be raised and lowered through the specified range of the height to ensure that the maximum signal is received.
- (15) The input signal to substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuation setting of the measuring receiver.
- (16) The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
- (17) The measurement shall be repeated with the test antenna and the substitution antenna oriented for horizontal polarization.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.





6.3 MEASUREMENT SETUP

RADIATED BELOW 1GHZ



RADIATED ABOVE 1 GHZ



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



8.4 MEASUREMENT RESULTS

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz for below 1GHz, and 1MHz for above 1GHz. Sufficient scans were taken to show any out of band emissions up to 10 harmonic.

In the semi-anechoic chamber, setup as illustrated above the DUT placed on the 0.8m height of Turn Table, rotated the table 45 degree each interval to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power for each degree interval. The “Read Value” is the spectrum reading of maximum power value.

The substitution antenna is substituted for DUT at the same position and signals generator (S.G) export the CW signal to the substitution antenna via a TX cable. The receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum radiation power. Record the power level of maximum radiation power from spectrum. So, the Measured substitution value = Ref level of S.G + TX cables loss – Substituted Antenna Gain.

EIRP = “Read Value” + Measured substitution value + 2.15.

Test limit calculation:


Preliminary calculation	Final Result
At least $50+10 \log (P) =50+10\log (5) =56.99$ (dB)	Limit=P- Preliminary calculation= $36.99-56.99=-20$ dBm
At least $50+10 \log (P) =50+10\log (1) =50.00$ (dB)	Limit=P- Preliminary calculation= $30.00-50.00=-20$ dBm
At least $43+10 \log (P) =43+10\log (5) =49.99$ (dB)	Limit=P- Preliminary calculation= $36.99-49.99=-13$ dBm
At least $43+10 \log (P) =43+10\log (1) =43.00$ (dB)	Limit=P- Preliminary calculation= $30.00-43.00=-13$ dBm

Note: In this case, Part 22 (-13 dBm) is less than the limit of Part 90 (-20 dBm), so we do not need to test Part 22, which meets the spurious limits of PART 90+22.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




Test Mode:	Freq. 400.025MHz-5W- Analog	Polarity:	Horizontal
------------	-----------------------------	-----------	------------




NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	800.1800	-91.82	-48.40	-20.00	28.40	43.42	276	Horizontal
2	1199.7700	-38.80	-42.64	-20.00	22.64	-3.84	144	Horizontal
3	1600.4850	-46.64	-49.10	-20.00	29.10	-2.46	210	Horizontal
4	2000.0250	-48.52	-47.99	-20.00	27.99	0.53	40	Horizontal
5	3200.9951	-34.56	-30.91	-20.00	10.91	3.65	134	Horizontal
6	4800.3300	-46.70	-43.06	-20.00	23.06	3.64	220	Horizontal

Test Mode:	Freq.400.025MHz-5W - Analog	Polarity:	Vertical
------------	-----------------------------	-----------	----------




NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	800.1800	-90.79	-48.42	-20.00	28.42	42.37	28	Vertical
2	1199.7700	-35.26	-35.09	-20.00	15.09	0.17	178	Vertical
3	1600.4850	-39.58	-37.77	-20.00	17.77	1.81	169	Vertical
4	2000.0250	-48.45	-48.04	-20.00	28.04	0.41	150	Vertical
5	3200.9951	-39.17	-36.02	-20.00	16.02	3.15	103	Vertical
6	7201.0951	-55.76	-42.92	-20.00	22.92	12.84	122	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




Test Mode: Freq. 453.225MHz-5W- Analog Polarity: Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	904.9400	-90.60	-47.55	-20.00	27.55	43.05	0	Horizontal
2	1359.5860	-31.50	-35.00	-20.00	15.00	-3.50	359	Horizontal
3	1813.1813	-46.93	-47.80	-20.00	27.80	-0.87	14	Horizontal
4	3172.7923	-38.18	-34.58	-20.00	14.58	3.60	126	Horizontal
5	5935.4935	-55.49	-44.93	-20.00	24.93	10.56	183	Horizontal
6	8194.0694	-58.74	-45.87	-20.00	25.87	12.87	164	Horizontal

Test Mode: Freq. 453.225MHz-5W- Analog Polarity: Vertical




NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	907.8500	-83.85	-40.46	-20.00	20.46	43.39	1	Vertical
2	1359.5860	-30.13	-28.90	-20.00	8.90	1.23	175	Vertical
3	1813.1813	-46.83	-45.77	-20.00	25.77	1.06	110	Vertical
4	3172.7923	-43.35	-40.19	-20.00	20.19	3.16	128	Vertical
5	6000.1250	-56.85	-45.92	-20.00	25.92	10.93	269	Vertical
6	7319.7820	-57.61	-44.36	-20.00	24.36	13.25	1	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




Test Mode:	Freq. 454.025MHz-5W- Analog	Polarity:	Horizontal
------------	-----------------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	907.8500	-90.20	-47.09	-20.00	27.09	43.11	13	Horizontal
2	1361.9362	-32.57	-36.07	-20.00	16.07	-3.50	32	Horizontal
3	1815.5316	-47.39	-48.24	-20.00	28.24	-0.85	13	Horizontal
4	1957.7208	-46.80	-46.59	-20.00	26.59	0.21	50	Horizontal
5	3178.6679	-38.18	-34.57	-20.00	14.57	3.61	136	Horizontal
6	5714.5715	-55.32	-45.59	-20.00	25.59	9.73	5	Horizontal

Test Mode:	Freq. 454.025MHz-5W- Analog	Polarity:	Vertical
------------	-----------------------------	-----------	----------




NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	907.8500	-86.07	-42.68	-20.00	22.68	43.39	147	Vertical
2	1361.9362	-45.19	-43.95	-20.00	23.95	1.24	1	Vertical
3	1898.9649	-53.00	-52.24	-20.00	32.24	0.76	326	Vertical
4	3178.6679	-49.02	-45.86	-20.00	25.86	3.16	9	Vertical
5	5886.1386	-56.50	-46.67	-20.00	26.67	9.83	1	Vertical
6	8618.2868	-58.15	-45.10	-20.00	25.10	13.05	213	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




Test Mode:	Freq. 479.975MHz-5W- Analog	Polarity:	Horizontal
------------	-----------------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	960.2300	-91.34	-47.09	-20.00	27.09	44.25	137	Horizontal
2	1439.4939	-36.91	-40.25	-20.00	20.25	-3.34	90	Horizontal
3	1920.1170	-43.46	-43.53	-20.00	23.53	-0.07	52	Horizontal
4	2880.1880	-45.51	-43.35	-20.00	23.35	2.16	183	Horizontal
5	3359.6360	-45.58	-41.65	-20.00	21.65	3.93	211	Horizontal
6	4800.3300	-44.26	-40.62	-20.00	20.62	3.64	192	Horizontal

Test Mode:	Freq. 479.975MHz-5W- Analog	Polarity:	Vertical
------------	-----------------------------	-----------	----------




NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	960.2300	-89.23	-45.31	-20.00	25.31	43.92	168	Vertical
2	1440.6691	-29.10	-27.33	-20.00	7.33	1.77	177	Vertical
3	1920.1170	-42.81	-42.12	-20.00	22.12	0.69	131	Vertical
4	2880.1880	-45.90	-43.72	-20.00	23.72	2.18	168	Vertical
5	3359.6360	-50.27	-47.17	-20.00	27.17	3.10	140	Vertical
6	3840.2590	-50.02	-46.80	-20.00	26.80	3.22	196	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




Test Mode: Freq.400.025MHz-1W- Analog Polarity: Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	800.1800	-92.18	-48.76	-20.00	28.76	43.42	258	Horizontal
2	1199.7700	-40.27	-44.11	-20.00	24.11	-3.84	73	Horizontal
3	1600.4850	-49.68	-52.14	-20.00	32.14	-2.46	26	Horizontal
4	2000.0250	-49.77	-49.24	-20.00	29.24	0.53	64	Horizontal
5	3199.8200	-43.54	-39.89	-20.00	19.89	3.65	138	Horizontal
6	4400.7901	-49.35	-45.62	-20.00	25.62	3.73	230	Horizontal

Test Mode: Freq. 400.025MHz-1W- Analog Polarity: Vertical




NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	800.1800	-89.94	-47.57	-20.00	27.57	42.37	18	Vertical
2	1199.7700	-31.40	-31.23	-20.00	11.23	0.17	176	Vertical
3	1600.4850	-45.63	-43.82	-20.00	23.82	1.81	176	Vertical
4	2000.0250	-50.69	-50.28	-20.00	30.28	0.41	176	Vertical
5	3199.8200	-47.90	-44.75	-20.00	24.75	3.15	111	Vertical
6	4400.7901	-52.21	-49.10	-20.00	29.10	3.11	167	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




Test Mode:	Freq. 453.225MHz-1W- Analog	Polarity:	Horizontal
------------	-----------------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	904.9400	-88.45	-45.40	-20.00	25.40	43.05	304	Horizontal
2	1359.5860	-40.60	-44.10	-20.00	24.10	-3.50	24	Horizontal
3	1974.1724	-43.51	-43.17	-20.00	23.17	0.34	191	Horizontal
4	3172.7923	-38.53	-34.93	-20.00	14.93	3.60	136	Horizontal
5	5830.9081	-56.03	-45.87	-20.00	25.87	10.16	200	Horizontal
6	7541.8792	-59.14	-45.54	-20.00	25.54	13.60	173	Horizontal

Test Mode:	Freq. 453.225MHz-1W- Analog	Polarity:	Vertical
------------	-----------------------------	-----------	----------




NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	906.8800	-91.96	-48.58	-20.00	28.58	43.38	168	Vertical
2	1359.5860	-39.23	-38.00	-20.00	18.00	1.23	177	Vertical
3	1714.4714	-37.99	-36.58	-20.00	16.58	1.41	360	Vertical
4	1957.7208	-37.17	-36.61	-20.00	16.61	0.56	289	Vertical
5	3172.7923	-43.39	-40.23	-20.00	20.23	3.16	111	Vertical
6	5954.2954	-56.50	-46.01	-20.00	26.01	10.49	121	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




Test Mode:	Freq. 454.025MHz-1W- Analog	Polarity:	Horizontal
------------	-----------------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	904.9400	-82.64	-39.59	-20.00	19.59	43.05	0	Horizontal
2	1361.9362	-42.21	-45.71	-20.00	25.71	-3.50	7	Horizontal
3	1974.1724	-46.54	-46.20	-20.00	26.20	0.34	359	Horizontal
4	3178.6679	-39.18	-35.57	-20.00	15.57	3.61	137	Horizontal
5	4087.0337	-52.33	-47.80	-20.00	27.80	4.53	230	Horizontal
6	5729.8480	-54.74	-44.96	-20.00	24.96	9.78	0	Horizontal

Test Mode:	Freq. 454.025MHz-1W - Analog	Polarity:	Vertical
------------	------------------------------	-----------	----------




NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	905.9100	-83.45	-40.08	-20.00	20.08	43.37	252	Vertical
2	1361.9362	-39.91	-38.67	-20.00	18.67	1.24	187	Vertical
3	1956.5457	-43.07	-42.51	-20.00	22.51	0.56	187	Vertical
4	3178.6679	-44.55	-41.39	-20.00	21.39	3.16	111	Vertical
5	4370.2370	-52.64	-49.52	-20.00	29.52	3.12	9	Vertical
6	5953.1203	-56.24	-45.76	-20.00	25.76	10.48	28	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




Test Mode: Freq. 479.975MHz-1W- Analog Polarity: Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	960.2300	-96.45	-52.20	-20.00	32.20	44.25	308	Horizontal
2	1440.6691	-38.55	-41.88	-20.00	21.88	-3.33	103	Horizontal
3	3359.6360	-51.02	-47.09	-20.00	27.09	3.93	9	Horizontal
4	4319.7070	-51.86	-47.92	-20.00	27.92	3.94	289	Horizontal
5	5766.2766	-55.66	-45.74	-20.00	25.74	9.92	360	Horizontal
6	8323.3323	-58.21	-45.32	-20.00	25.32	12.89	299	Horizontal

Test Mode: Freq. 479.975MHz-1W- Analog Polarity: Vertical




NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	960.2300	-92.07	-48.15	-20.00	28.15	43.92	222	Vertical
2	1440.6691	-29.78	-28.01	-20.00	8.01	1.77	167	Vertical
3	1956.5457	-43.54	-42.98	-20.00	22.98	0.56	332	Vertical
4	2962.4462	-53.31	-50.42	-20.00	30.42	2.89	351	Vertical
5	5902.5903	-56.16	-46.17	-20.00	26.17	9.99	48	Vertical
6	8318.6319	-58.05	-45.11	-20.00	25.11	12.94	122	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




Test Mode:	Freq. 136.025MHz-5W- Analog	Polarity:	Horizontal
------------	-----------------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	271.5300	-84.52	-51.46	-20.00	31.46	33.06	186	Horizontal
2	408.3000	-76.93	-42.35	-20.00	22.35	34.58	204	Horizontal
3	1224.4474	-33.26	-37.05	-20.00	17.05	-3.79	204	Horizontal
4	1360.7611	-40.85	-44.35	-20.00	24.35	-3.50	130	Horizontal
5	1783.8034	-39.61	-40.70	-20.00	20.70	-1.09	84	Horizontal
6	3128.1378	-43.11	-39.59	-20.00	19.59	3.52	130	Horizontal

Test Mode:	Freq. 136.025MHz-5W- Analog	Polarity:	Vertical
------------	-----------------------------	-----------	----------




NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	271.5300	-66.91	-36.73	-20.00	16.73	30.18	220	Vertical
2	408.3000	-58.48	-23.37	-20.00	3.37	35.11	359	Vertical
3	544.1000	-87.16	-49.75	-20.00	29.75	37.41	276	Vertical
4	1224.4474	-29.28	-28.95	-20.00	8.95	0.33	126	Vertical
5	1360.7611	-36.97	-35.73	-20.00	15.73	1.24	145	Vertical
6	1632.2132	-34.16	-32.46	-20.00	12.46	1.70	70	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




Test Mode: Freq. 151.850MHz-5W- Analog Polarity: Horizontal



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	455.8300	-87.36	-51.87	-20.00	31.87	35.49	18	Horizontal
2	1215.0465	-36.26	-40.07	-20.00	20.07	-3.81	168	Horizontal
3	1366.6367	-40.17	-43.66	-20.00	23.66	-3.49	168	Horizontal
4	1670.9921	-38.06	-39.99	-20.00	19.99	-1.93	345	Horizontal
5	1822.5823	-45.68	-46.48	-20.00	26.48	-0.80	196	Horizontal
6	3189.2439	-39.76	-36.13	-20.00	16.13	3.63	140	Horizontal

Test Mode: Freq. 151.850MHz-5W- Analog Polarity: Vertical



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	455.8300	-72.12	-36.35	-20.00	16.35	35.77	0	Vertical
2	911.7300	-87.41	-43.98	-20.00	23.98	43.43	184	Vertical
3	1215.0465	-28.52	-28.25	-20.00	8.25	0.27	128	Vertical
4	1518.2268	-41.63	-39.53	-20.00	19.53	2.10	138	Vertical
5	1670.9921	-33.97	-32.41	-20.00	12.41	1.56	101	Vertical
6	1822.5823	-40.07	-39.04	-20.00	19.04	1.03	73	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

