

**SPURIOUS EMISSION RADIATE**

EUT: WML-C06 / 24.10.2001  
 Manufacturer: Mitsumi  
 Operating Condition: TX on 2480 MHz  
 Test Site: 7 Layers Ratingen  
 Operator: gal  
 Test Specification: FCC 15.247 (15.35b, 15.209)  
 Comment: vertical + horizontal antenna polarisation  
 vertical EUT position

**SCAN TABLE: "FCC 15.209 C Field m"**

Short Description:		FCC ClassA Field Strength				
Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
30.0 MHz	1000.0 MHz	60.0 kHz	MaxPeak	100.0 ms	120 kHz	HL562
1.0 GHz	2.4 GHz	500.0 kHz	MaxPeak	100.0 ms	1 MHz	HF 906 / 001
Average						
2.5 GHz	7.0 GHz	500.0 kHz	MaxPeak	100.0 ms	1 MHz	HF 906 / 001
Average						
7.0 GHz	18.0 GHz	500.0 kHz	MaxPeak	100.0 μs	1 MHz	HF 906 / 001
Average						
18.0 GHz	25.0 GHz	500.0 kHz	MaxPeak	100.0 ms	1 MHz	EMCO 3160-09
Average						

