



## SOMA Networks, Inc.

185 Berry Street, Suite 4600 • San Francisco, California 94107

July 20, 2006

ATTN:Reviewing Engineer  
Federal Communications Commission  
7435 Oakland Mills Road  
Columbia, MD 21046

RE: MPE Calculation for SOMAport3, Model # CPE-300-2C0, FCC ID:  
POZCPE700006553D

To Whom It May Concern:

The RF exposure limits for radio transmitters are given in 47 CFR 1.1310. The EUT operates at 2305-2315 MHz and is intended for home use. Therefore the applicable exposure limits are in Table 1, section B (for General Population/Uncontrolled Exposure). The applicable Power Density limit for 1500-100,000 MHz from Table 1 is:

**1 mW/cm<sup>2</sup>**

The CPE-300-270 is intended for use at distances of >20cm from the user, and this safety requirement is explicitly stated in the user manual. The CPE-300-200 has the following transmitter operating parameters in the maximal case:

Maximum Transmitter Power (P): +27 dBm  
Maximum Numerical Antenna Gain (G): +5 dBi

As per FCC Bulletin 65, the formula used to calculate the exposure level, S (in mW/cm<sup>2</sup>) at a distance R=20 cm is:

$$S = \frac{PG}{4\pi R^2} = \frac{501mW \times 3.16}{5026cm^2} = 0.315mW/cm^2$$

Thus the CPE-300-2C0 is below the MPE limit of 1 mW/cm<sup>2</sup> at a distance of 20 cm.

Sincerely,

A handwritten signature in black ink, appearing to read 'Robin Grindley'.

Robin Grindley  
Chief Scientist – Hardware Systems  
SOMA Networks, Inc.