



1. MARK VENDOR NAME, LABEL DESIGNATION, AND SOMA NETWORKS PART NUMBER ON EACH SHEET OF LABELS.
2. BACKGROUND TO BE BLACK. LETTERING AND GRAPHICS TO BE SOLID SILVER. BACKGROUND COLOR NOT SHOWN FOR TEXT CLARITY.
3. REFER TO APPROPRIATE AGENCY LISTING MARK INFORMATION TO REPLACE REFERENCE SYMBOLS WITH APPROPRIATE REGISTERED MARKS.
4. FONT: ARIAL 14 POINT
5. FONT: ARIAL 5 POINT
6. FONT: ARIAL 9 POINT
7. LABEL CONSTRUCTION TO CONSIST OF A 0.010" THICK POLYCARBONATE LABEL STOCK WITH A 0.005" THICK 3M 468 PRESSURE SENSITIVE ADHESIVE. LABEL MUST BE A COMPONENT MARKING AND LABELING SYSTEM APPROVED BY UL AND CSA FOR THE FOLLOWING CONDITIONS:
  - INDOOR
  - TEMPERATURE RANGE: -40C TO +55C WHEN AFFIXED TO POWDER COATED STEEL
8. SERIAL NUMBER LABEL TO BE AFFIXED AT INDICATED LOCATION.
9. REFERENCE DOCUMENT "004703A\_01\_ARTWORK\_LABEL\_REGULATORY\_USA\_NPM\_24V\_MMDS.AI" FOR LABEL LAYOUT AND COLORS.
10. "ITE 91LF / E217858" AT NOTED LOCATION.

TITLE: <b>LABEL,REGULATORY,USA,NPM,24V,MMDS</b>				
 <b>soma</b> NETWORKS	UNLESS OTHERWISE SPECIFIED:			
	MATERIAL:			
	FINISH:			
DIMENSIONS ARE IN INCHES				
TOLERANCES:				
ANGULAR: $\pm 1^\circ$				
ONE PLACE DECIMAL $\pm .1$				
TWO PLACE DECIMAL $\pm .01$				
THREE PLACE DECIMAL $\pm .005$				
PROPRIETARY AND CONFIDENTIAL				
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOMA NETWORKS, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOMA NETWORKS IS PROHIBITED				
NAME	DATE	SIZE	DWG. NO.	REV
DRAWN jcrim	8/14/2003	<b>B</b>	<b>004703A</b>	<b>01</b>
ENG APPR. Checked By	8/14/2003	SCALE: 2:3		DO NOT SCALE DRAWING
				SHEET 1 OF 1