

# FCC PART 15.247



## TEST REPORT

For

### Shenzhen Rapoo Technology Co., Ltd.

22, Jinxiu Road East, Pingshan District, Shenzhen, China

**FCC ID: PP2D5**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Wi-Fi Storage
<b>Test Engineer:</b> Ares Liu	
<b>Report Number:</b> R2DG140604001-00	
<b>Report Date:</b> 2014-06-26	
<b>Reviewed By:</b> Jerry Zhang EMC Manager	
<b>Test Laboratory:</b>	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## TABLE OF CONTENTS

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
OBJECTIVE .....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY .....	4
TEST FACILITY .....	4
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>5</b>
DESCRIPTION OF TEST CONFIGURATION .....	5
EUT EXERCISE SOFTWARE .....	5
SUPPORT EQUIPMENT LIST AND DETAILS .....	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP .....	6
<b>SUMMARY OF TEST RESULTS .....</b>	<b>7</b>
<b>FCC §15.247 (i) &amp; §1.1310 &amp; §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....</b>	<b>8</b>
APPLICABLE STANDARD .....	8
<b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>	<b>9</b>
APPLICABLE STANDARD .....	9
ANTENNA CONNECTOR CONSTRUCTION .....	9
<b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS .....</b>	<b>10</b>
APPLICABLE STANDARD .....	10
MEASUREMENT UNCERTAINTY.....	10
EUT SETUP.....	10
EMI TEST RECEIVER SETUP.....	11
TEST PROCEDURE .....	11
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	11
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST RESULTS SUMMARY .....	12
TEST DATA .....	12
<b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS.....</b>	<b>15</b>
APPLICABLE STANDARD .....	15
MEASUREMENT UNCERTAINTY.....	15
EUT SETUP .....	15
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....	16
TEST PROCEDURE .....	16
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	17
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST RESULTS SUMMARY .....	17
TEST DATA .....	17
<b>FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....</b>	<b>31</b>
APPLICABLE STANDARD .....	31
TEST PROCEDURE .....	31
TEST EQUIPMENT LIST AND DETAILS.....	31
TEST DATA .....	31
<b>FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....</b>	<b>42</b>

APPLICABLE STANDARD .....42  
TEST PROCEDURE .....42  
TEST EQUIPMENT LIST AND DETAILS.....42  
TEST DATA .....43

**FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....53**  
APPLICABLE STANDARD .....53  
TEST PROCEDURE .....53  
TEST EQUIPMENT LIST AND DETAILS.....53  
TEST DATA .....53

**FCC §15.247(e) - POWER SPECTRAL DENSITY .....60**  
APPLICABLE STANDARD .....60  
TEST PROCEDURE .....60  
TEST EQUIPMENT LIST AND DETAILS.....60  
TEST DATA .....60

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *Shenzhen Rapoo Technology Co., Ltd.*'s product, model number: *D5 (FCC ID: PP2D5)* (the "EUT") in this report was a *Wi-Fi Storage*, which was measured approximately: 11.0cm (L) x 7.2 cm (W) x 1.2 cm (H), rated input voltage: DC 3.7V from lithium battery.

\* All measurement and test data in this report was gathered from production sample serial number: 140604001 (Assigned by *BACL.Dongguan*). The EUT was received on 2014-06-04

### Objective

This report is prepared on behalf of *Shenzhen Rapoo Technology Co., Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

No related submittal(s).

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

### Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer. For 2.4GHz band, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b and 802.11g modes were tested with Channel 1, 6 and 11.

For 802.11n40 mode were tested with Channel 3, 6 and 9.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

### EUT Exercise Software

The test software: 'MT7620QA' was used in testing, which was provided by manufacturer, and configured as following table:

Test Mode	Test Software Version	MT7620QA		
		2412MHz	2437MHz	2462MHz
802.11b	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	1Mbps	1Mbps	1Mbps
	Power Level Setting	5	3	3
802.11g	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	6Mbps	6Mbps	6Mbps
	Power Level Setting	7	6	6
802.11n20	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting (Chain 0)	7	6	6
	Power Level Setting (Chain 1)	7	6	6
802.11n40	Test Frequency	2422MHz	2437MHz	2452MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting (Chain 0)	8	8	8
	Power Level Setting (Chain 1)	8	7	7


**Support Equipment List and Details**

Manufacturer	Description	Model	Serial Number
DELL	Laptop	PP11L	QDS-BRCM1017
DELL	Keyboard	L100	CNORH656658907BL05DC

**External I/O Cable**

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Keyboard Cable	Yes	No	1.5	USB port of Laptop	Keyboard
RJ45 Cable	No	No	1.0	RJ45 Port of Laptop	EUT

**Block Diagram of Test Setup**



**SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
FCC §15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Peak Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

## FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

### Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

### Calculated Data:

Mode	Frequency (MHz)	Antenna Gain		Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
		(dBi)	(numeric)	(dBm)	(mW)			
802.11b	2412	2	1.58	17.68	58.61	20	0.018	1.0
802.11g	2412	2	1.58	17.69	58.75	20	0.019	1.0
802.11n20 Chain 0	2412	2	1.58	17.45	179	20	0.036	1.0
802.11n20 Chain 1	2412	2.2	1.66	17.40				
802.11n40 Chain 0	2437	2	1.58	17.49	180	20	0.036	1.0
802.11n40 Chain 1	2437	2.2	1.66	17.40				

**Result:** The device meet FCC MPE at 20 cm distance



---

## **FCC §15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

### **Antenna Connector Construction**

The EUT has two integral antenna, one is metal sheet antenna and antenna gain is 2.0 dBi, the other is PCB antenna and antenna gain is 2.2 dBi. Both antenna fulfill the requirement of this section. Please refer to the EUT photos.

**Result:** Compliance.

**FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS**

**Applicable Standard**

FCC§15.207

**Measurement Uncertainty**

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If  $U_{lab}$  is less than or equal to  $U_{cispr}$  of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If  $U_{lab}$  is greater than  $U_{cispr}$  of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by  $(U_{lab} - U_{cispr})$ , exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by  $(U_{lab} - U_{cispr})$ , exceeds the disturbance limit.

Based on CISPR 16-4-2:2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of  $U_{cispr}$

Measurement	$U_{cispr}$
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

**EUT Setup**



- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

### Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

$V_C$  (cord. Reading): corrected voltage amplitude

$V_R$ : reading voltage amplitude

$A_C$ : attenuation caused by cable loss

VDF: voltage division factor of AMN

$C_f$ : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2013-11-20	2014-11-19
R&S	Two-line V-network	ENV216	3560.6550.12	2014-01-22	2015-01-21
R&S	L.I.S.N	ESH3-Z5	100113	N/A	N/A
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

**15.90 dB** at **0.211298 MHz** in the **Neutral** conducted mode

### Test Data


#### Environmental Conditions

<b>Temperature:</b>	27.4 °C
<b>Relative Humidity:</b>	51 %
<b>ATM Pressure:</b>	99.6 kPa

*The testing was performed by Ares Liu on 2014-06-10.*

Test Mode: Charging & Transmitting


AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.212988	41.0	9.000	L1	10.8	22.0	63.1	Compliance
0.283749	29.1	9.000	L1	10.7	31.6	60.7	Compliance
0.354674	28.2	9.000	L1	10.7	30.7	58.9	Compliance
1.407671	27.7	9.000	L1	10.4	28.3	56.0	Compliance
17.183363	26.0	9.000	L1	10.8	34.0	60.0	Compliance
18.460903	35.9	9.000	L1	11.0	24.1	60.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.211298	36.1	9.000	L1	10.8	17.1	53.2	Compliance
0.283749	23.0	9.000	L1	10.7	27.7	50.7	Compliance
0.354674	20.9	9.000	L1	10.7	28.0	48.9	Compliance
0.426011	20.0	9.000	L1	10.6	27.3	47.3	Compliance
17.183363	21.0	9.000	L1	10.8	29.0	50.0	Compliance
18.460903	28.6	9.000	L1	11.0	21.4	50.0	Compliance

**AC120 V, 60 Hz, Neutral:**



Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.150000	32.1	9.000	N	10.3	33.9	66.0	Compliance
0.212988	42.1	9.000	N	11.3	21.0	63.1	Compliance
0.283749	30.4	9.000	N	11.2	30.3	60.7	Compliance
0.354674	27.5	9.000	N	11.0	31.4	58.9	Compliance
17.599071	30.1	9.000	N	10.9	29.9	60.0	Compliance
19.833426	32.2	9.000	N	11.1	27.8	60.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.211298	37.2	9.000	N	11.3	15.9	53.2	Compliance
0.281497	25.1	9.000	N	11.2	25.7	50.8	Compliance
0.354674	23.3	9.000	N	11.0	25.5	48.9	Compliance
1.065081	15.5	9.000	N	10.5	30.5	46.0	Compliance
1.773603	16.6	9.000	N	10.5	29.4	46.0	Compliance
19.364939	29.1	9.000	N	11.1	20.9	50.0	Compliance

**FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**

**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

**Measurement Uncertainty**

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If  $U_{lab}$  is less than or equal to  $U_{cispr}$  of Table 2, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If  $U_{lab}$  is greater than  $U_{cispr}$  of Table 2, then:

- compliance is deemed to occur if no measured disturbance level, increased by  $(U_{lab} - U_{cispr})$ , exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by  $(U_{lab} - U_{cispr})$ , exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:


- 30M~200MHz: 5.0 dB
- 200M~1GHz: 6.2 dB
- 1G~6GHz: 4.45 dB
- 6G~18GHz: 5.23 dB

Table 2 – Values of  $U_{cispr}$


Measurement	$U_{cispr}$
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

**EUT Setup**

**Below 1GHz:**



**Above 1GHz:**



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

**EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz – 1000 MHz	120 kHz	300 kHz	120kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

**Test Procedure**

During the radiated emission test, the adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.



## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2014-05-09	2015-05-08
Sunol Sciences	Antenna	JB3	A060611-1	2011-09-06	2014-09-05
HP	Amplifier	8447E	2434A02181	2013-09-06	2014-09-05
R&S	Spectrum Analyzer	FSEM	DE31388	2014-05-09	2015-05-08
ETS LINDGREN	Horn Antenna	3115	000 527 35	2012-09-06	2015-09-05
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2014-02-19	2015-02-18
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-08
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2013-06-16	2014-06-15
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2013-09-06	2014-09-05

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247, with the worst margin reading of:

**3.89 dB at 2390.0 MHz** in the **Vertical** polarization for 802.11g Mode

## Test Data

### Environmental Conditions

<b>Temperature:</b>	26.6 °C
<b>Relative Humidity:</b>	60 %
<b>ATM Pressure:</b>	100 kPa

*The testing was performed by Ares Liu on 2014-06-26.*

Mode: Transmitting  
802.11b Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	FCC 15.247	
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBµV/m)	Margin (dB)
Low Channel: 2412 MHz									
2412	58.63	PK	H	25.67	4.42	0.00	88.72	N/A	N/A
2412	52.41	AV	H	25.67	4.42	0.00	82.50	N/A	N/A
2412	77.55	PK	V	25.67	4.42	0.00	107.64	N/A	N/A
2412	70.24	AV	V	25.67	4.42	0.00	100.33	N/A	N/A
2390	28.17	PK	V	25.61	4.39	0.00	58.17	74.00	15.83
2390	18.33	AV	V	25.61	4.39	0.00	48.33	54.00	5.67
4824	48.63	PK	V	30.64	6.03	27.26	58.04	74.00	15.96
4824	32.2	AV	V	30.64	6.03	27.26	41.61	54.00	12.39
7236	36.43	PK	V	34.17	7.47	26.36	51.71	74.00	22.29
7236	21.47	AV	V	34.17	7.47	26.36	36.75	54.00	17.25
9648	35.14	PK	V	36.06	8.81	26.06	53.95	74.00	20.05
9648	20.22	AV	V	36.06	8.81	26.06	39.03	54.00	14.97
1860	42.36	PK	V	24.32	3.74	27.05	43.37	74.00	30.63
1860	33.11	AV	V	24.32	3.74	27.05	34.12	54.00	19.88
375.5	40.6	QP	V	15.73	2.35	21.71	36.97	46.00	9.03
Middle Channel: 2437 MHz									
2437	60.2	PK	H	25.74	4.41	0.00	90.35	N/A	N/A
2437	53.18	AV	H	25.74	4.41	0.00	83.33	N/A	N/A
2437	75.65	PK	V	25.74	4.41	0.00	105.80	N/A	N/A
2437	68.41	AV	V	25.74	4.41	0.00	98.56	N/A	N/A
4874	47.11	PK	V	30.77	6.09	27.26	56.71	74.00	17.29
4874	34.16	AV	V	30.77	6.09	27.26	43.76	54.00	10.24
7311	35.63	PK	V	34.35	7.51	26.51	50.98	74.00	23.02
7311	20.24	AV	V	34.35	7.51	26.51	35.59	54.00	18.41
9748	34.69	PK	V	36.30	8.83	25.68	54.14	74.00	19.86
9748	19.87	AV	V	36.30	8.83	25.68	39.32	54.00	14.68
1860	38.61	PK	V	24.32	3.74	27.05	39.62	74.00	34.38
1860	36.2	AV	V	24.32	3.74	27.05	37.21	54.00	16.79
3252	35.24	AV	V	28.01	6.30	27.44	42.11	54.00	11.89
3252	20.26	AV	V	28.01	6.30	27.44	27.13	54.00	26.87
375.5	41.5	QP	V	15.73	2.35	21.71	37.87	46.00	8.13
High Channel: 2462 MHz									
2462	59.33	PK	H	25.80	4.43	0.00	89.56	N/A	N/A
2462	52.01	AV	H	25.80	4.43	0.00	82.24	N/A	N/A
2462	75.43	PK	V	25.80	4.43	0.00	105.66	N/A	N/A
2462	68.29	AV	V	25.80	4.43	0.00	98.52	N/A	N/A
2483.5	30.14	PK	V	25.86	4.49	0.00	60.49	74.00	13.51
2483.5	17.65	AV	V	25.86	4.49	0.00	48.00	54.00	6.00
4924	45.54	PK	V	30.90	5.97	27.27	55.14	74.00	18.86
4924	32.37	AV	V	30.90	5.97	27.27	41.97	54.00	12.03
7386	33.26	PK	V	34.53	7.55	26.66	48.68	74.00	25.32
7386	20.04	AV	V	34.53	7.55	26.66	35.46	54.00	18.54
9848	34.15	PK	V	36.54	8.85	25.49	54.05	74.00	19.95
9848	21.03	AV	V	36.54	8.85	25.49	40.93	54.00	13.07
1860	38.45	PK	V	24.32	3.74	27.05	39.46	74.00	34.54
1860	27.19	AV	V	24.32	3.74	27.05	28.20	54.00	25.80
375	42	QP	V	15.72	2.35	21.71	38.36	46.00	7.64

802.11g Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	FCC 15.247	
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBµV/m)	Margin (dB)
Low Channel: 2412 MHz									
2412	62.33	PK	H	25.67	4.42	0.00	92.42	N/A	N/A
2412	49.14	AV	H	25.67	4.42	0.00	79.23	N/A	N/A
2412	72.15	PK	V	25.67	4.42	0.00	102.24	N/A	N/A
2412	59.08	AV	V	25.67	4.42	0.00	89.17	N/A	N/A
2390	30.66	PK	V	25.61	4.39	0.00	60.66	74.00	13.34
2390	20.11	AV	V	25.61	4.39	0.00	50.11	54.00	3.89*
4824	40.23	PK	V	30.64	6.03	27.26	49.64	74.00	24.36
4824	25.47	AV	V	30.64	6.03	27.26	34.88	54.00	19.12
7236	35.36	PK	V	34.17	7.47	26.36	50.64	74.00	23.36
7236	20.74	AV	V	34.17	7.47	26.36	36.02	54.00	17.98
9648	34.69	PK	V	36.06	8.81	26.06	53.50	74.00	20.50
9648	20.31	AV	V	36.06	8.81	26.06	39.12	54.00	14.88
1865	41.22	PK	V	24.33	3.72	27.05	42.22	74.00	31.78
1865	27.83	AV	V	24.33	3.72	27.05	28.83	54.00	25.17
375	39.9	QP	V	15.72	2.35	21.71	36.26	46.00	9.74
Middle Channel: 2437 MHz									
2437	61.53	PK	H	25.74	4.41	0.00	91.68	N/A	N/A
2437	49.32	AV	H	25.74	4.41	0.00	79.47	N/A	N/A
2437	71.56	PK	V	25.74	4.41	0.00	101.71	N/A	N/A
2437	58.44	AV	V	25.74	4.41	0.00	88.59	N/A	N/A
4874	38.63	PK	V	30.77	6.09	27.26	48.23	74.00	25.77
4874	22.46	AV	V	30.77	6.09	27.26	32.06	54.00	21.94
7311	35.69	PK	V	34.35	7.51	26.51	51.04	74.00	22.96
7311	20.27	AV	V	34.35	7.51	26.51	35.62	54.00	18.38
9748	34.58	PK	V	36.30	8.83	25.68	54.03	74.00	19.97
9748	20.42	AV	V	36.30	8.83	25.68	39.87	54.00	14.13
1865	39.57	PK	V	24.33	3.72	27.05	40.57	74.00	33.43
1865	35.71	AV	V	24.33	3.72	27.05	36.71	54.00	17.29
3622	35.85	PK	V	29.07	5.01	27.43	42.50	74.00	31.50
3622	20.74	AV	V	29.07	5.01	27.43	27.39	54.00	26.61
375	40.1	QP	V	15.72	2.35	21.71	36.46	46.00	9.54
High Channel: 2462 MHz									
2462	61.32	PK	H	25.80	4.43	0.00	91.55	N/A	N/A
2462	48.89	AV	H	25.80	4.43	0.00	79.12	N/A	N/A
2462	71.38	PK	V	25.80	4.43	0.00	101.61	N/A	N/A
2462	59.23	AV	V	25.80	4.43	0.00	89.46	N/A	N/A
2483.5	30.42	PK	V	25.86	4.49	0.00	60.77	74.00	13.23
2483.5	18.25	AV	V	25.86	4.49	0.00	48.60	54.00	5.40
4924	40.14	PK	V	30.90	5.97	27.27	49.74	74.00	24.26
4924	25.8	AV	V	30.90	5.97	27.27	35.40	54.00	18.60
7386	35.96	PK	V	34.53	7.55	26.66	51.38	74.00	22.62
7386	20.47	AV	V	34.53	7.55	26.66	35.89	54.00	18.11
9848	35.87	PK	V	36.54	8.85	25.49	55.77	74.00	18.23
9848	20.32	AV	V	36.54	8.85	25.49	40.22	54.00	13.78
1865	40.26	PK	V	24.33	3.72	27.05	41.26	74.00	32.74
1865	30.63	AV	V	24.33	3.72	27.05	31.63	54.00	22.37
375	40.4	QP	V	15.72	2.35	21.71	36.76	46.00	9.24

\*Within measurement uncertainty!

802.11 n20 Mode


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	FCC 15.247	
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB/m)				Limit (dBµV/m)	Margin (dB)
Low Channel: 2412 MHz									
2412	58.63	PK	H	25.67	4.42	0.00	88.72	N/A	N/A
2412	46.41	AV	H	25.67	4.42	0.00	76.50	N/A	N/A
2412	69.24	PK	V	25.67	4.42	0.00	99.33	N/A	N/A
2412	56.69	AV	V	25.67	4.42	0.00	86.78	N/A	N/A
2390	30.63	PK	V	25.61	4.39	0.00	60.63	74.00	13.37
2390	17.55	AV	V	25.61	4.39	0.00	47.55	54.00	6.45
4824	37.25	PK	V	30.64	6.03	27.26	46.66	74.00	27.34
4824	21.43	AV	V	30.64	6.03	27.26	30.84	54.00	23.16
7236	34.86	PK	V	34.17	7.47	26.36	50.14	74.00	23.86
7236	19.12	AV	V	34.17	7.47	26.36	34.40	54.00	19.60
9648	34.58	PK	V	36.06	8.81	26.06	53.39	74.00	20.61
9648	19.25	AV	V	36.06	8.81	26.06	38.06	54.00	15.94
1872	40.24	PK	V	24.34	3.70	27.06	41.22	74.00	32.78
1872	30.47	AV	V	24.34	3.70	27.06	31.45	54.00	22.55
375	40.7	QP	V	15.72	2.35	21.71	37.06	46.00	8.94
Middle Channel: 2437 MHz									
2437	57.26	PK	H	25.74	4.41	0.00	87.41	N/A	N/A
2437	44.82	AV	H	25.74	4.41	0.00	74.97	N/A	N/A
2437	68.28	PK	V	25.74	4.41	0.00	98.43	N/A	N/A
2437	55.19	AV	V	25.74	4.41	0.00	85.34	N/A	N/A
4874	37.64	PK	V	30.77	6.09	27.26	47.24	74.00	26.76
4874	20.37	AV	V	30.77	6.09	27.26	29.97	54.00	24.03
7311	34.26	PK	V	34.35	7.51	26.51	49.61	74.00	24.39
7311	19.52	AV	V	34.35	7.51	26.51	34.87	54.00	19.13
9748	34.74	PK	V	36.30	8.83	25.68	54.19	74.00	19.81
9748	20.11	AV	V	36.30	8.83	25.68	39.56	54.00	14.44
1872	38.69	PK	V	24.34	3.70	27.06	39.67	74.00	34.33
1872	25.71	AV	V	24.34	3.70	27.06	26.69	54.00	27.31
3664	35.36	PK	V	29.16	4.98	27.44	42.06	74.00	31.94
3664	20.23	AV	V	29.16	4.98	27.44	26.93	54.00	27.07
375	40.4	QP	V	15.72	2.35	21.71	36.76	46.00	9.24
High Channel: 2462 MHz									
2462	56.96	PK	H	25.80	4.43	0.00	87.19	N/A	N/A
2462	44.17	AV	H	25.80	4.43	0.00	74.40	N/A	N/A
2462	68.42	PK	V	25.80	4.43	0.00	98.65	N/A	N/A
2462	55.09	AV	V	25.80	4.43	0.00	85.32	N/A	N/A
2483.5	29.65	PK	V	25.86	4.49	0.00	60.00	74.00	14.00
2483.5	18.41	AV	V	25.86	4.49	0.00	48.76	54.00	5.24
4924	36.58	PK	V	30.90	5.97	27.27	46.18	74.00	27.82
4924	22.61	AV	V	30.90	5.97	27.27	32.21	54.00	21.79
7386	35.47	PK	V	34.53	7.55	26.66	50.89	74.00	23.11
7386	20.62	AV	V	34.53	7.55	26.66	36.04	54.00	17.96
9848	35.75	PK	V	36.54	8.85	25.49	55.65	74.00	18.35
9848	19.98	AV	V	36.54	8.85	25.49	39.88	54.00	14.12
1872	40.77	PK	V	24.34	3.70	27.06	41.75	74.00	32.25
1872	34.43	AV	V	24.34	3.70	27.06	35.41	54.00	18.59
375	43.8	QP	V	15.72	2.35	21.71	40.16	46.00	5.84

802.11 n40 Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	FCC 15.247	
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB/m)				Limit (dBµV/m)	Margin (dB)
Low Channel: 2422 MHz									
2422	55.63	PK	H	25.70	4.41	0.00	85.74	N/A	N/A
2422	42.36	AV	H	25.70	4.41	0.00	72.47	N/A	N/A
2422	66.71	PK	V	25.70	4.41	0.00	96.82	N/A	N/A
2422	53.15	AV	V	25.70	4.41	0.00	83.26	N/A	N/A
2390	29.63	PK	V	25.61	4.39	0.00	59.63	74.00	14.37
2390	16.88	AV	V	25.61	4.39	0.00	46.88	54.00	7.12
4844	35.69	PK	V	30.69	6.08	27.26	45.20	74.00	28.80
4844	20.17	AV	V	30.69	6.08	27.26	29.68	54.00	24.32
7266	35.44	PK	V	34.24	7.48	26.42	50.74	74.00	23.26
7266	19.16	AV	V	34.24	7.48	26.42	34.46	54.00	19.54
9688	35.62	PK	V	36.15	8.82	25.91	54.68	74.00	19.32
9688	19.21	AV	V	36.15	8.82	25.91	38.27	54.00	15.73
1874	41.33	PK	V	24.35	3.69	27.06	42.31	74.00	31.69
1874	32.06	AV	V	24.35	3.69	27.06	33.04	54.00	20.96
375	41.1	QP	V	15.72	2.35	21.71	37.46	46.00	8.54
Middle Channel: 2437 MHz									
2437	53.16	PK	H	25.74	4.41	0.00	83.31	N/A	N/A
2437	41.36	AV	H	25.74	4.41	0.00	71.51	N/A	N/A
2437	65.28	PK	V	25.74	4.41	0.00	95.43	N/A	N/A
2437	51.57	AV	V	25.74	4.41	0.00	81.72	N/A	N/A
4874	36.41	PK	V	30.77	6.09	27.26	46.01	74.00	27.99
4874	21.13	AV	V	30.77	6.09	27.26	30.73	54.00	23.27
7311	33.75	PK	V	34.35	7.51	26.51	49.10	74.00	24.90
7311	18.46	AV	V	34.35	7.51	26.51	33.81	54.00	20.19
9748	34.65	PK	V	36.30	8.83	25.68	54.10	74.00	19.90
9748	19.52	AV	V	36.30	8.83	25.68	38.97	54.00	15.03
1874	37.42	PK	V	24.35	3.69	27.06	38.40	74.00	35.60
1874	20.23	AV	V	24.35	3.69	27.06	21.21	54.00	32.79
3724.5	35.63	PK	V	29.29	5.01	27.44	42.49	74.00	31.51
3724.5	21.1	AV	V	29.29	5.01	27.44	27.96	54.00	26.04
375	40.8	QP	V	15.72	2.35	21.71	37.16	46.00	8.84
High Channel: 2452 MHz									
2452	53.68	PK	H	25.78	4.41	0.00	83.87	N/A	N/A
2452	41.19	AV	H	25.78	4.41	0.00	71.38	N/A	N/A
2452	66.2	PK	V	25.78	4.41	0.00	96.39	N/A	N/A
2452	53.14	AV	V	25.78	4.41	0.00	83.33	N/A	N/A
2483.5	29.63	PK	V	25.86	4.49	0.00	59.98	74.00	14.02
2483.5	17.2	AV	V	25.86	4.49	0.00	47.55	54.00	6.45
4904	37.62	PK	V	30.85	6.06	27.27	47.26	74.00	26.74
4904	23.31	AV	V	30.85	6.06	27.27	32.95	54.00	21.05
7356	36.78	PK	V	34.45	7.53	26.60	52.16	74.00	21.84
7356	21.57	AV	V	34.45	7.53	26.60	36.95	54.00	17.05
9808	35.63	PK	V	36.44	8.84	25.48	55.43	74.00	18.57
9808	20.09	AV	V	36.44	8.84	25.48	39.89	54.00	14.11
1874	38.69	PK	V	24.35	3.69	27.06	39.67	74.00	34.33
1874	29.47	AV	V	24.35	3.69	27.06	30.45	54.00	23.55
375	41.3	QP	V	15.72	2.35	21.71	37.66	46.00	8.34


### Conducted Spurious Emissions at Antenna Port

#### 802.11b Low Channel




Date: 26.JUN.2014 01:00:37

#### 802.11b Middle Channel




Date: 26.JUN.2014 00:59:07

### 802.11b High Channel




Date: 26.JUN.2014 01:02:25

### 802.11g Low Channel




Date: 26.JUN.2014 01:07:29

### 802.11g Middle Channel



Date: 26.JUN.2014 01:10:50


### 802.11g High Channel



Date: 26.JUN.2014 01:12:25




### Chain0: 802.11n20 Low Channel




Date: 26.JUN.2014 01:15:35

### Chain0: 802.11n20 Middle Channel




Date: 26.JUN.2014 01:17:28

### Chain0: 802.11n20 High Channel




Date: 26.JUN.2014 01:19:02

### Chain1: 802.11n20 Low Channel




Date: 26.JUN.2014 01:37:32

### Chain1: 802.11n20 Middle Channel




Date: 26.JUN.2014 01:40:19

### Chain1: 802.11n20 High Channel




Date: 26.JUN.2014 01:44:13

Chain0: 802.11n40 Low Channel




Date: 26.JUN.2014 01:23:34

Chain0: 802.11n40 Middle Channel




Date: 26.JUN.2014 01:25:57

### Chain0: 802.11n40 High Channel




Date: 26.JUN.2014 01:28:53

### Chain1: 802.11n40 Low Channel




Date: 26.JUN.2014 01:46:25

### Chain1: 802.11n40 Middle Channel



Date: 26.JUN.2014 01:48:32

### Chain1: 802.11n40 High Channel



Date: 26.JUN.2014 01:52:10


## FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

### Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-08

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	27.4 °C
<b>Relative Humidity:</b>	68 %
<b>ATM Pressure:</b>	100 kPa

\* The testing was performed by Ares Liu on 2014-06-26.

**Test Result:** Pass.


Please refer to the following tables and plots.

*Test Mode: Transmitting*

Test Mode	Channel	Frequency	6 dB Bandwidth (MHz)		Limit
		(MHz)	Chain 0	Chain 1	(kHz)
802.11b	Low	2412	8.39	/	>500
	Middle	2437	8.79	/	>500
	High	2462	8.49	/	>500
802.11g	Low	2412	16.48	/	>500
	Middle	2437	16.53	/	>500
	High	2462	16.53	/	>500
802.11n20	Low	2412	17.68	17.63	>500
	Middle	2437	17.68	17.68	>500
	High	2462	17.73	17.73	>500
802.11n40	Low	2422	36.46	36.66	>500
	Middle	2437	36.56	36.56	>500
	High	2452	36.56	36.46	>500




### 802.11b Low Channel




Date: 26.JUN.2014 00:59:54

### 802.11b Middle Channel




Date: 26.JUN.2014 00:58:25

### 802.11b High Channel




Date: 26.JUN.2014 01:01:42

### 802.11g Low Channel




Date: 26.JUN.2014 01:06:35

### 802.11g Middle Channel




Date: 26.JUN.2014 01:10:03

### 802.11g High Channel




Date: 26.JUN.2014 01:11:33

### Chain 0: 802.11n20 Low Channel




Date: 26.JUN.2014 01:14:45

### Chain 0: 802.11n20 Middle Channel




Date: 26.JUN.2014 01:16:38

### Chain 0: 802.11n20 High Channel




Date: 26.JUN.2014 01:18:14

### Chain 1: 802.11n20 Low Channel




Date: 26.JUN.2014 01:36:43

### Chain 1: 802.11n20 Middle Channel




Date: 26.JUN.2014 01:39:29

### Chain 1: 802.11n20 High Channel




Date: 26.JUN.2014 01:43:22

**Chain 0: 802.11n40 Low Channel**




Date: 26.JUN.2014 01:22:25

**Chain 0: 802.11n40 Middle Channel**




Date: 26.JUN.2014 01:24:52

### Chain 0: 802.11n40 High Channel



Date: 26.JUN.2014 01:27:46


### Chain 1: 802.11n40 Low Channel



Date: 26.JUN.2014 01:45:26




### Chain 1: 802.11n40 Middle Channel



Date: 26.JUN.2014 01:47:33

### Chain 1: 802.11n40 High Channel



Date: 26.JUN.2014 01:51:05


## FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

### Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

1. According to KDB 558074 D01 DTS Meas Guidance v03r02, place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to a spectrum Analyzer.
3. Add a correction factor to the display.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-08

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	27.4 °C
<b>Relative Humidity:</b>	68 %
<b>ATM Pressure:</b>	100 kPa


\* The testing was performed by Ares Liu on 2014-06-26.

Test Mode: Transmitting

Test Mode	Channel	Frequency	Conducted Output Power (dBm)			Limit	Result
		(MHz)	Chain 0	Chain 1	Total	(dBm)	
802.11b	Low	2412	17.68	/	17.68	30	PASS
	Middle	2437	17.23	/	17.23	30	PASS
	High	2462	17.47	/	17.47	30	PASS
802.11g	Low	2412	17.69	/	17.69	30	PASS
	Middle	2437	17.38	/	17.38	30	PASS
	High	2462	17.65	/	17.65	30	PASS
802.11n20	Low	2412	17.45	17.40	20.44	30	PASS
	Middle	2437	17.14	17.20	20.18	30	PASS
	High	2462	17.32	17.46	20.41	30	PASS
802.11n40	Low	2422	17.44	17.19	20.33	30	PASS
	Middle	2437	17.49	17.40	20.46	30	PASS
	High	2452	17.64	17.24	20.45	30	PASS


Please refer to the following plots

### 802.11b RF Output Power, Low Channel




Date: 26.JUN.2014 01:00:15

### 802.11b RF Output Power, Middle Channel




Date: 26.JUN.2014 00:58:44

### 802.11b RF Output Power, High Channel




Date: 26.JUN.2014 01:02:02

### 802.11g RF Output Power, Low Channel




Date: 26.JUN.2014 01:07:03

### 802.11g RF Output Power, Middle Channel




Date: 26.JUN.2014 01:10:24

### 802.11g RF Output Power, High Channel




Date: 26.JUN.2014 01:11:59

### Chain0: 802.11n20 RF Output Power, Low Channel




Date: 26.JUN.2014 01:15:08

### Chain0: 802.11n20 RF Output Power, Middle Channel




Date: 26.JUN.2014 01:17:01

### Chain0: 802.11n20 RF Output Power, High Channel



Date: 26.JUN.2014 01:18:35


### Chain1: 802.11n20 RF Output Power, Low Channel



Date: 26.JUN.2014 01:37:05




### Chain1: 802.11n20 RF Output Power, Middle Channel




Date: 26.JUN.2014 01:39:52

### Chain1: 802.11n20 RF Output Power, High Channel




Date: 26.JUN.2014 01:43:46

### Chain0: 802.11n40 RF Output Power, Low Channel




Date: 26.JUN.2014 01:22:54

### Chain0: 802.11n40 RF Output Power, Middle Channel




Date: 26.JUN.2014 01:25:17

### Chain0: 802.11n40 RF Output Power, High Channel




Date: 26.JUN.2014 01:28:13

### Chain1: 802.11n40 RF Output Power, Low Channel




Date: 26.JUN.2014 01:45:45

### Chain1: 802.11n40 RF Output Power, Middle Channel



Date: 26.JUN.2014 01:47:52

### Chain1: 802.11n40 RF Output Power, High Channel



Date: 26.JUN.2014 01:51:30

## **FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**

### **Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### **Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### **Test Equipment List and Details**

<b>Manufacturer</b>	<b>Description</b>	<b>Model</b>	<b>Serial Number</b>	<b>Calibration Date</b>	<b>Calibration Due Date</b>
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-08

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### **Test Data**

#### **Environmental Conditions**


<b>Temperature:</b>	27.4 °C
<b>Relative Humidity:</b>	68 %
<b>ATM Pressure:</b>	100 kPa

\* The testing was performed by Ares Liu on 2014-06-26.

#### **Test Result: Compliance**


Please refer to following table and plots.

### 802.11b: Band Edge, Left Side




Date: 26.JUN.2014 01:00:49

### 802.11b: Band Edge, Right Side




Date: 26.JUN.2014 01:02:37

**802.11g: Band Edge, Left Side**




Date: 26.JUN.2014 01:07:42

**802.11g: Band Edge, Right Side**




Date: 26.JUN.2014 01:12:37

**Chain0: 802.11n20 Band Edge, Left Side**



Date: 26.JUN.2014 01:15:47


**Chain0: 802.11n20 Band Edge, Right Side**



Date: 26.JUN.2014 01:19:14




**Chain1: 802.11n20 Band Edge, Left Side**




Date: 26.JUN.2014 01:37:45

**Chain1: 802.11n20 Band Edge, Right Side**




Date: 26.JUN.2014 01:44:25

**Chain0: 802.11n40 Band Edge, Left Side**




Date: 26.JUN.2014 01:23:46

**Chain0: 802.11n40 Band Edge, Right Side**




Date: 26.JUN.2014 01:29:05

**Chain1: 802.11n40 Band Edge, Left Side**



Date: 26.JUN.2014 01:46:37

**Chain1: 802.11n40 Band Edge, Right Side**



Date: 26.JUN.2014 01:52:23

## FCC §15.247(e) - POWER SPECTRAL DENSITY

### Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the RBW = 3 kHz, VBW = 10 kHz, Set the span to 1.5 times the DTS bandwidth.
4. Use the peak marker function to determine the maximum amplitude level.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-08

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

Temperature:	27.4 °C
Relative Humidity:	68 %
ATM Pressure:	100 kPa

\* The testing was performed by Ares Liu on 2014-06-26.


*Test Mode: Transmitting*

**Test Result: Pass**

Test Mode	Channel	PSD (dBm/3kHz)			Limit (dBm/3kHz)	Result
		Chain 0	Chain 1	Total		
802.11b	Low	-10.21	/	-10.21	8	Pass
	Middle	-11.46	/	-11.46	8	Pass
	High	-10.34	/	-10.34	8	Pass
802.11g	Low	-17.34	/	-17.34	8	Pass
	Middle	-18.77	/	-18.77	8	Pass
	High	-18.16	/	-18.16	8	Pass
802.11n20	Low	-17.54	-17.72	-14.62	8	Pass
	Middle	-18.12	-18.37	-15.23	8	Pass
	High	-18.44	-17.79	-15.09	8	Pass
802.11n40	Low	-21.34	-21.71	-18.51	8	Pass
	Middle	-20.90	-21.17	-18.02	8	Pass
	High	-21.35	-20.59	-17.94	8	Pass


Please refer to the following plots

### Power Spectral Density, 802.11b Low Channel




Date: 26.JUN.2014 01:00:24

### Power Spectral Density, 802.11b Middle Channel




Date: 26.JUN.2014 00:58:53

### Power Spectral Density, 802.11b High Channel




Date: 26.JUN.2014 01:02:11

### Power Spectral Density, 802.11g Low Channel




Date: 26.JUN.2014 01:07:16

### Power Spectral Density, 802.11g Middle Channel



Date: 26.JUN.2014 01:10:37


### Power Spectral Density, 802.11g High Channel



Date: 26.JUN.2014 01:12:12




### Chain0: Power Spectral Density, 802.11n20 Low Channel




Date: 26.JUN.2014 01:15:22

### Chain0: Power Spectral Density, 802.11n20 Middle Channel




Date: 26.JUN.2014 01:17:15

### Chain0: Power Spectral Density, 802.11n20 High Channel




Date: 26.JUN.2014 01:18:48

### Chain1: Power Spectral Density, 802.11n20 Low Channel




Date: 26.JUN.2014 01:37:19

### Chain1: Power Spectral Density, 802.11n20 Middle Channel




Date: 26.JUN.2014 01:40:06

### Chain1: Power Spectral Density, 802.11n20 High Channel




Date: 26.JUN.2014 01:44:00

### Chain0: Power Spectral Density, 802.11n40 Low Channel




Date: 26.JUN.2014 01:23:20

### Chain0: Power Spectral Density, 802.11n40 Middle Channel




Date: 26.JUN.2014 01:25:43

### Chain0: Power Spectral Density, 802.11n40 High Channel




Date: 26.JUN.2014 01:28:40

### Chain1: Power Spectral Density, 802.11n40 Low Channel




Date: 26.JUN.2014 01:46:12

### Chain1: Power Spectral Density, 802.11n40 Middle Channel



Date: 26.JUN.2014 01:48:18

### Chain1: Power Spectral Density, 802.11n40 High Channel



Date: 26.JUN.2014 01:51:57

\*\*\*\*\* END OF REPORT \*\*\*\*\*