

## FCC PART 15.249

## TEST REPORT

For

### Shenzhen Rapoo Technology Co., Ltd.

22, Jinxiu Road East, Pingshan District, Shenzhen, China

**FCC ID: PP2E9090P**

<b>Report Type:</b> Original Report		<b>Product Type:</b> Touch Illuminated Keyboard	
<b>Test Engineer:</b>	Leon.Chen	<i>leon chen</i>	
<b>Report Number:</b>	R2DG140307007-00		
<b>Report Date:</b>	2014-03-27		
<b>Reviewed By:</b>	Ivan Cao RF Leader	<i>Ivan Cao</i>	
<b>Test Laboratory:</b>	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>		

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## TABLE OF CONTENTS

<b>GENERAL INFORMATION</b> .....	<b>3</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
OBJECTIVE .....	3
TEST METHODOLOGY .....	3
TEST FACILITY .....	3
<b>SYSTEM TEST CONFIGURATION</b> .....	<b>4</b>
JUSTIFICATION .....	4
EUT EXERCISE SOFTWARE .....	4
EQUIPMENT MODIFICATIONS .....	4
BLOCK DIAGRAM OF TEST SETUP .....	4
<b>SUMMARY OF TEST RESULTS</b> .....	<b>5</b>
<b>FCC§15.203 - ANTENNA REQUIREMENT</b> .....	<b>6</b>
APPLICABLE STANDARD .....	6
ANTENNA CONNECTOR CONSTRUCTION .....	6
<b>FCC§15.205, §15.209&amp;§15.249- RADIATED EMISSIONS</b> .....	<b>7</b>
APPLICABLE STANDARD .....	7
MEASUREMENT UNCERTAINTY .....	7
EUT SETUP .....	8
TEST EQUIPMENT SETUP .....	9
TEST PROCEDURE .....	9
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	9
TEST EQUIPMENT LIST AND DETAILS.....	10
TEST RESULTS SUMMARY .....	10
TEST DATA .....	10
<b>FCC §15.215(C)– 20 DB BANDWIDTH TESTING</b> .....	<b>12</b>
APPLICABLE STANDARD .....	12
TEST PROCEDURE .....	12
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST DATA .....	12

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *Shenzhen Rapoo Technology Co., Ltd.* 's product, model number: *E9090P (FCC ID: PP2E9090P)* (the "EUT") in this report was a *Touch Illuminated Keyboard*, which was measured approximately: 40 cm (L) x 15 cm (W) x 1.8 cm (H), rated input voltage: DC 3.7V from lithium battery or charged by wireless charge.

\* All measurement and test data in this report was gathered from production sample serial number: 140307007 (Assigned by BACL, Dongguan). The EUT was received on 2014-03-07.

### Objective

This type approval report was prepared on behalf of *Shenzhen Rapoo Technology Co., Ltd.* in accordance with Part 2-Subpart J, and Part 15-Subparts A, B and C of the Federal Communications Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.249 rules.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Dongguan).

### Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## SYSTEM TEST CONFIGURATION

### Justification

The system was configured for testing in Engineering Mode, which was provided by the manufacturer. The engineering mode was configured as maximum power and switched the channels by keys.

16 channels were provided by the manufacturer:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	5727	5	5750	9	5771	13	5796
2	5730	6	5753	10	5776	14	5799
3	5734	7	5756	11	5779	15	5802
4	5738	8	5759	12	5782	16	5804

EUT was tested with Channel 5727MHz, 5771MHz and 5804MHz.


### EUT Exercise Software

No software was used in the test.

### Equipment Modifications

No modifications were made to the unit tested.

### Block Diagram of Test Setup



**SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207(a)	Conduction Emissions	Not Applicable*
15.205, §15.209, §15.249	Radiated Emissions	Compliance
§15.215 (c)	20 dB Bandwidth	Compliance

Not Applicable\*: the EUT was powered by lithium battery in normal operation.

---

## **FCC§15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

### **Antenna Connector Construction**

The EUT has an internal antenna permanently soldering on the printed circuit board, which complied with 15.203, the maximum gain was 1.4 dBi. Please refer to the internal photos.

**Result:** Compliant.

## **FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS**

### **Applicable Standard**

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

<b>Fundamental frequency</b>	<b>Field strength of fundamental (millivolts/meter)</b>	<b>Field strength of harmonics (microvolts/meter)</b>
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

### **Measurement Uncertainty**

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If  $U_{lab}$  is less than or equal to  $U_{cispr}$  of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If  $U_{lab}$  is greater than  $U_{cispr}$  of Table 1, then:

- compliance is deemed to occur if no measured disturbance level, increased by  $(U_{lab} - U_{cispr})$ , exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by  $(U_{lab} - U_{cispr})$ , exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:

30M~200MHz: 5.0 dB

200M~1GHz: 6.2 dB

1G~6GHz: 4.45 dB


6G~18GHz: 5.23 dB

Table 1 – Values of  $U_{cispr}$


Measurement	$U_{cispr}$
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

**EUT Setup**

Below 1 GHz:



Above 1 GHz:



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.



The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

### Test Equipment Setup

The system was investigated from 30 MHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz – 1000 MHz	120 kHz	300 kHz	120kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

### Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detection mode from 30MHz to 1GHz, Peak and average detection mode above 1 GHz.

### Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Extrapolation result}$$

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100035	2013-05-06	2014-05-05
Sunol Sciences	Antenna	JB3	A060611-2	2011-09-06	2014-09-05
HP	Amplifier	8447D	2727A05902	2013-09-06	2014-09-05
R&S	Spectrum Analyzer	FSEM	DE31388	2013-05-07	2014-05-06
ETS-Lindgren	Horn Antenna	3115	000 527 35	2012-09-06	2015-09-05
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2014-02-19	2015-02-18
R&S	Spectrum Analyzer	FSP 38	100478	2013-06-16	2014-06-15
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2013-06-16	2014-06-15
Ducommun Technologies	Horn Antenna	ARH-2823-02	1007726-01 1302	2013-06-16	2014-06-15
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2013-09-06	2014-09-05

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Results Summary**

According to the data in the following table, the EUT complied with the FCC Part 15.209 &15.205 & 15.249, with the worst margin reading of:

**4.13 dB at 17181MHz in the Vertical polarization**

**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	24.2 °C
<b>Relative Humidity:</b>	65 %
<b>ATM Pressure:</b>	100.9 kPa

\* *The testing was performed by Leon Chen on 2014-03-26.*

Test Mode: Transmitting

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB(1/m))					
<b>frequency: 5727MHz</b>									
5727	74.53	PK	V	32.15	6.04	26.62	86.10	114.00	27.90
5727	56.21	AV	V	32.15	6.04	26.62	67.78	94.00	26.22
5727	71.74	PK	H	32.15	6.04	26.62	83.31	114.00	30.69
5727	46.88	AV	H	32.15	6.04	26.62	58.45	94.00	35.55
5725	54.79	PK	V	32.15	6.04	26.63	66.35	74.00	7.65
5725	23.33	AV	V	32.15	6.04	26.63	34.89	54.00	19.11
11454	35.35	PK	V	37.85	9.79	26.17	56.82	74.00	17.18
11454	20.56	AV	V	37.85	9.79	26.17	42.03	54.00	11.97
17181	31.78	PK	V	40.59	14.31	25.58	61.10	74.00	12.90
17181	20.55	AV	V	40.59	14.31	25.58	49.87	54.00	4.13*
1328.62	30.28	PK	V	23.15	2.98	26.93	29.48	74.00	44.52
1328.62	20.17	AV	V	23.15	2.98	26.93	19.37	54.00	34.63
3266.15	30.44	PK	V	28.05	6.13	27.31	37.31	74.00	36.69
3266.15	20.18	AV	V	28.05	6.13	27.31	27.05	54.00	26.95
159.01	26.8	QP	V	12.81	1.53	21.44	19.70	43.50	23.80
<b>frequency: 5771MHz</b>									
5771	71.65	PK	V	32.15	6.12	26.57	83.35	114.00	30.65
5771	57.77	AV	V	32.15	6.12	26.57	69.47	94.00	24.53
5771	71.26	PK	H	32.15	6.12	26.57	82.96	114.00	31.04
5771	47.45	AV	H	32.15	6.12	26.57	59.15	94.00	34.85
11542	35.29	PK	V	37.90	9.81	26.10	56.90	74.00	17.10
11542	20.45	AV	V	37.90	9.81	26.10	42.06	54.00	11.94
17313	30.36	PK	V	41.38	13.60	25.63	59.71	74.00	14.29
17313	20.27	AV	V	41.38	13.60	25.63	49.62	54.00	4.38*
1328.62	30.69	PK	V	23.15	2.98	26.93	29.89	74.00	44.11
1328.62	20.26	AV	V	23.15	2.98	26.93	19.46	54.00	34.54
3266.15	30.28	PK	V	28.05	6.13	27.31	37.15	74.00	36.85
3266.15	20.54	AV	V	28.05	6.13	27.31	27.41	54.00	26.59
3628.67	30.16	PK	V	29.08	5.00	27.29	36.95	74.00	37.05
3628.67	20.37	AV	V	29.08	5.00	27.29	27.16	54.00	26.84
159.01	26.5	QP	V	12.81	1.53	21.44	19.40	43.50	24.10
<b>frequency: 5804MHz</b>									
5804	71.2	PK	H	32.16	6.15	26.55	82.96	114.00	31.04
5804	56.27	AV	H	32.16	6.15	26.55	68.03	94.00	25.97
5804	74.81	PK	V	32.16	6.15	26.55	86.57	114.00	27.43
5804	47.83	AV	V	32.16	6.15	26.55	59.59	94.00	34.41
5875	38.26	PK	V	32.18	6.31	26.75	50.00	74.00	24.00
5875	19.05	AV	V	32.18	6.31	26.75	30.79	54.00	23.21
11608	33.86	PK	V	37.90	9.70	26.00	55.46	74.00	18.54
11608	20.14	AV	V	37.90	9.70	26.00	41.74	54.00	12.26
17412	30.65	PK	V	41.97	13.07	25.59	60.10	74.00	13.90
17412	20.18	AV	V	41.97	13.07	25.59	49.63	54.00	4.37*
1328.62	30.55	PK	V	23.15	2.98	26.93	29.75	74.00	44.25
1328.62	20.68	AV	V	23.15	2.98	26.93	19.88	54.00	34.12
3266.15	30.39	PK	V	28.05	6.13	27.31	37.26	74.00	36.74
3266.15	20.43	AV	V	28.05	6.13	27.31	27.30	54.00	26.70
159.01	26.8	QP	V	12.81	1.53	21.44	19.70	43.50	23.80

\*Within measurement uncertainty!

## FCC §15.215(c)– 20 dB BANDWIDTH TESTING

### Applicable Standard

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2013-06-16	2014-06-15
ETS-Lindgren	Horn Antenna	3115	000 527 35	2012-09-06	2015-09-05
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2014-02-19	2015-02-18

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	20.6 °C
<b>Relative Humidity:</b>	38 %
<b>ATM Pressure:</b>	100.6 kPa

\* The testing was performed by Leon Chen on 2014-03-27.


**Test Result:** Compliance.

Please refer to following tables and plots

Test Mode: Transmitting


Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	5727	1.64
Middle	5771	1.64
High	5804	1.64

Please refer to the following plots.




Date: 27.MAR.2014 09:21:12

### Middle Channel



Date: 27.MAR.2014 09:19:09

### High Channel



Date: 27.MAR.2014 09:21:56

\*\*\*\*\* END OF REPORT \*\*\*\*\*