



SAR EVALUATION REPORT

For

Atheros Communications, Inc.

1700 Technology Drive,
San Jose, CA 95110, USA

FCC ID: PPD-ARS263
IC: 4104A-ARS263

Report Type: CIIPC	Product Type: 1x1 802.11a/b/g/b+BT SDIO-WLAN/USB-BT Card
Test Engineer:	Quinn Jiang 
Report Number:	R1104055-SAR
Report Date:	2011-05-03
Reviewed By:	Victor Zhang RF Lead 
Prepared By: (91)	Bay Area Compliance Laboratories Corp. 1274 Anvilwood Avenue, Sunnyvale, CA 94089, USA Tel: (408) 732-9162 Fax: (408) 732 9164

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, NIST, or any agency of the Federal Government.
* This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "*" Rev.2

Summary of Test Results		
Rule Part(s):	FCC §2.1093 IC RSS-102, Issue 4	
Test Procedure(s):	FCC OET 65-C; IEEE 1528-2003 IC RSS-102, Issue 4	
Device Category: Exposure Category:	Portable Device General Population/Uncontrolled Exposure	
Device Type:	1x1 802.11a/b/g/n + BT SDIO-WLAN/USB-BT Card	
Modulation Type:	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM	
TX Frequency Range:	Bluetooth: 2402-2480 MHz DTS: 802.11 b/g/n20: 2412-2462 MHz (11 CH) 802.11a/n20: 5745-5825 MHz (5 CH) 802.11n40: 5755-5795 MHz (2 CH) NII: 802.11 a/n20: 5180-5320 MHz (8 CH), 5500-5700 MHz (11 CH) 802.11n40: 5190-5310 MHz (4 CH), 5510-5670 MHz (5 CH)	
Conducted RF Out Power:	DTS: 802.11b: 17.3 dBm 802.11g: 17.1 dBm 802.11n20: 16.2 dBm (2.4 GHz); 16.4 dBm (5.8 GHz) 802.11a: 17.2 dBm 802.11n40: 14 dBm	
	NII: 802.11a: 17.5 dBm (5180-5320 MHz) 802.11n20: 16.4 dBm (5180-5320 MHz) 802.11n40: 14.1 dBm (5180-5320 MHz) 802.11a: 17.2 dBm (5500-5700 MHz) 802.11n20: 16.5 dBm (5500-5700 MHz) 802.11n40: 14.0 dBm (5500-5700 MHz)	
Antenna Type(s):	Integrated Antenna	
Body-Worn Accessories:	None	
Face-Head Accessories:	None	
Battery Type (s):	Li-Ion rechargeable Battery: 14.8V/2900mAh (Host PC)	
Max. SAR Level (s) Measured:	0.328 W/Kg, Body 1g Tissue (802.11b)	2.4 GHz
	0.385 W/Kg, Body 1g Tissue (802.11a)	5 GHz
	0.202 W/Kg, Body 1g Tissue (802.11n40)	

TABLE OF CONTENTS

1	GENERAL DESCRIPTION	5
1.1	PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2	EUT TECHNICAL SPECIFICATION	5
2	TEST FACILITY	6
3	REFERENCE, STANDARDS AND GUIDELINES	7
3.1	SAR LIMITS	8
4	DESCRIPTION OF TEST SYSTEM	9
4.1	RECOMMENDED TISSUE DIELECTRIC PARAMETERS	10
4.2	MEASUREMENT SYSTEM DIAGRAM	11
4.3	SYSTEM COMPONENTS	12
4.4	DASY4 MEASUREMENT SERVER.....	12
4.5	DATA ACQUISITION ELECTRONICS	13
4.6	PROBES	13
4.7	ET3DV6 PROBE SPECIFICATION.....	13
4.8	E-FIELD PROBE CALIBRATION PROCESS	14
4.9	DATA EVALUATION	15
4.10	LIGHT BEAM UNIT	16
4.11	MEDIUM.....	16
4.12	SAM TWIN PHANTOM	17
4.13	DEVICE HOLDER FOR SAM TWIN PHANTOM	18
4.14	SYSTEM VALIDATION KITS	18
4.15	ROBOT	19
5	EQUIPMENT LIST AND CALIBRATION	20
5.1	EQUIPMENTS LIST & CALIBRATION INFO.....	20
6	SAR MEASUREMENT SYSTEM VERIFICATION	21
6.1	SYSTEM ACCURACY VERIFICATION	21
6.2	SETUP FOR SYSTEM VERIFICATION	21
6.3	SYSTEM CHECK TARGET VALUE.....	21
7	EUT TEST STRATEGY AND METHODOLOGY	23
7.1	TEST POSITIONS FOR DEVICE OPERATING NEXT TO A PERSON’S EAR.....	23
7.2	CHEEK/TOUCH POSITION	24
7.3	EAR/TILT POSITION.....	24
7.4	TEST POSITIONS FOR BODY-WORN AND OTHER CONFIGURATIONS	25
7.5	SAR EVALUATION PROCEDURE.....	26
8	DASY4 SAR EVALUATION PROCEDURE	27
8.1	POWER REFERENCE MEASUREMENT	27
8.2	AREA SCAN.....	27
8.3	ZOOM SCAN	28
8.4	POWER DRIFT MEASUREMENT	28
8.5	Z-SCAN.....	28
9	RF OUTPUT VERIFICATION	29
9.1	TEST RESULTS	29
10	SAR MEASUREMENT RESULTS	31
10.1	TEST ENVIRONMENTAL CONDITIONS	31

11 APPENDIX A – MEASUREMENT UNCERTAINTY.....34

12 APPENDIX B – PROBE CALIBRATION CERTIFICATES35

13 APPENDIX C – DIPOLE CALIBRATION CERTIFICATES55

14 APPENDIX D - TEST SYSTEM VERIFICATIONS SCANS67

14.1 LIQUID AND SYSTEM VALIDATION.....67

15 APPENDIX E – EUT SCAN RESULTS76

16 APPENDIX F – TEST SETUP PHOTOS.....103

16.1 TABLET PC BACK SIDE TOUCH TO THE FLAT PHANTOM SETUP PHOTO.....103

16.2 TABLET PC LEFT SIDE TOUCH TO THE FLAT PHANTOM SETUP PHOTO103

16.3 TABLET PC RIGHT SIDE TOUCH TO THE FLAT PHANTOM SETUP PHOTO104

17 APPENDIX G – EUT PHOTOS.....105

17.1 WLAN MODULE VIEW (FRONT SIDE WITH SHIELD).....105

17.2 WLAN MODULE VIEW (BACK SIDE).....105

17.3 WLAN MODULE VIEW (FRONT SIDE WITHOUT SHIELD)106

17.4 TABLET PC -FRONT VIEW.....106

17.5 TABLET PC -BACK VIEW107

17.6 TABLET PC - BOTTOM SIDE VIEW107

17.7 TABLET PC - RIGHT SIDE VIEW108

17.8 TABLET PC - LEFT SIDE VIEW108

17.9 TABLET PC - TOP SIDE VIEW109

17.10 WLAN MODULE BUILT INTO THE TABLET PC (MOTION FWS-001)109

18 APPENDIX H - INFORMATIVE REFERENCES.....110

1 GENERAL DESCRIPTION

1.1 Product Description for Equipment Under Test (EUT)

This test and measurement report was prepared on behalf of Atheros Communications, Inc. and their product, *model: NL900S*, which will henceforth be referred to as the EUT “Equipment Under Test”. The EUT is 802.11a/b/g/n and BT SDIO-WLAN/USB-BT Mini Card built into Motion Tablet PC CL900 (Model Number: FWS-001) that operates at 2.4 GHz and 5 GHz.

1.2 EUT Technical Specification

Item	Description
Modulation	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Frequency Range	Bluetooth: 2402-2480 MHz DTS: 802.11 b/g/n20: 2412-2462 MHz (11 CH) 802.11a/n20: 5745-5825 MHz (5 CH) 802.11n40: 5755-5795 MHz (2 CH) NII: 802.11 a/n20: 5180-5320 MHz (8 CH), 5500-5700 MHz (11 CH) 802.11n40: 5190-5310 MHz (4 CH), 5510-5670 MHz (5 CH)
Output Power	DTS: 802.11b: 17.3 dBm 802.11g: 17.1 dBm 802.11n20: 16.2 dBm (2.4 GHz); 16.4 dBm (5.8 GHz) 802.11a: 17.2 dBm 802.11n40: 14 dBm NII: 802.11a: 17.5 dBm (5180-5320 MHz) 802.11n20: 16.4 dBm (5180-5320 MHz) 802.11n40: 14.1 dBm (5180-5320 MHz) 802.11a: 17.2 dBm (5500-5700 MHz) 802.11n20: 16.5 dBm (5500-5700 MHz) 802.11n40: 14.0 dBm (5500-5700 MHz)
Dimensions (L*W*H)	WLAN Mini Card: 27mm(L)×30mm(W)×3mm (H) Tablet PC: 179.2mm(L)×276.7mm(W)×15mm(H)
Power Source	Li-Ion: 14.8V/2900mAh
Weight	3g (Mimi Card) 968g (Tablet PC with battery)
Normal Operation	Tablet-Lap Held (Bottom face)

The test data gathered are from typical production sample, serial number: R1104055, provided by BAACL.

2 TEST FACILITY

The test site used by Bay Area Compliance Laboratories Corp. (BACL) to collect data is located at 1274 Anvilwood Ave, Sunnyvale, California 94089, USA.

BACL is a National Institute of Standards and Technology (NIST) accredited laboratory under the National Voluntary Laboratory Accredited Program (Lab Code 200167-0).



The current scope of accreditations can be found at: <http://ts.nist.gov/Standards/scopes/2001670.htm>

3 REFERENCE, STANDARDS AND GUIDELINES

FCC:

The Report and Order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g as recommended by the ANSI/IEEE standard C95.1-1992 [6] for an uncontrolled environment (Paragraph 65). According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in North America is 1.6 mW/g average over 1 gram of tissue mass.

CE:

The CE requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 2 mW/g as recommended by the EN50360 for an uncontrolled environment. According to the Standard, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits? SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in Europe is 2 mW/g average over 10 gram of tissue mass.

The test configurations were laid out on a specially designed test fixture to ensure the reproducibility of measurements. Each configuration was scanned for SAR. Analysis of each scan was carried out to characterize the above effects in the device.

3.1 SAR Limits

FCC Limit (1g Tissue)

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1 g of tissue)	1.60	8.0
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0

CE Limit (10g Tissue)

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1 g of tissue)	2.0	10
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

General Population/Uncontrolled environments Spatial Peak limit 1.6 W/kg (FCC) & 2 W/kg (CE) applied to the EUT.

4 DESCRIPTION OF TEST SYSTEM

These measurements were performed with the automated near-field scanning system DASY4 from Schmid & Partner Engineering AG (SPEAG) which is the fourth generation of the system shown in the figure hereinafter:



The system is based on a high precision robot (working range greater than 0.9m), which positions the probes with a positional repeatability of better than $\pm 0.02\text{mm}$. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit.

The SAR measurements were conducted with the dosimetric probe ET3DV6 SN: 1604 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure with accuracy of better than $\pm 10\%$. The spherical isotropy was evaluated with the procedure and found to be better than $\pm 0.25\text{dB}$.


The phantom used was the Generic Twin Phantom". The ear was simulated as a spacer of 4 mm thickness between the earpiece of the phone and the tissue simulating liquid. The Tissue simulation liquid used for each test is in according with the FCC OET65 supplement C as listed below.

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton x-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

4.1 Recommended Tissue Dielectric Parameters

Frequency (MHz)	Head Tissue		Body Tissue	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800-2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5200	36.0	4.66	49.0	5.30
5500	35.6	4.96	48.6	5.65
5800	35.3	5.27	48.2	6.00

4.2 Measurement System Diagram



The DASY4 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stäubli RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 2000 or Windows XP.
- DASY4 software.

- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing system validation.

4.3 System Components

- DASY4 Measurement Server
- Data Acquisition Electronics
- Probes
- Light Beam Unit
- Medium
- SAM Twin Phantom
- Device Holder for SAM Twin Phantom
- System Validation Kits
- Robot

4.4 DASY4 Measurement Server

The DASY4 measurement server is based on a PC/104 CPU board with a 166MHz low-power Pentium, 32MB chip disk and 64MB RAM. The necessary circuits for communication with either the DAE4 (or DAE3) electronic box as well as the 16-bit AD-converter system for optical detection and digital I/O interface are contained on the DASY4 I/O-board, which is directly connected to the PC/104 bus of the CPU board.



The measurement server performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. The PC-operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with two expansion slots which are reserved for future applications. Please note that the expansion slots do not have a standardized pin out and therefore only the expansion cards provided by SPEAG can be inserted. Expansion cards from any other supplier could seriously damage the measurement server.

4.5 Data Acquisition Electronics

The data acquisition electronics DAE3 consists of a highly sensitive electrometer grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.



4.6 Probes


The DASY system can support many different probe types.

Dosimetric Probes: These probes are specially designed and calibrated for use in liquids with high permittivities. They should not be used in air, since the spherical isotropy in air is poor (± 2 dB). The dosimetric probes have special calibrations in various liquids at different frequencies.

Free Space Probes: These are electric and magnetic field probes specially designed for measurements in free space. The z-sensor is aligned to the probe axis and the rotation angle of the x-sensor is specified. This allows the DASY system to automatically align the probe to the measurement grid for field component measurement. The free space probes are generally not calibrated in liquid. (The H-field probes can be used in liquids without any change of parameters.)


4.7 ET3DV6 Probe Specification

Construction Symmetrical design with triangular core
 Built-in optical fiber for surface detection System
 Built-in shielding against static charges
 Calibration In air from 10 MHz to 2.5 GHz
 In brain and muscle simulating tissue at
 Frequencies of 450 MHz, 900 MHz and
 1.8 GHz (accuracy $\pm 8\%$)
 Frequency 10 MHz to > 6 GHz; Linearity: ± 0.2 dB
 (30 MHz to 3 GHz)
 Directivity ± 0.2 dB in brain tissue (rotation around probe axis)
 ± 0.4 dB in brain tissue (rotation normal probe axis)
 Dynamic 5 mW/g to > 100 mW/g;
 Range Linearity: ± 0.2 dB
 Surface ± 0.2 mm repeatability in air and clear liquids
 Detection over diffuse reflecting surfaces.
 Dimensions Overall length: 330 mm
 Tip length: 16 mm
 Body diameter: 12 mm
 Tip diameter: 6.8 mm
 Distance from probe tip to dipole centers: 2.7 mm
 Application General dosimetric up to 3 GHz
 Compliance tests of mobile phones
 Fast automatic scanning in arbitrary phantoms



Photograph of the probe

The SAR measurements were conducted with the dosimetric probe ET3DV6 designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multi-fiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY3 software reads the reflection during a software approach and looks for the maximum using a 2nd order fitting. The approach is stopped when reaching the maximum.



**Inside view of
ET3DV6 E-field Probe**

4.8 E-Field Probe Calibration Process

Each probe is calibrated according to a dosimetric assessment procedure described in [6] with accuracy better than $\pm 10\%$. The spherical isotropy was evaluated with the procedure described in [7] and found to be better than $\pm 0.25\text{dB}$. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz, and in a waveguide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

4.9 Data Evaluation

The DASY4 postprocessing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Normi, ai0, ai1, ai2
	- Conversion factor	ConvFi
	- Diode compression point	dcp _i
Device parameters:	- Frequency	f
	- Crest factor	cf
Media parameters:	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

With V_i = compensated signal of channel i (i =x, y, z)
 U_i = input signal of channel i (i =x, y, z)
 cf = crest factor of exciting field (DASY parameter)
 dcp_i = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$\text{E - fieldprobes : } E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

$$\text{H - fieldprobes : } H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

With V_i = compensated signal of channel i (i =x, y, z)
 Norm_i = sensor sensitivity of channel i (i =x, y, z)
 μV/ (V/m)² for E-field probes
 ConF = sensitivity enhancement in solution
 a_{ij} = sensor sensitivity factors for H-field probes
 f = carrier frequency [GHz]
 E_i = electric field strenggy of channel i in V/m
 H_i = diode compression point (DASY parameter)

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1'000}$$

With SAR = local specific absorption rate in mW/g
 E_{tot} = total field strength in V/m
 σ = conductivity in [mho/meter] or [Siemens/meter]
 ρ = equivalent tissue density in g/cm³

Note that the density is normally set to 1, to account for actual brain density rather than the density of the simulation liquid.

4.10 Light Beam Unit

The light beam switch allows automatic “tooling” of the probe. During the process, the actual position of the probe tip with respect to the robot arm is measured, as well as the probe length and the horizontal probe offset. The software then corrects all movements, so that the robot coordinates are valid for the probe tip. The repeatability of this process is better than 0.1 mm. If a position has been taught with an aligned probe, the same position will be reached with another aligned probe within 0.1 mm, even if the other probe has different dimensions. During probe rotations, the probe tip will keep its actual position.

4.11 Medium

Parameters

The parameters of the tissue simulating liquid strongly influence the SAR in the liquid. The parameters for the different frequencies are defined in the corresponding compliance standards (e.g., EN 50361, IEEE 1528-2003).

Parameter measurements

Several measurement systems are available for measuring the dielectric parameters of liquids:

- The open coax test method (e.g., HP85070 dielectric probe kit) is easy to use, but has only moderate accuracy. It is calibrated with open, short, and deionized water and the calibrations a critical process.
- The transmission line method (e.g., model 1500T from DAMASKOS, INC.) measures the transmission and reflection in a liquid filled high precision line. It needs standard two port calibration and is probably more accurate than the open coax method.

- The reflection line method measures the reflection in a liquid filled shorted precision lined. The method is not suitable for these liquids because of its low sensitivity.
- The slotted line method scans the field magnitude and phase along a liquid filled line. The evaluation is straight forward and only needs a simple response calibration. The method is very accurate, but can only be used in high loss liquids and at frequencies above 100 to 200MHz. Cleaning the line can be tedious.

4.12 SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region where shell thickness increases to 6mm). It has three measurement areas:

- Left hand
- Right hand
- Flat phantom

The phantom table comes in two sizes: A 100 x 50 x 85 cm (L x W x H) table for use with free standing robots (DASY4 professional system option) or as a second phantom and a 100 x 75 x 85 cm(L x W x H) table with reinforcements for table mounted robots (DASY4 compact system option) .

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. Only one device holder is necessary if two phantoms are used (e.g., for different liquids) A white cover is provided to tap the phantom during o₂-periods to prevent water evaporation and changes in the liquid parameters. Free space scans of devices on the cover are possible. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

The phantom can be used with the following tissue simulating liquids:


- Water-sugar based liquids can be left permanently in the phantom. Always cover the liquid if the system is not used, otherwise the parameters will change due to water evaporation.
- Glycol based liquids should be used with care. As glycol is a softener for most plastics, the liquid should be taken out of the phantom and the phantom should be dried when the system is not used (desirable at least once a week).
- Do not use other organic solvents without previously testing the phantom's compatibility.



4.13 Device Holder for SAM Twin Phantom

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source in 5mm distance, a positioning uncertainty of $\pm 0.5\text{mm}$ would produce a SAR uncertainty of $\pm 20\%$. An accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions, in which the devices must be measured, are defined by the standards.

The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation centers for both scales are the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.



The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon_r=3$ and loss tangent $\tan \delta=0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.

4.14 System Validation Kits

Each DASY system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the DASY software, enable the user to conduct the system performance check and system validation. For that purpose a well defined SAR distribution in the flat section of the SAM twin phantom is produced.

System validation kit includes a dipole, tripod holder to fix it underneath the flat phantom and a corresponding distance holder. Dipoles are available for the variety of frequencies between 300MHz and 6 GHz (dipoles for other frequencies or media and other calibration conditions are available upon request).

The dipoles are highly symmetric and matched at the center frequency for the specified liquid and distance to the flat phantom (or flat section of the SAM-twin phantom). The accurate distance between the liquid surface and the dipole center is achieved with a distance holder that snaps on the dipole.

4.15 Robot

The DASY4 system uses the high precision industrial robots RX60L, RX90 and RX90L, as well as the RX60BL and RX90BL types out of the newer series from Stäubli SA (France). The RX robot series offers many features that are important for our application:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance-free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchronous motors; no stepper motors)
- Low ELF interference (the closed metallic construction shields against motor control fields)

For the newly delivered DASY4 systems as well as for the older DASY3 systems delivered since 1999, the CS7MB robot controller version from Stäubli is used. Previously delivered systems have either a CS7 or CS7M controller; the differences to the CS7MB are mainly in the hardware, but some procedures in the robot software from Stäubli are also not completely the same. The following descriptions about robot hard- and software correspond to CS7MB controller with software version 13.1 (edit S5). The actual commands, procedures and configurations, also including details in hardware, might differ if an older robot controller is in use. In this case please also refer to the Stäubli manuals for further information.



5 EQUIPMENT LIST AND CALIBRATION

5.1 Equipments List & Calibration Info

Type / Model	Cal. Due Date	S/N
DASY4 Professional Dosimetric System	N/A	N/A
Robot RX60L	N/A	CS7MBSP / 467
Robot Controller	N/A	F01/5J72A1/A/01
Dell Computer Dimension 3000	N/A	N/A
SPEAG EDC3	N/A	N/A
SPEAG DAE3	2011-12-07	456
DASY4 Measurement Server	N/A	1176
SPEAG E-Field Probe ET3DV6	2011-09-16	1604
SPEAG E-Field Probe EX3DV4	2011-09-18 ¹	3619
Antenna, Dipole, D-2450-S-1	2011-07-14	BCL-141
Antenna, Dipole, D5100V2	2011-12-24	1001
SPEAG Flat Phantom	N/A	1004
Brain Equivalent Matter (2450 MHz)	Each Time	N/A
Muscle Equivalent Matter (2450 MHz)	Each Time	N/A
Brain Equivalent Matter (5200 MHz)	Each Time	N/A
Muscle Equivalent Matter (5200 MHz)	Each Time	N/A
Brain Equivalent Matter (5600 MHz)	Each Time	N/A
Muscle Equivalent Matter (5600 MHz)	Each Time	N/A
Brain Equivalent Matter (5800 MHz)	Each Time	N/A
Muscle Equivalent Matter (5800 MHz)	Each Time	N/A
Agilent, Spectrum Analyzer E4446A	2011-05-09	MY44303352
Microwave Amp. 8349A	N/A	2644A02662
Mini-Circuits, Amplifier, ZVA-183-S	2011-05-10	570400946
Power Meter Agilent E4419B	2012-09-01	MY4121511
Power Sensor Agilent E9301A	2012-02-19	US39211706
Dielectric Probe Kit HP85070A	N/A	US99360201
HP, Signal Generator, 83650B	2012-06-21	3614A00276
Amplifier, ST181-20	N/A	E012-0101
Antenna, Horn DRH-118	N/A	A052704


Note: ¹First time using the Probe 3619 after the calibration, calibration extend to two years cycle time.

6 SAR MEASUREMENT SYSTEM VERIFICATION

6.1 System Accuracy Verification

Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of $\pm 10\%$. The validation results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

6.2 Setup for System Verification



6.3 System Check Target Value

Frequency (MHz)	1 g SAR (W/Kg)	10 g SAR (W/Kg)	Local SAR at surface (above feed point)	Local SAR at surface (v=2cm offset from feed point)
300	3.0	2.0	4.4	2.1
450	4.9	3.3	7.2	3.2
835	9.5	6.2	14.1	4.9
900	10.8	6.9	16.4	5.4
1450	29.0	16.0	50.2	6.5
1800	38.1	19.8	69.5	6.8
1900	39.7	20.5	72.1	6.6
2000	41.1	21.1	74.6	6.5
2450	52.4	24.0	104.2	7.7
3000	63.8	25.7	140.2	9.5

DASY4 Manual recommended reference value at 5 GHz


Frequency (MHz)	Head Tissue			Body Tissue		
	1 g SAR (W/Kg)	10 g SAR (W/Kg)	SAR Peak	1 g SAR (W/Kg)	10 g SAR (W/Kg)	SAR Peak
5000	72.9	20.7	285.6	68.1	19.2	260.3
5100	74.6	21.1	297.5	78.8	19.6	272.3
5200	76.5	21.6	310.3	71.8	20.1	284.7
5500	83.3	23.4	349.4	79.1	22.0	326.3
5800	78.0	21.9	340.9	74.1	20.5	324.7

7 EUT TEST STRATEGY AND METHODOLOGY

7.1 Test Positions for Device Operating Next to a Person’s Ear

This category includes most wireless handsets with fixed, retractable or internal antennas located toward the top half of the device, with or without a foldout, sliding or similar keypad cover. The handset should have its earpiece located within the upper ¼ of the device, either along the centerline or off-centered, as perceived by its users. This type of handset should be positioned in a normal operating position with the “test device reference point” located along the “vertical centerline” on the front of the device aligned to the “ear reference point”. The “test device reference point” should be located at the same level as the center of the earpiece region. The “vertical centerline” should bisect the front surface of the handset at its top and bottom edges. An “ear reference point” is located on the outer surface of the head phantom on each ear spacer. It is located 1.5 cm above the center of the ear canal entrance in the “phantom reference plane” defined by the three lines joining the center of each “ear reference point” (left and right) and the tip of the mouth.

A handset should be initially positioned with the earpiece region pressed against the ear spacer of a head phantom. For the SCC-34/SC-2 head phantom, the device should be positioned parallel to the “N-F” line defined along the base of the ear spacer that contains the “ear reference point”. For interim head phantoms, the device should be positioned parallel to the cheek for maximum RF energy coupling. The “test device reference point” is aligned to the “ear reference point” on the head phantom and the “vertical centerline” is aligned to the “phantom reference plane”. This is called the “initial ear position”. While maintaining these three alignments, the body of the handset is gradually adjusted to each of the following positions for evaluating SAR:



7.2 Cheek/Touch Position


The device is brought toward the mouth of the head phantom by pivoting against the “ear reference point” or along the “N-F” line for the SCC-34/SC-2 head phantom.

This test position is established:

- When any point on the display, keypad or mouthpiece portions of the handset is in contact with the phantom.
- (or) When any portion of a foldout, sliding or similar keypad cover opened to its intended self-adjusting normal use position is in contact with the cheek or mouth of the phantom.

For existing head phantoms – when the handset loses contact with the phantom at the pivoting point, rotation should continue until the device touches the cheek of the phantom or breaks its last contact from the ear spacer.

Cheek /Touch Position




7.3 Ear/Tilt Position

With the handset aligned in the “Cheek/Touch Position”:

- 1) If the earpiece of the handset is not in full contact with the phantom’s ear spacer (in the “Cheek/Touch position”) and the peak SAR location for the “Cheek/Touch” position is located at the ear spacer region or corresponds to the earpiece region of the handset, the device should be returned to the “initial ear position” by rotating it away from the mouth until the earpiece is in full contact with the ear spacer.
- 2) (otherwise) The handset should be moved (translated) away from the cheek perpendicular to the line passes through both “ear reference points” (note: one of these ear reference points may not physically exist on a split head model) for approximate 2-3 cm. While it is in this position, the device handset is tilted away from the mouth with respect to the “test device reference point” until the inside angle between the vertical centerline on the front surface of the phone and the horizontal line passing through the ear reference point is by 15 80°. After the tilt, it is then moved (translated) back toward the head perpendicular to the line passes through both “ear reference points” until the device touches the phantom or the ear spacer. If the antenna touches the head first, the positioning process should be repeated with a tilt angle less than 15 80° so that the device and its antenna would touch the phantom simultaneously. This test position may require a device holder or positioner to achieve the translation and tilting with acceptable positioning repeatability.

If a device is also designed to transmit with its keypad cover closed for operating in the head position, such positions should also be considered in the SAR evaluation. The device should be tested on the left and right side of the head phantom in the “Cheek/Touch” and “Ear/Tilt” positions. When applicable, each configuration should be tested with the antenna in its fully extended and fully retracted positions. These test configurations should be tested at the high, middle and low frequency channels of each operating mode; for example, AMPS, CDMA, and TDMA. If the SAR measured at the middle channel for each test configuration (left, right, Cheek/Touch, Tile/Ear, extended and retracted) is at least 2.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s). If the transmission band of the test device is less than 10 MHz, testing at the high and low frequency channels is optional.

Ear /Tilt 15° Position



7.4 Test positions for body-worn and other configurations

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations. Devices with a headset output should be tested with a headset connected to the device. When multiple accessories that do not contain metallic components are supplied with the device, the device may be tested with only the accessory that dictates the closest spacing to the body. When multiple accessories that contain metallic components are supplied with the device, the device must be tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component (e.g., the same metallic belt-clip used with different holsters with no other metallic components), only the accessory that dictates the closest spacing to the body must be tested.

Body-worn accessories may not always be supplied or available as options for some devices that are intended to be authorized for body-worn use. A separation distance of 1.5 cm between the back of the device and a flat phantom is recommended for testing body-worn SAR compliance under such circumstances. Other separation distances may be used, but they should not exceed 2.5 cm. In these cases, the device may use body-worn accessories that provide a separation distance greater than that tested for the device provided however that the accessory contains no metallic components.

7.5 SAR Evaluation Procedure

The evaluation was performed with the following procedure:

Step 1: Measurement of the SAR value at a fixed location above the ear point or central position was used as a reference value for assessing the power drop. The SAR at this point is measured at the start of the test and then again at the end of the testing.

Step 2: The SAR distribution at the exposed side of the head was measured at a distance of 4 mm from the inner surface of the shell. The area covered the entire dimension of the head or EUT and the horizontal grid spacing was 15 mm x 15 mm. Based on these data, the area of the maximum absorption was determined by line interpolation. The first Area Scan covers the entire dimension of the EUT to ensure that the hotspot was correctly identified.

Step 3: Around this point, a volume of 30 mm x 30 mm x 21 mm was assessed by measuring 5 x 5 x 7 points. On the basis of this data set, the spatial peak SAR value was evaluated under the following procedure:

1. The data at the surface were extrapolated, since the center of the dipoles is 1.2 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.3 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.
2. The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed by the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one dimensional splines with the "Not a knot"-condition (in x, y and z-directions). The volume was integrated with the trapezoidal-algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the averages.
3. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement of the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation was repeated.

8 DASY4 SAR EVALUATION PROCEDURE

8.1 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurement jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method. The Minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. By default, the Minimum distance of probe sensors to surface is 4mm. This distance can be modified by the user, but cannot be smaller than the Distance of sensor calibration points to probe tip as defined in the probe properties (for example, 2.7mm for an ET3DV6 probe type).



8.2 Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in DASY4 software can find the maximum locations even in relatively coarse grids.

The scanning area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom. When the Area Scan's property sheet is brought-up, grid settings can be edited by a user.

When an Area Scan has measured all reachable points, it computes the field maxima found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE 1528-2003, EN 50361 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan). If only one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of Zoom Scans has to be increased accordingly.

After measurement is completed, all maxima and their coordinates are listed in the Results property page. The maximum selected in the list is highlighted in the 3-D view. For the secondary maxima returned from an Area Scan, the user can specify a lower limit (peak SAR value), in addition to the Find secondary maxima within x dB condition. Only the primary maximum and any secondary maxima within x dB from the primary maximum and above this limit will be measured.



8.3 Zoom Scan


Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default Zoom Scan measures 5 x 5 x 7 points within a cube whose base faces are centered around the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1 g and 10 g and displays these values next to the job's label.

8.4 Power drift measurement

The Power Drift Measurement job measures the field at the same location as the most recent power reference measurement job within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

8.5 Z-Scan

The Z Scan job measures points along a vertical straight line. The line runs along the Z axis of a one-dimensional grid. A user can anchor the grid to the section reference point, to any defined user point or to the current probe location. As with any other grids, the local Z axis of the anchor location establishes the Z axis of the grid.



9 RF OUTPUT VERIFICATION

9.1 Test Results

Mode	Frequency (MHz)	Conducted Average Output Power	
		(dBm)	(mW)
2.4 GHz			
802.11b	2412	17.2	52.48
	2437	17.3	53.70
	2462	17.2	52.48
802.11g	2412	11.9	15.49
	2417	15.2	33.11
	2437	17.1	51.29
	2457	16.2	41.69
	2462	12.5	17.70
802.11n20	2412	10.8	12.02
	2417	15.0	31.62
	2437	16.2	41.69
	2457	15.7	37.15
	2462	11.4	13.80
5 GHz			
802.11a	5180	14.0	25.12
	5200	14.0	25.12
	5240	13.6	22.91
	5260	17.5	56.23
	5300	17.1	51.29
	5320	17.1	51.29
	5500	15.1	32.36
	5600	17.2	52.48
	5700	12.9	19.50
	5745	17.2	52.48
	5785	17.2	52.48
5825	17.2	52.48	
5 GHz			
802.11n20	5180	14.0	25.12
	5200	14.0	25.12
	5240	13.8	23.99
	5260	16.4	43.65
	5300	16.2	41.69
	5320	16.2	41.69
	5500	14.9	30.90
	5600	16.5	44.67
	5700	12.5	17.78
	5745	16.2	41.69
	5785	16.4	43.65
	5825	16.2	41.69

Mode	Frequency (MHz)	Conducted Average Output Power	
		(dBm)	(mW)
5 GHz			
802.11n20	5190	14.0	25.12
	5230	14.0	25.12
	5270	14.1	25.70
	5310	14.0	25.12
	5510	12.2	16.60
	5590	14.0	25.12
	5670	14.0	25.12
	5755	14.0	25.12
	5795	14.0	25.12

Note: According to KDB248227, SAR is not required for 802.11g/n20 channels when the maximum average output power is less than 1/4 dB higher than that measured on the corresponding 802.11b.

10 SAR MEASUREMENT RESULTS

This page summarizes the results of the performed dosimetric evaluation. The plots with the corresponding SAR distributions, which reveal information about the location of the maximum SAR with respect to the device, could be found in Appendix E.

10.1 Test Environmental Conditions

Temperature:	22-24C
Relative Humidity:	45-50 %
ATM Pressure:	101 - 102kPa

Testing was performed by Quinn Jiang on 2011-04-15 through 2011-04-22 in SAR chamber.

Radio Mode	EUT Position	Frequency (MHz)	Antenna	Liquid	Phantom	SAR Value (W/kg) 1g	Limit (W/kg) 1g	Plot #
2.4 GHz								
802.11b	Back Touch (Mid CH)	2437	Integral	Body	Flat	0.328	1.6	1
	Left Side Touch (Mid CH)	2437	Integral	Body	Flat	0.052	1.6	2
	Right Side Touch (Mid CH)	2437	Integral	Body	Flat	0.000246	1.6	3
5 GHz								
802.11a	Back Touch (Mid CH)	5200	Integral	Body	Flat	0.142	1.6	4
	Left Side Touch (Mid CH)	5200	Integral	Body	Flat	0.024	1.6	5
	Right Side Touch (Mid CH)	5200	Integral	Body	Flat	0.00747	1.6	6
	Back Touch (Low CH)	5260	Integral	Body	Flat	0.385	1.6	7
	Left Side Touch (Low CH)	5260	Integral	Body	Flat	0.061	1.6	8
	Right Side Touch (Low CH)	5260	Integral	Body	Flat	0.00967	1.6	9
	Back Touch (Mid CH)	5600	Integral	Body	Flat	0.346	1.6	10
	Left Side Touch (Mid CH)	5600	Integral	Body	Flat	0.082	1.6	11
	Right Side Touch (Mid CH)	5600	Integral	Body	Flat	0.0259	1.6	12
	Back Touch (Mid CH)	5785	Integral	Body	Flat	0.323	1.6	13
	Left Side Touch (Mid CH)	5785	Integral	Body	Flat	0.011	1.6	14
	Right Side Touch (Mid CH)	5785	Integral	Body	Flat	0.011	1.6	15

Radio Mode	EUT Position	Frequency (MHz)	Antenna	Liquid	Phantom	SAR Value (W/kg) 1g	Limit (W/kg) 1g	Plot #
5 GHz								
802.11n40	Back Touch (Low CH)	5190	Integral	Body	Flat	0.104	1.6	16
	Left Side Touch (Low CH)	5190	Integral	Body	Flat	0.024	1.6	17
	Right Side Touch (Low CH)	5190	Integral	Body	Flat	0.011	1.6	18
	Back Touch (Low CH)	5270	Integral	Body	Flat	0.119	1.6	19
	Left Side Touch (Low CH)	5270	Integral	Body	Flat	0.022	1.6	20
	Right Side Touch (Low CH)	5270	Integral	Body	Flat	0.00525	1.6	21
	Back Touch (Mid CH)	5590	Integral	Body	Flat	0.202	1.6	22
	Left Side Touch (Mid CH)	5590	Integral	Body	Flat	0.034	1.6	23
	Right Side Touch (Mid CH)	5590	Integral	Body	Flat	0.015	1.6	24
	Back Touch (Mid CH)	5795	Integral	Body	Flat	0.190	1.6	25
	Left Side Touch (Mid CH)	5795	Integral	Body	Flat	0.017	1.6	26
	Right Side Touch (Mid CH)	5795	Integral	Body	Flat	0.012	1.6	27

Based on the manufacturer’s statement, the tablet computer (Motion Computing CL900, model: FWS-001) only supports 3 screen orientations:

- a. Landscape mode (fig. 1)
- b. Portrait mode-right (fig. 2)
- c. Portrait mode-left (fig. 3)

The CL900 (model: FWS-001) tablet PC does not support the orientation that places the top of the product (RF antenna) against the body.




Fig.1:



Fig. 2:





Fig. 3:

The Motion Computing CL900 tablet PC (Model: FWS-001) contains at most three radio modules inside, namely Bluetooth, WLAN and WWAN radios, each internal radio has individual registration identifiers, the antenna distance between BT and WLAN or WWAN antenna is more than 5 cm (please refer to the antenna location below). Based on the manufacturer’s statement, WLAN and WWAN radio modules are not allowed to transmit simultaneously. The manufacturer has embedded a software tool that notifies the user that the two radios are not allowed to transmit at the same time, please refer to the statement with this filing.



11 APPENDIX A – MEASUREMENT UNCERTAINTY

The uncertainty budget has been determined for the DASY4 measurement system and is given in the following Table.

SASY4 Uncertainty Budget According to IEEE 1528								
Error Description	Uncertainty Value	Prob. Dist.	Div.	(c i) 1g	(c i) 10g	Std. Unc. (1g)	Std. Unc. (10g)	(v i) veff
Measurement System								
Probe Calibration	± 5.9 %	N	1	1	1	± 5.9 %	± 5.9 %	∞
Axial Isotropy	± 4.7 %	R	$\sqrt{3}$	0.7	0.7	± 1.9 %	± 1.9 %	∞
Hemispherical Isotropy	± 9.6 %	R	$\sqrt{3}$	0.7	0.7	± 3.9 %	± 3.9 %	∞
Boundary Effects	± 1.0 %	R	$\sqrt{3}$	1	1	± 0.6 %	± 0.6 %	∞
Linearity	± 4.7 %	R	$\sqrt{3}$	1	1	± 2.7 %	± 2.7 %	∞
System Detection Limits	± 1.0 %	R	$\sqrt{3}$	1	1	± 0.6 %	± 0.6 %	∞
Readout Electronics	± 0.3 %	N	1	1	1	± 0.3 %	± 0.3 %	∞
Response Time	± 0.8 %	R	$\sqrt{3}$	1	1	± 0.5 %	± 0.5 %	∞
Integration Time	± 2.6 %	R	$\sqrt{3}$	1	1	± 1.5 %	± 1.5 %	∞
RF Ambient Conditions	± 3.0 %	R	$\sqrt{3}$	1	1	± 1.7 %	± 1.7 %	∞
Probe Positioner	± 0.4 %	R	$\sqrt{3}$	1	1	± 0.2 %	± 0.2 %	∞
Probe Positioning	± 2.9 %	R	$\sqrt{3}$	1	1	± 1.7 %	± 1.7 %	∞
Max. SAR Eval.	± 1.0 %	R	$\sqrt{3}$	1	1	± 0.6 %	± 0.6 %	∞
Test Sample Related								
Device Positioning	± 2.9 %	N	1	1	1	± 2.9 %	± 2.9 %	145
Device Holder	± 3.6 %	N	1	1	1	± 3.6 %	± 2.6 %	5
Power Drift	± 5.0 %	R		1	1	± 2.9 %	± 2.9 %	∞
Phantom and Setup								
Phantom Uncertainty	± 4.0 %	R	$\sqrt{3}$	1	1	± 2.3 %	± 2.3 %	∞
Liquid Conductivity (Target)	± 5.0 %	R	$\sqrt{3}$	0.64	0.43	± 1.8 %	± 1.2 %	∞
Liquid Conductivity (meas.)	± 2.5 %	N	1	0.64	0.43	± 1.6 %	± 1.1 %	∞
Liquid Permittivity (Target)	± 5.0 %	R	$\sqrt{3}$	0.6	0.49	± 1.7 %	± 1.4 %	∞
Liquid Permittivity (Target)	± 2.5 %	N	1	0.6	0.49	± 1.5 %	± 1.0 %	∞
Combined Std. Uncertainty	-	-	-	-	-	± 10.8 %	± 10.6 %	330
Expanded STD Uncertainty	-	-	-	-	-	± 21.6 %	± 21.1 %	-

12 APPENDIX B – PROBE CALIBRATION CERTIFICATES

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **BACL**

Certificate No: **ET3-1604_Sep10**

CALIBRATION CERTIFICATE

Object: **ET3DV6 - SN:1604**

Calibration procedure(s): **QA CAL-01.v6, QA CAL-12.v6, QA CAL-23.v3 and QA CAL-25.v2
Calibration procedure for dosimetric E-field probes**

Calibration date: **September 16, 2010**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	1-Apr-10 (No. 217-01136)	Apr-11
Power sensor E4412A	MY41495277	1-Apr-10 (No. 217-01136)	Apr-11
Power sensor E4412A	MY41498087	1-Apr-10 (No. 217-01136)	Apr-11
Reference 3 dB Attenuator	SN: S5054 (3c)	30-Mar-10 (No. 217-01159)	Mar-11
Reference 20 dB Attenuator	SN: S5086 (20b)	30-Mar-10 (No. 217-01161)	Mar-11
Reference 30 dB Attenuator	SN: S5129 (30b)	30-Mar-10 (No. 217-01160)	Mar-11
Reference Probe ES3DV2	SN: 3013	30-Dec-09 (No. ES3-3013_Dec09)	Dec-10
DAE4	SN: 660	20-Apr-10 (No. DAE4-660_Apr10)	Apr-11

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-09 (in house check Oct-09)	In house check: Oct 11
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-09)	In house check: Oct10

Calibrated by:	Name Jeton Kastrati	Function Laboratory Technician	Signature
Approved by:	Name Katja Pokovic	Function Technical Manager	

Issued: September 16, 2010

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: ET3-1604_Sep10

Page 1 of 11

verified OK [Signature] 9/24/2010

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C	modulation dependent linearization parameters
Polarization ϕ	ϕ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not effect the E²-field uncertainty inside TSL (see below *ConvF*).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * *frequency_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; VR_{x,y,z}**: A, B, C are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

ET3DV6 SN:1604

September 16, 2010

Probe ET3DV6

SN:1604

Manufactured:	July 30, 2001
Last calibrated:	September 23, 2008
Recalibrated:	September 16, 2010

Calibrated for DASY/EASY Systems

(Note: non-compatible with DASY2 system!)

ET3DV6 SN:1604

September 16, 2010

DASY/EASY - Parameters of Probe: ET3DV6 SN:1604**Basic Calibration Parameters**

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	1.93	1.86	1.92	± 10.1%
DCP (mV) ^B	91.4	91.1	91.5	

Modulation Calibration Parameters

UID	Communication System Name	PAR		A dB	B dBuV	C	VR mV	Unc ^E (k=2)
10000	CW	0.00	X	0.00	0.00	1.00	300.0	± 1.5%
			Y	0.00	0.00	1.00	300.0	
			Z	0.00	0.00	1.00	300.0	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E²-field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the maximum deviation from linear response applying recatangular distribution and is expressed for the square of the field value.

ET3DV6 SN:1604

September 16, 2010

DASY/EASY - Parameters of Probe: ET3DV6 SN:1604**Calibration Parameter Determined in Head Tissue Simulating Media**

f [MHz]	Validity [MHz]^c	Permittivity	Conductivity	ConvF X	ConvF Y	ConvF Z	Alpha	Depth Unc (k=2)
450	± 50 / ± 100	43.5 ± 5%	0.87 ± 5%	7.32	7.32	7.32	0.20	2.22 ± 13.3%
835	± 50 / ± 100	41.5 ± 5%	0.90 ± 5%	6.26	6.26	6.26	0.43	2.21 ± 11.0%
900	± 50 / ± 100	41.5 ± 5%	0.97 ± 5%	6.12	6.12	6.12	0.34	2.66 ± 11.0%
1810	± 50 / ± 100	40.0 ± 5%	1.40 ± 5%	5.14	5.14	5.14	0.60	2.51 ± 11.0%
1900	± 50 / ± 100	40.0 ± 5%	1.40 ± 5%	5.04	5.04	5.04	0.69	2.17 ± 11.0%
2450	± 50 / ± 100	39.2 ± 5%	1.80 ± 5%	4.33	4.33	4.33	0.99	1.63 ± 11.0%

^c The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

ET3DV6 SN:1604

September 16, 2010

DASY/EASY - Parameters of Probe: ET3DV6 SN:1604**Calibration Parameter Determined in Body Tissue Simulating Media**

f [MHz]	Validity [MHz]^c	Permittivity	Conductivity	ConvF X	ConvF Y	ConvF Z	Alpha	Depth Unc (k=2)
450	± 50 / ± 100	56.7 ± 5%	0.94 ± 5%	7.72	7.72	7.72	0.13	2.30 ± 13.3%
835	± 50 / ± 100	55.2 ± 5%	0.97 ± 5%	6.10	6.10	6.10	0.31	2.92 ± 11.0%
900	± 50 / ± 100	55.0 ± 5%	1.05 ± 5%	6.09	6.09	6.09	0.28	3.23 ± 11.0%
1810	± 50 / ± 100	53.3 ± 5%	1.52 ± 5%	4.61	4.61	4.61	0.75	2.61 ± 11.0%
1900	± 50 / ± 100	53.3 ± 5%	1.52 ± 5%	4.44	4.44	4.44	0.88	2.41 ± 11.0%
2450	± 50 / ± 100	52.7 ± 5%	1.95 ± 5%	4.06	4.06	4.06	0.99	1.32 ± 11.0%


^c The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

ET3DV6 SN:1604

September 16, 2010

Frequency Response of E-Field

(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ (k=2)

ET3DV6 SN:1604

September 16, 2010

Receiving Pattern (ϕ), $\vartheta = 0^\circ$




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ (k=2)

ET3DV6 SN:1604

September 16, 2010

Dynamic Range f(SAR_{head}) (Waveguide R22, f = 1800 MHz)




Uncertainty of Linearity Assessment: ± 0.6% (k=2)

ET3DV6 SN:1604


September 16, 2010

Conversion Factor Assessment



Deviation from Isotropy in HSL

Error (ϕ , θ), f = 900 MHz



Uncertainty of Spherical Isotropy Assessment: $\pm 2.6\%$ (k=2)

ET3DV6 SN:1604

September 16, 2010

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	Not applicable
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	enabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	6.8 mm
Probe Tip to Sensor X Calibration Point	2.7 mm
Probe Tip to Sensor Y Calibration Point	2.7 mm
Probe Tip to Sensor Z Calibration Point	2.7 mm
Recommended Measurement Distance from Surface	4 mm

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **BACL**

Certificate No: **EX3-3619_Sep09**

CALIBRATION CERTIFICATE

Object: **EX3DV4 - SN:3619**

Calibration procedure(s): **QA CAL-01.v6, QA CAL-14.v3, QA CAL-23.v3 and QA CAL-25.v2
Calibration procedure for dosimetric E-field probes**

Calibration date: **September 18, 2009**

Condition of the calibrated item: **In Tolerance**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41233874	1-Apr-09 (No. 217-01030)	Apr-10
Power sensor E4412A	MY41495277	1-Apr-09 (No. 217-01030)	Apr-10
Power sensor E4412A	MY41498087	1-Apr-09 (No. 217-01030)	Apr-10
Reference 3 dB Attenuator	SN: S5254 (3c)	31-Mar-09 (No. 217-01026)	Mar-10
Reference 20 dB Attenuator	SN: S5386 (20b)	31-Mar-09 (No. 217-01028)	Mar-10
Reference 30 dB Attenuator	SN: S5129 (30b)	31-Mar-09 (No. 217-01027)	Mar-10
Reference Probe ES3DV2	SN: 3013	2-Jan-09 (No. ES3-3013_Jan09)	Jan-10
DAE4	SN: 660	9-Sep-08 (No. DAE4-660_Sep08)	Sep-09

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Oct-07)	In house check: Oct-09
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-08)	In house check: Oct-09

	Name	Function	Signature
Calibrated by:	Katja Pekovic	Technical Manager	
Approved by:	Niels Kuster	Quality Manager	

Issued: September 22, 2009

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: EX3-3619_Sep09

Page 1 of 9

*Verified
Greenman
Sept. 28, 2009*

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not effect the E^2 -field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z} = NORM_{x,y,z} * frequency_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

EX3DV4 SN:3619

September 18, 2009

Probe EX3DV4

SN:3619

Manufactured:	July 3, 2007
Last calibrated:	September 19, 2008
Recalibrated:	September 18, 2009

Calibrated for DASY Systems

(Note: non-compatible with DASY2 system!)


Certificate No. EX3-3619_Sep09

Page 3 of 9

EX3DV4 SN:3619

September 18, 2009

Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ (k=2)

EX3DV4 SN:3619

September 18, 2009

Receiving Pattern (ϕ), $\vartheta = 0^\circ$





Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ (k=2)

EX3DV4 SN:3619

September 18, 2009

Dynamic Range $f(SAR_{head})$ (Waveguide R22, $f = 1800$ MHz)




Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

EX3DV4 SN:3619

September 18, 2009

Conversion Factor Assessment



f [MHz]	Validity [MHz] ^c	TSL	Permittivity	Conductivity	Alpha	Depth	ConvF Uncertainty
5200	± 50 / ± 100	Head	36.0 ± 5%	4.66 ± 5%	0.35	1.90	4.49 ± 13.1% (k=2)
5600	± 50 / ± 100	Head	35.5 ± 5%	5.07 ± 5%	0.40	1.90	4.15 ± 13.1% (k=2)
5800	± 50 / ± 100	Head	35.3 ± 5%	5.27 ± 5%	0.40	1.90	4.17 ± 13.1% (k=2)
5200	± 50 / ± 100	Body	49.0 ± 5%	5.30 ± 5%	0.48	1.95	3.78 ± 13.1% (k=2)
5600	± 50 / ± 100	Body	48.5 ± 5%	5.77 ± 5%	0.48	1.95	3.59 ± 13.1% (k=2)
5800	± 50 / ± 100	Body	48.2 ± 5%	6.00 ± 5%	0.55	1.95	3.74 ± 13.1% (k=2)


^c The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

EX3DV4 SN:3619

September 18, 2009

Deviation from Isotropy in HSL

Error (ϕ, θ), $f = 900$ MHz



Uncertainty of Spherical Isotropy Assessment: $\pm 2.6\%$ ($k=2$)

13 APPENDIX C – DIPOLE CALIBRATION CERTIFICATES



Bay Area Compliance Laboratories Corp.
 1274 Anvilwood Ave, Sunnyvale, CA 94089
 Tel: (408)732-9162 / Fax: (408)732-9164

Verification of Calibration Report

Report Number: CAL 2010-07-15
Description: Dipole Antenna
Manufacturer: Aprel Laboratories
Model Number: D-2400-S-1
Serial Number: SN: BCL-141
Date of Calibration: 14 July 2010
Condition Received: In Tolerance
Condition Returned: In Tolerance

Conditions and results of calibration: See attachment

This device has been instrumented, measured and calibrated in accordance with the Bay Area Compliance Laboratories Corp. ("BACL") Quality Assurance Manual procedures and the results being traceable to the National Institute of Standards and Technology (NIST). The BACL Quality System is accredited by NVLAP to ISO/IEC 17025:2005. Unless stated otherwise; Measurement Uncertainties are derived from ISO Guide to the Determination of Uncertainties with a Coverage Factor of $k = 2$ for a 95% level of confidence, no sampling plan or other process was used for this calibration (unless stated otherwise), the results reported herein apply only to the calibration of the item described above, and limitations of use (if any) shall be stated this Calibration Report.

Calibrated By:	 _____ Victor Zhang	07/16/2010 _____ Date
Reviewed By:	 _____ Hans Mellberg	2010-07-17 _____ Date
Quality Assurance:	 _____ Steve Hubbard	7-19-10 _____ Date

Attachment

Ambient Environment of Calibration

Temperature	Relative Humidity	Pressure
24 ° C	48.5 %	101.4 k Pa

Equipment List

Description	Manufacturer	Model	Serial #	Cal Date
Signal Generator	Rohde & Schwarz	SMIQ	849192/0085/DE23746	2010-03-31
Network Analyzer	HP	8753D	3410A04346	2010-06-03
Power meter	Agilent	E4419B	MY41291511	2008-10-10
Power Sensor	Agilent	E9301A	MY41497252	2010-02-19
Reference Probe	SPEAG	ET3DV2	3019	2009-09-22

Measurement Conditions

DASY Version	DASY4	V4.7
Extrapolation	Advanced Extrapolation	
Phantom	Flat Phantom	
Distance Dipole Center-TSL	10 mm	
Area Scan resolution	dx,dy = 15 mm	
Zoom Scan resolution	dx,dy,dz = 15 mm	
Frequency	2450 MHz ± 1MHz	

Calibration is performed According to the Following Standards:

1. IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
2. IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devise used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
3. DASY 4 System Handbook

Calibration Data:

Head TSL Parameters

The following parameters and calculations were applied

	Temperature	Permittivity	Conductivity
Nominal Head TSL Parameters	22.0 °C	39.2	1.80 mho/m
Measured Head TSL Parameters	(22.0±0.3) °C	38.0	1.88 mho/m
Head TSL Temperature during test	(23.5±0.3) °C		

SAR result with Head TSL

SAR average over 1 cm3 (1g) of Head TSL	Condition	
SAR measured	500 mW input power	26.9 mW / g
SAR normalized	Normalized to 1W	53.8 mW / g
SAR for nominal Head TSL parameters ¹	Normalized to 1W	55.6 mW / g ± 6.6% (k=2)

SAR average over 10 cm3 (10g) of Head TSL	Condition	
SAR measured	500 mW input power	12.3 mW / g
SAR normalized	Normalized to 1W	24.6 mW / g
SAR for nominal Head TSL parameters ¹	Normalized to 1W	25.0 mW / g ± 3.2% (k=2)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	49.375 Ω
Return Loss	-32.886 dB

¹Correction to nominal TSL parameters according to DASY 4 System Handbook, chapter "SAR Sensitivities"

DASY4 Validation Report for Head TSL

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)

DUT: Dipole 2450 MHz; Type: D-2450-S-1; Serial: D2450V2 - SN: BCL-141


Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 2450$ MHz; $\sigma = 1.88$ mho/m; $\epsilon_r = 38$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY4 Configuration:


- Probe: ES3DV2 - SN3019; ConvF(4.15, 4.15, 4.15); Calibrated: 9/22/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 11/8/2007
- Phantom: SAM with CRP; Type: Twin SAM; Serial: TP-1032
- Measurement SW: DASY4, V4.6 Build 23; Post processing SW: SEMCAD, V1.8 Build 184

d = 10 mm, Pin = 0.5W/Area Scan (61x101x1); Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 33.4 mW/g


d = 10 mm, Pin = 0.5W/Zoom Scan (8x8x7)/Cube 0; Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 120.9 V/m; Power Drift = -0.141 dB
Peak SAR (extrapolated) = 57.5 W/kg
SAR(1 g) = 26.9 mW/g; SAR(10 g) = 12.3 mW/g
Maximum value of SAR (measured) = 30.9 mW/g



Impedance Measurement Plot for Head TSL



Return Loss Measurement Plot for Head TSL








Bay Area Compliance Laboratories Corp.
 1274 Anvilwood Ave, Sunnyvale, CA 94089
 Tel: (408)732-9162 / Fax: (408)732-9164

Verification of Calibration Report

Report Number: CAL 12-24-2010
Description: Dipole Antenna
Manufacturer: Schmid & Partner Engineering AG
Model Number: D5100V2
Serial Number: SN: 1001
Date of Calibration: December 24, 2010
Condition Received: In Tolerance
Condition Returned: In Tolerance

Conditions and results of calibration: See attachment

This device has been instrumented, measured and calibrated in accordance with the Bay Area Compliance Laboratories Corp. ("BACL") Quality Assurance Manual procedures and the results being traceable to the National Institute of Standards and Technology (NIST). The BACL Quality System is accredited by NVLAP to ISO/IEC 17025:2005. Unless stated otherwise; Measurement Uncertainties are derived from ISO Guide to the Determination of Uncertainties with a Coverage Factor of $k = 2$ for a 95% level of confidence, no sampling plan or other process was used for this calibration (unless stated otherwise), the results reported herein apply only to the calibration of the item described above, and limitations of use (if any) shall be stated this Calibration Report.

Calibrated By:	 _____ Quinn Jiang	<u>12/24/2010</u> _____ Date
Reviewed By:	 _____ Victor Zhang	<u>12/24/2010</u> _____ Date
Quality Assurance:	 _____ Kaveh Moraghebi	<u>12/24/2010</u> _____ Date

*Done
archive*

Attachment

Ambient Environment of Calibration

Temperature	Relative Humidity	Pressure
22 ° C	58.5 %	103.5 k Pa

Equipment List

Description	Manufacturer	Model	Serial #	Cal Date
Signal Generator	HP	8648C	3426A00417	2010-08-30
Network Analyzer	HP	8753D	3410A04346	2010-06-03
Power meter	Agilent	E4419B	MY4121511	2010-09-01
Power Sensor	Agilent	E9301A	US39211706	2010-02-19
Reference Probe	SPEAG	EX3DV4	3619	2007-09-10

Measurement Conditions

DASY Version	DASY4	V4.6
Extrapolation	Advanced Extrapolation	
Phantom	Flat Phantom	
Distance Dipole Center-TSL	10 mm	With Spacer
Area Scan resolution	dx,dy = 10 mm	
Zoom Scan resolution	dx,dy = 4.3, dz = 3 mm	
Frequency	5200 MHz ± 1MHz 5800 MHz ± 1MHz	

Calibration is performed According to the Following Standards:

1. IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
2. IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devise used in close proximity to the ear (frequency range of to 3 GHz to 6 GHz)", October 2006
3. DASY 4 System Handbook

Calibration Data:

Head TSL Parameters at 5200 MHz

The following parameters and calculations were applied

	Temperature	Permittivity	Conductivity
Nominal Head TSL Parameters	22.0°C	36.0	4.66
Measured Head TSL Parameters	22.0°C	34.3	4.49
Head TSL Temperature during test	23.0°C		

SAR result with Head TSL at 5200 MHz

SAR average over 1 cm ³ (1g) of Head TSL	Condition	
SAR measured	500 mW input power	40.3 mW / g
SAR normalized	Normalized to 1W	80.6 mW / g
SAR for nominal Head TSL parameters ¹	Normalized to 1W	76.5 mW / g ± 10%

SAR average over 10 cm ³ (10g) of Head TSL	Condition	
SAR measured	500 mW input power	11.2 mW / g
SAR normalized	Normalized to 1W	22.4 mW / g
SAR for nominal Head TSL parameters ¹	Normalized to 1W	21.6 mW / g ± 10%

Head TSL Parameters at 5800 MHz

The following parameters and calculations were applied

	Temperature	Permittivity	Conductivity
Nominal Head TSL Parameters	22.0°C	35.3	5.27
Measured Head TSL Parameters	22.0°C	36.7	5.47
Head TSL Temperature during test	23.0°C		

SAR result with Head TSL at 5800 MHz

SAR average over 1 cm ³ (1g) of Head TSL	Condition	
SAR measured	500 mW input power	37.3 mW / g
SAR normalized	Normalized to 1W	74.6 mW / g
SAR for nominal Head TSL parameters ¹	Normalized to 1W	78.0 mW / g ± 10%

SAR average over 10 cm ³ (10g) of Head TSL	Condition	
SAR measured	500 mW input power	11.3 mW / g
SAR normalized	Normalized to 1W	22.6 mW / g
SAR for nominal Head TSL parameters ¹	Normalized to 1W	21.9 mW / g ± 10%

Antenna Parameters with Head TSL at 5200 MHz

Impedance, transformed to feed point	47.732 Ω
Return Loss	-31.983 dB

Antenna Parameters with Head TSL at 5800 MHz

Impedance, transformed to feed point	48.041 Ω
Return Loss	-28.792 dB

¹Correction to nominal TSL parameters according to DASY 4 System Handbook, chapter "SAR Sensitivities"

Test Laboratory: Bay Area Compliance Lab Corp.(BACL)

System Performance Test (5200 MHz Head Tissue)

DUT: D5100V2; Type: D5100; Serial: SN:1001

Communication System: CW; Frequency: 5200 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 5200$ MHz; $\sigma = 4.49$ mho/m; $\epsilon_r = 34.3$; $\rho = 1000$ kg/m³
Phantom section: Flat Section


DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(4.64, 4.64, 4.64); Calibrated: 9/10/2007
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: SAM with CRP; Type: Twin SAM; Serial: TP-1032
- Measurement SW: DASY4, V4.6 Build 23; Post processing SW: SEMCAD, V1.8 Build 184

d =10 mm, Pin = 0.5W /Area Scan (101x151x1): Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (interpolated) = 96.5 mW/g

d =10 mm, Pin = 0.5W /Zoom Scan (7x7x8)/Cube 0: Measurement grid: dx=4.3mm, dy=4.3mm, dz=3mm
Reference Value = 91.6 V/m; Power Drift = -0.072 dB
Peak SAR (extrapolated) = 282.7 W/kg

SAR(1 g) = 40.3 mW/g; SAR(10 g) = 11.2 mW/g
Maximum value of SAR (measured) = 77.9 mW/g



System Performance at 5200 MHz

Test Laboratory: Bay Area Compliance Lab Corp.(BACL)

System Performance Test (5800 MHz Head Tissue)

DUT: Dipole 5800MHZ; Type: D5800; Serial: D5100V2-SN:1001

Communication System: CW; Frequency: 5800 MHz; Duty Cycle: 1:1
 Medium parameters used (interpolated): $f = 5800 \text{ MHz}$; $\sigma = 5.47 \text{ mho/m}$; $\epsilon_r = 36.7$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section


DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(4.07, 4.07, 4.07); Calibrated: 9/10/2007
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: SAM with CRP; Type: Twin SAM; Serial: TP-1032
- Measurement SW: DASY4, V4.6 Build 23; Post processing SW: SEMCAD, V1.8 Build 184

d =10 mm, Pin = 0.5W /Area Scan (101x151x1): Measurement grid: dx=10mm, dy=10mm
 Maximum value of SAR (interpolated) = 93.0 mW/g

d =10 mm, Pin = 0.5W /Zoom Scan (7x7x8)/Cube 0: Measurement grid: dx=4.3mm, dy=4.3mm, dz=3mm
 Reference Value = 72.3 V/m; Power Drift = -0.235 dB
 Peak SAR (extrapolated) = 316.9 W/kg


SAR(1 g) = 37.3 mW/g; SAR(10 g) = 11.3 mW/g
 Maximum value of SAR (measured) = 71.5 mW/g




0 dB = 71.5mW/g

System Performance at 5800 MHz

Impedance Measurement Plot for Head TSL



Return Loss Measurement Plot for Head TSL



14 APPENDIX D - TEST SYSTEM VERIFICATIONS SCANS

14.1 Liquid and System Validation

Measured Date	Simulant	Freq. [MHz]	Parameters	Liquid Temp [°C]	Target Value	Measured Value	Deviation [%]	Limits [%]
2011-04-15	Head	2450	ϵ_r	23	39.2	38.0	-3.06	± 5
			σ	23	1.80	1.88	4.44	± 5
			1g SAR	23	52.4	50.2	-4.20	± 10
2011-04-15	Body	2450	ϵ_r	23	52.7	50.7	-3.80	± 5
			σ	23	1.95	2.02	3.60	± 5
			1g SAR	23	52.4	54.8	4.58	± 10
2011-04-18	Head	5200	ϵ_r	23	36.0	34.3	-4.72	± 5
			σ	23	4.66	4.49	-3.65	± 5
			1g SAR	23	76.5	74.0	-3.27	± 10
2011-04-18	Body	5200	ϵ_r	23	49.0	47.2	-3.67	± 5
			σ	23	5.3	5.3	0	± 5
			1g SAR	23	71.8	68.8	-4.18	± 10
2011-04-18	Head	5500	ϵ_r	23	35.6	34.9	-1.97	± 5
			σ	23	4.96	4.95	-0.21	± 5
			1g SAR	23	83.3	78.8	-5.40	± 10
2011-04-18	Body	5500	ϵ_r	23	48.6	49.2	1.23	± 5
			σ	23	5.65	5.53	-2.12	± 5
			1g SAR	23	79.1	81.6	3.16	± 10
2011-04-19	Head	5800	ϵ_r	23	35.3	36.7	3.97	± 5
			σ	23	5.27	5.47	3.80	± 5
			1g SAR	23	78.0	82.4	5.64	± 10
2011-04-19	Body	5800	ϵ_r	23	48.2	48.3	0.21	± 5
			σ	23	6.00	5.97	-0.50	± 5
			1g SAR	23	74.1	77.6	4.72	± 10

ϵ_r = relative permittivity, σ = conductivity and $\rho=1000$ kg/m³

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)

System Performance Test (2450 MHz, Head Tissue)

Dipole 2450 MHz; Type: D-2450-S-1; Serial: SN: BCL-141

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 2450$ MHz; $\sigma = 1.88$ mho/m; $\epsilon_r = 38$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section


DASY4 Configuration:

- Probe: ET3DV6 - SN1604; ConvF(4.33, 4.33, 4.33); Calibrated: 9/16/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

d =10 mm, Pin = 0.5W/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
 Maximum value of SAR (interpolated) = 27.3 mW/g

d =10 mm, Pin = 0.5W/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
 Reference Value = 126.4 V/m; Power Drift = -0.147 dB
 Peak SAR (extrapolated) = 54.2 W/kg

SAR (1 g) = 25.1 mW/g; SAR (10 g) = 11.2 mW/g
 Maximum value of SAR (measured) = 27.2 mW/g



0 dB = 27.2mW/g

2450 MHz System Validation with Head Tissue

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)

System Performance Test (2450 MHz, Body Tissue)

Dipole 2450 MHz; Type: D-2450-S-1; Serial: SN: BCL-141

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1
 Medium parameters used (interpolated): $f = 2450 \text{ MHz}$; $\sigma = 2.02 \text{ mho/m}$; $\epsilon_r = 50.7$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section


DASY4 Configuration:

- Probe: ET3DV6 - SN1604; ConvF(4.06, 4.06, 4.06); Calibrated: 9/16/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

d =10 mm, Pin = 0.5W/Area Scan (61x101x1): Measurement grid: dx=15mm, dy=15mm
 Maximum value of SAR (interpolated) = 29.7 mW/g

d =10 mm, Pin = 0.5W/Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
 Reference Value = 122.6 V/m; Power Drift = -0.143 dB
 Peak SAR (extrapolated) = 55.3 W/kg

SAR (1 g) = 27.4 mW/g; SAR (10 g) = 12.5 mW/g
 Maximum value of SAR (measured) = 29.4 mW/g



0 dB = 29.4mW/g

2450 MHz System Validation with Body Tissue

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)**System Performance Test (5200 MHz, Head Tissue)****Dipole D5100V2; Type: D5100; Serial: SN: 1001**

Communication System: CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5200$ MHz; $\sigma = 4.49$ mho/m; $\epsilon_r = 34.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(4.49, 4.49, 4.49); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

d =10 mm, Pin = 0.25W/Area Scan (81x131x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 41.6 mW/g


d =10 mm, Pin = 0.25W/Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm

Reference Value = 63.3 V/m; Power Drift = 0.153 dB

Peak SAR (extrapolated) = 80.6 W/kg

SAR (1 g) = 18.5 mW/g; SAR (10 g) = 5.29 mW/g

Maximum value of SAR (measured) = 37.5 mW/g



0 dB = 37.5mW/g

5200 MHz System Validation with Head Tissue

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)**System Performance Test (5200 MHz, Body Tissue)****Dipole D5100V2; Type: D5100; Serial: SN: 1001**

Communication System: CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5200$ MHz; $\sigma = 5.3$ mho/m; $\epsilon_r = 47.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.78, 3.78, 3.78); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

d =10 mm, Pin = 0.25W /Area Scan (81x131x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 34.3 mW/g


d =10 mm, Pin = 0.25W /Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm

Reference Value = 58.0 V/m; Power Drift = 0.101 dB

Peak SAR (extrapolated) = 68.3 W/kg

SAR (1 g) = 17.2 mW/g; SAR (10 g) = 5.06 mW/g

Maximum value of SAR (measured) = 33.1 mW/g



0 dB = 33.1mW/g

5200 MHz System Validation with Body Tissue

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)**System Performance Test (5500 MHz, Head Tissue)****Dipole D5100V2; Type: D5100; Serial: SN: 1001**

Communication System: CW; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5500$ MHz; $\sigma = 4.95$ mho/m; $\epsilon_r = 34.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(4.15, 4.15, 4.15); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

d =10 mm, Pin = 0.25W /Area Scan (81x131x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 41.3 mW/g


d =10 mm, Pin = 0.25W /Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm

Reference Value = 60.4 V/m; Power Drift = -0.074 dB

Peak SAR (extrapolated) = 83.6 W/kg

SAR (1 g) = 19.7 mW/g; SAR (10 g) = 5.59 mW/g

Maximum value of SAR (measured) = 37.2 mW/g

**5500 MHz System Validation with Head Tissue**

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)**System Performance Test (5500 MHz, Body Tissue)****Dipole D5100V2; Type: D5100; Serial: SN: 1001**

Communication System: CW; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5500$ MHz; $\sigma = 5.53$ mho/m; $\epsilon_r = 49.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.59, 3.59, 3.59); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

d =10 mm, Pin = 0.25W/Area Scan (81x131x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 46.2 mW/g


d =10 mm, Pin = 0.25W/Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm

Reference Value = 64.5 V/m; Power Drift = -0.016 dB

Peak SAR (extrapolated) = 85.5 W/kg

SAR (1 g) = 20.4 mW/g; SAR (10 g) = 5.82 mW/g

Maximum value of SAR (measured) = 42.7 mW/g



0 dB = 42.7mW/g

5500 MHz System Validation with Body Tissue

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)**System Performance Test (5800 MHz, Head Tissue)****Dipole D5100V2; Type: D5100; Serial: SN: 1001**

Communication System: CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 5800$ MHz; $\sigma = 5.47$ mho/m; $\epsilon_r = 36.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(4.17, 4.17, 4.17); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

d =10 mm, Pin = 0.25W/Area Scan (81x131x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 50.5 mW/g


d =10 mm, Pin = 0.25W/Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm

Reference Value = 61.6 V/m; Power Drift = 0.038 dB

Peak SAR (extrapolated) = 89.3 W/kg

SAR (1 g) = 20.6 mW/g; SAR (10 g) = 5.77 mW/g

Maximum value of SAR (measured) = 43.6 mW/g



0 dB = 43.6mW/g

5800 MHz System Validation with Head Tissue

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)**System Performance Test (5800 MHz, Body Tissue)****Dipole D5100V2; Type: D5100; Serial: SN: 1001**

Communication System: CW; Frequency: 5800 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 5800$ MHz; $\sigma = 5.97$ mho/m; $\epsilon_r = 48.3$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section


DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.74, 3.74, 3.74); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

d =10 mm, Pin = 0.25W/Area Scan (81x131x1): Measurement grid: dx=10mm, dy=10mm
 Maximum value of SAR (interpolated) = 44.5 mW/g

d =10 mm, Pin = 0.25W/Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm
 Reference Value = 57.4 V/m; Power Drift = 0.137 dB
 Peak SAR (extrapolated) = 84.5 W/kg

SAR (1 g) = 19.4 mW/g; SAR (10 g) = 5.29 mW/g
 Maximum value of SAR (measured) = 43.0 mW/g

**5800 MHz System Validation with Body Tissue**

15 APPENDIX E – EUT SCAN RESULTS

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)

Back Side Touch to the Phantom (Middle Channel)

Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 2437$ MHz; $\sigma = 2.01$ mho/m; $\epsilon_r = 50.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1604; ConvF(4.06, 4.06, 4.06); Calibrated: 9/16/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Back Side Touch to the Phantom/Area Scan (91x121x1): Measurement grid: dx=30mm, dy=30mm

Maximum value of SAR (interpolated) = 0.301 mW/g


Back Side Touch to the Phantom/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.21 V/m; Power Drift = 0.109 dB

Peak SAR (extrapolated) = 0.883 W/kg

SAR (1 g) = 0.328 mW/g; SAR (10 g) = 0.152 mW/g

Maximum value of SAR (measured) = 0.340 mW/g



Plot # 1

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)

Left Side Touch to the Phantom (Mid Channel)

Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1
 Medium parameters used (interpolated): $f = 2437 \text{ MHz}$; $\sigma = 2.01 \text{ mho/m}$; $\epsilon_r = 50.7$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section


DASY4 Configuration:

- Probe: ET3DV6 - SN1604; ConvF(4.06, 4.06, 4.06); Calibrated: 9/16/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Left Side Touch to the Phantoms/Area Scan (41x121x1): Measurement grid: dx=30mm, dy=30mm
 Maximum value of SAR (interpolated) = 0.055 mW/g

Left Side Touch to the Phantoms/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
 Reference Value = 4.15 V/m; Power Drift = -0.298 dB
 Peak SAR (extrapolated) = 0.125 W/kg

SAR (1 g) = 0.052 mW/g; SAR (10 g) = 0.027 mW/g
 Maximum value of SAR (measured) = 0.055 mW/g



0 dB = 0.055mW/g

Plot # 2

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)

Right Side Touch to the Phantom (Mid Channel)

Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1
 Medium parameters used (interpolated): $f = 2437 \text{ MHz}$; $\sigma = 2.01 \text{ mho/m}$; $\epsilon_r = 50.7$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section


DASY4 Configuration:

- Probe: ET3DV6 - SN1604; ConvF(4.06, 4.06, 4.06); Calibrated: 9/16/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Right Side Touch to the Phantom /Area Scan (41x121x1): Measurement grid: $dx=30\text{mm}$, $dy=30\text{mm}$
 Maximum value of SAR (interpolated) = 0.007 mW/g

Right Side Touch to the Phantom /Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
 Reference Value = 0.692 V/m; Power Drift = 0.160 dB
 Peak SAR (extrapolated) = 0.011 W/kg

SAR (1 g) = 0.000246 mW/g; SAR (10 g) = 4.01e-005 mW/g
 Maximum value of SAR (measured) = 0.011 mW/g



Plot # 3

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)

Back Side Touch to the Phantom (Middle Channel)

Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055

Communication System: 802.11a; Frequency: 5200 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 5200 \text{ MHz}$; $\sigma = 5.3 \text{ mho/m}$; $\epsilon_r = 47.2$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.78, 3.78, 3.78); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Back Side Touch to the Phantom/Area Scan (121x151x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$
 Maximum value of SAR (interpolated) = 0.195 mW/g


Back Side Touch to the Phantom/Zoom Scan (11x11x8)/Cube 0: Measurement grid: $dx=3\text{mm}$, $dy=3\text{mm}$, $dz=3\text{mm}$

Reference Value = 1.40 V/m; Power Drift = -0.102 dB

Peak SAR (extrapolated) = 1.61 W/kg

SAR (1 g) = 0.142 mW/g; SAR (10 g) = 0.040 mW/g

Maximum value of SAR (measured) = 0.339 mW/g



0 dB = 0.339mW/g

Plot # 4

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)**Left Side Touch to the Phantom (Middle Channel)****Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055**

Communication System: 802.11a; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5200$ MHz; $\sigma = 5.3$ mho/m; $\epsilon_r = 47.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.78, 3.78, 3.78); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Left Side Touch to the Phantom/Area Scan (61x181x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.057 mW/g


Left Side Touch to the Phantom/Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm

Reference Value = 1.34 V/m; Power Drift = 0.203 dB

Peak SAR (extrapolated) = 0.269 W/kg

SAR (1 g) = 0.024 mW/g; SAR (10 g) = 0.011 mW/g

Maximum value of SAR (measured) = 0.269 mW/g

**Plot # 5**

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)**Right Side Touch to the Phantom (Middle Channel)****Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055**

Communication System: 802.11a; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5200$ MHz; $\sigma = 5.3$ mho/m; $\epsilon_r = 47.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.78, 3.78, 3.78); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Right Side Touch to the Phantom/Area Scan (61x181x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.043 mW/g


Right Side Touch to the Phantom/Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm

Reference Value = 0.811 V/m; Power Drift = 0.104 dB

Peak SAR (extrapolated) = 0.095 W/kg

SAR (1 g) = 0.00747 mW/g; SAR (10 g) = 0.00479 mW/g

Maximum value of SAR (measured) = 0.076 mW/g



Plot # 6

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)

Back Side Touch to the Phantom (Low Channel)

Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055

Communication System: 802.11a; Frequency: 5260 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 5260$ MHz; $\sigma = 5.5$ mho/m; $\epsilon_r = 48.5$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.78, 3.78, 3.78); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Back Side Touch to the Phantom/Area Scan (121x151x1): Measurement grid: dx=20mm, dy=20mm
 Maximum value of SAR (interpolated) = 0.650 mW/g


Back Side Touch to the Phantom/Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm

Reference Value = 1.11 V/m; Power Drift = 0.171 dB

Peak SAR (extrapolated) = 1.54 W/kg

SAR (1 g) = 0.385 mW/g; SAR (10 g) = 0.129 mW/g

Maximum value of SAR (measured) = 0.779 mW/g



0 dB = 0.779mW/g

Plot # 7

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)**Left Side Touch to the Phantom (Low Channel)****Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055**

Communication System: 802.11a; Frequency: 5260 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5260$ MHz; $\sigma = 5.5$ mho/m; $\epsilon_r = 48.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.78, 3.78, 3.78); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Left Side Touch to the Phantom/Area Scan (61x181x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.135 mW/g


Left Side Touch to the Phantom/Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm

Reference Value = 2.58 V/m; Power Drift = -0.286 dB

Peak SAR (extrapolated) = 0.251 W/kg

SAR (1 g) = 0.061 mW/g; SAR (10 g) = 0.024 mW/g

Maximum value of SAR (measured) = 0.125 mW/g



0 dB = 0.125mW/g

Plot # 8

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)

Right Side Touch to the Phantom (Low Channel)

Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055

Communication System: 802.11a; Frequency: 5260 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 5260 \text{ MHz}$; $\sigma = 5.5 \text{ mho/m}$; $\epsilon_r = 48.5$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.78, 3.78, 3.78); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Right Side Touch to the Phantom /Area Scan (61x181x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$
 Maximum value of SAR (interpolated) = 0.046 mW/g


Right Side Touch to the Phantom /Zoom Scan (11x11x8)/Cube 0: Measurement grid: $dx=3\text{mm}$, $dy=3\text{mm}$, $dz=3\text{mm}$

Reference Value = 1.72 V/m; Power Drift = -0.211 dB

Peak SAR (extrapolated) = 0.099 W/kg

SAR (1 g) = 0.00967 mW/g; SAR (10 g) = 0.00612 mW/g

Maximum value of SAR (measured) = 0.099 mW/g



0 dB = 0.099mW/g

Plot # 9

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)

Back Side Touch to the Phantom (Mid Channel)

Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055

Communication System: 802.11a; Frequency: 5600 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 5600$ MHz; $\sigma = 5.59$ mho/m; $\epsilon_r = 49.7$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.59, 3.59, 3.59); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Back Side Touch to the Phantom/Area Scan (121x151x1): Measurement grid: dx=20mm, dy=20mm
 Maximum value of SAR (interpolated) = 0.715 mW/g


Back Side Touch to the Phantom/Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm

Reference Value = 1.283 V/m; Power Drift = 0.102 dB

Peak SAR (extrapolated) = 1.50 W/kg

SAR (1 g) = 0.346 mW/g; SAR (10 g) = 0.118 mW/g

Maximum value of SAR (measured) = 0.707 mW/g



0 dB = 0.707mW/g

Plot # 10

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)**Left Side Touch to the Phantom (Mid Channel)****Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055**

Communication System: 802.11a; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5600$ MHz; $\sigma = 5.59$ mho/m; $\epsilon_r = 49.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.59, 3.59, 3.59); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Left Side Touch to the Phantom/Area Scan (61x181x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.160 mW/g


Left Side Touch to the Phantom/Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm

Reference Value = 0.675 V/m; Power Drift = 0.135 dB

Peak SAR (extrapolated) = 0.323 W/kg

SAR (1 g) = 0.082 mW/g; SAR (10 g) = 0.035 mW/g

Maximum value of SAR (measured) = 0.193 mW/g



Plot # 11

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)**Right Side Touch to the Phantom (Mid Channel)****Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055**

Communication System: 802.11a; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5600$ MHz; $\sigma = 5.59$ mho/m; $\epsilon_r = 49.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.59, 3.59, 3.59); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Right Side Touch to the Phantom/Area Scan (61x181x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.053 mW/g


Right Side Touch to the Phantom/Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm

Reference Value = 0.361 V/m; Power Drift = 0.241 dB

Peak SAR (extrapolated) = 0.232 W/kg

SAR (1 g) = 0.026 mW/g; SAR (10 g) = 0.013 mW/g

Maximum value of SAR (measured) = 0.111 mW/g



Plot # 12

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)

Back Side Touch to the Phantom (Mid Channel)

Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055

Communication System: 802.11a; Frequency: 5785 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 5785 \text{ MHz}$; $\sigma = 5.9 \text{ mho/m}$; $\epsilon_r = 47.2$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.74, 3.74, 3.74); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Back Side Touch to the Phantom /Area Scan (121x151x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$
 Maximum value of SAR (interpolated) = 0.435 mW/g


Back Side Touch to the Phantom /Zoom Scan (11x11x8)/Cube 0: Measurement grid: $dx=3\text{mm}$, $dy=3\text{mm}$, $dz=3\text{mm}$

Reference Value = 2.00 V/m; Power Drift = -0.201 dB

Peak SAR (extrapolated) = 1.55 W/kg

SAR (1 g) = 0.323 mW/g; SAR (10 g) = 0.102 mW/g

Maximum value of SAR (measured) = 0.690 mW/g



0 dB = 0.690mW/g

Plot # 13

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)

Left Side Touch to the Phantom (Mid Channel)

Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055

Communication System: 802.11a; Frequency: 5785 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 5785 \text{ MHz}$; $\sigma = 5.9 \text{ mho/m}$; $\epsilon_r = 47.2$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section


DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.74, 3.74, 3.74); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Left Side Touch to the Phantom/Area Scan (61x181x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$
 Maximum value of SAR (interpolated) = 0.080 mW/g

Left Side Touch to the Phantom/Zoom Scan (11x11x8)/Cube 0: Measurement grid: $dx=3\text{mm}$, $dy=3\text{mm}$, $dz=3\text{mm}$
 Reference Value = 1.431 V/m; Power Drift = 0.178 dB
 Peak SAR (extrapolated) = 0.089 W/kg

SAR (1 g) = 0.011 mW/g; SAR (10 g) = 0.00711 mW/g
 Maximum value of SAR (measured) = 0.089 mW/g



0 dB = 0.089mW/g

Plot # 14

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)

Right Side Touch to the Phantom (Mid Channel)

Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055

Communication System: 802.11a; Frequency: 5785 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 5785 \text{ MHz}$; $\sigma = 5.9 \text{ mho/m}$; $\epsilon_r = 47.2$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.74, 3.74, 3.74); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Right Side Touch to the Phantom/Area Scan (61x181x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$
 Maximum value of SAR (interpolated) = 0.078 mW/g


Right Side Touch to the Phantom/Zoom Scan (11x11x8)/Cube 0: Measurement grid: $dx=3\text{mm}$, $dy=3\text{mm}$, $dz=3\text{mm}$

Reference Value = 1.12 V/m; Power Drift = 0.205 dB

Peak SAR (extrapolated) = 0.101 W/kg

SAR (1 g) = 0.011 mW/g; SAR (10 g) = 0.00524 mW/g

Maximum value of SAR (measured) = 0.101 mW/g



0 dB = 0.101mW/g

Plot # 15

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)

Back Side Touch to the Phantom (Low Channel)

Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055

Communication System: 802.11n40; Frequency: 5190 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 5190 \text{ MHz}$; $\sigma = 5.2 \text{ mho/m}$; $\epsilon_r = 47.1$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.78, 3.78, 3.78); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Back Side Touch to the Phantom /Area Scan (121x151x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$
 Maximum value of SAR (interpolated) = 0.150 mW/g


Back Side Touch to the Phantom /Zoom Scan (11x11x8)/Cube 0: Measurement grid: $dx=3\text{mm}$, $dy=3\text{mm}$, $dz=3\text{mm}$

Reference Value = 1.73 V/m; Power Drift = -0.101 dB

Peak SAR (extrapolated) = 0.387 W/kg

SAR (1 g) = 0.104 mW/g; SAR (10 g) = 0.034 mW/g

Maximum value of SAR (measured) = 0.220 mW/g



0 dB = 0.220mW/g

Plot # 16

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)**Left Side Touch to the Phantom (Low Channel)****Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055**

Communication System: 802.11n40; Frequency: 5190 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 5190$ MHz; $\sigma = 5.2$ mho/m; $\epsilon_r = 47.1$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section


DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.78, 3.78, 3.78); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Left Side Touch to the Phantom/Area Scan (61x181x1): Measurement grid: dx=20mm, dy=20mm
 Maximum value of SAR (interpolated) = 0.060 mW/g

Left Side Touch to the Phantom/Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm
 Reference Value = 1.46 V/m; Power Drift = 0.186 dB
 Peak SAR (extrapolated) = 0.220 W/kg

SAR (1 g) = 0.024 mW/g; SAR (10 g) = 0.011 mW/g
 Maximum value of SAR (measured) = 0.099 mW/g

**Plot # 17**

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)

Right Side Touch to the Phantom (Low Channel)

Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055

Communication System: 802.11n40; Frequency: 5190 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 5190$ MHz; $\sigma = 5.2$ mho/m; $\epsilon_r = 47.1$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.78, 3.78, 3.78); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Right Side Touch to the Phantom/Area Scan (61x181x1): Measurement grid: dx=20mm, dy=20mm
 Maximum value of SAR (interpolated) = 0.035 mW/g


Right Side Touch to the Phantom/Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm

Reference Value = 1.17 V/m; Power Drift = -0.118 dB

Peak SAR (extrapolated) = 0.123 W/kg

SAR (1 g) = 0.011 mW/g; SAR (10 g) = 0.00694 mW/g

Maximum value of SAR (measured) = 0.123 mW/g



0 dB = 0.123mW/g

Plot # 18

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)

Back Side Touch to the Phantom (Low Channel)

Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055

Communication System: 802.11n40; Frequency: 5270 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 5270$ MHz; $\sigma = 5.54$ mho/m; $\epsilon_r = 48.7$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.78, 3.78, 3.78); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Back Side Touch to the Phantom/Area Scan (121x151x1): Measurement grid: dx=20mm, dy=20mm
 Maximum value of SAR (interpolated) = 0.227 mW/g


Back Side Touch to the Phantom/Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm

Reference Value = 1.88 V/m; Power Drift = 0.151 dB

Peak SAR (extrapolated) = 0.473 W/kg

SAR (1 g) = 0.119 mW/g; SAR (10 g) = 0.038 mW/g

Maximum value of SAR (measured) = 0.254 mW/g



0 dB = 0.254mW/g

Plot # 19

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)**Left Side Touch to the Phantom (Low Channel)****Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055**

Communication System: 802.11n40; Frequency: 5270 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 5270$ MHz; $\sigma = 5.54$ mho/m; $\epsilon_r = 48.7$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.78, 3.78, 3.78); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Left Side Touch to the Phantom /Area Scan (61x181x1): Measurement grid: dx=20mm, dy=20mm
 Maximum value of SAR (interpolated) = 0.072 mW/g


Left Side Touch to the Phantom /Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm

Reference Value = 1.298 V/m; Power Drift = 0.107 dB

Peak SAR (extrapolated) = 0.204 W/kg

SAR (1 g) = 0.022 mW/g; SAR (10 g) = 0.00946 mW/g

Maximum value of SAR (measured) = 0.123 mW/g

**Plot # 20**

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)

Right Side Touch to the Phantom (Low Channel)

Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055

Communication System: 802.11n40; Frequency: 5270 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 5270$ MHz; $\sigma = 5.54$ mho/m; $\epsilon_r = 48.7$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.78, 3.78, 3.78); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Right Side Touch to the Phantom /Area Scan (61x181x1): Measurement grid: dx=20mm, dy=20mm
 Maximum value of SAR (interpolated) = 0.054 mW/g


Right Side Touch to the Phantom /Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm

Reference Value = 1.181 V/m; Power Drift = 0.121 dB

Peak SAR (extrapolated) = 0.058 W/kg

SAR (1 g) = 0.00525 mW/g; SAR (10 g) = 0.00319 mW/g

Maximum value of SAR (measured) = 0.058 mW/g



0 dB = 0.058mW/g

Plot # 21

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)

Back Side Touch to the Phantom (Mid Channel)

Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055

Communication System: 802.11n40; Frequency: 5590 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 5590 \text{ MHz}$; $\sigma = 5.55 \text{ mho/m}$; $\epsilon_r = 49.3$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.59, 3.59, 3.59); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Back Side Touch to the Phantom /Area Scan (121x151x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$
 Maximum value of SAR (interpolated) = 0.249 mW/g


Back Side Touch to the Phantom /Zoom Scan (11x11x8)/Cube 0: Measurement grid: $dx=3\text{mm}$, $dy=3\text{mm}$, $dz=3\text{mm}$

Reference Value = 1.543 V/m; Power Drift = -0.231 dB

Peak SAR (extrapolated) = 0.784 W/kg

SAR (1 g) = 0.202 mW/g; SAR (10 g) = 0.064 mW/g

Maximum value of SAR (measured) = 0.449 mW/g



0 dB = 0.449mW/g

Plot # 22

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)**Left Side Touch to the Phantom (Mid Channel)****Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055**

Communication System: 802.11n40; Frequency: 5590 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 5590$ MHz; $\sigma = 5.55$ mho/m; $\epsilon_r = 49.3$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section


DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.59, 3.59, 3.59); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Left Side Touch to the Phantom/Area Scan (61x181x1): Measurement grid: dx=20mm, dy=20mm
 Maximum value of SAR (interpolated) = 0.057 mW/g

Left Side Touch to the Phantom/Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm
 Reference Value = 1.01 V/m; Power Drift = -0.141 dB
 Peak SAR (extrapolated) = 0.401 W/kg

SAR (1 g) = 0.034 mW/g; SAR (10 g) = 0.015 mW/g
 Maximum value of SAR (measured) = 0.401 mW/g



0 dB = 0.401mW/g

Plot # 23

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)**Right Side Touch to the Phantom (Mid Channel)****Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055**

Communication System: 802.11n40; Frequency: 5590 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 5590$ MHz; $\sigma = 5.55$ mho/m; $\epsilon_r = 49.3$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.59, 3.59, 3.59); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Right Side Touch to the Phantom/Area Scan (61x181x1): Measurement grid: dx=20mm, dy=20mm
Maximum value of SAR (interpolated) = 0.048 mW/g


Right Side Touch to the Phantom/Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm

Reference Value = 0.97 V/m; Power Drift = 0.112 dB

Peak SAR (extrapolated) = 0.126 W/kg

SAR (1 g) = 0.015 mW/g; SAR (10 g) = 0.009 mW/g

Maximum value of SAR (measured) = 0.126 mW/g

**Plot # 24**

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)

Back Side Touch to the Phantom (Mid Channel)

Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055

Communication System: 802.11n40; Frequency: 5795 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 5795 \text{ MHz}$; $\sigma = 5.96 \text{ mho/m}$; $\epsilon_r = 48.1$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.74, 3.74, 3.74); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Back Side Touch to the Phantom /Area Scan (121x151x1): Measurement grid: $dx=20\text{mm}$, $dy=20\text{mm}$
 Maximum value of SAR (interpolated) = 0.290 mW/g


Back Side Touch to the Phantom /Zoom Scan (11x11x8)/Cube 0: Measurement grid: $dx=3\text{mm}$, $dy=3\text{mm}$, $dz=3\text{mm}$

Reference Value = 0.613 V/m; Power Drift = 0.205 dB

Peak SAR (extrapolated) = 0.783 W/kg

SAR (1 g) = 0.190 mW/g; SAR (10 g) = 0.060 mW/g

Maximum value of SAR (measured) = 0.414 mW/g



0 dB = 0.414mW/g

Plot # 25

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)**Left Side Touch to the Phantom (Mid Channel)****Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055**

Communication System: 802.11n40; Frequency: 5795 MHz; Duty Cycle: 1:1
 Medium parameters used: $f = 5795$ MHz; $\sigma = 5.96$ mho/m; $\epsilon_r = 48.1$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.74, 3.74, 3.74); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Left Side Touch to the Phantom /Area Scan (61x181x1): Measurement grid: dx=20mm, dy=20mm
 Maximum value of SAR (interpolated) = 0.062 mW/g


Left Side Touch to the Phantom /Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm, dz=3mm

Reference Value = 0.97 V/m; Power Drift = 0.161 dB

Peak SAR (extrapolated) = 0.265 W/kg

SAR (1 g) = 0.017 mW/g; SAR (10 g) = 0.00811 mW/g.

Maximum value of SAR (measured) = 0.194 mW/g

**Plot # 26**

Test Laboratory: Bay Area Compliance Lab Corp. (BACL)**Right Side Touch to the Phantom (Mid Channel)****Motion Computing, Inc.; Type: WLAN Module with Motion Tablet PC; Serial: R1104055**

Communication System: 802.11n40; Frequency: 5795 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5795$ MHz; $\sigma = 5.96$ mho/m; $\epsilon_r = 48.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3619; ConvF(3.74, 3.74, 3.74); Calibrated: 9/18/2009
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn456; Calibrated: 12/7/2010
- Phantom: Flat Phantom 4.4; Type: Flat Phantom 4.4; Serial: 1004
- Measurement SW: DASY4, V4.7 Build 80; Post processing SW: SEMCAD, V1.8 Build 186

Right Side Touch to the Phantom /Area Scan (61x181x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 0.079 mW/g

Right Side Touch to the Phantom /Zoom Scan (11x11x8)/Cube 0: Measurement grid: dx=3mm, dy=3mm,


dz=3mm

Reference Value = 1.24 V/m; Power Drift = -0.115 dB

Peak SAR (extrapolated) = 0.133 W/kg

SAR (1 g) = 0.012 mW/g; SAR (10 g) = 0.00709 mW/g

Maximum value of SAR (measured) = 0.133 mW/g



Plot # 27

16 APPENDIX F – TEST SETUP PHOTOS

16.1 Tablet PC Back Side Touch to the Flat Phantom Setup Photo



16.2 Tablet PC Left Side Touch to the Flat Phantom Setup Photo




16.3 Tablet PC Right Side Touch to the Flat Phantom Setup Photo




17 APPENDIX G – EUT PHOTOS


17.1 WLAN Module View (Front Side with Shield)



17.2 WLAN Module View (Back Side)



17.3 WLAN Module View (Front Side without Shield)



17.4 Tablet PC -Front View



17.5 Tablet PC -Back View



17.6 Tablet PC - Bottom Side View



17.7 Tablet PC - Right Side View



17.8 Tablet PC - Left Side View



17.9 Tablet PC - Top Side View



17.10 WLAN Module Built into the Tablet PC (Motion FWS-001)



18 APPENDIX H - INFORMATIVE REFERENCES

[1] Federal Communications Commission, \Report and order: Guidelines for evaluating the environmental effects of radiofrequency radiation", Tech. Rep. FCC 96-326, FCC, Washington, D.C. 20554, 1996.

[2] David L. Means Kwok Chan, Robert F. Cleveland, \Evaluating compliance with FCC guidelines for human exposure to radiofrequency electromagnetic fields", Tech. Rep., Federal Communication Commission, Office of Engineering & Technology, Washington, DC, 1997.

[3] Thomas Schmid, Oliver Egger, and Niels Kuster, \Automated E-field scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp. 105{113, Jan. 1996.

[4] Niels Kuster, Ralph Kastle, and Thomas Schmid, \Dosimetric evaluation of mobile communications equipment with known precision", IEICE Transactions on Communications, vol. E80-B, no. 5, pp. 645{652, May 1997.

[5] CENELEC, \Considerations for evaluating of human exposure to electromagnetic fields (EMFs) from mobile telecommunication equipment (MTE) in the frequency range 30MHz - 6GHz", Tech. Rep., CENELEC, European Committee for Electrotechnical Standardization, Brussels, 1997.

[6] ANSI, ANSI/IEEE C95.1-1992: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992.

[7] Katja Pokovic, Thomas Schmid, and Niels Kuster, \Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies", in ICECOM _ 97, Dubrovnik, October 15{17, 1997, pp. 120-24.

[8] Katja Pokovic, Thomas Schmid, and Niels Kuster, \E-field probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23{25 June, 1996, pp. 172-175.

[9] Volker Hombach, Klaus Meier, Michael Burkhardt, Eberhard Kuhn, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 900 MHz", IEEE Transactions on Microwave Theory and Techniques, vol. 44, no. 10, pp. 1865-1873, Oct. 1996.

[10] Klaus Meier, Ralf Kastle, Volker Hombach, Roger Tay, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 1800 MHz", IEEE Transactions on Microwave Theory and Techniques, Oct. 1997, in press.

[11] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.

[12] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992. Dosimetric Evaluation of Sample device, month 1998 9

[13] NIS81 NAMAS, \The treatment of uncertainty in EMC measurement", Tech. Rep., NAMAS Executive, National Physical Laboratory, Teddington, Middlesex, England, 1994.

[14] Barry N. Taylor and Christ E. Kuyatt, \Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994. Dosimetric Evaluation of Sample device, month 1998 10.

[15] FCC KDB 248227, SAR Measurement Procedure for 802.11a/b/g Transmitters

[16] FCC KDB 447498, Mobile and portable Device RF Exposure Procedures and Equipment Authorization Policies.

- [17] FCC KDB 616217, SAR Evaluation Considerations for Laptop/Notebook and Tablet Computers.
- [18] FCC KDB 648474, SAR Evaluation Considerations for Handsets with Multiple Transmitters and Antennas.
- [19] SPEAG DASY4 System Handbook.

******* END OF REPORT *******