

Qualcomm Atheros, Inc.

1700 Technology Dr, San Jose, California 95110, United States

Date: May 2, 2012

Request for Modular Approval for Bluetooth/WLAN

FCC ID: PPD-QCWB335

| Item | Requirements | EUT |
|------|--|--|
| 1 | The modular transmitter must have its own RF shielding. | The modular transmitter is equipped with an own metal shielding. |
| 2 | The modular transmitter must have buffered modulation / data inputs. | The EUT has buffer modulation / data inputs. |
| 3 | The modular transmitter must have its own power supply regulation. | The EUT has its own power supply regulation. |
| 4 | The modular transmitter must comply with the antenna requirements of the Section 15.203 and 15.204(c). | The EUT meets the FCC antenna requirements. The spurious emission, unique antenna connector and photo of antennas are shown in the External and Internal photos. |
| 5 | The modular transmitter must be tested in a stand-alone configuration. | The module was tested on evaluation board which is a stand-alone HW. |
| 6 | The modular transmitter must be labeled with its own FCC ID number. | The modular transmitter will be labeled with in own FCC ID and the integration manual contains labeling instructions for the host device into which this module will be integrated. |
| 7 | The modular transmitter must comply with any specific rule or operating requirements applicable to the transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. | The modular approved transmitter complied with all applicable rules and the integration manual contains any specific requirements addressed to the integrator and / or to the end-user of the final end-product. |
| 8 | The modular transmitter must comply with any applicable RF exposure requirement. | With the dedicated antenna (3.62 dBi) the modular transmitter complied with the FCC RF exposure requirements for fixed and mobile applications. |

Effective Date: Immediately.