


FCC Part 22/24 Compliance Test Report

Test Report no.:	Cph_FCC_0519_03.doc	Date of Report:	2005-06-11
Number of pages:	7	Customer's Contact person:	Thomas Reitmayer
Testing laboratory:	TCC Nokia Copenhagen Laboratory Frederikskaj 1790 COPENHAGEN V DENMARK Tel. +45 33 292929 Fax. +45 33 292934	Client:	Nokia Corporation Lise Meitner Strasse 10 89081 ULM GERMANY Tel. +49 731 1754 0 Fax. +49 731 1754 6800
FCC listing no.:	99059		
IC recognition no.:	4820 and 4820-1		
Tested devices/ accessories:	Phone; RM-77 (HW: V.9), Battery; BL-4C, Headset; HS-23, Charger; AC-3		
FCC ID:	PPIRM-77X	IC:	661U-RM77
Supplement reports:			
Testing has been carried out in accordance with:	CFR 47, FCC rules Parts 22 and 24, TIA-603-B-2002 and IC standards RSS-132 and RSS-133. Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document.		

Date and signature for the contents:

2005-06-11



Allan F. Henriksen
Test Engineer

1. Summary for FCC Part 22/24 Compliance Test Report

Date of receipt	2005-04-06
Testing completed	2005-04-18
The customer's contact person	Thomas Reitmayer
Test Plan referred to	\\satcc01nmp\tcc_salo\Projects\RM-77\testplans\EMC\TCC\HJ12_RM77_official_EMC_test_plan.xls
Notes	V-9 black
Document name	\\satcc01nmp\tcc_salo\Projects\RM-77\results\emc\FCC\Cph_FCC_0519_03.doc

1.1. EUT and Accessory Information

The EUT is a triple band (GSM850/1800/1900) mobile phone with GPRS and EGPRS and a camera. The EUT is tested with maximum rated TX power, modulated with pseudo random bit sequence (PRBS9).

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-77	004400/63/179554/7	3830	-	3.03	28738
Battery	BL-4C	0670386417535 L425A10268050	-	-	-	28730
Headset	HS-23	0025	0.5	0.3	0.2	28941
Charger	AC-3	067537040904 M02601 0000220	1.1	0.3	-	28636

1.2. Summary of Test Results

GSM 850:

Section in CFR 47	Section in RSS-132	Name of the test	Result
§2.1046(a), 22.913(a)	4.4	Conducted RF output power	NP
§22.913(a)	4.4, 6.4	Radiated RF output power	Passed
§2.1049(h)	4.2	99 % occupied bandwidth	NP
§22.917(a)	4.5	Band edge compliance	NP
§22.917(a), §2.1051	4.5	Spurious emissions at antenna terminals	NP
§22.917(a), §2.1053	4.5	Spurious radiated emissions	NP
§2.1055(a)	4.3, 6.3	Frequency stability, temperature variation	NP
§2.1055(d)	4.3, 6.3	Frequency stability, voltage variation	NP

PASSED
FAILED
NP

The EUT complies with the essential requirements in the standard.
The EUT does not comply with the essential requirements in the standard.
The test was not performed by the TCC Nokia Copenhagen Laboratory.


CONTENTS

1. Summary for FCC Part 22/24 Compliance Test Report	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results	2
2. Radiated RF output power (FCC §22.913(a), §24.232(b), RSS-132 6.4, RSS-133 6.2)	4
2.1. Test setup	4
2.2. Test method and limit	4
2.3. GSM 850 Test results – phone open	5
2.4. GSM 850 Test results – phone closed	6
3. Test Equipment	7
3.1. Radiated measurements	7

2. Radiated RF output power (FCC §22.913(a), §24.232(b), RSS-132 6.4, RSS-133 6.2)

EUT with DUT number	RM-77 Dut#28738
Accessories with DUT numbers	BL-4C dut#28730, AC-3 Dut 28636, HS-23 Dut#28941
Result	Passed
Remarks	None
Temp °C / Humidity RH % / Air Pressure mbar	21.6°C / 36.0% / 1010 mbar
Date of measurements	2005-04-12
Measured by	Christian Andersen

2.1. Test setup



2.2. Test method and limit

The measurement is made according to TIA-603-B-2002 as follows:

The measurement is performed in the Anechoic Chamber with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system. The turntable is rotated 360 degrees and this is repeated for both horizontal and vertical receive antenna polarizations.

The EUT is placed on a nonconductive plate at 170 cm height.

The substitution method is used. Substitution values at each frequency are measured beforehand and saved to the test software.

The substitution corrections are obtained as described below:

$$A_{SUBST} = P_{SUBST_TX} - P_{SUBST_RX} - L_{SUBST_CABLES} + G_{SUBST_TX_ANT}$$

Where A_{SUBST} is the final substitution correction including receive antenna gain. P_{SUBST_TX} is signal generator level, P_{SUBST_RX} is receiver level, L_{SUBST_CABLES} is cable losses including both TX and RX cables and $G_{SUBST_TX_ANT}$ is substitution antenna gain.

The measurement results are obtained as described below:

$$P [dBm] = P_{MEAS} + A_{CORRECTIONS}$$

Where P_{MEAS} is receiver reading in dBm and $A_{CORRECTIONS}$ is combined correction factor including cable loss and substitution correction ($A_{CORRECTIONS} = L_{CABLES} + A_{SUBST}$).

Limits for radiated RF output power measurements

Frequency range [MHz]	Limit [W]	Limit [dBm]
824 - 849	7	38.5
1850 - 1910	2	33

2.3. GSM 850 Test results – phone open

GSM mode

Channel	Frequency [MHz]	ERP [dBm]	ERP [W]	A _{CORRECTION} [dB]	Polarisation	Result
128	824.200000	27.60	0.575	35.60	VERTICAL	Passed
190	836.600000	29.00	0.794	34.40	VERTICAL	Passed
251	848.800000	28.90	0.776	33.70	VERTICAL	Passed

GPRS mode, 2 TX Slots

Channel	Frequency [MHz]	ERP [dBm]	ERP [W]	A _{CORRECTION} [dB]	Polarisation	Result
128	824.200000	27.90	0.617	35.60	VERTICAL	Passed
190	836.600000	24.90	0.309	34.40	VERTICAL	Passed
251	848.800000	26.30	0.427	33.70	VERTICAL	Passed

EGPRS mode, 1 TX Slot

Channel	Frequency [MHz]	ERP [dBm]	ERP [W]	A _{CORRECTION} [dB]	Polarisation	Result
128	824.200000	24.40	0.275	35.60	VERTICAL	Passed
190	836.600000	26.80	0.479	34.40	VERTICAL	Passed
251	848.800000	26.80	0.479	33.70	VERTICAL	Passed

2.4. GSM 850 Test results – phone closed

GSM mode

Channel	Frequency [MHz]	ERP [dBm]	ERP [W]	A _{CORRECTION} [dB]	Polarisation	Result
128	824.200000	23.60	0.229	35.60	VERTICAL	Passed
190	836.600000	25.70	0.372	34.40	VERTICAL	Passed
251	848.800000	26.80	0.479	33.70	VERTICAL	Passed

GPRS mode, 2 TX Slots

Channel	Frequency [MHz]	ERP [dBm]	ERP [W]	A _{CORRECTION} [dB]	Polarisation	Result
128	824.200000	23.70	0.234	35.60	VERTICAL	Passed
190	836.600000	25.70	0.372	34.40	VERTICAL	Passed
251	848.800000	26.80	0.479	33.70	VERTICAL	Passed

EGPRS mode, 1 TX Slot

Channel	Frequency [MHz]	ERP [dBm]	ERP [W]	A _{CORRECTION} [dB]	Polarisation	Result
128	824.200000	20.60	0.115	35.60	VERTICAL	Passed
190	836.600000	23.00	0.200	34.40	VERTICAL	Passed
251	848.800000	23.80	0.240	33.70	VERTICAL	Passed

3. Test Equipment

3.1. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
14020	Programmable Relay Switching System	-	Pickering	15B,15C,22,24
18792	Multi Device Controller	2090	ETS-EMCO	15B,15C,22,24
13829	Turntable Controller	4630-100	Comtest	15B,15C,22,24
14963	RF Preamplifier 100MHz-4GHz (Metal Chassis)	AFS3-00100400	Miteq/NMP Cph	15B,15C,22,24
13668	BiLog Antenna 30-2000MHz	BiLog-CBL6112A	Chase	15B,15C,22,24
18861	EMI Test Receiver 20Hz-26,5GHz	ESI	Rohde&Schwarz	15B,15C,22,24
12679	Dual Log Periodic Antenna 1-18 GHz	HL025	Rohde&Schwarz	15B,15C,22,24
18860	Ultra Broadband Antenna Ultralog 30-3000MHz	HL562	Rohde&Schwarz	15B,15C,22,24
18773	Shielded Chamber	RFD-100	ETS-Lindgren	15B,15C,22,24
18774	Shielded Chamber	RFSD-F/A-100	ETS-Lindgren	15B,15C,22,24
18324	High Pass Filter 3GHz SMA f Conn	WHJS3000-10SS	Wainwright	15B,15C,22,24
14114	Highpass Filter 1000MHz-4500MHz	WHK1000-12SS	Wainwright	15B,15C,22,24
13918	Highpass Filter 2000-4000MHz 50OHM SMA Conn	WHKS2000-10SS	Wainwright Instruments	15B,15C,22,24
13937	Ultra Stable Notch Filter 902,4MHz	WRCA902.4-0.2/40-6SS	Wainwright Instruments	15B,15C,22,24
13936	Ultra Stable Notch Filter 1747,5MHz	WRCD1747.5-0.2/40-10SS	Wainwright Instruments	15B,15C,22,24
13917	Highpass Filter 1000-3000MHz 50OHM SMA Conn	WHKS1000-10SS	Wainwright Instruments	15B,15C,22,24
14188	Ultra Stable Notch Filter 902,4MHz	WRCA902.4-0.2/40-6SS	Wainwright	15B,15C,22,24
14187	Ultra Stable Notch Filter 1747,5MHz	WRCD1747.5-0.2/40-10SS	Wainwright	15B,15C,22,24
16633	Ultra Stable Notch Filter 1880,0MHz	WRCD1880.0-0.2/40-10SS	Wainwright	15B,15C,22,24
18323	Band reject filter 1947-1953MHz 40dB	WRCG1947/1953-1940/1960-40/6SS	Wainwright	15B,15C,22,24
15190	Infra Red Remote Control Unit	4630	Emco	22,24,15B,15C
14993	EMI Test Receiver 9KHz-2750MHz	ESCS30	Rohde&Schwarz	22,24,15B,15C
15191	Turntable Contoller Unit	G-800SDX	YAESU	22,24,15B,15C
14900	Antenna Controller	HD100	HD GmbH	22,24,15B,15C