


FCC Part 22/24 Compliance Test Report

Test Report no.:	Cph_FCC_0522_04.doc	Date of Report:	31-05-2005
Number of pages:	8	Customer's Contact person:	Thomas Reitmayer
Testing laboratory:	TCC Nokia Copenhagen Laboratory Frederikskaj 1790 COPENHAGEN V DENMARK Tel. +45 33 292929 Fax. +45 33 292934	Client:	Nokia Corporation Lise Meitner Strasse 10 89081 ULM GERMANY Tel. +49 731 1754 0 Fax. +49 731 1754 6800
FCC listing no.:	99059		
IC recognition no.:	4820 and 4820-1		
Tested devices/ accessories:	Phone; RM-77 (V.10), Battery; BL-4C, AC-Charger; AC-3, Headset; HS-23		
FCC ID:	PPIRM-77X	IC:	661U-RM77
Supplement reports:			
Testing has been carried out in accordance with:	CFR 47, FCC rules Parts 22 and 24, TIA-603-B-2002 and IC standards RSS-132 and RSS-133. Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document.		

Date and signature for the contents:

31-05-2005



Allan F. Henriksen
Test Engineer

1. Summary for FCC Part 22/24 Compliance Test Report

Date of receipt	4 th April 2005
Testing completed	31 st May 2005
The customer's contact person	Thomas Reitmayer
Test Plan referred to	\\EMC\\TESTPLAN\\
Notes	V.10
Document name	\\satcc01nmp\\tcc_salo\\Projects\\RM-77\\results\\emc\\FCC\\Cph_0522_04.doc

1.1. EUT and Accessory Information

The EUT is a tri band (GSM850/1800/1900) mobile phone with GPRS and EGPRS. The EUT is tested with maximum rated TX power, modulated with pseudo random bit sequence (PRBS9).

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-77	004400/63/179761/8	3830	-	3.03	28739
Battery	BL-4C	067038610717244311	-	-	-	28935

1.2. Summary of Test Results

GSM 1900:

Section in CFR 47	Section in RSS-133	Name of the test	Result
§2.1046(a)	6.2	Conducted RF output power	NP
§24.232(b)	6.2	Radiated RF output power	Passed
§2.1049(h)	5.6	99 % occupied bandwidth	NP
§24.238(a)	6.3	Band edge compliance	NP
§24.238(a), §2.1051	6.3	Spurious emissions at antenna terminals	NP
§24.238(a), §2.1053	6.3	Spurious radiated emissions	NP
§2.1055(a)	7	Frequency stability, temperature variation	NP
§2.1055(d)	7	Frequency stability, voltage variation	NP

PASSED
FAILED
NP

The EUT complies with the essential requirements in the standard.
The EUT does not comply with the essential requirements in the standard.
The test was not performed by the TCC Nokia Copenhagen Laboratory.


CONTENTS

1. Summary for FCC Part 22/24 Compliance Test Report	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results	2
2. Radiated RF output power (FCC §22.913(a), §24.232(b), RSS-132 6.4, RSS-133 6.2)	4
2.1. Test setup	4
2.2. Test method and limit	4
2.3. GSM 1900 Test results – Phone open	5
2.4. GSM 1900 Test results – Phone closed	6
3. Test Equipment	7
3.1. Conducted measurements	7
3.2. Radiated measurements	7

2. Radiated RF output power (FCC §22.913(a), §24.232(b), RSS-132 6.4, RSS-133 6.2)

EUT with DUT number	RM-77 Dut # 28739
Accessories with DUT numbers	BL-4C Dut # 28935
Operation Voltage V / Hz	230V
Result	Passed
Remarks	None
Temp °C / Humidity RH % / Air Pressure kPa	22 / 42 / 1018
Date of measurements	27 th may 2005
Measured by	Christian Andersen

2.1. Test setup



2.2. Test method and limit

The measurement is made according to TIA-603-B-2002 as follows:

The measurement is performed in the Anechoic Chamber with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system. The turntable is rotated 360 degrees and this is repeated for both horizontal and vertical receive antenna polarizations.

The EUT is placed on a nonconductive plate at 170 cm height.

The substitution method is used. Substitution values at each frequency are measured beforehand and saved to the test software.

The substitution corrections are obtained as described below:

$$A_{SUBST} = P_{SUBST_TX} - P_{SUBST_RX} - L_{SUBST_CABLES} + G_{SUBST_TX_ANT}$$

Where A_{SUBST} is the final substitution correction including receive antenna gain. P_{SUBST_TX} is signal generator level, P_{SUBST_RX} is receiver level, L_{SUBST_CABLES} is cable losses including both TX and RX cables and $G_{SUBST_TX_ANT}$ is substitution antenna gain.

The measurement results are obtained as described below:

$$P [dBm] = P_{MEAS} + A_{CORRECTIONS}$$

Where P_{MEAS} is receiver reading in dBm and $A_{CORRECTIONS}$ is combined correction factor including cable loss and substitution correction ($A_{CORRECTIONS} = L_{CABLES} + A_{SUBST}$).

Limits for radiated RF output power measurements

Frequency range [MHz]	Limit [W]	Limit [dBm]
824 - 849	7	38.5
1850 - 1910	2	33

2.3. GSM 1900 Test results – Phone open

GSM mode

Channel	Frequency [MHz]	EIRP [dBm]	EIRP [W]	A _{CORRECTION} [dB]	Polarisation	Result
512	1850.200000	27.20	0.525	42.80	HORIZONTAL	Passed
661	1880.000000	30.50	1.122	44.00	HORIZONTAL	Passed
810	1909.800000	28.20	0.661	44.00	HORIZONTAL	Passed

GPRS mode, 2 TX Slots

Channel	Frequency [MHz]	EIRP [dBm]	EIRP [W]	A _{CORRECTION} [dB]	Polarisation	Result
512	1850.200000	27.95	0.624	43.50	VERTICAL	Passed
661	1880.000000	26.87	0.486	43.30	VERTICAL	Passed
810	1909.800000	28.50	0.708	43.40	VERTICAL	Passed

EGPRS mode, 1 TX Slot

Channel	Frequency [MHz]	EIRP [dBm]	EIRP [W]	A _{CORRECTION} [dB]	Polarisation	Result
512	1850.200000	27.32	0.540	43.50	VERTICAL	Passed
661	1880.000000	25.53	0.357	43.30	VERTICAL	Passed
810	1909.800000	26.59	0.456	43.40	VERTICAL	Passed

2.4. GSM 1900 Test results – Phone closed

GSM mode

Channel	Frequency [MHz]	EIRP [dBm]	EIRP [W]	A _{CORRECTION} [dB]	Polarisation	Result
512	1850.200000	28.20	0.661	42.80	HORIZONTAL	Passed
661	1880.000000	29.10	0.813	44.00	HORIZONTAL	Passed
810	1909.800000	29.20	0.832	43.40	VERTICAL	Passed

GPRS mode, 2 TX Slots

Channel	Frequency [MHz]	EIRP [dBm]	EIRP [W]	A _{CORRECTION} [dB]	Polarisation	Result
512	1850.200000	27.81	0.604	42.80	HORIZONTAL	Passed
661	1880.000000	29.51	0.893	44.00	HORIZONTAL	Passed
810	1909.800000	29.58	0.908	43.40	VERTICAL	Passed

EGPRS mode, 1 TX Slot

Channel	Frequency [MHz]	EIRP [dBm]	EIRP [W]	A _{CORRECTION} [dB]	Polarisation	Result
512	1850.200000	25.90	0.389	42.80	HORIZONTAL	Passed
661	1880.000000	28.33	0.681	44.00	HORIZONTAL	Passed
810	1909.800000	27.60	0.575	43.40	VERTICAL	Passed

3. Test Equipment

3.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
13037	Power Supply 0-15V 10A	EA3012	LP Instruments	15B,15C
13513	Pulse Limiter 9KHz-30MHz	ESH3Z2	Rohde&Schwarz	15B,15C
13666	EMI Test Reciever 9KHz-2,5GHz	ESPC	Rohde&Schwarz	15B,15C
13935	Two Lines Artificial Mains Network	ESH3-Z5	Rohde&Schwarz	15B,15C
16995	Directional Coupler 20dB 0,5-2,0 GHz SMA Conn.	1538RA-20	Weinschel	15B,15C
18772	Shielded Chamber	RFD-100	ETS-Lindgren	15B,15C
19171	Universal Radio Communication Tester	CMU200	Rohde&Schwarz	15B,15C
11386	System DC Power Supply	HP6632A	Hewlett Packard	22.24
11487	Network analyzer 300KHz-3,0GHz	HP8753A	Hewlett Packard	22.24
11584	Spectrum analyzer 50Hz-6,5GHz	HP8561B	Hewlett Packard	22.24
13134	Tracking generator	HP85645A	Hewlett Packard	22.24
13302	Spectrum Analyzer 9KHz-12.8GHz	HP8596E	Hewlett Packard	22.24
13371	Temperature Chamber	S-1,2C	Thermotron	22.24
13524	Digital Radiocomm. Tester	CMD55	Rohde&Schwarz	22.24
14807	S - Parameter Test Set 300KHz-6GHz	HP85047A	Hewlett Packard	22.24
15859	Digital Radio Communication Test Set	4201S	Wavetek	22.24
17277	Multimeter Digital 6 1/2 Digit	AT34401A	Agilent Technologies	22.24
17796	Radio Communication Test Set	4400M	Wavetek	22.24
19374	Resonant Dipole Antenna 850MHz SMA m Conn.	-	NMP Cph	22.24
19375	Resonant Dipole Antenna 1900MHz SMA m Conn.	-	NMP Cph	22.24
13037	Power Supply 0-15V 10A	EA3012	LP Instruments	15B,15C

3.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
14020	Programmable Relay Switching System	-	Pickering	15B,15C,22,24
18792	Multi Device Controller	2090	ETS-EMCO	15B,15C,22,24
13829	Turntable Controller	4630-100	Comtest	15B,15C,22,24
14963	RF Preamplifier 100MHz-4GHz (Metal Chassis)	AFS3-00100400	Miteq/NMP Cph	15B,15C,22,24
13668	BiLog Antenna 30-2000MHz	BiLog-CBL6112A	Chase	15B,15C,22,24
18861	EMI Test Receiver 20Hz-26,5GHz	ESI	Rohde&Schwarz	15B,15C,22,24
12679	Dual Log Periodic Antenna 1-18 GHz	HL025	Rohde&Schwarz	15B,15C,22,24
18860	Ultra Broadband Antenna	HL562	Rohde&Schwarz	15B,15C,22,24

Eq. No	Equipment	Type	Manufacturer	Used in
	Ultralog 30-3000MHz			
18773	Shielded Chamber	RFD-100	ETS-Lindgren	15B,15C,22,24
18774	Shielded Chamber	RFSD-F/A-100	ETS-Lindgren	15B,15C,22,24
18324	High Pass Filter 3GHz SMA f Conn	WHJS3000-10SS	Wainwright	15B,15C,22,24
14114	Highpass Filter 1000MHz-4500MHz	WHK1000-12SS	Wainwright	15B,15C,22,24
13918	Highpass Filter 2000-4000MHz 50OHM SMA Conn	WHKS2000-10SS	Wainwright Instruments	15B,15C,22,24
13937	Ultra Stable Notch Filter 902,4MHz	WRCA902.4-0.2/40-6SS	Wainwright Instruments	15B,15C,22,24
13936	Ultra Stable Notch Filter 1747,5MHz	WRCD1747.5-0.2/40-10SS	Wainwright Instruments	15B,15C,22,24
13917	Highpass Filter 1000-3000MHz 50OHM SMA Conn	WHKS1000-10SS	Wainwright Instruments	15B,15C,22,24
14188	Ultra Stable Notch Filter 902,4MHz	WRCA902.4-0.2/40-6SS	Wainwright	15B,15C,22,24
14187	Ultra Stable Notch Filter 1747,5MHz	WRCD1747.5-0.2/40-10SS	Wainwright	15B,15C,22,24
16633	Ultra Stable Notch Filter 1880,0MHz	WRCD1880.0-0.2/40-10SS	Wainwright	15B,15C,22,24
18323	Band reject filter 1947-1953MHz 40dB	WRCG1947/1953-1940/1960-40/6SS	Wainwright	15B,15C,22,24
15190	Infra Red Remote Control Unit	4630	Emco	22,24,15B,15C
14993	EMI Test Receiver 9KHz-2750MHz	ESCS30	Rohde&Schwarz	22,24,15B,15C
15191	Turntable Contoller Unit	G-800SDX	YAESU	22,24,15B,15C
14900	Antenna Controller	HD100	HD GmbH	22,24,15B,15C