

RF Exposure Evaluation declaration

Product Name	DOCK FOR iPhone/iPad WITH AirPlay
Model No.	DMI-40.4, DS-A5
FCC ID	PPQ-DSA5

Applicant	Lite-On Technology Corp.
Address	4F, 90, Chien 1 Road, Chung-Ho, Taipei Hsien 235, Taiwan, R.O.C.

Date of Receipt	June 25, 2012
Date of Declaration	July 12, 2012
Report No.	126416R-RFUSP42V01

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $Pd = (Pout * G) / (4 * \pi * R^2)$

Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product : DOCK FOR iPhone/iPad WITH AirPlay
 Test Item : RF Exposure Evaluation
 Test Site : No.3 OATS

Antenna Gain:

The maximum Gain measured in fully anechoic chamber is 2.35 dBi in logarithm scale.

802.11b

Output Power Into Antenna & RF Exposure Evaluation Distance (2.35 dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412.00	65.1628	0.022271
6	2437.00	67.2977	0.023000
11	2462.00	68.7068	0.023482

Power density in column 4 is much lower than the limit (1 mW/cm²).

802.11g

Output Power Into Antenna & RF Exposure Evaluation Distance (2.35 dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412.00	158.8547	0.054291
6	2437.00	177.0109	0.060497
11	2462.00	155.9553	0.053300

Power density in column 4 is much lower than the limit (1 mW/cm²).