

# RF EXPOSURE REPORT

## **CERTIFICATE OF CONFORMITY**

FCC Rule Part: FCC Part 2 (Section 2.1091)

Report No.: MFBCFP-WTW-P21050667A

FCC ID: PPQ-MS4

Product: MS4 Module

Model No.: MS4

**Received Date: 2023/6/29** 

Test Date: 2023/8/1

Issued Date: 2023/10/24

Applicant: LITE-ON Technology Corp.

Address: Bldg. C, 90, Chien 1 Rd., Chung-Ho, New Taipei City, 23585, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Hsin Chu Laboratory

**Lab Address:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan **Test Location:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan

FCC Registration / 723255 / TW2022

**Designation Number:** 

Approved by:		, Date:	2023/10/24	
	May Chen / Manager			

This test report consists of 8 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.





Prepared by : Phoenix Huang / Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <a href="http://www.bureauveritas.com/home/about-us/curbusiness/cps/about-us/terms-conditions/">https://www.bureauveritas.com/home/about-us/curbusiness/cps/about-us/terms-conditions/</a> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Report No.: MFBCFP-WTW-P21050667A Page No. 1 / 8 Report Format Version: 7.1.0 Reference No.: BBDJ-WTW-P23060577



## **Table of Contents**

Relea	ise Control Record	3
1	Certificate	4
2	Applicable RF Exposure Limit	5
3	Test Results	7
4	Conclusion	7
5	Information of the Testing Laboratories	8



## **Release Control Record**

Issue No.	Description	Date Issued
MFBCFP-WTW-P21050667A	Original release.	2023/10/24

Report No.: MFBCFP-WTW-P21050667A Page No. 3 / 8 Report Format Version: 7.1.0 Reference No.: BBDJ-WTW-P23060577



## 1 Certificate

Product: MS4 Module

Test Model: MS4

Sample Status: Engineering sample

Applicant: LITE-ON Technology Corp.

**Test Date:** 2023/8/1

FCC Rule Part: FCC Part 2 (Section 2.1091)

Standard: KDB 447498 D04 Interim General RF Exposure Guidance v01

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Report No.: MFBCFP-WTW-P21050667A Page No. 4 / 8 Report Format Version: 7.1.0

Reference No.: BBDJ-WTW-P23060577



#### 2 **Applicable RF Exposure Limit**

- § 1.1310 Radiofrequency radiation exposure limits.
- (a) Specific absorption rate (SAR) shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in § 1.1307(b) of this part within the frequency range of 100 kHz to 6 GHz (inclusive).
- (b) The SAR limits for occupational/controlled exposure are 0.4 W/kg, as averaged over the whole body, and a peak spatialaverage SAR of 8 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit for occupational/controlled exposure is 20 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 6 minutes to determine compliance with occupational/controlled SAR limits.
- (c) The SAR limits for general population/uncontrolled exposure are 0.08 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 1.6 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 30 minutes to determine compliance with general population/uncontrolled SAR limits.

#### (e) Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields

Limits for General Population/Uncontrolled Exposure

Fraguency Dange			Dower Density	Average Time	
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (minutes)	
Limits For General Population / Uncontrolled Exposure					
0.3-1.34	614	1.63	(100)*	30	
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30	
30-300	27.5	0.073	0.2	30	
300-1500			f/1500	30	
1500-100,000			1.0	30	

f = frequency in MHz. \* = Plane-wave equivalent power density.

Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (minutes)	
Limits For General Population / Uncontrolled Exposure					
0.3-3.0	614	1.63	*(100)	⊴6	
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6	
30-300	61.4	0.163	1.0	<6	
300-1,500			f/300	<6	
1,500-100,000			5	<6	

f = frequency in MHz. \* = Plane-wave equivalent power density.

Report No.: MFBCFP-WTW-P21050667A Page No. 5 / 8 Report Format Version: 7.1.0

Reference No.: BBDJ-WTW-P23060577



## 1 mW Blanket Exemption - §1.1307(b)(3)(i)(A)

The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in <u>paragraph (b)(3)(ii)(A)</u> of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A).

Report No.: MFBCFP-WTW-P21050667A Page No. 6 / 8 Report Format Version: 7.1.0 Reference No.: BBDJ-WTW-P23060577



## 3 Test Results

Environmental 25°C, 76% RH	Tested By:	Waydi Tuan
----------------------------	------------	------------

1 mW Blanket Exemption				
Operation Mode	Frequency Band (MHz)	Maximum ERP (mW)	Limit (mW)	Test Result
GFSK	2415-2459	0.001452	1	Pass

### Notes:

1. Calculate the ERP of GFSK from the radiated field strength:
ERP (dBm) = Radiated field strength (dBuV/m) + 20 x Log(d) - 104.77 - 2.15
d is the measurement distance, in 3 m.
ERP = 69 + 20 x Log(3) - 104.77 - 2.15 = -28.38 dBm (0.001452 mW)

## 4 Conclusion

Source-base time average power is below Exemption Criteria and/or Routine Evaluation MPE thresholds, therefore the device is compliant FCC RF exposure requirement.

Report No.: MFBCFP-WTW-P21050667A Page No. 7 / 8 Report Format Version: 7.1.0

Reference No.: BBDJ-WTW-P23060577



## 5 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

Hsin Chu EMC/RF/Telecom Lab

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180 Tel: 886-3-6668565 Fax: 886-2-26051924 Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: <a href="mailto:service.adt@bureauveritas.com">service.adt@bureauveritas.com</a>. <a href="mailto:web.bureauveritas.com.tw">web Site: <a href="mailto:http://ee.bureauveritas.com.tw">http://ee.bureauveritas.com.tw</a>.

The address and road map of all our labs can be found in our web site also.

--- END ---

Report No.: MFBCFP-WTW-P21050667A Page No. 8 / 8 Report Format Version: 7.1.0 Reference No.: BBDJ-WTW-P23060577