

RF Exposure Evaluation declaration

Product Name : PREMIUM SPEAKER DOCK

Model No. : MS7000

FCC ID : PPQ-MS7000

Applicant : Lite-On Technology Corp.

Address : 4F,90,Chien 1 Road,Chung-Ho,Taipei Hsien
235,Taiwan,R.O.C.

Date of Receipt : Apr. 25, 2012

Date of Declaration : Aug. 14, 2012

Report No. : 124518R-RFUSP42V01

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

R = distance between observation point and center of the radiator is 20 cm.

1.3. Test Result of RF Exposure Evaluation

Product : PREMIUM SPEAKER DOCK
 Test Item : RF Exposure Evaluation
 Test Site : No.3 OATS

(802.11b 1Mbps)

Output Power Into Antenna & RF Exposure Evaluation Distance (6.41 dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
01	2412.00	105.9254	0.092200
06	2437.00	103.0386	0.089687
11	2462.00	56.4937	0.049173

Power density in column 4 is much lower than the limit (1 mW/cm²).

(802.11g 6Mbps)

Output Power Into Antenna & RF Exposure Evaluation Distance (6.41 dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
01	2412.00	184.9269	0.160965
06	2437.00	253.5129	0.220664
11	2462.00	186.2087	0.162080

Power density in column 4 is much lower than the limit (1 mW/cm²).