

# RF Exposure Evaluation declaration

Product Name : GPS  
Model No. : PND-K3  
FCC ID : PPQ-PND-K3

Applicant : LITE-ON Technology Corp.

Address : 4F,90,Chien 1 Road, Chung-Ho, Taipei Hsien 235, Taiwan,  
R.O.C.

Date of Receipt : Apr. 15, 2008  
Date of Declaration : May. 02, 2008  
Report No. : 084248R-RFUSP06V01

The declaration results relate only to the samples calculated.  
The declaration shall not be reproduced except in full without the written approval of Quietek Corporation.  
This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b) LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

### 1.3. Test Result of RF Exposure Evaluation

Product : GPS  
 Test Item : RF Exposure Evaluation  
 Test Site : CTR1

#### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.41dBi in logarithm scale.

#### 1Mbps(GFSK)

##### Output Power Into Antenna & RF Exposure Evaluation Distance (1.41dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
00	2402.00	1.3964	0.000384
39	2441.00	1.4125	0.000389
78	2480.00	1.3646	0.000376

The distance r (4<sup>th</sup> column) calculated from the Fries transmission formula is far shorter than 20 cm separation requirement.

#### 3Mbps(8DPSK)

##### Output Power Into Antenna & RF Exposure Evaluation Distance (1.41dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
00	2402.00	1.4555	0.000401
39	2441.00	1.4791	0.000407
78	2480.00	1.3552	0.000373

The distance r (4<sup>th</sup> column) calculated from the Fries transmission formula is far shorter than 20 cm separation requirement.