Applica	nt/Grantee Lite-On Technology Corp.					
FCC ID	: PPQ-WN4510L					
Section 15.212 Modular Transmitters						
Request	: for Modular Approval 🛛 🛛 🛛 🛛 🛛 🤅	uest for Limited Modular Approval				
	Requirements	EUT Conditions	Comply (Y/N)			
Single Modular Approval Requirements						
1	The radio elements of the modular	The modular have RF own shielding	Y			
	transmitter must have their own					
	shielding. The physical crystal and					
	tuning capacitors may be located					
	external to the shielded radio elements.					
2	The modular transmitter must have	The modular transmitter have	Y			
	buffered modulation/data inputs (if such	buffered modulation/data inputs				
	inputs are provided) to ensure that the					
	module will comply with Part 15					
	requirements under conditions of					
2	excessive data rates or over-modulation.		X 7			
3	The modular transmitter must have its	The module contains its own power	Y			
	own power supply regulation.	supply regulation. Please refer to the schematic.				
4	The modular transmitter must comply	The modular must to built-in PIFA	Y			
4	with the antenna and transmission	applicant together and transmission	1			
	system requirements of Sections 15.203,	system requirements of Sections 15.203,				
	15.204(b) and 15.204(c). The antenna	15.204(b) and 15.204(c).				
	must either be permanently attached or					
	employ a "unique" antenna coupler (at					
	all connections between the module and					
	the antenna, including the cable). The					
	"professional installation" provision of					
	Section 15.203 is not applicable to					
	modules but can apply to limited					
	modular approvals under paragraph (b)					
	of this section.					
5	The modular transmitter must be tested	The EUT module can't be operated by	Y			
	in a stand-alone configuration, <i>i.e.</i> , the	its own due to its power-less				
	module must not be inside another	characteristic and hence needs external				
	device during testing for compliance	power supply to make it function.				
	with Part 15 requirements. Unless the transmitter module will be battery	Under testing condition, no matter in pure verification or manufacturing stage				
	powered, it must comply with the AC	pure verification or manufacturing stage, the specified test fixture must be				
	line conducted requirements found in	provided to help testing the function and				
	Section 15.207. AC or DC power lines	performance of the EUT sample.				
	and data input/output lines connected to	rentermanee of the Delt sumple.				
	the module must not contain ferrites,					
	unless they will be marketed with the					
	module (see Section 15.27(a)). The					
	length of these lines shall be the length					
	typical of actual use or, if that length is					
	unknown, at least 10 centimeters to					
	insure that there is no coupling between					

	the case of the module and supporting		
	equipment. Any accessories, peripherals,		
	or support equipment connected to the		
	module during testing shall be		
	unmodified and commercially available		
	(see Section 15.31(i)).		
6		The ECC identification much as an i	Y
6	The modular transmitter must be	The FCC identification number can put	1
	equipped with either a permanently	on the modular with either a	
	affixed label or must be capable of	permanently affixed label	
	electronically displaying its FCC		
	identification number.		
	(A) If using a permanently affixed label, the		
	modular transmitter must be labeled with its own		
	FCC identification number, and, if the FCC identification number is not visible when the		
	module is installed inside another device, then		
	the outside of the device into which the module is		
	installed must also display a label referring to		
	the enclosed module. This exterior label can use		
	wording such as the following: "Contains		
	Transmitter Module		
	FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording		
	that expresses the same meaning may be used.		
	The Grantee may either provide such a label, an		
	example of which must be included in the		
	application for equipment		
	authorization, or, must provide adequate		
	instructions along with the module which explain		
	this requirement. In the latter case, a copy of		
	these instructions must be included in the application for equipment authorization.		
	(B) If the modular transmitter uses an electronic		
	display of the FCC identification number, the		
	information must be readily accessible and		
	visible on the modular transmitter or on the		
	device in which it is installed. If the module is		
	installed inside another device, then the outside		
	of the device into which the module is installed		
	must display a label referring to the enclosed module. This exterior label can use wording such		
	as the following:		
	"Contains FCC certified transmitter module(s)."		
	Any similar wording that expresses the same		
	meaning may be used. The user manual must		
	include instructions on how to access the		
	electronic display. A copy of these instructions		
	must be included in the application for		
7	equipment authorization.	The modular have specific rules or	V
/	The modular transmitter must comply	The modular have specific rules or	Y
	with any specific rules or operating	operating requirements	
	requirements that		
	ordinarily apply to a complete		
	transmitter and the manufacturer must		
	provide adequate instructions along with		
	the module to explain any such		
	requirements. A copy of these		
	instructions must be included in the		

	application for equipment authorization.				
8	The modular transmitter must comply		Y		
	with any applicable RF exposure				
	requirements in its final configuration.				
A modular approval may be granted for single or split modular transmitters that do not comply with all of the					
above requirements, <i>e.g.</i> , shielding, minimum signaling amplitude, buffered modulation/data inputs, or power					
supply regulation, if the manufacturer can demonstrate by alternative means in the application for equipment					
authorization that the modular transmitter meets all the applicable Part 15 requirements under the operating					
conditions in which the transmitter will be used. Limited modular approval also may be granted in those					
instances where compliance with RF exposure rules is demonstrated only for particular product configurations.					
The applicant for certification must state how control of the end product into which the module will be installed					
will be maintained such that full compliance of the end product is always ensured.					

Ta. chuan Wu

Name/Title: TC Wu / Director Company Name: Lite-On Technology Corp. Address: 4F, 90, Chien 1 Road, Chung Ho, New Taipei City 23585, Taiwan, R.O.C. TEL: 886-2-2222-6181 FAX: 886-2-2226-6749 Email: sandra.liu@liteon.com Date: May 6, 2014