12. Radio Frequency Exposure

12.1 Applicable Standards

The measurements shown in this test report were made in accordance with the procedures given in FCC Part 2 (Section 2.1091)

Report No.: 22090062-TRFCC03

$$P_{\rm th} \; ({\rm mW}) = ERP_{\rm 20 \; cm} \; ({\rm mW}) = \begin{cases} 2040f & 0.3 \; {\rm GHz} \leq f < 1.5 \; {\rm GHz} \\ \\ 3060 & 1.5 \; {\rm GHz} \leq f \leq 6 \; {\rm GHz} \end{cases}$$

12.2 EUT Specification

Lo i opcomoation					
Frequency band (Operating)	☐ WLAN: 2412MHz ~ 2462MHz				
	☐ WLAN: 5150MHz ~ 5250MHz				
	⊠ Bluetooth: 2402MHz ~ 2480MHz				
Device category	☐ Portable (<20cm separation)				
Exposure	Occupational/Controlled exposure				
classification	☐ General Population/Uncontrolled exposure				
	Single antenna				
	☐ Multiple antennas				
Antenna diversity	☐ Tx diversity				
	Rx diversity				
	☐ Tx/Rx diversity				
Evaluation applied	☐ SAR Evaluation				
	□ N/A				
Remark:					
4 TI	Late Late (2.10 and 2.10 and 2				
1. The maximum conducted output power is <u>-0.67dBm (0.857mW) at 2480MHz (with 2.55dBi</u>					
<u>antenna gain.)</u>					
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the					
compliance.					

3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density

Cerpass Technology Corp.

would be larger.

T-FD-506-0 Ver 1.5 Page No. : 57 of 58

Issued Date : Jan. 07, 2023

Page No. : 57 of 58

FCC ID. : PPQ-WPX8324

12.3 Maximum Permissible Exposure

Channel	Max. Conducted			Max.Tune up e.r.p.	Max. Tune up e.r.p	Lingit
Frequency	output power	power	Antenna	Power	power	Limit
(MHz)	(dBm)	(dBm)	Gain(dBi)	(dBm)	(mW)	(mW)
2402-2480	-0.67	-0.17	2.55	0.23	1.05	3060

Report No.: 22090062-TRFCC03

-----THE END OF REPORT-----

Cerpass Technology Corp. T-FD-506-0 Ver 1.5

Page No. : 58 of 58 FCC ID. : PPQ-WPX8324

Issued Date : Jan. 07, 2023