## 12. Radio Frequency Exposure

## 12.1 Applicable Standards

The measurements shown in this test report were made in accordance with the procedures given in FCC Part 2 (Section 2.1091)

Report No.: 21120269-TRFCC03

$$P_{\rm th} \left( \mathrm{mW} \right) = ERP_{20 \mathrm{~cm}} \left( \mathrm{mW} \right) = \begin{cases} 2040 f & 0.3 \mathrm{~GHz} \leq f < 1.5 \mathrm{~GHz} \\ \\ 3060 & 1.5 \mathrm{~GHz} \leq f \leq 6 \mathrm{~GHz} \end{cases}$$

## 12.2 EUT Specification

| Lo i opecification |                                            |  |  |  |  |  |
|--------------------|--------------------------------------------|--|--|--|--|--|
| Frequency band     | ☐ WLAN: 2412MHz ~ 2462MHz                  |  |  |  |  |  |
|                    | ☐ WLAN: 5150MHz ~ 5250MHz                  |  |  |  |  |  |
|                    | ☐ WLAN: 5250MHz ~ 5350MHz                  |  |  |  |  |  |
| (Operating)        | ☐ WLAN: 5470MHz ~ 5725MHz                  |  |  |  |  |  |
|                    | ☐ WLAN: 5725MHz ~ 5850MHz                  |  |  |  |  |  |
|                    |                                            |  |  |  |  |  |
| Device category    | ☐ Portable (<20cm separation)              |  |  |  |  |  |
|                    |                                            |  |  |  |  |  |
| Exposure           | Occupational/Controlled exposure           |  |  |  |  |  |
| classification     | ☐ General Population/Uncontrolled exposure |  |  |  |  |  |
| Antenna diversity  | Single antenna                             |  |  |  |  |  |
|                    | ☐ Multiple antennas                        |  |  |  |  |  |
|                    | ☐ Tx diversity                             |  |  |  |  |  |
|                    | Rx diversity                               |  |  |  |  |  |
|                    | ☐ Tx/Rx diversity                          |  |  |  |  |  |
|                    |                                            |  |  |  |  |  |
| Evaluation applied | ☐ SAR Evaluation                           |  |  |  |  |  |
|                    | □ N/A                                      |  |  |  |  |  |
| Remark:            |                                            |  |  |  |  |  |
|                    |                                            |  |  |  |  |  |

- 1. The maximum conducted output power is <u>8.6dBm (7.244mW)</u> at <u>2480MHz</u> (with <u>7.17dBi antenna gain</u>.)
- DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
- For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.

Cerpass Technology Corp. Issued Date: Mar. 21, 2022

T-FD-506-0 Ver 1.5 Page No. : 47 of 48

FCC ID. : PPQ-WPX9926

12.3 Maximum Permissible Exposure

| Channel<br>Frequency<br>(MHz) | Max. Conducted output power (dBm) | Max. Tune up<br>power<br>(dBm) | Antenna<br>Gain(dBi) | Max.Tune<br>up e.r.p.<br>Power<br>(dBm) | Max. Tune<br>up e.r.p<br>power<br>(mW) | Limit<br>(mW) |
|-------------------------------|-----------------------------------|--------------------------------|----------------------|-----------------------------------------|----------------------------------------|---------------|
| 2402-2480                     | 8.60                              | 9.10                           | 7.17                 | 14.12                                   | 25.82                                  | 3060          |

-----THE END OF REPORT-----

Cerpass Technology Corp. T-FD-506-0 Ver 1.5 Issued Date : Mar. 21, 2022
Page No. : 48 of 48

Report No.: 21120269-TRFCC03

FCC ID. : PPQ-WPX9926