

CHARGING STATION

Model: EX-1193-1

In/Out: 208-240VAC, 1Ø, 50/60Hz, Max.80A

Enclosure Type: Type 3R

Temp: -35°C~50°C, 50°C~55°C de-rating Max.60A

Date:

SN:

FOR USE WITH ELECTRIC VEHICLES.

VENTILATION NOT REQUIRED.

FOR INDOOR OR OUTDOOR USE.

MADE IN TAIWAN.

CAN ICES-3(B) / NMB-3(B)



UL US
LISTED
EVSE
E534122

FCC ID: xxxxxxxx
FCC ID: xxxxxxxx
FCC ID: xxxxxxxxxxxxxx

Contains FCC ID: PPQ201707BG96

Contains FCC ID: PPQLILYW131

Contains FCC ID: PPQRYORR2L

Contains IC: 4491A-201709BG96

Contains IC: 4491A-LILYW131

Contains IC: 4491A-RYORR2L

CHARGING STATION

Model: EX-1193-1-48

In/Out: 208-240VAC, 1Ø, 50/60Hz, Max.48A

Enclosure Type: Type 3R

Temp: -35°C~55°C

Date:

SN:

FOR USE WITH ELECTRIC VEHICLES.

VENTILATION NOT REQUIRED.

FOR INDOOR OR OUTDOOR USE.

MADE IN TAIWAN.

CAN ICES-3(B) / NMB-3(B)



UL US
LISTED
EVSE
E354962

FCC ID: xxxxxxxx
FCC ID: xxxxxxxx
FCC ID: xxxxxxxxxxxxxx

Contains FCC ID: PPQ201707BG96

Contains FCC ID: PPQLILYW131

Contains FCC ID: PPQRYORR2L

Contains IC: 4491A-201709BG96

Contains IC: 4491A-LILYW131

Contains IC: 4491A-RYORR2L