

CHARGING STATION

MODEL: W1-UC166-OMK1ER

MFG: LITEON

IN/OUT: 208-240VAC, 1Ø, 60HZ, MAX. 48A

TEMP. : -30°C~50°C

ENCLOSURE: TYPE 4. FOR INDOOR OR OUTDOOR USE.

MFGDT:

S/N:

THIS DEVICE CONTAINS

FCC ID: PPO202008E99 | NAXD IC: 449 | A-02 | EG9 | NAXD

FCC ID: PPQLILYW131 IC: 449 | A-LILYW131

FCC ID: PPORYORR2L IC: 449 | A-RYORR2L



EVSE
E354962
FACTORY ID:

FOR USE WITH ELECTRIC VEHICLES.
VENTILATION NOT REQUIRED.
CAN ICES-3(B) / NMB-3(B)
MADE IN TAIWAN

CHARGING STATION

MODEL: W1-UC168-OMF1FR

MFG: LITEON

IN/OUT: 208-240VAC, 1Ø, 60HZ, MAX. 48A

TEMP. : -30°C~50°C

ENCLOSURE: TYPE 4. FOR INDOOR OR OUTDOOR USE.

MFGDT:

S/N:

THIS DEVICE CONTAINS

FCC ID: PPQLILYW131

IC:4491A-LILYW131

FCC ID: PPRYORR2L

IC:4491A-RYORR2L



EVSE
E354962
FACTORY ID:

FOR USE WITH ELECTRIC VEHICLES.
VENTILATION NOT REQUIRED.
CAN ICES-3(B) / NMB-3(B)
MADE IN TAIWAN

CHARGING STATION

MODEL: W1-UC168-OMF1FO

MFG: LITEON

IN/OUT: 208-240VAC, 1Ø, 60Hz, MAX. 48A

TEMP. : -30°C~50°C

ENCLOSURE: TYPE 4. FOR INDOOR OR OUTDOOR USE.

MFGDT:

S/N:

THIS DEVICE CONTAINS

FCC ID: PPQLILYW131

IC: 4491A-LILYW131



EVSE
E354962
FACTORY ID:

FOR USE WITH ELECTRIC VEHICLES.
VENTILATION NOT REQUIRED.
CAN ICES-3(B) / NMB-3(B)
MADE IN TAIWAN