



# TEST REPORT

No. 2013EEB00553-EMC

for

**HONG KONG IPRO TECHNOLOGY CO.,LIMITED**

**Mobile phone**

**Model Name: i3200**

**Marketing Name: IPRO**

**FCC ID: PQ4IPROI3200**

with

**Hardware Version: I3183\_MB\_P2\_v01**

**Software Version: MT6260M\_I3200\_IPRO\_V9\_0**

**Issued Date: 2013-12-05**

**Test Laboratory:**

*FCC 2.948 Listed: No.310359*

*IC O.A.T.S listed: No.6629C-1*

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China 100191

Tel:+86(0)10-62304633-2678 , Fax:+86(0)10-62304633-2504 Email:welcome@emcite.com. www.emcite.com

## **CONTENTS**

<b>1. TEST LABORATORY .....</b>	<b>3</b>
<b>1.1. TESTING LOCATION .....</b>	<b>3</b>
<b>1.2. TESTING ENVIRONMENT .....</b>	<b>3</b>
<b>1.3. PROJECT DATA .....</b>	<b>3</b>
<b>1.4. SIGNATURE .....</b>	<b>3</b>
<b>2. CLIENT INFORMATION .....</b>	<b>4</b>
<b>2.1. APPLICANT INFORMATION .....</b>	<b>4</b>
<b>2.2. MANUFACTURER INFORMATION .....</b>	<b>4</b>
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>5</b>
<b>3.1. ABOUT EUT .....</b>	<b>5</b>
<b>3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....</b>	<b>5</b>
<b>3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....</b>	<b>5</b>
<b>3.4. EUT SET-UPS .....</b>	<b>5</b>
<b>4. REFERENCE DOCUMENTS .....</b>	<b>6</b>
<b>4.1. REFERENCE DOCUMENTS FOR TESTING .....</b>	<b>6</b>
<b>5. LABORATORY ENVIRONMENT .....</b>	<b>7</b>
<b>6. SUMMARY OF TEST RESULTS .....</b>	<b>8</b>
<b>7. TEST EQUIPMENTS UTILIZED .....</b>	<b>9</b>
<b>ANNEX A: MEASUREMENT RESULTS .....</b>	<b>10</b>

## 1. Test Laboratory

### 1.1. Testing Location

Company Name: TMC Shenzhen, Telecommunication Metrology Center of MIIT  
Address: No. 12 Building, Shangsha Innovation and Technology Park, Futian District  
Postal Code: 518048  
Telephone: +86(0)755-33322000  
Fax: +86(0)755-33322001


### 1.2. Testing Environment

Normal Temperature: 15-35°C  
Relative Humidity: 20-75%

### 1.3. Project data

Testing Start Date: 2013-11-19  
Testing End Date: 2013-12-04

### 1.4. Signature



---

Du Zhaoxuan


(Prepared this test report)



---

Zhang Bojun

(Reviewed this test report)



---

Lu Minniu

Director of the laboratory  
(Approved this test report)

## **2. Client Information**

### **2.1. Applicant Information**

Company Name: HONG KONG IPRO TECHNOLOGY CO.,LIMITED  
Address /Post: ROOM C1D,6/F, WING HING INDUSTRIAL BUILDING,14 HING YIP STREET, KWUN TONG, KOWLOON, HONG KONG.  
City: HONG KONG.  
Postal Code: /  
Country: CHINA  
Telephone: 00852-96669759

### **2.2. Manufacturer Information**

Company Name: SHENZHEN ZHIKE COMMUNICATION CO., LTD  
Address /Post: 1805,Tower A , Phase I, Tianan High-Tech Plaza, Futian District, Shenzhen, R.P.China  
City: Shenzhen  
Postal Code: 518000  
Country: CHINA  
Telephone: 0755-83496450

### **3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**

#### **3.1. About EUT**

Description	Mobile phone
Model Name	i3200
Marketing Name	IPRO
FCC ID	PQ4IPROI3200

#### **3.2. Internal Identification of EUT used during the test**

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	356910053519716	I3183_MB_P2_v01	MT6260M_I3200_IPRO_V9_0

\*EUT ID: is used to identify the test sample in the lab internally.

#### **3.3. Internal Identification of AE used during the test**

AE ID*	Description	SN
AE1	Battery	/
AE2	Travel charger	/
AE3	USB cable	/

##### AE1

Model	BL-4C
Manufacturer	HONG KONG IPRO TECHNOLOGY CO.,LIMITED
Capacitance	1000mAh
Nominal voltage	3.7V

##### AE2

Model	TC-02
Manufacturer	HONG KONG IPRO TECHNOLOGY CO.,LIMITED
Length of cable	84cm

##### AE3

Model	/
Manufacturer	/
Length of cable	84cm

\*AE ID: is used to identify the test sample in the lab internally.

#### **3.4. EUT set-ups**

EUT set-up No.	Combination of EUT and AE	Remarks
Set.1	EUT1+ AE1 + AE2	Charging mode
Set.2	EUT1+ AE1 + AE3	USB mode

## **4. Reference Documents**

### **4.1. Reference Documents for testing**

The following documents listed in this section are referred for testing.

<b>Reference</b>	<b>Title</b>	<b>Version</b>
FCC Part 15, Subpart B	Radio frequency devices	10-1-2012 Edition
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2003

## 5. LABORATORY ENVIRONMENT

**Semi-anechoic chamber** (11.20 meters×6.10meters×5.60meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.5 dB, 3 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

**Control room** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 0.5 Ω

**Conducted chamber** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. =35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 0.5 Ω

**Fully-anechoic chamber** (11.20 meters×6.10 meters×6.60 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 0.5 Ω
Voltage Standing Wave Ratio (VSWR)	≤ 6 dB, from 1 to 6 GHz, 3 m distance

## 6. SUMMARY OF TEST RESULTS

<b>Abbreviations used in this clause:</b>	
P	Pass
NA	Not applicable
F	Fail

<b>Items</b>	<b>Test Name</b>	<b>Clause in FCC rules</b>	<b>Section in this report</b>	<b>Verdict</b>
1	Radiated Emission	15.109(a)	A.1	P
2	Conducted Emission	15.107(a)	A.2	P



**7. Test Equipments Utilized**

<b>NO.</b>	<b>Description</b>	<b>TYPE</b>	<b>SERIES NUMBER</b>	<b>MANUFACTURE</b>	<b>CAL DUE DATE</b>	<b>CAL PERIOD</b>
1	Test Receiver	ESCI	100701	R&S	2014.07.31	1 year
2	Test Receiver	ESCI	100702	R&S	2014.07.31	1 year
3	Test Receiver	FSP 40	100378	R&S	2013.12.21	1 year
4	BiLog Antenna	VULB9163	9163 330	Schwarzbeck	2014.02.24	3 years
5	LISN	ESH2-Z5	100196	R&S	2014.01.23	1 year
6	Dual-Ridge Waveguide Horn Antenna	3117	00066577	ETS-Lindgren	2016.04.01	3 years
7	Universal Radio Communication Tester	E5515C	GB47460389	Agilent	2014.08.01	1 year

## **ANNEX A: MEASUREMENT RESULTS**

### **A.1 Radiated Emission (§15.109(a))**

#### **Reference**

FCC: CFR Part 15.109(a)

#### **A.1.1 Method of measurement**

The field strength of radiated emissions from the unintentional radiator (USB mode of MS and charging mode of MS) at a distance of 3 meters is tested. Tested in accordance with the procedures of ANSI C63.4 - 2003, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

#### **A.1.2 EUT Operating Mode:**

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is Lenovo Thinkcentre M4099t, and the serial number of the PC is SA08850737. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

#### **A.1.3 Measurement Limit**

Limit from CFR Part 15.109(a)

Frequency of emission (MHz)	Field strength (microvolts/meter)
30-88	100
88-216	150
216-960	200
Above 960	500

\*Note: The original limit is defined at 10m test distance. This limit is calculated according to CISPR requirements.

#### **A.1.4 Test Condition**

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	120kHz (IF bandwidth)	5
1000-4000	1MHz/1MHz	15

### A.1.5 Measurement Results

A "reference path loss" is established and the  $A_{Rpl}$  is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{\text{Rpl}} = P_{\text{Mea}} + G_A + G_{\text{PL}}$$

Where

$G_A$ : Antenna factor of receive antenna

$G_{\text{PL}}$ : Path Loss

$P_{\text{Mea}}$ : Measurement result on receiver.


Note: the result contains vertical part and Horizontal part

#### Set.1 Charging mode


Frequency(MHz)	Result(dBuV/m)	$A_{\text{Rpl}}$ (dB)	$P_{\text{mea}}$ (dBuV)	Polarity
1030	31.4	-5.9	37.3	V
1320	29.6	-4.2	33.8	H
1865	33.4	-0.1	33.5	V
2357	36.7	1.7	35	V
3134.625	34.1	3.2	30.9	H
3240	34.9	3.3	31.6	V

#### Set.2 USB mode

Frequency(MHz)	Result(dBuV/m)	$A_{\text{Rpl}}$ (dB)	$P_{\text{Mea}}$ (dBuV)	Polarity
1073	38.5	-5.6	44.1	V
1500	43	-3.4	46.4	V
1596	36.1	-2.5	38.6	V
2357	36.5	1.7	34.8	V
3000.125	37.8	3	34.8	V
3239.75	34.8	3.3	31.5	H



**Figure A.1 Radiated Emission from 30MHz to 1GHz (Set.1, Charging mode)**



**Figure A.2 Radiated Emission from 1GHz to 4GHz (Set.1, Charging mode)**




Figure A.3 Radiated Emission from 30MHz to 1GHz (Set.2, USB mode)




Figure A.4 Radiated Emission from 1GHz to 4GHz (Set.2, USB mode)

## A.2 Conducted Emission (§15.107(a))

### Reference

FCC: CFR Part 15.107(a)

### A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 - 2003, section 7.2.

### A.2.2 EUT Operating Mode:

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is Lenovo Thinkcentre M4099t, and the serial number of the PC is SA08850737. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

### A.2.3 Measurement Limit


Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency		

### A.2.4 Test Condition in charging mode

Voltage (V)	Frequency (Hz)
120	60

RBW	Sweep Time(s)
9kHz	1

### A.2.5 Measurement Results




**Figure A.5 Conducted Emission (Set.1, Charging mode)**

#### Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.142000	41.9	FLO	L1	10.1	14.1	56.0
1.350000	39.5	FLO	L1	10.1	16.5	56.0
1.422000	40.5	FLO	L1	10.1	15.5	56.0
3.626000	35.8	FLO	L1	10.2	20.2	56.0
3.702000	40.9	FLO	L1	10.2	15.1	56.0
3.782000	39.3	FLO	L1	10.2	16.7	56.0

#### Final Measurement Detector 2

Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.574000	31.2	FLO	N	10.1	14.8	46.0
0.646000	32.2	FLO	N	10.0	13.8	46.0
0.718000	31.2	FLO	N	10.0	14.8	46.0
1.142000	33.4	FLO	L1	10.1	12.6	46.0
1.210000	30.3	FLO	L1	10.1	15.7	46.0
1.426000	31.5	FLO	L1	10.1	14.5	46.0



**Figure A.6 Conducted Emission (Set.2, USB mode)**

**Final Measurement Detector 1**

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.302000	44.7	FLO	N	10.1	11.3	56.0
1.462000	38.9	FLO	N	10.1	17.1	56.0
2.714000	40.3	FLO	N	10.2	15.7	56.0
3.122000	43.8	FLO	L1	10.2	12.2	56.0
4.918000	43.5	FLO	N	10.2	12.5	56.0
4.962000	42.3	FLO	L1	10.2	13.7	56.0

**Final Measurement Detector 2**

Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.302000	36.5	FLO	N	10.1	9.5	46.0
3.066000	37.3	FLO	N	10.2	8.7	46.0
4.862000	31.5	FLO	L1	10.2	14.5	46.0
4.918000	30.1	FLO	N	10.2	15.9	46.0
17.578000	35.5	FLO	N	10.6	14.5	50.0
23.998000	34.6	FLO	N	10.6	15.4	50.0

\*\*\*END OF REPORT\*\*\*