

7. Measurement Data (continued)

7.7. Public Exposure to Radio Frequency Energy Levels (15.247(i) (1.1307 (b)(1)) RSS-GEN 5.5, RSS 102

Channel Frequency	MPE Distance (cm)	DUT Output Power (dBm)	DUT Antenna Gain (dBi)	Power Density		Limit (mW/cm ²)	Result
				(mW/cm ²)	(W/m ²)		
	(1)	(2)	(3)	(4)		(5)	
1395.900	20.0	26.73753	2.0	0.1487589	1.4875890	1	Compliant
1399.100	20.0	26.73753	2.0	0.1487589	1.4875890	1	Compliant
1427.900	20.0	18.49785	2.0	0.0223108	0.2231080	1	Compliant
1431.100	20.0	17.26320	2.0	0.0167900	0.1678997	1	Compliant

$$PD = \frac{OP + AG}{(4 \times \pi \times d^2)}$$

- PD = Power Density (mW/cm²)
- OP = DUT Output Power (dBm)
- AG = DUT Antenna Gain (dBi)
- d = MPE Distance (cm)

- Reference CFR 2.1093(b): For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.
1. Reference CFR 2.1093(b): For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.
 2. Section 7.1 of this test report. Output power was calculated from the measured field strength.
 3. Antenna gain value for this product was taken from the client's specification data sheet.
 4. Power density is calculated from power measurement and antenna gain.
 5. Reference CFR 1.1310, Table 1: Limits for Maximum Permissible Exposure (MPE), Section (B): Limits for General Population/Uncontrolled Exposure.