

**FCC ID:** PQC-SRRBV5  
**Model:** IntelliVue CL SpO2  
**Hardware Version:** 1  
**Software Version:** D.00.70

**EUT technologies:**

Technologies:	EIRP
MBAN 2.4 GHz	-8.9 dBm +/-1 dB
SRR 2.45 GHz	3.2 dBm +/-1 dB

**SAR test exclusion according to KDB447498 (General RF Exposure Guidance v05)**

Equation from Chapter 4.3.1: Standalone SAR test exclusion considerations page 11 and ff.

1. Standalone SAR test exclusion for 100 MHz to 6 GHz at test separation distances  $\leq 50\text{mm}$

$$(\text{Threshold}_{1\text{-g};10\text{-g}}) \times d_{\text{separation}} / f^{0.5}$$

where

Threshold<sub>1-g;10-g</sub> is 3 for 1-g; 7.5 for 10-g

$d_{\text{separation}}$  is the min. test separation distance; 5mm is used if the distance is less

$f$  is the RF channel transmit frequency

The table below gives the calculated maximal power that could be used for source based time averaged conducted power, adjusted for tune up tolerance. If this is below the calculated value SAR testing is excluded.

f in [MHz]	$d_{\text{separation}}$ [mm]	Threshold <sub>1-g</sub>	Powerlimit [mW]	$P_{\text{max-declared}}$ [mW]	Exclusion
2400.00	5	3	9.68	0.16	yes
2450.00	5	3	9.58	2.63	yes
<b>SUM</b>	5	3	<b>9.58</b>	<b>2.79</b>	<b>yes</b>

**Document authorized:**

Alexander Hnatovskiy  
 Lab Manager  
 Radio Communications & EMC