

## TEST REPORT

Report No.: HK11090668-1

**Spin Master Toys Far East Limited**

Application  
For  
Certification

(Original Grant)

**(FCC ID: PQN44422TX49MHZ)**

Transmitter

Prepared and Checked by:

Approved by:

Signed On File  
Wong Cheuk Ho, Herbert  
Engineer

---

Chan Chi Hung, Terry  
Assistant Supervisor  
Date: October 13, 2011

- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## INTERTEK TESTING SERVICES

### GENERAL INFORMATION

**Spin Master Toys Far East Limited**  
**BRAND NAME: Spin Master Ltd, MODEL: 44422**

**FCC ID: PQN44422TX49MHZ**

Grantee:	Spin Master Toys Far East Limited
Grantee Address:	Room 1113, 11/F., Chinachem Golden Plaza, 77 Mody Road, Tsim Sha Tsui East, Kowloon, Hong Kong.
Contact Person:	Allen Yang
Tel:	N/A
Fax:	N/A
e-mail:	alleny/georgew@spinmaster.com
Manufacturer:	First Union Toys Co., Ltd
Manufacturer Address:	Gong Lian Industrial Estate, Wan Jiang, Dong Guan City, China.
Brand Name:	Spin Master Ltd
Model:	44422
Additional Model:	1021361/6016876, 1023913/6018296, 1023915/6018296, 1023996/6018354, 1023999/6018357, 1024001/6018360
Type of EUT:	Transmitter
Description of EUT:	NASCAR 1/24TH RF (44422) AHN RDC NASCAR 1:24th RF Ast GTL 4pk M01(1021361/6016876), AHN RDC NASCAR1:24thScI Ast GTL 2pk M01A(1023913/6018296), AHN RDC NASCAR1:24thScI Ast GTL 2pk M01B(1023915/6018296), AHN RDC NASCAR1:24DaleJRsrFAst GTL4pkM01(1023996/6018354), AHN RDC NASCAR1:24th Jimmy RF GTL 4pkSLD(1023999/6018357), AHN RDC NASCAR1:24th Tony RF GTL 4pkSLD(1024001/6018360)
Serial Number:	N/A
FCC ID:	PQN44422TX49MHZ
Date of Sample Submitted:	September 19, 2011
Date of Test:	September 21, 2011
Report No.:	HK11090668-1
Report Date:	October 13, 2011
Environmental Conditions:	Temperature: +10 to 40°C Humidity: 10 to 90%

---

---

## INTERTEK TESTING SERVICES

---

---

### SUMMARY OF TEST RESULT

**Spin Master Toys Far East Limited**  
**BRAND NAME: Spin Master Ltd, MODEL: 44422**

**FCC ID: PQN44422TX49MHZ**

TEST SPECIFICATION	REFERENCE	RESULTS
Maximum Peak Output Power	15.247(b), (c) / RSS-210 A8.4	N/A
Hopping Channel Carrier Frequencies Separation	15.247(e) / RSS-210 A8.1	N/A
20dB Bandwidth of the Hopping Channel	15.247(a) / RSS-210 A8.1	N/A
Number of Hopping Frequencies	15.247(e) / RSS-210 A8.1	N/A
Average Time of Occupancy of Hopping Frequency	15.247(e) / RSS-210 A8.1	N/A
Antenn Conducted Spurious Emissions	15.247(d) / RSS-210 A8.5	N/A
Radiated Spurious Emissions	15.247(d) / RSS-210 A8.5	N/A
RF Exposure Compliance	15.247(i) / RSS-Gen 5.5	N/A
Transmitter Power Line Conducted Emissions	15.207 / RSS-Gen 7.2.2	N/A
Transmitter Field Strength	15.227 / RSS-310 3.8	N/A
Transmitter Field Strength	15.229 / RSS-210 A2.7	N/A
Transmitter Field Strength, Bandwidth and Timing Requirement	15.231(a) / RSS-210 A1.1.1	N/A
Transmitter Field Strength, Bandwidth and Timing Requirement	15.231(e) / RSS-210 A1.1.5	N/A
Transmitter Field Strength and Bandwidth Requirement	15.239 / RSS-210 A2.8	N/A
Transmitter Field Strength and Bandwidth Requirement	15.249 / RSS-210 A2.9	N/A
Transmitter Field Strength and Bandwidth Requirement	15.235 / RSS-310 3.9	Pass
Receiver / Digital Device Radiated Emissions	15.109 / ICES-003	N/A
Digital Device Conducted Emissions	15.107 / ICES-003	N/A

- Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.
2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

---

# INTERTEK TESTING SERVICES

---

## Table of Contents

1.0	<b><u>General Description</u></b> .....	1
1.1	Product Description .....	1
1.2	Related Submittal(s) Grants.....	1
1.3	Test Methodology.....	1
1.4	Test Facility .....	1
2.0	<b><u>System Test Configuration</u></b> .....	2
2.1	Justification .....	2
2.2	EUT Exercising Software.....	2
2.3	Special Accessories .....	2
2.4	Equipment Modification .....	2
2.5	Measurement Uncertainty.....	2
2.6	Support Equipment List and Description .....	3
3.0	<b><u>Emission Results</u></b> .....	3
3.1	Field Strength Calculation.....	3
3.2	Radiated Emission Configuration Photograph.....	4
3.3	Radiated Emission Data .....	4
3.4	Conducted Emission Configuration Photograph.....	4
3.5	Conducted Emission Data .....	4
4.0	<b><u>Equipment Photographs</u></b> .....	6
5.0	<b><u>Product Labelling</u></b> .....	6
6.0	<b><u>Technical Specifications</u></b> .....	6
7.0	<b><u>Instruction Manual</u></b> .....	6
8.0	<b><u>Miscellaneous Information</u></b> .....	7
8.1	Measured Bandwidth.....	7
8.2	Discussion Pulse Desensitivity .....	7
8.3	Calculation of Average Factor.....	7
8.4	Emissions Test Procedures .....	7
9.0	<b><u>Equipment List</u></b> .....	8

---

## INTERTEK TESTING SERVICES

---

### 1.0 General Description

#### 1.1 Product Description

The Equipment Under Test (EUT) is a transmitter of an RC Car operating at 49.860 MHz as dictated by a crystal. The EUT is powered by a 4.5 V DC source (3 x 1.5V "AA" size batteries). The EUT has a left / right control lever, a forward / backward control lever and a power ON/OFF switch.

After switching ON the EUT and the receiver of the RC Car, activating the control levers on the EUT can control the receiver moving forward, backward, left and right.

The Model: 1021361/6016876, 1023913/6018296, 1023915/6018296, 1023996/6018354, 1023999/6018357 and 1024001/6018360 are the same as the Model: 44422 in hardware aspect. The difference in model number and item name only.

Antenna Type : External, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

#### 1.2 Related Submittal(s) Grants

The Certification procedure of receiver for this transmitter (with FCC ID: PQN44422RX49MHZ) is being processed as the same time of this application.

#### 1.3 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.4 (2003). All radiated measurements were performed in an Open Area Test Site. Preliminary scans were performed in the Open Area Test Site only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

#### 1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

---

## INTERTEK TESTING SERVICES

---

### 2.0 **System Test Configuration**

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2003).

The EUT was powered by 3 X new 1.5V "AA" size batteries.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

#### 2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

#### 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

#### 2.4 Equipment Modification

Any modifications installed previous to testing by Spin Master Toys Far East Limited will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Intertek Testing Services Hong Kong Ltd.

#### 2.5 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

#### 2.6 Support Equipment List and Description

N/A.

---

## INTERTEK TESTING SERVICES

---

### 3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

#### 3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where

- FS = Field Strength in dB $\mu$ V/m
- RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where

- FS = Field Strength in dB $\mu$ V/m
- RR = RA - AG - AV in dB $\mu$ V
- LF = CF + AF in dB

Assume a receiver reading of 52.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

RA = 52.0 dB $\mu$ V/m	
AF = 7.4 dB	RR = 18.0 dB $\mu$ V
CF = 1.6 dB	LF = 9.0 dB
AG = 29.0 dB	
AV = 5.0 dB	
FS = RR + LF	
FS = 18 + 9 = 27 dB $\mu$ V/m	

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm} [(27 \text{ dB}\mu\text{V/m})/20] = 22.4 \mu\text{V/m}$$

## INTERTEK TESTING SERVICES

---

### 3.2 Radiated Emission Configuration Photograph

#### Worst Case Radiated Emission at 49.860 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

### 3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 3.2 dB



---

---

## INTERTEK TESTING SERVICES

---

---

Applicant: Spin Master Toys Far East Limited  
Model: 44422  
Mode: Transmitting  
Sample: 1/2

Date of Test: September 21, 2011

Table 1

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp (dB)	Antenna Factor (dB)	Average Factor (dB)	Net at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	49.860	81.8	16	11.0	0.0	76.8	80.0	-3.2
V	99.720	40.8	16	12.0	-	36.8	43.5	-6.7
V	149.580	36.7	16	14.0	-	34.7	43.5	-8.8
H	199.440	34.9	16	16.0	-	34.9	43.5	-8.6
H	249.300	31.2	16	20.0	-	35.2	46.0	-10.8
H	299.160	29.7	16	22.0	-	35.7	46.0	-10.3
H	349.020	26.8	16	24.0	-	34.8	46.0	-11.2
H	398.880	24.9	16	25.0	-	33.9	46.0	-12.1
H	448.740	24.7	16	26.0	-	34.7	46.0	-11.3
H	498.600	24.1	16	26.0	-	34.1	46.0	-11.9

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emissions over 1000MHz.

## INTERTEK TESTING SERVICES

---

### 4.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

### 5.0 **Product Labelling**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

### 6.0 **Technical Specifications**

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

### 7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

---

## INTERTEK TESTING SERVICES

---

### 8.0 Miscellaneous Information

This miscellaneous information includes details of the measured bandwidth.

#### 8.1 Measured Bandwidth

The plot saved in bw.pdf which shows the fundamental emission is confined in the specified band. The field strength of any emission appearing between the band edges and up to 10kHz above and below the band edges (49.81 and 49.91 MHz) is at least 35.68 dB below the carrier level. And at 49.81 & 49.91 MHz, there are at least 26 dB below the carrier level. It meets requirement of Section 15.235(b).

#### 8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. Since the transmitter transmits the RF signal continuously.

#### 8.3 Calculation of Average Factor

The average factor is not applicable for this device as the transmitted signal is a continuously signal.

#### 8.4 Emissions Test Procedures

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.4 - 2003.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

## INTERTEK TESTING SERVICES

---

### 9.0 Equipment List

#### 1) Radiated Emissions Test

Equipment	EMI Test Receiver	EMI Test Receiver	Biconical Antenna
Registration No.	EW-2500	EW-2251	EW-0954
Manufacturer	R&S	ROHDESCHWARZ	EMCO
Model No.	ESCI	ESCI	3104C
Calibration Date	Jan 25, 2011	May 06, 2011	Apr 14, 2010
Calibration Due Date	Jan 25, 2012	May 06, 2012	Oct 14, 2011

Equipment	Log Periodic Antenna	14m Double Shield RF Cable (20MHz - 6GHz)
Registration No.	EW-0446	EW-2528
Manufacturer	EMCO	RADIALL
Model No.	3146	nm / br5d / sma 14m
Calibration Date	Apr 26, 2010	Dec 14, 2010
Calibration Due Date	Oct 26, 2011	Dec 14, 2011

#### 2) Bandedge Measurement

Equipment	Spectrum Analyzer
Registration No.	EW-2249
Manufacturer	R&S
Model No.	FSP30
Calibration Date	Oct 22, 2010
Calibration Due Date	Oct 22, 2011