

# Analysis Report

Report No.: 13050635HKG-003

The Equipment Under Test (EUT) is a portable 2.4GHz Transceiver (Helicopter Unit) for a RC helicopter operating at 2412 – 2469MHz with 1 MHz channel spacing. The EUT is powered by 1 X3.7V rechargeable battery (Li-Poly). After switch on the EUT and paired with controller, the EUT can be controlled to fly forward, backward, turning left and right direction by the corresponding controller. To charge the internal battery in the helicopter, either plug the charging connector from the controller into the charging jack on the helicopter for starting the charge process or using USB charging cable for charging via PC.

An internal, integral antenna has been used.

Antenna Gain: 0dBi

Nominal rated field strength: 82.0dB $\mu$ V/m at 3m

Maximum allowed field strength of production tolerance: +/- 4dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 86.0dB $\mu$ V/m at 3m in frequency 2.4GHz, thus;

The EIRP =  $[(FS \cdot D)^2 \cdot 1000 / 30] = 0.12\text{mW}$

Conducted power = Radiated Power (EIRP) – Antenna Gain  
So;

Conducted Power = 0.12mW.

The SAR Exclusion Threshold Level:

=  $3.0 \cdot (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$

=  $3.0 \cdot 5 / \text{sqrt}(2.469) \text{ mW}$

= 9.55 mW

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.