

## Technical Description

The brief circuit description is listed as below:

- 1) M1 acts as MCU (WT24DK2015) consist 2.4GHz Module Circuit (SSV7241).
- 2) Y1 is 16MHz crystal oscillator providing clock for U2.
- 3) U1 acts as Field Programmable Processor Array (PMC234-28).
- 4) U2 acts as Voltage Regulator (LC1218 SOT89).
- 5) U3 acts as Linear Charger (ETA4054).
- 6) U4 acts as DC-to-DC step-down converter (ETA1483).

**Antenna Type:** Internal antenna

**Antenna Gain:** 0dBi

**Nominal rated field strength:** 89.1dB $\mu$ V/m at 3m

**Maximum allowed field strength of production tolerance:** +/- 3dB



# WAILLY TECHNOLOGY LTD.

## WT24DK2015

Address: Unit 503-505, Fook Hong Industrial Building, 19 Sheung Yuet Road,  
Kowloon Bay, Kowloon.

Tel: (852) 2756 4500

Fax: (852) 2624 8510

E-mail: [szfree@public.szonline.net](mailto:szfree@public.szonline.net)

<http://www.wailly.net>



## WT24DK2015 Specification

### 1. General Description

The WT24DK2015A is a 2.4GHz ISM band RF transceiver module consists of SSV7241 transceiver, 16MHz crystal in a small board size.

In normal applications, WT24DK2015A module is connected to a low cost microcontroller. This module has high transmission data rate, low current consumption and simple control interface is easy to apply to the wireless products.

### 2. Features

- 2.4 GHz ISM band operation
- 250kbps, 1Mbps, and 2Mbps air rate
- Continuous TX mode, no re-lock between packets required\*
- Programmable status monitor: dedicated RX/FIFO monitor mode\*
- 1.9 to 3.6V supply range
- Automatic packet processing
- Advanced RSSI recording mode\*
- Up to 6 data pipes for 1 RX to multiple TXs

WT24DK2015 series including three kinds of models:

models	WT24DK2015A
appearance	
characteristics	Stamp hole &. DIP crystal oscillator

Pin Assignment	
1	GND
2	VCC
3	CE
4	SS
5	CLK
6	MOSI
7	MISO
8	IRQ

models	WT24DK2015B
appearance	
characteristics	Gold finger &. DIP crystal oscillator

Pin Assignment	
1	CE
2	SS
3	CLK
4	MISO
5	VCC
6	GND
7	IRQ
8	MOSI



models	WT24DK2015C
appearance	
characteristics	Stamp hole &. SMD crystal oscillator

Pin Assignment	
1	GND
2	VCC
3	CE
4	SS
5	CLK
6	MOSI
7	MISO
8	IRQ

**Note:**

If it is on the PCB, PCB need blank where module crystals foot enough location, Because the crystal oscillator welding feet have outstanding.

### 3. Electrical Characteristics

	MIN	TYP	MAX	单位
VDD	-0.3		3.6	V
VDD_IO Supply Voltage	-0.3		5.25	V
Operating Temp.	-20		85	°C
Storage Temp.	-40		125	°C
VDD Supply voltages	1.9		3.6	V
Power-down Current		9		uA
Standby Current		47		uA
Operating Frequency Range	2400		2484	MHz
TX DC current, 0 dBm output power		20.5		mA
RX DC current consumption		26.6		mA

### 4. Applications

- Wireless PC peripherals
- Wireless keyboards and mice
- Wireless gamepads
- Wireless audio
- VOIP & wireless headsets
- Remote controls
- Home automation
- Toys
- Consumer electronics
- Personal health and entertainment products