

## Analysis Report

The Equipment Under Test (EUT), is a portable 2.4GHz Transceiver (Controller Unit) for a RC car. The sample supplied operated on 61 channels, normally at 2412 - 2472 MHz for transmitter and receiver. The channels are separated by 1 MHz spacing.

The EUT is powered by 2 x 1.5V AAA batteries. After switch on the EUT, the car will be moved forward or backward and turned left and right based on the switches pressed in the controller.

Antenna Type: Internal, Integral antenna

Antenna Gain: 0dBi

Nominal rated field strength is 102.3 dB $\mu$ V/m at 3m

Maximum allowed production tolerance: 100 - 103dB $\mu$ V/m at 3m

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 103dB $\mu$ V/m at 3m in frequency 2.472GHz.

Thus, it below calculated field strength according to minimum SAR exclusion threshold level as follows:

The worst case of SAR Exclusion Threshold Level:

=  $3.0 * (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$

=  $3.0 * 5 / \text{sqrt}(2.483.5)$  mW

= 9.52 mW

According to the KDB 412172 D01:

$\text{EIRP} = [(\text{FS} * \text{D})^2 * 1000 / 30]$

Calculated Field Strength for 9.52mW is 105dBuV/m @3m

Since maximum field strength plus production tolerance  $\leq$  105dBuV/m @3m and antenna gain is  $\geq$  0.0dBi, it is concluded that maximum Conducted Power and Field Strength are well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.