

Analysis Report

The Equipment Under Test (EUT), is a portable 2.4GHz Transceiver (Controller Unit) for a RC car. The operation frequency range is between 2411MHz and 2472MHz with 21 channels, where 2457MHz is for pairing channel.

| | |
|------|------|
| 2411 | 2441 |
| 2413 | 2443 |
| 2420 | 2445 |
| 2422 | 2451 |
| 2424 | 2453 |
| 2426 | 2455 |
| 2428 | 2461 |
| 2435 | 2468 |
| 2437 | 2470 |
| 2439 | 2472 |
| 2457 | |

The EUT is powered by 2 x 1.5 V AAA batteries. After switch on the EUT, the car will be moved forward or backward, turned left or right based on the switches pressed in the controller.

Antenna Type: Internal, Integral

Antenna Type: Internal antenna

Antenna Gain: 0dBi

Nominal rated field strength is 86.8 dB μ V/m at 3m

Maximum allowed production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 89.8dB μ V/m at 3m in frequency 0.027145GHz, thus;

The EIRP = $[(FS * D)^2 * 1000 / 30] = 0.286mW$

Conducted power = Radiated Power (EIRP) – Antenna Gain

So;

Conducted Power = 0.286mW.

The SAR Exclusion Threshold Level:

$$= 3.0 * (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$$

$$= 3.0 * 5 / \text{sqrt}(2.472) \text{ mW}$$

$$= 9.540 \text{ mW}$$

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.