

# Analysis Report

The Equipment Under Test (EUT), is a portable 2.4GHz Transceiver (Controller Unit) for a RC car. The operation frequency range is between 2411MHz and 2472MHz with 21 channels, where 2457MHz is the pairing channel.

<b>2411</b>	<b>2443</b>
<b>2413</b>	<b>2445</b>
<b>2420</b>	<b>2451</b>
<b>2422</b>	<b>2453</b>
<b>2424</b>	<b>2455</b>
<b>2426</b>	<b>2457</b>
<b>2428</b>	<b>2461</b>
<b>2435</b>	<b>2468</b>
<b>2437</b>	<b>2470</b>
<b>2439</b>	<b>2472</b>
<b>2441</b>	

The EUT is powered by 2 x 1.5 V AAA batteries. After switch on the EUT, the car will be moved forward or backward, turned left or right based on the switches pressed in the controller.

**Antenna Type:** Internal, Integral

**Antenna Type:** Internal antenna

**Antenna Gain:** 0dBi

**Nominal rated field strength is 97.5 dB $\mu$ V/m at 3m**

**Maximum allowed production tolerance: +/- 3dB**

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 100.5dB $\mu$ V/m at 3m in frequency 0.027145GHz, thus;

$$\text{The EIRP} = [(FS \cdot D)^2 \cdot 1000 / 30] = 3.366\text{mW}$$

Conducted power = Radiated Power (EIRP) – Antenna Gain

So;

$$\text{Conducted Power} = 3.366\text{mW}$$

The SAR Exclusion Threshold Level:

$$= 3.0 * (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$$

$$= 3.0 * 5 / \sqrt{2.472} \text{ mW}$$

$$= 9.540 \text{ mW}$$

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.