

1. Firmware Updata

2013/03/28

To upgrade the version of the firmware on a Web setup screen using a Web browser, follow the procedure below.

1. Start a web browser and access and log in to the AP.
2. Open the “Maintenance” menu
3. And then open the “Firmware”page.
4. Click the [参照...] button and select the desired firmware then,
5. Click the [Update] button to upgrade the firmware.
6. After the firmware uploaded into the device, it requires to save and restart the access point to activate.

The screenshot shows the 'Wireless LAN Manager' web interface in Microsoft Internet Explorer. The browser address bar shows 'http://192.168.0.12/en/mnt_firmware.cgi'. The page title is 'Firmware Update'. On the left, a 'Menu' sidebar contains 'Maintenance' and 'Firmware' (both highlighted with red boxes and arrow 3). The 'Firmware' sub-menu includes 'Time Adjustment', 'Password', 'Download', 'Upload', 'Default Setting', and 'Ping'. Below the sidebar are 'Top Page', 'Cancel Setting', 'Help', 'Japanese', and 'Save / Reboot' (with 'Save & Reboot' highlighted by arrow 6). The main content area has a search box with a '参照...' button (arrow 4) and an 'Update' button (arrow 5) next to a 'Clear' button. The status bar at the bottom shows 'ページが表示されました' and 'インターネット'.