

**The Approval
Specialists****BWS Tech, Inc.**294-9, Jungdae-Dong, Gwangju-City, Gyeonggi-Do 464-809 Korea
TEL: 82 31 764 0125 FAX: 82 31 764 0126**FCC EMI TEST REPORT**

Date of Test : Dec. 28, 2001
Test Report No. : 02BWS001.FCC
Test Site : BWS Tech, Inc. (Registration No. : 553281)

Trade Name : N/A
Manufacturer : Digital Device, Inc.
Address : 4th Fl., Hanhwa B/D, 78-1 Karakbon-Dong, Songpa-Gu, Seoul 138-169
Korea.

Contact Person : So-Yeon Jin, Manager
Tel No. : 82-2-431-8471
Fax No. : 82-2-431-8472

Product : 42" PLASMA DISPLAY MONITOR

Model : DPD-4200

Fcc Rule Part(s) : FCC Part 15 Subpart B

Classification : Class B

The device bearing the trade name and model specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C.63.4-2000.

I attest to the accuracy of data and all measurement reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualification of all persons taking them.



TaeHyun Nam
President-BWS Tech, Inc.
<http://www.approvalspecialists.co.kr>

TABLE OF CONTENTS	PAGE
1. Description of device	3
1.1 General	3
1.2 EUT Description	3
2. Test facility	4
3. Summary of results	4
3.1 Electromagnetic Emission	4
3.2 Modifications to the EUT	4
4. Tested system details	5
4.1 Peripherals and Others	5
4.2 Type of Cables Used	5
4.3 System layout on EUT and peripherals	6
5. Test result	7
5.1 RFI Voltage Measurement	7
5.2 RFI Field Strength Measurement	8
5.3 Minimum Margin	13
5.4 Sample Calculations	13
6. Test Equipments	14
7. Measurement Photos	15
7.1 Setup with RFI Voltage Emission Level	15
7.2 Setup with RFI Field Strength Emission Level	16

1. DESCRIPTION OF DEVICE

1.1 General

Responsible Party	Digital Device, Inc.	
Contact Person	So-Yeon Jin	Tel No. : 82-2-431-8471 Fax No. : 82-2-431-8472
Manufacturer	Digital Device, Inc. 4th Fl., Hanhwa B/D, 78-1 Karakbon-Dong, Songpa-Gu, Seoul 138-169 Korea.	

- Trade name N/A
- Model name **DPD-4200**
- EUT Type **42" PLASMA DISPLAY MONITOR**
- Classification **FCC Part 15 Subpart B Class B**
- Clock Speed **Main Clock : 31.48,16.7741,20.250,20.48,18.431MHz**
- Rule Part(s) **FCC Part 15 & Part 2**
- Test Procedure(s) **ANSI C63.4-2000**
- Date of Tests **Dec. 28, 2001**
- Place of Tests **BWS Tech, Inc.**

1.2 EUT Description

With its ultra slim design, PDP can be placed anywhere to let you enjoy multimedia contents. It is the perfect multimedia display terminal with direct connections to PCs, Terrestrial / CABLE / Satellite receivers, DVD players, TV RF, Camcorders, and more.

Note. This report may be reproduced in full. Partial reproduction may only be made with the written permission of the laboratory. The results in this report is only applied to the sample(s) tested.

Note. Please refer to the duties and responsibilities of the Responsible Party attached.

2. TEST FACILITY

The open field test site and conducted measurement facility used for this measurement, is located following address. This site was fully described in a report dated Dec. 26, 2001 that was submitted to the FCC. Our site and facility had been accepted in a letter dated Dec. 26, 2001(Registration No. : 553281) :

BWS Tech, Inc.

Address : 294-9, Jungdae-Dong, Gwangju-City, Gyeonggi-Do 464-809 Korea

The detailed description of the measurement facility was found to be in compliance with the requirements of §2.948 according to ANSI C63.4 on Dec. 08, 2000.

3. SUMMARY OF RESULTS

3.1 Electromagnetic Emission

RFI Voltage Measurement **PASS**

RFI Field Strength Measurement **PASS**

Although the measured emissions indicate that the EUT complies with the required limits, some measurement are close to these limits.

When the uncertainty of measurement is considered, there is some possibility that the EUT may not be compliant.

3.2 Modifications to the EUT : None

4. TESTED SYSTEM DETAILS

4.1 Peripherals and Others :

Description	Model Name	Serial No.	Manufacturer	FCC ID
Computer	KAYAK	5064-7432A034598	HP	DoC
Keyboard	RT235BTW	B13BC90L39GU	Compaq	AQ6-22K15
PS2 Mouse	M-S34	F13490N5BGF	Compaq	DZL211029
Serial Mouse #1	OK-520	00DAC0231	A4 TECH	DoC
Serial Mouse #2	Pro Mouse II	96002117	NEOTEC	FSUGMZC7
Joystick	GAMEPAD USB	S1050910000564	CREATIVE	DoC
Modem	0775	-	3COM	DoC
42" PLASMA DISPLAY MONITOR	DPD-4200	-	Digital Device, Inc.	EUT

4.2 Type of Cables Used:

Device from	Device to	Type of Cable	Length	Type of shield
Computer	Keyboard	Signal cable	2.0	Shielded
Computer	PS2 Mouse	Signal cable	1.5	Shielded
Computer	Mouse #1,#2	Signal cable	1.5	Shielded
Computer	Joystick	Signal cable	1.5	Shielded
Computer	Modem	Signal cable	1.5	Shielded
Computer	EUT	Power cable	2.0	Non-shielded
Video	Computer	-	1.5	Shielded
Power Cable	Power	-	1.5	Non-shielded

4.3 System layout on EUT and peripherals




Figure 4-1 System layout

5. TEST RESULT

5.1 RFI Voltage Measurement

5.1.1 Measurement Instrumentation Used

(model/serial no./manufacturer/last calibration/next calibration)

EMI Receiver (ESH3/892580/R&S/01 Jun. 2001/Jun. 2002)

L.I.S.N (L3-25/1110K70403/PMM/01 Sep. 2001/Sep. 2002)

Coaxial cable (RG213U/---/MARLOW/-/-)

Shield Room (JASH01/---/SEMITECH/---/---)

5.1.2 Measurement Procedure

The power line conducted interference measurement were performed according to ANSI C63.4-2000 in a Shielded room placed on a table, 0.8 m high over a metal floor. It was located more than required distance away from the shielded enclosure wall. Deviations from the standard was none. The EUT was plugged into the LISN and the frequency range of interest scanned. **We measured device in normal operation mode.** We reported at maximum emission levels.

5.1.3 Operation Modes

EUT was tested according to the specifications given by the manufacturer, and exercised in the most unfavorable manner.

5.1.4 Measurement Uncertainty

Measurement uncertainty of RFI Voltage Measurement test was estimated at ± 1.8 dB(k=2)

5.1.5 Test Data

RFI Voltage Measurement Results (0.45 MHz to 30 MHz)

Operating mode : **Normal operation Mode.**

Test procedure : ANSI C63.4-2000

Date of measurement : Dec. 28, 2001

Temperature : 11°C

Humidity : 38 %

Model : **DPD-4200**

FREQ(MHz)	LEVEL(dBuV)	LINE	LIMIT(dBuV)	Result(dBuV)	MARGIN(dBuV)
0.160	43.20	N	48.00	43.20	-4.80
0.174	31.70	H		31.70	-16.30
0.217	23.20	H		23.20	-24.80
0.302	14.00	N		14.00	-34.00
0.417	24.70	H		24.70	-23.30
0.486	17.50	H		17.50	-30.50
2.386	34.50	H		34.50	-13.50
2.653	35.00	H		35.00	-13.00
2.932	35.50	N		35.50	-12.50
3.222	34.00	N		34.00	-14.00
3.478	30.20	H		30.20	-17.80
4.325	32.00	N		32.00	-16.00
6.840	42.00	H		42.00	-6.00
7.700	39.20	H		39.20	-8.80
8.460	39.00	H		39.00	-9.00
15.240	45.20	H		45.20	-2.80
16.260	41.50	H		41.50	-6.50
23.290	44.50	H		44.50	-3.50

Table 1. Line Conducted Emission Tabulated Data

Note :

1. All modes of operation were investigated and the worst-case emissions are reported.
See attached Plots.
2. The limit for Class B digital device is 250 μV (48.0 dBμV) from 450 KHz to 30 MHz.
3. Line H = Hot Line N = Neutral


** Measurement using CISPR quasi-peak mode




Tested by **Hyung-Seok Lee**

5.2 RFI Field Strength Measurement

PLOTS OF EMISSIONS



PLOTS OF EMISSIONS



5.2.1 Measurement Instrumentation Used

(model/serial no./manufacturer/last calibration/next calibration)

Signal Analyzer (PMM9000/3100J70602/PMM/17 Oct. 2001/Oct. 2002)

Spectrum Analyzer(R3261C/61720002/Advantest/22 Aug. 2001/Aug. 2002)

Biconical antenna (BC01/0020J70501/PMM/17 Oct. 2001/Oct. 2002)

Log periodic antenna (LP01/0020J70501/PMM/17 Oct. 2001/Oct. 2002)

Coaxial cable (RG213U/---/MARLOW/--/--)

5.2.2 Measurement Procedure

Final test was performed according to ANSI C63.4-2000 at the open field site .
Deviations from the standard were none.

The EUT was placed in a 0.8 m high table along with the peripherals. The turn table was separated from the antenna with the distance of 3 meter. Cables were placed in a position to produce maximum emissions as determined by experimentation, and operation mode was selected for maximum.

The frequencies and amplitudes of maximum emission were measured at varying azimuths, antenna heights and antenna polarities. **We measured device in normal operation mode.**
We reported at maximum emission levels.

5.2.3 Operation Modes

EUT was tested according to the specifications given by the manufacturer, and exercised in the most unfavorable manner.

5.2.4 Measurement Uncertainty

Measurement uncertainty of RFI Field Strength Measurement test was estimated at ± 3.5 dB(k=2)

5.2.5 Test Data

RFI Field Strength Measurement Results(30 MHz to 1000 MHz)

Operating mode : **Normal Operation Mode.**

Test procedure : ANSI C63.4-2000

Date of measurement : Dec. 28, 2001

Temperature : 19°C

Humidity : 38%

Model : **DPD-4200**

MEASEMENT FREQ (MHz)	MEASEMEN TLEVEL (dBuV)	ANTENNA POLARITY (H/V)	ANTENNA FACTOR (dB)	CABLE LOSS (dB)	LIMIT (dBuV)	FIELD STRENGTH (dBuV/m)	MARGIN (dBuV/m)
37.73	10.00	V	12.60	1.27	40.00	23.87	-16.13
41.69	10.40	V	13.69	2.61		26.70	-13.30
49.61	14.10	V	9.73	1.38		25.21	-14.79
127.97	9.60	V	12.52	2.30	43.5	24.42	-19.08
174.95	8.50	V	13.40	2.74		24.64	-18.86
199.96	7.60	V	14.28	2.93		24.81	-18.69
255.97	14.40	H	12.19	3.42	46	30.01	-15.99
383.98	12.70	H	15.48	4.18		32.36	-13.64
411.98	11.80	H	15.97	4.35		32.12	-13.88
639.97	7.40	H	20.68	5.56		33.64	-12.36
767.97	6.20	V	22.43	6.27		34.90	-11.10
895.97	4.30	V	24.69	6.27		35.26	-10.74

Table 2. Radiated Measurements at 3meters.


Note :

- 1. All modes of operation were investigated and the worst-case emissions are reported.**
- 2. The limit for Class B digital device is 100 µV/m (40.0 dBµV/m) from 30 MHz to 88 MHz, 150 µV/m (43.5 dBµV/m) from 88 MHz to 216 MHz, 200 µV/m(46.0 dBµV/m) from 216 MHz to 960 MHz and 500 µV/m (53.98 dBµV/m) from above 960 MHz.**

* AFCL = Antenna Factor and Cable Loss

** Measurements using CISPR quasi-peak mode. Above 1 GHz, peak detector function mode is using a resolution bandwidth of 1 MHz and a video bandwidth of 1 MHz.

The peak level complies with the average limit. Peak mode is used with linearly polarized horn antenna and low-loss microwave cable.



Tested by **Hyung-Seok Lee**

5.3 Minimum Margin

Conducted emission

42" PLASMA DISPLAY MONITOR Normal operation mode 15.24 MHz, 2.8 dB

Radiated emission

42" PLASMA DISPLAY MONITOR Normal operation mode 895.97 MHz, 10.74 dB

5.4 SAMPLE CALCULATIONS

$$\text{dB}\mu\text{V} = 20 \log_{10} (\mu\text{V}/\text{m})$$

$$\mu\text{V} = 10^{(\text{dB}\mu\text{V}/20)}$$

EX. 1.

@ 15.24 MHz

Class B limit = 250 μV = 48 dB μV

Reading = 45.2 dB μV (calibrated level)

$$10^{(45.2/20)} = 181.97 \mu\text{V}/\text{m}$$

Margin = 45.2 - 48 = -2.8

2.8 dB ; below limit

EX. 2.

@ 895.97 MHz

Class B limit = 200 $\mu\text{V}/\text{m}$ = 46.0 dB $\mu\text{V}/\text{m}$

Reading = 4.3 dB μV (calibrated level)

Antenna factor + Cable Loss = 30.96 dB

Total = 35.26 dB $\mu\text{V}/\text{m}$

$$10^{(35.26/20)} = 57.94 \mu\text{V}/\text{m}$$

Margin = 35.26 - 46.0 = -10.74 dB

10.74 dB ; below limit

6. TEST EQUIPMENTS

The listing below denotes the test equipments utilized for the test(s).

<u>Nomenclature</u>	<u>Manufacture Model Number</u>	<u>Serial Number</u>	<u>Calibration Date</u>
Signal Analyzer (9kHz – 1.2GHz)	PMM PMM 9000	3100J70602	01/10/17
Spectrum Analyzer (9kHz – 2.6GHz)	ADVANTEST R3261C	61720002	01/08/22
EMI Receiver	ESH3	892580	01/06/01
Amplifier (0.1MHz-1.3GHz)	HP 8447E	2945A02712	01/08/19
AMN(LISN)	PMM L3-25	1110k70403	01/09/01
Biconical Antenna	PMM BC01	0020J70501	01/10/17
Biconical Antenna	SWALZBECK BBA9106	-	01/09/06
Log Periodic Antenna	PMM LP01	0020J70501	01/10/17
Log Periodic Antenna	SCHAFFNER UPA6109	-	01/09/06
Dipole Antenna	SWALZBECK VDA6106A	1277	01/09/10
Dipole Antenna	SWALZBECK UHA9105	91052168	01/09/10
Plotter	HP 7475A	007475A	-
Shield Room 7m x 4m x 4m	SEMITECH -	000815	-
Turn Table	JAEMC JAC-2	980723	-
Antenna Mast	Dai-il EMC JAC-1	970815	-

7. MEASUREMENT PHOTOS

7.1 Setup with the Maximized RFI Voltage Emission Level



7.2 Setup with the Maximized RFI Field Strength Emission Level

