

TEST REPORT

Applicant Name : Whirlpool Microwave Products Development Limited.
Address : 17th Fl, Elite Centre, 22 Hung To Rd, Kwun Tong, Hong Kong
Report Number : RA230625-36010E-EM-01
FCC ID: PR4FLUSHP2MT

Test Standard (s)

FCC Part 18

Sample Description

Product Type: Microwave Oven
Model No.: MMMF8030P
Trade Mark: Whirlpool
Date Received: 2023-06-25
Date of Test: 2023-06-26
Report Date: 2023-07-06

| | |
|--------------|-------|
| Test Result: | Pass* |
|--------------|-------|

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Zeki Ma

Zeki.Ma
EMC Engineer

Approved By:

Candy Li

Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "**". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503290 Web: www.atc-lab.com

TABLE OF CONTENTS

| | |
|--|-----------|
| DOCUMENT REVISION HISTORY | 3 |
| GENERAL INFORMATION..... | 4 |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) | 4 |
| OBJECTIVE | 4 |
| TEST METHODOLOGY | 4 |
| MEASUREMENT UNCERTAINTY | 5 |
| TEST FACILITY | 5 |
| OPERATING CONDITION/TEST CONFIGURATION..... | 6 |
| JUSTIFICATION | 6 |
| EUT EXERCISE SOFTWARE | 6 |
| SPECIAL ACCESSORIES | 6 |
| EQUIPMENT MODIFICATIONS | 6 |
| SUPPORT EQUIPMENT LIST AND DETAILS | 6 |
| EXTERNAL CABLE LIST AND DETAILS | 6 |
| CONFIGURATION OF TEST SETUP | 6 |
| BLOCK DIAGRAM OF TEST SETUP | 7 |
| SUMMARY OF TEST RESULT | 8 |
| TEST EQUIPMENT LIST | 9 |
| FCC §18.313, §1.1310, §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE..... | 11 |
| APPLICABLE STANDARD | 11 |
| MEASUREMENT | 11 |
| CONDUCTED EMISSIONS | 13 |
| APPLICABLE STANDARD | 13 |
| EUT SETUP | 13 |
| EMI TEST RECEIVER SETUP | 13 |
| TEST PROCEDURE | 14 |
| CALCULATION | 14 |
| TEST DATA | 14 |
| RADIATION HAZARD MEASUREMENT | 17 |
| APPLICABLE STANDARD | 17 |
| ENVIRONMENTAL CONDITIONS | 17 |
| INPUT POWER | 17 |
| LOAD FOR HOUSEHOLD MICROWAVE OVENS | 17 |
| RF OUTPUT POWER MEASUREMENT | 18 |
| OPERATING FREQUENCY MEASUREMENT | 19 |
| VARIATION IN OPERATING FREQUENCY WITH LINE VOLTAGE..... | 21 |
| RADIATED EMISSIONS..... | 23 |
| APPLICABLE STANDARD | 23 |
| EUT SETUP | 23 |
| EMI TEST RECEIVER SETUP AND SPECTRUM ANALYZER SETUP | 24 |
| TEST PROCEDURE | 24 |
| CALCULATION | 24 |
| TEST DATA AND PLOTS | 24 |

DOCUMENT REVISION HISTORY

| Revision Number | Report Number | Description of Revision | Date of Revision |
|------------------------|-----------------------|--------------------------------|-------------------------|
| 0 | RA230625-36010E-EM-01 | Original Report | 2023-07-06 |

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

| | |
|-------------------------------|--------------------------|
| Product | Microwave Oven |
| Tested Model | MMM8030P |
| Voltage Range | AC 120V/60Hz |
| Microwave operating frequency | 2450MHz |
| Microwave Output power | 950W |
| Microwave Input power | 1800W |
| Sample serial number | 277Y-1 (Assigned by ATC) |
| Sample/EUT Status | Good condition |

Objective

This report is in accordance with Part 2-Subpart J, and Part 18-Subparts A, B and C of the Federal Communication Commission's rules and regulations.

The objective of the manufacturer is to determine compliance with FCC Part 18 limits.

Test Methodology

All measurements contained in this report were conducted with MP-5, FCC Methods of Measurements of Radio Noise Emissions from ISM Equipment, February 1986. All measurements were performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters. Each test item follows test standards and with no deviation.

Measurement Uncertainty

| Parameter | | Uncertainty |
|------------------------------------|-----------------|------------------------|
| RF Frequency | | 0.082×10^{-7} |
| AC Power Lines Conducted Emissions | | 2.74dB |
| Emissions, Radiated | 30MHz - 1GHz | 5.08dB |
| | 1GHz - 18GHz | 4.96dB |
| | 18GHz - 26.5GHz | 5.16dB |
| Temperature | | 1°C |
| Humidity | | 6% |
| Supply voltages | | 0.4% |

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189.

Accredited by American Association for Laboratory Accreditation (A2LA). The Certificate Number is 4297.01

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0016. The Registration Number is 30241.

OPERATING CONDITION/TEST CONFIGURATION

Justification

The EUT was operated at maximum (continuous) RF output power. The loads consisted of water in a glass beaker in the amounts specified in the test procedure.

EUT Exercise Software

No exercise software was used.

Special Accessories

No special accessory was used.

Equipment Modifications

No modifications were made to the EUT tested.


Support Equipment List and Details

| Manufacturer | Description | Model | Serial Number |
|--------------|--------------|-------|---------------|
| / | Glass beaker | / | / |

External Cable List and Details


| Cable Description | Length (m) | From/Port | To |
|-----------------------------------|------------|-----------|--------|
| Unshielded un-detachable AC cable | 1.10 | EUT | Socket |
| Unshielded un-detachable AC cable | 1.01 | Socket | LISN |

Configuration of Test Setup




Block Diagram of Test Setup

For Conducted Emission:



For Radiated Emission:



SUMMARY OF TEST RESULT

| FCC Rules | Description of Test | Results |
|----------------------------------|------------------------------|----------------|
| FCC §18.313, §1.1310, §2.1091 | Maximum Permissible Exposure | Compliant |
| FCC §18.307 | AC Line Conducted Emissions | Compliant |
| FCC/OST MP-5 FCC §18.301 | Radiation Hazard Measurement | Compliant |
| FCC §18.305 | Field Strength | Compliant |

TEST EQUIPMENT LIST

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--|---------------------|---------------------------------|---------------|------------------|----------------------|
| Conducted Emissions Test | | | | | |
| Rohde & Schwarz | EMI Test Receiver | ESCI | 100784 | 2022/11/25 | 2023/11/24 |
| R & S | L.I.S.N. | ENV216 | 101314 | 2022/11/25 | 2023/11/24 |
| Anritsu Corp | 50Ω Coaxial Switch | MP59B | 6100237248 | 2022/12/07 | 2023/12/06 |
| Unknown | RF Coaxial Cable | No.17 | N0350 | 2022/11/25 | 2023/11/24 |
| Conducted Emission Test Software: e3 191218 (V9) | | | | | |
| Radiated Emissions Test | | | | | |
| Rohde & Schwarz | Test Receiver | ESR | 102725 | 2022/11/25 | 2023/11/24 |
| Rohde & Schwarz | Spectrum Analyzer | FSV40 | 101949 | 2022/11/25 | 2023/11/24 |
| A.H. Systems, inc. | Preamplifier | PAM-0118P | 135 | 2022/11/08 | 2023/11/07 |
| SONOMA INSTRUMENT | Amplifier | 310 N | 186131 | 2022/11/08 | 2023/11/07 |
| Quinstar | Amplifier | QLW-18405536-J0 | 15964001002 | 2022/11/08 | 2023/11/07 |
| Schwarzbeck | Bilog Antenna | VULB9163 | 9163-323 | 2021/07/06 | 2024/07/05 |
| Schwarzbeck | Horn Antenna | BBHA9120D | 837 | 2023/02/22 | 2026/02/21 |
| Wainwright | Band Reject Filter | WRCG2400/2485-2375/2510-60/11SS | 10 | 2022/11/25 | 2023/11/24 |
| Unknown | RF Coaxial Cable | No.10 | N050 | 2022/11/25 | 2023/11/24 |
| Unknown | RF Coaxial Cable | No.11 | N1000 | 2022/11/25 | 2023/11/24 |
| Unknown | RF Coaxial Cable | No.12 | N040 | 2022/11/25 | 2023/11/24 |
| Unknown | RF Coaxial Cable | No.13 | N300 | 2022/11/25 | 2023/11/24 |
| Unknown | RF Coaxial Cable | No.14 | N800 | 2022/11/25 | 2023/11/24 |
| Radiated Emission Test Software:e3 191218 (V9) | | | | | |
| Radiation Hazard Measurement | | | | | |
| Qingzhi | Digital Power Meter | 8716C | 870307126 | 2022/11/23 | 2023/11/22 |
| OHAUS | Electronic Scale | R2000-6 | 8339220237 | 2022/11/23 | 2023/11/22 |
| MC | Thermometer | Unknown | Unknown | 2022/10/31 | 2023/10/30 |
| Rohde & Schwarz | Spectrum Analyzer | FSV40 | 101949 | 2022/11/25 | 2023/11/24 |
| Schwarzbeck | Horn Antenna | BBHA9120D | 837 | 2023/02/22 | 2026/02/21 |
| Unknown | RF Coaxial Cable | No.10 | N050 | 2022/11/25 | 2023/11/24 |
| Unknown | RF Coaxial Cable | No.11 | N1000 | 2022/11/25 | 2023/11/24 |

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|-------------------------------------|------------------------|-------|---------------|------------------|----------------------|
| Maximum Permissible Exposure | | | | | |
| ETS | Microwave Survey Meter | 1501 | 123654 | 2022/10/11 | 2023/10/10 |

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §18.313, §1.1310, §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE

Applicable Standard

According to subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

| (B) Limits for General Population/Uncontrolled Exposure | | | | |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Averaging Time (minutes) |
| 0.3–1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34–30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30–300 | 27.5 | 0.073 | 0.2 | 30 |
| 300–1500 | / | / | f/1500 | 30 |
| 1500–100,000 | / | / | 1.0 | 30 |

f = frequency in MHz; * = Plane-wave equivalent power density;

Measurement

Environmental Conditions

| | |
|---------------------------|-----------|
| Temperature: | 23 °C |
| Relative Humidity: | 55 % |
| ATM Pressure: | 101.0 kPa |

The testing was performed by Jason Liu on 2023-06-26.

For Microwave function:

Radiation leakage was measured in the as-received condition with the oven door closed using a microwave leakage meter.

A 275 mL water load was placed in the center of the oven and the oven was operated at maximum output power.

There was no microwave leakage exceeding a power level of 0.1mW/cm² observed at any point 5 cm or more from the external surface of the oven.

A maximum of 1.0 mW/cm² is allowed in accordance with the applicable Federal Standards. Hence, microwave leakage in the as-received condition with the oven door closed was below the maximum allowed.

For BT/Wi-Fi Function:

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For worst case (PCB antenna 2)

| Mode | Frequency (MHz) | Antenna Gain | | Tune Up Conducted Power* | | Distance (cm) | Power Density (mW/cm ²) | MPE Limit (mW/cm ²) |
|---------|-----------------|--------------|-----------|--------------------------|--------|---------------|-------------------------------------|---------------------------------|
| | | (dBi) | (numeric) | (dBm) | (mW) | | | |
| BLE | 2402-2480 | 4.2 | 2.63 | 0 | 1.00 | 20 | 0.0005 | 1 |
| BDR/EDR | 2402-2480 | 4.2 | 2.63 | 3 | 2.00 | 20 | 0.0010 | 1 |
| Wi-Fi | 2412-2462 | 4.2 | 2.63 | 22 | 158.49 | 20 | 0.0829 | 1 |

Note 1: Please refer to the certified module of FCC ID: 2AC7Z-RIGEL (Report number: RSHA180913005-00A& RSHA180913005-00B) for the tune up conducted power for the Bluetooth and Wi-Fi.

Note 2: The BT function can't transmit at the same time with the Wi-Fi function.

Note 3: The BT/Wi-Fi function can transmit at the same time with Microwave function.

Note 4: Simultaneous transmitting was considerate to be compliant to the limit, since low power density for BT/Wi-Fi and Microwave functions.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.


Result: Compliant.

CONDUCTED EMISSIONS

Applicable Standard

FCC §18.307

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with MP-5: 1986 measurement procedure. Specification used was with the FCC Part 18.

The socket was connected to 120 V AC / 60Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz |

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Test Data


Environmental Conditions

| | |
|---------------------------|-----------|
| Temperature: | 23 °C |
| Relative Humidity: | 48 % |
| ATM Pressure: | 101.0 kPa |

The testing was performed by Jerry Wu on 2023-06-26.

Test mode: Microwave


AC 120V/60 Hz, Line



Site : Shielding Room
 Condition: Line
 Job No. : RA230625-36010E-EM
 Mode : Microwave

| | Freq | Factor | Read Level | Limit Level | Limit Line | Over Limit | Remark |
|----|--------|--------|------------|-------------|------------|------------|---------|
| | MHz | dB | dBuV | dBuV | dBuV | dB | |
| 1 | 0.153 | 10.36 | 21.43 | 31.79 | 55.84 | -24.05 | Average |
| 2 | 0.153 | 10.36 | 40.73 | 51.09 | 65.84 | -14.75 | QP |
| 3 | 0.239 | 10.34 | 17.99 | 28.33 | 52.13 | -23.80 | Average |
| 4 | 0.239 | 10.34 | 36.90 | 47.24 | 62.13 | -14.89 | QP |
| 5 | 0.466 | 10.54 | 23.46 | 34.00 | 46.59 | -12.59 | Average |
| 6 | 0.466 | 10.54 | 36.77 | 47.31 | 56.59 | -9.28 | QP |
| 7 | 0.545 | 10.60 | 29.03 | 39.63 | 46.00 | -6.37 | Average |
| 8 | 0.545 | 10.60 | 36.52 | 47.12 | 56.00 | -8.88 | QP |
| 9 | 2.120 | 10.41 | 5.08 | 15.49 | 46.00 | -30.51 | Average |
| 10 | 2.120 | 10.41 | 17.06 | 27.47 | 56.00 | -28.53 | QP |
| 11 | 11.460 | 10.47 | 14.30 | 24.77 | 50.00 | -25.23 | Average |
| 12 | 11.460 | 10.47 | 20.34 | 30.81 | 60.00 | -29.19 | QP |

AC 120V/60 Hz, Neutral



Site : Shielding Room
 Condition: Neutral
 Job No. : RA230625-36010E-EM
 Mode : Microwave

| | Freq | Factor | Read Level | Level | Limit Line | Over Limit | Remark |
|----|--------|--------|------------|-------|------------|------------|---------|
| | MHz | dB | dBuV | dBuV | dBuV | dB | |
| 1 | 0.196 | 10.29 | 22.24 | 32.53 | 53.79 | -21.26 | Average |
| 2 | 0.196 | 10.29 | 37.00 | 47.29 | 63.79 | -16.50 | QP |
| 3 | 0.293 | 10.35 | 19.85 | 30.20 | 50.44 | -20.24 | Average |
| 4 | 0.293 | 10.35 | 39.80 | 50.15 | 60.44 | -10.29 | QP |
| 5 | 0.437 | 10.44 | 22.44 | 32.88 | 47.13 | -14.25 | Average |
| 6 | 0.437 | 10.44 | 41.77 | 52.21 | 57.13 | -4.92 | QP |
| 7 | 0.525 | 10.47 | 23.83 | 34.30 | 46.00 | -11.70 | Average |
| 8 | 0.525 | 10.47 | 38.86 | 49.33 | 56.00 | -6.67 | QP |
| 9 | 2.105 | 10.50 | 7.99 | 18.49 | 46.00 | -27.51 | Average |
| 10 | 2.105 | 10.50 | 21.85 | 32.35 | 56.00 | -23.65 | QP |
| 11 | 11.768 | 10.50 | 18.27 | 28.77 | 50.00 | -21.23 | Average |
| 12 | 11.768 | 10.50 | 24.38 | 34.88 | 60.00 | -25.12 | QP |

RADIATION HAZARD MEASUREMENT

Applicable Standard

FCC §18.301 & FCC/OST MP-5

Environmental Conditions

| | |
|---------------------------|-----------|
| Temperature: | 23 °C |
| Relative Humidity: | 54 % |
| ATM Pressure: | 101.0 kPa |

The testing was performed by Jason Liu on 2023-06-26.

Input Power

Input power and current was measured using a power analyzer. A 1000 mL water load was placed in the center of the oven and the oven was operated at maximum output power. A 1000mL water load was chosen for its compatibility with the procedure commonly used by manufacturers to determine their input ratings.

| Input Voltage (V_{AC}/Hz) | Input Current (Amps) | Measured Input Power (Watts) | Rated Input Power (Watts) |
|--|---------------------------------|---|--------------------------------------|
| 110.6 | 13.8 | 1526.28 | 1800 |

Based on the measured input power, the EUT was found to be operating within the intended specifications.

Load for Household Microwave Ovens

For all measurements, the energy developed by the oven was absorbed by a dummy load consisting of a quantity of tap water in a beaker. If the oven was provided with a shelf or other utensil support, this support was in its initial normal position. For ovens rated at 1000 watts or less power output, the beaker contained quantities of water as listed in the following subparagraphs. For ovens rated at more than 1000 watts output, each quantity was increased by 50% for each 500watts or fraction thereof in excess of 1000 watts. Additional beakers were used if necessary.

- Load for power output measurement: 1000 milliliters of water in the beaker located in the center of the oven.
- Load for frequency measurement: 1000 milliliters of water in the beaker located in the center of the oven.
- Load for measurement of radiation on second and third harmonic: Two loads, one of 700 and the other of 300 milliliters, of water are used. Each load is tested both with the beaker located in the center of the oven and with it in the right front corner.

RF Output Power Measurement

A cylindrical container of borosilicate glass is used for the test. It has a maximum thickness of 3 mm, an external diameter of approximately 190 mm and a height of approximately 90 mm. The mass of the container is determined.

At the start of the test, the oven and the empty container are at ambient temperature. Water having an initial temperature is used for the test. The water temperature is measured immediately before it is poured into the container.

A quantity of $1000 \text{ g} \pm 5 \text{ g}$ of water is added to the container and its actual mass obtained. The container is then immediately placed in the centre of the oven shelf, which is in its lowest normal position. The oven is operated and the time for the water temperature to attain is measured. The oven is then switched off and the final water temperature is measured within 60 s.

| m_w (g) | m_c (g) | T_0 (°C) | T_1 (°C) | T_2 (°C) | t (s) |
|--------------|--------------|---------------|---------------|---------------|----------|
| 1000 | 377.0 | 23 | 10.2 | 18.1 | 40 |

$$\text{RF Output Power} = (4.187 \times 1000 \times (18.1 - 10.2) + 0.55 \times 377.0 \times (18.1 - 23)) / 40 = 801.532 \text{ Watts}$$

- P** is the microwave power output, in watts;
 m_w is the mass of the water, in grams;
 m_c is the mass of the container, in grams;
 T_0 is the ambient temperature, in degrees Celsius;
 T_1 is the initial temperature of the water, in degrees Celsius;
 T_2 is the final temperature of the water, in degrees Celsius;
t is the heating time, in seconds, excluding the magnetron filament heating-up time.

The measurement output power was found to be less than 500 watts. Therefore, in accordance with Section 18.305 of Subpart-C, the measured out-of-band emissions were compared to the limit of $25 \mu\text{V}/\text{meter}$ at a 300-meter measurement distance.

The measured output power was found to exceed 500 watts. Therefore, in accordance with Section 18.305 of Subpart-C, the measured out-of-band emissions were compared with the limit calculated as following:

$$\text{LFS} = 25 * \text{SQRT} (\text{Power Output}/500)$$

$$\text{LFS} = 25 * \text{SQRT} (801.532/500)$$

$$\text{LFS} = \underline{31.65}$$

Where: LFS is the maximum allowable field strength for out-of-band emissions in $\mu\text{V}/\text{meter}$ at a 300-meter measurement distance. Power Output is the measured output power in watts.

| LFS $\mu\text{V}/\text{m}@300\text{m}$ | $\text{dB}\mu\text{V}/\text{m}@300\text{m}$ | $\text{dB}\mu\text{V}/\text{m}@3\text{m}$ |
|---|---|---|
| 31.65 | 30.01 | 70.01 |

Note: Limit ($\text{dB}\mu\text{V}/\text{m}@3\text{m}$) = Limit ($\text{dB}\mu\text{V}/\text{m}@300\text{m}$) + 40(dB)

Operating Frequency Measurement

Variation in Operating Frequency with Time


The operating frequency was measured using a spectrum analyzer. Starting with the EUT at room temperature, a 1000mL water load was placed in the center of the oven and the oven was operated at maximum output power. The fundamental operating frequency was monitored until the water load was reduced to 20 percent of the original load.

The results of this test are as follows:

| Frequency at Start time (MHz) | Frequency at End time (MHz) |
|-------------------------------|-----------------------------|
| 2468.67 | 2463.02 |


Refer to data pages for details of the variation in operating frequency with time measurement.

Start Time



Date: 25 JUN 2023 19:45:49

End Time



Date: 26.JUN.2023 20:26:51

Variation in Operating Frequency with Line Voltage

The EUT was operated / warmed by at least 10 minutes of use with a 1000 mL water load at room temperature at the beginning of the test. Then the operating frequency was monitored as the input voltage was varied between 80 and 125 percent of the nominal rating.


The results of this test are as follows:

Line voltage varied from 96 V_{AC} to 150 V_{AC}.


| (Low voltage) Frequency (MHz) | (High voltage) Frequency (MHz) |
|-------------------------------|--------------------------------|
| 2462.16 | 2469.54 |

Please refer to following pages for details of the variation in operating frequency with line voltage measurement.

Low Voltage



High Voltage



Date: 26.JUN.2023 20:57:45


RADIATED EMISSIONS

Applicable Standard


FCC §18.305 and FCC §18.309

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the FCC MP-5. The specification used was the FCC part 18 limits.

The socket was connected to 120 V AC /60 Hz power source.

EMI Test Receiver Setup and Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver and Spectrum Analyzer were set with the following configurations:

| Frequency Range | RBW | Video B/W | IF B/W | Measurement |
|------------------|---------|-----------|--------|-------------|
| 30MHz – 1000 MHz | 100 kHz | 300 kHz | 120kHz | QP |
| Above 1 GHz | 1MHz | 3 MHz | / | PK. |
| | 1MHz | 10 Hz | / | Ave. |

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions to ensure that the EUT complied with all installation combinations.

The EUT was in the normal (naïve) operating mode during the final qualification test to represent the worst results.

Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data and Plots

Environmental Conditions


| | |
|---------------------------|-----------|
| Temperature: | 23 °C |
| Relative Humidity: | 53-58 % |
| ATM Pressure: | 101.0 kPa |

*The Below 1GHz testing was performed by Jason Liu on 2023-06-26.
The Above 1GHz testing was performed by Jimi Zheng on 2023-06-26.*

Test mode: Microwave

30 MHz - 1 GHz


Horizontal



Site : chamber
 Condition: 3m HORIZONTAL
 Job No. : RA230625-36010E-EM
 Test Mode: Microwave

| | Freq | Factor | Read Level | Level | Limit Line | Over Limit | Remark |
|---|---------|--------|------------|--------|------------|------------|--------|
| | MHz | dB/m | dBuV | dBuV/m | dBuV/m | dB | |
| 1 | 55.052 | -10.28 | 35.90 | 25.62 | 70.01 | -44.39 | Peak |
| 2 | 104.262 | -11.77 | 60.14 | 48.37 | 70.01 | -21.64 | Peak |
| 3 | 144.019 | -15.52 | 51.96 | 36.44 | 70.01 | -33.57 | Peak |
| 4 | 304.076 | -9.10 | 48.22 | 39.12 | 70.01 | -30.89 | Peak |
| 5 | 384.100 | -7.08 | 48.48 | 41.40 | 70.01 | -28.61 | Peak |
| 6 | 672.255 | -1.63 | 41.85 | 40.22 | 70.01 | -29.79 | Peak |

Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No. : RA230625-36010E-EM
 Test Mode: Microwave

| | Freq | Factor | Read Level | Level | Limit Line | Over Limit | Remark |
|---|---------|--------|------------|--------|------------|------------|--------|
| | MHz | dB/m | dBuV | dBuV/m | dBuV/m | dB | |
| 1 | 31.662 | -12.21 | 52.56 | 40.35 | 70.01 | -29.66 | Peak |
| 2 | 86.883 | -14.93 | 50.54 | 35.61 | 70.01 | -34.40 | Peak |
| 3 | 104.216 | -11.76 | 56.45 | 44.69 | 70.01 | -25.32 | Peak |
| 4 | 112.032 | -12.25 | 56.99 | 44.74 | 70.01 | -25.27 | Peak |
| 5 | 352.016 | -7.38 | 47.47 | 40.09 | 70.01 | -29.92 | Peak |
| 6 | 592.011 | -2.72 | 41.26 | 38.54 | 70.01 | -31.47 | Peak |

1 GHz - 25 GHz:

| Frequency (MHz) | Receiver | | Turntable Degree | Rx Antenna | | Corrected Factor (dB/m) | Corrected Amplitude (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|-----------------|----------------------|----------|------------------|------------|-------------|-------------------------|------------------------------------|----------------------|-------------|
| | Reading (dB μ V) | PK/QP/AV | | Height (m) | Polar (H/V) | | | | |
| 2372.500 | 52.31 | AV | 190 | 2.0 | H | -10.68 | 41.63 | 70.01 | -28.38 |
| 2372.500 | 50.87 | AV | 334 | 2.1 | V | -10.68 | 40.19 | 70.01 | -29.82 |
| 2522.500 | 46.26 | AV | 199 | 1.6 | H | -10.42 | 35.84 | 70.01 | -34.17 |
| 2522.500 | 47.47 | AV | 350 | 1.9 | V | -10.42 | 37.05 | 70.01 | -32.96 |
| 4475.500 | 45.36 | AV | 5 | 1.0 | H | -6.15 | 39.21 | 70.01 | -30.8 |
| 4475.500 | 44.36 | AV | 347 | 1.4 | V | -6.15 | 38.21 | 70.01 | -31.8 |
| 700ml Water | | | | | | | | | |
| 4961.500 | 48.64 | AV | 284 | 2.2 | H | -4.88 | 43.76 | 70.01 | -26.25 |
| 4961.500 | 40.00 | AV | 215 | 1.8 | V | -4.88 | 35.12 | 70.01 | -34.89 |
| 7396.000 | 48.37 | AV | 348 | 1.5 | H | 1.21 | 49.58 | 70.01 | -20.43 |
| 7396.000 | 47.21 | AV | 213 | 1.6 | V | 1.21 | 48.42 | 70.01 | -21.59 |
| 300ml Water | | | | | | | | | |
| 4961.500 | 50.22 | AV | 283 | 1.9 | H | -4.88 | 45.34 | 70.01 | -24.67 |
| 4961.500 | 40.95 | AV | 334 | 2.1 | V | -4.88 | 36.07 | 70.01 | -33.94 |
| 7396.000 | 50.33 | AV | 135 | 1.5 | H | 1.21 | 51.54 | 70.01 | -18.47 |
| 7396.000 | 48.17 | AV | 306 | 2.2 | V | 1.21 | 49.38 | 70.01 | -20.63 |

Note:

Factor = Antenna factor (RX) + Cable Loss - Amplifier Factor

Corrected Amplitude = Factor + Reading

Margin = Corrected Amplitude - Limit

******* END OF REPORT *******