# 9. RADIO FREQUENCY EXPOSURE

### 9.1 Limit

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

## 9.2 EUT Specification

EUT	Bluetooth Mini Keyboard
Frequency Band (Operating)	<ul> <li>WLAN: 2.412GHz ~ 2.462GHz</li> <li>WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz</li> <li>WLAN: 5.745GHz ~ 5.825GHz</li> <li>✓ Others: Bluetooth: 2.402GHz ~ 2.480GHz</li> </ul>
<b>Device Category</b>	Portable (<20cm separation)  Mobile (>20cm separation)  Others
Exposure Classification	Occupational/Controlled exposure $(S = 5mW/cm^2)$ Seneral Population/Uncontrolled exposure $(S=1mW/cm^2)$
Antenna Diversity	<ul> <li>Single antenna</li> <li>Multiple antennas</li> <li>□ Tx diversity</li> <li>□ Rx diversity</li> <li>□ Tx/Rx diversity</li> </ul>
Max. Output Power	1.92 dBm (1.56mW)
Antenna Gain (Max)	1.5 dBi
<b>Evaluation Applied</b>	<ul><li></li></ul>
<ol> <li>DTS device is not subject compliance.</li> <li>For mobile or fixed less separation generally bedistance would be lesse</li> </ol>	power is 1.92dBm (1.56mW) at 2441MHz. iect to routine RF evaluation; MPE estimate is used to justify the ocation transmitters, no SAR consideration applied. The minimum ocused is at least 20 cm, even if the calculations indicate that the MPE or.
9.3 Test Results	

#### Non-compliance.

(SAR evaluation is not required	l for the portable device	e while its maximum	output power is
lower than the general populati	ion low threshold: 60/f	(GHz)=60/2.441=24	1.58mW)