

MEASUREMENT REPORT

of

WIRELESS 2.4G USB DONGLE

Applicant : TopSeed Technology Corp.

EUT : USB Dongle

Model : TSEQ-2401

FCC ID : PTITSEQ-2401

Tested by :

Training Research Co., Ltd.

TEL : 886-2-26935155 FAX : 886-2-26934440

No. 255, Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C.

CERTIFICATION

We here by verify that:

The test data, data evaluation, test procedures and equipment configurations shown in this report were made mainly in accordance with the procedures given in ANSI C63.4 (2003) as a reference. All test were conducted by **Training Research Co., Ltd.**, 255 Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C. Also, we attest to the accuracy of each.


We further submit that the energy emitted by the sample EUT tested as described in the report is **in compliance with** the technical requirements set forth in the FCC Rules Part 15 Subpart B (Declaration of Conformity) and C Section 15.247.

Applicant : TopSeed Technology Corp.
Applicant Address : 9F-3, No.16, Jain Ba Rd, Chung Ho, Taipei Hsien, Taiwan
Product Name : USB Dongle
Model : TSEQ-2401
Report No. : AA515050308
Test Date : May 20, 2005

Prepared by:


Jack Tsai

Approved by:


Frank Tsai

Conditions of issue :

- (1) ***This test report shall not be reproduced except in full, without written approval of TRC. And the test result contained within this report only relate to the sample submitted for testing.***
- (2) ***This report must not be used by the client to claim product endorsement by NVLAP or any agency of U.S. Government.***
- (3) ***This test report, measurements made by TRC are traceable to the NIST only Conducted and Radiated Method.***

★ NVLAP LAB CODE: 200174-0

Federal Communications Commission **Declaration of Conformity**

for the following equipment:

Product name : USB Dongle
Trade name : TopSeed; DELL
Model name : TSEQ-2401

Is herewith confirmed and found to comply with the requirements of CFR 47 part15 Subpart B - Unintentional Radiators regulation. The results of electromagnetic mission evaluation are shown in the report number : AA515050308

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received,
including interference that may cause undesired operation

<i>Manufacturer</i>	<i>USA local representative</i>
Company name: Dong Guan Jess-Link Electronics Co., Ltd.	To be determined
Computer address: XiSheng Rd., XiTou Country, HouJie Town, DongGuan City, Canton, P.R.China	
ZIP / Postal code	
Contact person: Bell Kao	
Title:	
Internet e-mail address: bellkao@jpcco.con.cn	
Tel / Fax: (0769)-5912571 ~ 4 / (0769)-5912575	

Tables of Contents

I.	GENERAL	6
1.1	Introduction	6
1.2	Description of EUT	6
1.3	Test method	7
1.4	Description of Support Equipment	7
1.5	Configuration of System Under Test	9
1.6	Verify the Frequency and Channel	11
1.7	Test Procedure	12
1.8	Location of the Test Site	12
1.9	General Test Condition	12
II.	Section 15.101(a) : Equipment Authorization of Unintentional Radiators	13
III.	Section 15.203 : Antenna Requirement	14
IV.	Section 15.207 : Power Line Conducted Emissions for AC Powered Units	15
4.1	Test Condition & Setup	15
4.2	List of Test Instruments	16
4.3	Test Result of Conducted Emissions	17
	RX mode	17
	CH 01	18
	CH 39	18
	CH 78	19
V.	Section 15.247(a) : Technical Description of the EUT.....	20

VI. Section 15.247(a)(2) : Bandwidth for Direct Sequence System	21
6.1 Test Condition & Setup	21
6.2 Test Instruments Configuration	21
6.3 List of Test Instruments	21
6.4 Test Result of Bandwidth	21
CH 01	22
CH 39	23
CH 78	24
VII. Section 15.247(b) : Power Output	25
7.1 Test Condition & Setup	25
7.2 List of Test Instruments	25
7.3 Test Result	25
VIII. Section 15.247(c) : Spurious Emissions (Radiated)	26
8.1 Test Condition & Setup	26
8.2 List of Test Instruments	28
8.3 Test Result of Spurious Radiated Emissions	29
RX mode	29
CH 01	31
CH 39	33
CH 78	35
8.4 Test Result of Bandedge	37
CH 01	38
CH 78	39
IX. Section 15.247(d) : Power Spectral Density	40
9.1 Test Condition & Setup	40
9.2 Test Instruments Configuration	40
9.3 List of Test Instruments	40
9.4 Test Result of Power Spectral Density	40
CH 01	41
CH 39	42
CH 78	43

I . GENERAL

1.1 Introduction

The following measurement report is submitted on behalf of applicant in support that the certification in accordance with Part 2 Subpart J and Part 15 Subpart A, B and C of the Commission's Rules and Regulations.

1.2 Description of EUT

FCC ID	:	PTITSEQ-2401
Product Name	:	USB Dongle
Model Name	:	TSEQ-2401
Part No.	:	RCEQ0001-2401
Frequency Range	:	2402MHz to 2479MHz
Support Channel	:	78 Channels
Channel Spacing	:	1MHz
Modulation Skill	:	GFSK
Power Type	:	Powered by USB interface
Data Cable	:	None

1.3 Test method

- 1.3.1 Insert the EUT into the USB port of the notebook computer.
- 1.3.2 Using the notebook computer and software provided by the manufacturer to control EUT. The software is operated under the Windows to control the EUT in the mode of continuous transmission; the test is performed under the specific conditions.
- 1.3.3 Set different data rate and channel (CH01/CH39/CH78) being tested
 - (a) Radiated for Intentional test:
 - making EUT to the mode of continuous transmission
 - (b) Conduction test and Radiated for unintentional test:
 - making EUT to the linking (RX/TX) mode with far support equipments
- 1.3.4 Deviation: No deviation.

1.4 Description of Support Equipment

In order to construct the minimum testing, following equipment were used as the support units.

Notebook : IBM Think Pad X20

Model No. : 2662-11T
Serial No. : FX-1192200/09
FCC ID : N/A, DoC Approved
BSMI : 3892B565

Adaptor : IBM

Model No. : PA2450U
Serial No. : 02K6654
FCC ID : N/A, DoC Approved
Power type : I/P: 100 ~ 240vac, 50 ~ 60 Hz, 0.5A ~ 1.2A; O/P: 16Vdc, 4.5A
Power cord : Non-shielded, 1.80m long, Plastic, with ferrite core

Printer : EPSON

Model No. : B241A
Serial No. : FAPY155090
FCC ID : N/A, DoC Approved
BSMI : R33126
Power type : Switching adaptor
Power cord : Non-shielded, 198cm length, No ferrite core
Data cable : Shielded, 1.50m length, No ferrite core

PS/2 Mouse : HP

Model No. : M-S69
Serial No. : 334684-002 323614-001
FCC ID : DoC Approved
BSMI : R41126
Power type : By PC
Power cord : Shielded, 1.90m length, No ferrite core

Modem : **ACEEX**
Model No. : DM-1414
Serial No. : 9010583
FCC ID : IFAXDM1414
Power type : Linear
Power cord : Non-shielded, 1.9m length, No ferrite cord
Data cable : RS232, Shielded, 1.2m length, No ferrite core
RJ11C x 2, 7' length non-shielded, No ferrite core

USB Game pad : **Logitech**
Model No. : G-UC3B
Serial No. : AE3500500
FCC ID : DoC Approved
BSMI : 4902A047
Power type : Powered by PC
Power Cable : Shielded, 187cm length, Plastic hood, No ferrite core.


Notebook PC : **Twinhead**
Model No. : N222S
Serial No. : SY3261000988
FCC ID : DoC (Declaration of Confirmation) Approved
BSMI : 71001018

Power adaptor : **LI Shin International Enterprise Corp.**
Model No. : LSE9802A2060
Serial No. : A20231065818
BSMI : 3882B381
Power type : 100 ~ 240VAC / 50 ~ 60Hz, 1.5A, Switching
Power cord : Non-shielded, 1.0m length, Plastic hood, No ferrite core
(Main power to adaptor)
Shielded, 1.5m length, Plastic hood, ferrite core
(DC plug to adaptor)

WLAN AP : **ASUS**
Model No. : WL-330g
FCC ID : MSQWL330G

1.5 Configuration of System Under Test


1.5.1 Conduction and Radiated for Unintentional



Connections of Computer:

- *Parallel Port --- a printer
- *Serial Port --- an external modem
- *PS/2 Port --- a P/2 mouse
- *USB Port --- a USB gamepad
- *USB Port --- **EUT**

1.5.2 Radiated Test



The tests below are carried with the EUT transmitter set at high power in TDD mode. The EUT is forced to select of output power level and channel number by notebook computer.

The setting up procedure was recorded in 1.3 test method.

1.6 Verify the Frequency and Channel

CH	0	1	2	3	4	5	6	7	8	9
0		2402	2403	2404	2405	2406	2407	2408	2409	2410
1	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420
2	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430
3	2431	2432	2433	2434	2435	2436	2437	2438	2439	2440
4	2441	2442	2443	2444	2445	2446	2447	2448	2449	2450
5	2451	2452	2453	2454	2455	2456	2457	2458	2459	2460
6	2461	2462	2463	2464	2465	2466	2467	2468	2469	2470
7	2471	2472	2473	2474	2475	2476	2477	2478	2479	

Note:

1. This is for confirming that all frequencies are in 2.400GHz to 2.4835GHz.
2. Section 15.31(m): Measurements on intentional radiators or receivers shall be performed at three frequencies for operating frequency range over 10 MHz
(The locations of these frequencies one near the top, one near the middle and one near the bottom.)
3. After test, the EUT operating frequencies are in 2.402GHz to 2.479GHz. So all the items as followed in testing report are need to test these three frequencies:
Top: Channel – 1; Middle: Channel – 39 Bottom: Channel – 78.

1.7 Test Procedure

All measurements contained in this report were performed mainly according to the techniques described in ANSI C63.4 (2003) and the pre-setup was written on 1.3 test method, the detail setup was written on each test item.

1.8 Location of the Test Site

The radiated emissions measurements required by the rules were performed on the **three-meter, Anechoic Chamber (FCC Registration Number: 93906)** maintained by *Training Research Co., Ltd.* 1F, No. 255 Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C. Complete description and measurement data have been placed on file with the commission. The conducted power line emissions tests and other test items were performed in a anechoic chamber also located at Training Research Co., Ltd.

No. 255 Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C. *Training Research Co., Ltd.* is listed by the FCC as a facility available to do measurement work for others on a contract basis.

1.9 General Test Condition

The conditions under which the EUT operates were varied to determine their effect on the equipment's emission characteristics. The final configuration of the test system and the mode of operation used during these tests were chosen as that which produced the highest emission levels. However, only those conditions, which the EUT was considered likely to encounter in normal use were investigated.

In test, they were set in high power and continuously transmitting mode that controlled by computer. The CH01, CH39 and CH78 of EUT were all tested. The setting up procedure is recorded on 1.3 test method.

II. Section 15.101(a): Equipment authorization of unintentional radiators

The EUT equipped with a USB interface and should be operated with the computer. It was categorized to *Class B personal computers and peripherals* as cannot be operated stand-alone. The authorization requires **Declaration of Conformity (DoC)** and the items required such as Section15.107 (Conducted limits) and Section15.109 (Radiated emission limits) is same as Section15.207 and 15.247(C).

III. Section 15.203: Antenna requirement

The EUT has an integrated antenna permanently attached on the PCB (PCB Track). In addition, there is no external antenna or connector employed. The antenna requirement stated in Section 15.203 is inapplicable to this EUT.

VI. Section 15.207: Power Line Conducted Emissions for AC Powered Units

4.1 Test Condition & Setup

The power line conducted emission measurements were performed in an anechoic chamber. The EUT was assembled on a wooden table, which is 80 centimeters high, was placed 40 centimeters from the backwall and at least 1 meter from the sidewall.

Power was fed to the EUT from the public utility power grid through a line filter and Line Impedance Stabilization Networks (LISNs). The LISN housing, measuring instrumentation case, ground plane, etc., were electrically bonded together at the same RF potential. The Spectrum analyzer (or EMI receiver) was connected to the AC line through an isolation transformer. The 50-ohm output of the LISN was connected to the spectrum analyzer directly. Conducted emission levels were in the CISPR quasi-peak and average detection mode. The analyzer's 6 dB bandwidth was set to 9 KHz. No post-detector video filter was used.

The spectrum was scanned from 150 KHz to 30 MHz. The physical arrangement of the test system and associated cabling was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude and frequency. All spurious emission frequencies were observed. The highest emission amplitudes relative to the appropriate limit were measured and have been recorded in paragraph 4.3

There is a test condition apply in this test item, the test procedure description as <1.3>. Three channels were tested, one in the top (CH01), one in the middle (CH39) and the other in bottom (CH78).

4.2 List of Test Instruments

Instrument Name	Model	Brand	Serial No.	Calibration Date
				Next time
EMI Receiver	8546A	HP	3520A00242	08/05/05
RF Filter Section	85460A	HP	3448A00217	08/05/05
LISN (EUT)	LISN-01	TRC	99-05	10/07/05
LISN (Support E.)	LISN-01	TRC	9912-03, 04	11/04/05
Pre-amplifier	15542 ZFL-500	Mini – Circuits	0 0117	05/20/05
6dB Attenuator	MCL BW-S6W2	Mini – Circuits	9915 – Conducted	05/20/05
10dB Attenuator	A5542 VAT010	Mini – Circuits	0215 – Conducted	05/20/05
Coaxial Cable (2 meter)	A30A30-0058-50FS-2M	Jyebao	SMA-08	05/20/05
Coaxial Cable (1.1 meter)	A30A30-0058-50FS-1M	Jyebao	SMA-09	05/20/05
Coaxial Cable (20 meter)	RG-214/U	Jyebao	NP-01	05/20/05
Coaxial Cable (20 meter)	RG-214/U	Jyebao	NP-02	05/20/05
Auto Switch Box (< 30MHz)	ASB-01	TRC	9904-01	05/20/05

4.3 Test Result of Power Line Conducted Emissions

The following table shows a summary of the highest emissions of power line conducted emissions on the LIVE and NETURAL conductors of the EUT power cord. Show as follows.

Test Conditions: Temperature : 24 °C Humidity : 73 % RH

Test mode: RX mode

<i>Power Connected Emissions</i>					<i>Class B</i>		
<i>Conductor</i>	<i>Frequency (KHz)</i>	<i>Peak (dBμV)</i>	<i>QP (dBμV)</i>	<i>Average (dBμV)</i>	<i>QP-limit (dBμV)</i>	<i>AVG-limit (dBμV)</i>	<i>Margin (dB)</i>
Line 1	398.000	44.68	---	---	58.91	48.91	-4.23
	604.000	41.66	---	---	56.00	46.00	-4.34
	752.000	41.59	---	---	56.00	46.00	-4.41
	989.000	39.55	---	---	56.00	46.00	-6.45
	1713.000	41.61	---	---	56.00	46.00	-4.39
	4666.000	40.15	---	---	56.00	46.00	-5.85
Line 2	248.000	48.85	---	---	63.20	53.20	-4.35
	439.000	42.01	---	---	57.74	47.74	-5.73
	695.000	39.08	---	---	56.00	46.00	-6.92
	876.000	41.89	---	---	56.00	46.00	-4.11
	3670.000	39.76	---	---	56.00	46.00	-6.24
	5260.000	41.59	---	---	60.00	50.00	-8.41

NOTE:

- (1) Margin = Peak Amplitude – Limit, The reading amplitudes are all under limit.
- (2) A "+" sign in the margin column means the emission is OVER the Class B Limit
and "-" sign of means UNDER the Class B limit

Test mode: Channel 1

Power Connected Emissions					Class B		
Conductor	Frequency (KHz)	Peak (dBμV)	QP (dBμV)	Average (dBμV)	QP-limit (dBμV)	AVG-limit (dBμV)	Margin (dB)
Line 1	183.000	50.13	---	---	65.06	55.06	-4.93
	384.000	44.03	---	---	59.31	49.31	-5.28
	598.000	39.13	---	---	56.00	46.00	-6.87
	876.000	40.99	---	---	56.00	46.00	-5.01
	1256.000	39.71	---	---	56.00	46.00	-6.29
	1766.000	39.10	---	---	56.00	46.00	-6.90
Line 2	191.000	48.97	---	---	64.83	54.83	-5.86
	384.000	41.94	---	---	59.31	49.31	-7.37
	485.000	38.70	---	---	56.43	46.43	-7.73
	681.000	38.04	---	---	56.00	46.00	-7.96
	867.000	39.43	---	---	56.00	46.00	-6.57
	1256.000	39.31	---	---	56.00	46.00	-6.69

Test mode: Channel 39

Power Connected Emissions					Class B		
Conductor	Frequency (KHz)	Peak (dBμV)	QP (dBμV)	Average (dBμV)	QP-limit (dBμV)	AVG-limit (dBμV)	Margin (dB)
Line 1	199.000	47.58	---	---	64.60	54.60	-7.02
	394.000	44.54	---	---	59.03	49.03	-4.49
	592.000	40.87	---	---	56.00	46.00	-5.13
	884.000	40.47	---	---	56.00	46.00	-5.53
	1295.000	39.29	---	---	56.00	46.00	-6.71
	1783.000	39.04	---	---	56.00	46.00	-6.96
Line 2	191.000	49.45	---	---	64.83	54.83	-5.38
	398.000	44.41	---	---	58.91	48.91	-4.50
	598.000	40.26	---	---	56.00	46.00	-5.74
	902.000	39.78	---	---	56.00	46.00	-6.22
	1269.000	38.51	---	---	56.00	46.00	-7.49
	1582.000	38.35	---	---	56.00	46.00	-7.65

Test mode: Channel 11

Power Connected Emissions					Class B		
Conductor	Frequency (KHz)	Peak (dBμV)	QP (dBμV)	Average (dBμV)	QP-limit (dBμV)	AVG-limit (dBμV)	Margin (dB)
Line 1	197.000	50.40	---	---	64.66	54.66	-4.26
	401.000	43.89	---	---	58.83	48.83	-4.94
	592.000	40.42	---	---	56.00	46.00	-5.58
	893.000	40.20	---	---	56.00	46.00	-5.80
	1295.000	40.52	---	---	56.00	46.00	-5.48
	1696.000	39.59	---	---	56.00	46.00	-6.41
Line 2	199.000	48.04	---	---	64.60	54.60	-6.56
	398.000	44.13	---	---	58.91	48.91	-4.78
	598.000	40.04	---	---	56.00	46.00	-5.96
	893.000	39.74	---	---	56.00	46.00	-6.26
	1269.000	39.45	---	---	56.00	46.00	-6.55
	1994.000	37.40	---	---	56.00	46.00	-8.60

V. Section 15.247 (a): Technical description of the EUT


Direct Sequence System is a spread spectrum system in which the carrier has been modulated by a high speed spreading code and an information data stream. The high speed code sequence dominates the “modulating function” and is the direct cause of the wide spreading of the transmitted signal. In the operational description demonstrates the operation principles of the Baseband processor employed by the EUT, shows that which is a complete DSSS baseband processor and meets the definition of the direct sequence spread spectrum system.

VI. Section 15.247(a)(2): Bandwidth for Direct Sequence System.

6.1 Test Condition & Setup

The transmitter bandwidth measurements were performed by the contact manner. The EUT was set to transmit continuously, also various channels were investigated to find the maximum occupied bandwidth. The output of the EUT was connected to the spectrum analyzer. The bandwidth of the fundamental frequency is observed by the spectrum analyzer with 100kHz RBW and 100kHz VBW.

6.2 Test Instruments Configuration



PC to control the EUT at maximal power output and channel number and set antenna kit

6.3 List of Test Instruments


Instrument Name	Model No.	Brand	Serial No.	Next time
Spectrum Analyzer	MS2665C	ANRITSU	6200175476	11/02/05

6.4 Test Result of Bandwidth


Channel	6dB Bandwidth
01	980 kHz
39	960 kHz
78	970 kHz

- Note: 1. The data in the above table are summarizing the following attachment spectrum analyzer hard copy. According to the guidance, we'd made the measurement with the spectrum analyzer's resolution bandwidth (RBW)=100kHz and set the $span \gg RBW$. The results show the measured 6dB bandwidth comply with the minimum 500kHz requirement.
2. The attachments show these on the following pages.


6dB Bandwidth of Channel 01 (The minimum 6dB BW at least 500kHz)



6dB Bandwidth of Channel 39 (The minimum 6dB BW at least 500kHz)




6dB Bandwidth of Channel 78 (The minimum 6dB BW at least 500kHz)



VII. Section 15.247(b): Power Output

7.1 Test Condition & Setup



1. The output of the transmitter is connected to the BOONTON RF Power Meter.
2. The calibration is performed before every test. The values of the output power of the EUT will shown in the dBm directly are the transmitter output peak power. Recording as follows.

7.2 List of Test Instruments

Instrument Name	Model	Brand	Serial No.	Next time
RF Power Meter	4532	BOONTON	117501	04/16/06
Peak Power Sensor	57340	BOONTON	2696	04/21/06

7.3 Test Result

Formula:

RF Output of EUT + |Cable Loss| = Output Peak Power

Channel	RF Output	Cable Loss	Output Peak Power	
	dBm	dBm	dBm	mW
CH 01	-11.24	1.00	-10.24	0.095
CH 39	-11.44	1.00	-10.44	0.090
CH 78	-10.95	1.00	-9.95	0.101

VIII. Section 15.247 (C): Spurious Emissions (Radiated)

8.1 Test Condition & Setup

We'd performed the test by the *radiated emission* skill: The EUT was placed in an anechoic chamber, and set the EUT transmitting continuously and scanned at 3-meter distance to determine its emission characteristics. The physical arrangement of the EUT was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude, directivity, and frequency. The exact system configuration, which produced the highest emissions was noted so it could be reproduced later during the final tests. For the measurement above 1GHz, according to the guidance we'd set the spectrum analyzer's 6dB bandwidth RBW to 1MHz.

This was done to ensure that the final measurements would demonstrate the worst-case interference potential of the EUT.

Final radiation measurements were made on a three-meter, anechoic chamber. The EUT system was placed on a nonconductive turntable, which is 0.8 meters height, top surface 1.0 x 1.5 meter.

The spectrum was examined from 30MHz to 1000MHz using an Hewlett Packard 85460A EMI Receiver, SCHWARZECK whole range Small Biconical Antenna (Model No.: UBAA9114 & BBVU9135) is used to measure frequency from 30 MHz to 1GHz. The final test is used the HP 85460A spectrum and 8564E spectrum was examined from 1GHz to 25GHz using an Hewlett Packard Spectrum Analyzer, EMCO/HP Horn Antenna (Model 3115 / 84125-80008) for 1G - 25GHz.

At each frequency, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. There are two spectrum analyzers use on this testing, HP 85460A for frequency 30MHz to 1000MHz, and 8564E for frequency 1GHz to 25GHz. No post-detector video filters were used in the test. The spectrum analyzer's 6dB bandwidth was set to 120KHz (spectrum was examined from 30 MHz to 1000 MHz), the spectrum analyzer's 6 dB bandwidth was set to 1 MHz (spectrum was examined from 1GHz to 25GHz) and the analyzer was operated in the maximum hold mode. There is a test condition applies in this test item, the test procedure description as the following:

Three channels were tested, one in the top (CH01), one in the middle (CH39) and the other in bottom (CH78). The setting up procedure is recorded on <1.3>

With the transmitter operating from a AC source and using the internal of EUT, radiates spurious emissions falling within the restricted bands of 15.209 were measured at operating frequencies corresponding to upper, middle and bottom channels in the 2400 ~ 2483.5 MHz band.

The actual field intensity in decibels referenced to 1 microvolt per meter (dB μ V/m) is determined by algebraically adding the measured reading in dB μ V, the antenna factor (dB), and cable loss (dB) at the appropriate frequency. Since the EUT was set to transmit continuously, no *duty cycle* is present.

For frequency between 30MHz to 1000MHz

$$F_{Ia} \text{ (dB}\mu\text{V/m)} = F_{Ir} \text{ (dB}\mu\text{V)} + \text{Correction Factors}$$

F_{Ia} : Actual Field Intensity

F_{Ir} : Reading of the Field Intensity

$$\text{Correction Factors} = \text{Antenna Factor} + (\text{Cable Loss} - \text{Amplifier Gain}) + \text{Switching Box Loss}$$

For frequency between 1GHz to 25GHz

$$F_{Ia} \text{ (dB}\mu\text{V/m)} = F_{Ir} \text{ (dB}\mu\text{V)} + \text{Correction Factor}$$

F_{Ia} : Actual Field Intensity

F_{Ir} : Reading of the Field Intensity

$$\text{Correction Factors} = \text{Antenna Factor} + (\text{Cable Loss} - \text{Amplifier Gain}) + \text{Switching Box Loss}$$

8.2 List of Test Instruments

Instrument Name	Model	Brand	Serial No.	Calibration Date
				Next time
EMI Receiver	8546A	HP	3520A00242	08/05/05
RF Filter Section	85460A	HP	3448A00217	08/05/05
Small Biconical Antenna	UBAA9114 & BBVU9135	SCHWARZECK	127	10/11/05
Pre-amplifier	PA1F	TRC	1FAC	05/20/05
Auto Switch Box (>30MHz)	ASB-01	TRC	9904-01	05/20/05
Coaxial Cable (Double shielded, 15 meter)	A30A30-0058-50FS-15M	JYEBAO	SMA-01	05/20/05
Coaxial Cable (1.1 meter)	A30A30-0058-50FS-1M	JYEBAO	SMA-02	05/20/05
Spectrum Analyzer	8564E	HP	3720A00840	08/13/05
Microwave Preamplifier	84125C	HP	US36433002	08/13/05
Horn Antenna	3115	EMCO	9104-3668	12/27/05
Standard Guide Horn Antenna	84125-80008	HP	18-26.5GHz	10/15/05
Standard Guide Horn Antenna	84125-80001	HP	26.5-40GHz	10/15/05
Horn Antenna	1196E (3115)	HP (EMCO)	9704-5178	01/11/06
Pre-amplifier	PA2F	TRC	2F1GZ	06/20/05
Coaxial Cable (3 miter)	A30A30-0058-50FST118	JYEBAO	MSA-05	06/20/05
Coaxial Cable (1 meter)	A30A30-0058-50FST118	JYEBAO	MSA-04	06/20/05

8.3 Test Result of Spurious Radiated Emissions

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarizations, EUT orientation, etc. are recorded on the following.

Test Conditions: Temperature : 25 ° C Humidity : 73 % RH

Test mode: RX mode for 30MHz to 1GHz [Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table (°)			Limit (dBμV/m)	Margin (dB)
200.36	34.88	1.00	126	-3.81	31.07	43.50	-12.43
241.58	31.81	1.00	92	-4.01	27.80	46.00	-18.20
298.57	33.01	1.00	272	-3.72	29.29	46.00	-16.71
336.76	34.51	1.00	235	-2.99	31.52	46.00	-14.48
399.21	32.14	1.00	128	-1.03	31.11	46.00	-14.89
558.65	25.33	1.00	41	5.30	30.63	46.00	-15.37

Test mode: RX mode for 30MHz to 1GHz [Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table (°)			Limit (dBμV/m)	Margin (dB)
120.33	28.85	1.00	182	-2.16	26.69	43.50	-16.81
200.36	34.57	1.00	136	-3.81	30.76	43.50	-12.74
240.97	30.87	1.00	192	-4.01	26.86	46.00	-19.14
336.76	32.66	1.00	186	-2.99	29.67	46.00	-16.33
433.16	31.01	1.00	204	0.33	31.34	46.00	-14.66
558.65	27.42	1.00	210	5.30	32.72	46.00	-13.28

Note:

1. Margin = Amplitude – limit, if margin is minus means under limit.
2. Corrected Amplitude = Reading Amplitude + Correction Factors
3. Correction factor = Antenna factor + (Cable Loss – Amplitude gain) + Switching Box Loss

Test mode: RX mode for 1GHz to 25GHz [Horizontal]

Frequency	Ant. H.	Table	Amplitude		Correction Factor	Corrected Amplitude		Limit		Margin
			Peak / Ave.			Peak / Ave.		Peak / Ave.		
MHz	m	degree	dBμV		dB/m	dBμV/m		dBμV/m		dB
2515.83	1.00	284	31.92	---	7.01	38.93	---	73.96	53.96	-15.03
4152.08	1.00	272	30.24	---	12.74	42.98	---	73.96	53.96	-10.98
6213.33	1.00	360	25.91	---	18.49	44.40	---	73.96	53.96	-9.56
9967.50	1.00	93	25.74	---	22.95	48.69	---	73.96	53.96	-5.27
24268.75	1.00	341	47.49	---	2.93	50.42	---	73.96	53.96	-3.54

Test mode: RX mode for 1GHz to 25GHz [Vertical]

Frequency	Ant. H.	Table	Amplitude		Correction Factor	Corrected Amplitude		Limit		Margin
			Peak / Ave.			Peak / Ave.		Peak / Ave.		
MHz	m	degree	dBμV		dB/m	dBμV/m		dBμV/m		dB
2487.50	1.00	88	31.91	---	6.83	38.74	---	73.96	53.96	-15.22
4017.50	1.00	325	30.57	---	12.53	43.10	---	73.96	53.96	-10.86
5930.00	1.00	237	26.58	---	17.83	44.41	---	73.96	53.96	-9.55
9719.58	1.00	246	24.24	---	23.15	47.39	---	73.96	53.96	-6.57
25012.50	1.00	74	50.16	---	2.43	52.59	---	73.96	53.96	-1.37

Note:

1. Margin = Corrected - Limit.
2. The EUT utilizes a *permanently attached antenna*. In addition the spurious RF radiated emissions levels do comply with the *20dBc limit* both at its bandedges and other spurious emissions.
3. As stated in Section 15.35(b), for any frequencies above 1000MHz, radiated limits shown are based upon the use of measurement instrumentation employing an average detector function. As the results of our test, the peak amplitudes are already below the FCC limit. Thus the average amplitudes of the rest are omitted.

Test mode: CH01 for 30MHz to 1GHz [Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table (°)			Limit (dBμV/m)	Margin (dB)
200.36	36.98	1.00	130	-3.81	33.17	43.50	-10.33
240.97	38.97	1.00	100	-4.01	34.96	46.00	-11.04
336.76	35.08	1.00	88	-2.99	32.09	46.00	-13.91
373.74	34.34	1.00	275	-1.91	32.43	46.00	-13.57
398.60	32.70	1.00	278	-1.05	31.65	46.00	-14.35
558.65	25.23	1.00	109	5.30	30.53	46.00	-15.47

Test mode: CH01 for 30MHz to 1GHz [Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table (°)			Limit (dBμV/m)	Margin (dB)
145.19	30.06	1.00	242	-3.00	27.06	43.50	-16.44
213.69	32.69	1.00	336	-3.92	28.77	43.50	-14.73
373.74	29.46	1.00	342	-1.91	27.55	46.00	-18.45
432.55	30.70	1.00	254	0.31	31.01	46.00	-14.99
498.63	28.43	1.00	257	2.85	31.28	46.00	-14.72
558.65	27.90	1.00	274	5.30	33.20	46.00	-12.80

Test mode: CH01 for 1GHz to 25GHz [Horizontal]

Frequency	Ant. H.	Table	Amplitude		Correction Factor	Corrected Amplitude		Limit		Margin
			Peak / Ave.			Peak / Ave.		Peak / Ave.		
MHz	m	degree	dBμV		dB/m	dBμV/m		dBμV/m		dB
2095.83	1.00	289	35.67	---	8.36	44.03	---	73.96	53.96	-9.93
2802.08	1.00	217	34.66	---	10.06	44.72	---	73.96	53.96	-9.24
7209.58	1.00	16	35.77	---	9.95	45.72	---	73.96	53.96	-8.24
9608.12	1.00	164	34.94	---	11.47	46.41	---	73.96	53.96	-7.55
12012.71	1.00	164	37.27	---	10.01	47.28	---	73.96	53.96	-6.68

Test mode: CH01 for 1GHz to 25GHz [Vertical]

Frequency	Ant. H.	Table	Amplitude		Correction Factor	Corrected Amplitude		Limit		Margin
			Peak / Ave.			Peak / Ave.		Peak / Ave.		
MHz	m	degree	dBμV		dB/m	dBμV/m		dBμV/m		dB
2039.58	1.00	346	35.50	---	8.20	43.70	---	73.96	53.96	-10.26
2743.75	1.00	80	34.50	---	9.95	44.45	---	73.96	53.96	-9.51
4805.00	1.00	285	38.60	---	3.69	42.29	---	73.96	53.96	-11.67
7209.58	1.00	165	35.27	---	9.95	45.22	---	73.96	53.96	-8.74
9608.12	1.00	178	35.44	---	11.47	46.91	---	73.96	53.96	-7.05
12012.71	1.00	153	36.94	---	10.01	46.95	---	73.96	53.96	-7.01

Test mode: CH39 for 30MHz to 1GHz [Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table (°)			Limit (dBμV/m)	Margin (dB)
140.94	31.57	1.00	89	-2.88	28.69	43.50	-14.81
200.36	36.27	1.00	124	-3.81	32.46	43.50	-11.04
240.97	36.20	1.00	100	-4.01	32.19	46.00	-13.81
299.18	36.29	1.00	116	-3.71	32.58	46.00	-13.42
334.34	34.11	1.00	229	-3.04	31.07	46.00	-14.93
399.21	30.75	1.00	292	-1.03	29.72	46.00	-16.28

Test mode: CH39 for 30MHz to 1GHz [Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table (°)			Limit (dBμV/m)	Margin (dB)
144.58	31.55	1.00	223	-2.98	28.57	43.50	-14.93
199.75	31.82	1.00	83	-3.81	28.01	43.50	-15.49
299.18	31.86	1.00	45	-3.71	28.15	46.00	-17.85
373.74	32.73	1.00	351	-1.91	30.82	46.00	-15.18
432.55	31.96	1.00	234	0.31	32.27	46.00	-13.73
558.65	27.81	1.00	248	5.30	33.11	46.00	-12.89

Test mode: CH39 for 1GHz to 25GHz [Horizontal]

Frequency	Ant. H.	Table	Amplitude		Correction Factor	Corrected Amplitude		Limit		Margin
			Peak / Ave.			Peak / Ave.		Peak / Ave.		
MHz	m	degree	dBμV		dB/m	dBμV/m		dBμV/m		dB
2152.08	1.00	233	34.66	---	8.52	43.18	---	73.96	53.96	-10.78
2787.50	1.00	185	34.00	---	10.03	44.03	---	73.96	53.96	-9.93
4877.50	1.00	51	40.61	---	3.97	44.58	---	73.96	53.96	-9.38
7318.33	1.00	91	35.11	---	10.31	45.42	---	73.96	53.96	-8.54
9759.17	1.00	152	34.94	---	11.90	46.84	---	73.96	53.96	-7.12
12200.00	1.00	241	39.44	---	9.77	49.21	---	73.96	53.96	-4.75

Test mode: CH39 for 1GHz to 25GHz [Vertical]

Frequency	Ant. H.	Table	Amplitude		Correction Factor	Corrected Amplitude		Limit		Margin
			Peak / Ave.			Peak / Ave.		Peak / Ave.		
MHz	m	degree	dBμV		dB/m	dBμV/m		dBμV/m		dB
2150.00	1.00	155	34.83	---	8.51	43.34	---	73.96	53.96	-10.62
2808.33	1.00	58	34.33	---	10.07	44.40	---	73.96	53.96	-9.56
7318.33	1.00	2	36.61	---	10.31	46.92	---	73.96	53.96	-7.04
9759.17	1.00	309	35.11	---	11.90	47.01	---	73.96	53.96	-6.95
12200.00	1.00	312	39.28	---	9.77	49.05	---	73.96	53.96	-4.91

Test mode: CH78 for 30MHz to 1GHz [Horizontal]

Radiated Emission				Correction Factors (dB)	Corrected Amplitude (dBμV/m)	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table (°)			Limit (dBμV/m)	Margin (dB)
200.36	32.15	1.00	67	-3.81	28.34	43.50	-15.16
227.03	36.06	1.00	100	-4.05	32.01	46.00	-13.99
240.97	36.22	1.00	88	-4.01	32.21	46.00	-13.79
279.17	35.34	1.00	48	-3.98	31.36	46.00	-14.64
373.74	33.15	1.00	276	-1.91	31.24	46.00	-14.76
558.65	24.14	1.00	112	5.30	29.44	46.00	-16.56

Test mode: CH78 for 30MHz to 1GHz [Vertical]

Radiated Emission				Correction Factors (dB)	Corrected Amplitude (dBμV/m)	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table (°)			Limit (dBμV/m)	Margin (dB)
144.58	31.09	1.00	266	-2.98	28.11	43.50	-15.39
200.36	32.08	1.00	6	-3.81	28.27	43.50	-15.23
373.74	33.78	1.00	15	-1.91	31.87	46.00	-14.13
399.21	33.81	1.00	18	-1.03	32.78	46.00	-13.22
432.55	32.80	1.00	229	0.31	33.11	46.00	-12.89
558.65	28.28	1.00	283	5.30	33.58	46.00	-12.42

Test mode: CH78 for 1GHz to 25GHz [Horizontal]

Frequency	Ant. H.	Table	Amplitude		Correction Factor	Corrected Amplitude		Limit		Margin
			Peak / Ave.			Peak / Ave.		Peak / Ave.		
MHz	m	degree	dBμV		dB/m	dBμV/m		dBμV/m		dB
2104.17	1.00	107	34.34	---	8.38	42.72	---	73.96	53.96	-11.24
2910.42	1.00	18	34.83	---	10.26	45.09	---	73.96	53.96	-8.87
4956.04	1.00	285	39.94	---	4.23	44.17	---	73.96	53.96	-9.79
7439.17	1.00	181	34.11	---	10.33	44.44	---	73.96	53.96	-9.52
9916.25	1.00	318	34.44	---	11.70	46.14	---	73.96	53.96	-7.82
12393.33	1.00	0	37.44	---	9.05	46.49	---	73.96	53.96	-7.47

Test mode: CH78 for 1GHz to 25GHz [Vertical]

Frequency	Ant. H.	Table	Amplitude		Correction Factor	Corrected Amplitude		Limit		Margin
			Peak / Ave.			Peak / Ave.		Peak / Ave.		
MHz	m	degree	dBμV		dB/m	dBμV/m		dBμV/m		dB
2120.83	1.00	268	35.00	---	8.43	43.43	---	73.96	53.96	-10.53
2929.17	1.00	102	34.66	---	10.30	44.96	---	73.96	53.96	-9.00
7439.17	1.00	82	35.44	---	10.33	45.77	---	73.96	53.96	-8.19
9916.25	1.00	299	35.61	---	11.70	47.31	---	73.96	53.96	-6.65
12393.33	1.00	155	37.10	---	9.05	46.15	---	73.96	53.96	-7.81
24789.37	1.00	46	46.33	---	2.23	48.56	---	73.96	53.96	-5.40

8.4 Test Result of the Bandedge


If any 100kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either *at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in §15.209(a)*,

We perform this section by the *radiated manner*, the RBW is set to 100kHz and VBW>RBW. We'd made the observation *up to 10th harmonics and the criterion is all the harmonic/spurious emissions must be 20dB below the highest emission level measured*. If the emissions fall in the restricted bands stated in the Part 15.205(a) must also *comply with the radiated emission limits specified in Part 15.209(a)*. (Peak mode: RBW=VBW=1MHz, Average mode: RBW=1MHz; VBW=10Hz)

The following pages show our observations referring to the channel 1 and 78 respectively.

Test Condition & Setup: same as < 8.1 >

Channel 01




This is the hard copy of our bandedge measurement generated by our bandedge testing program. The plot shown above is the bandedge of channel 1.

1. The lobe left by the fundamental side is already 20dB below the highest emission level.
2. The emissions recorded in the restricted band is do comply with the Part 15.209(a) – as below.

Radiated Emission					Corrected Amplitude		Class B (3m)		
Frequency (MHz)	Ant. P.	Ant. H. (m)	Table (°)	Factors (dB)	(dBμV/m)		Limit (dBμV/m)		Margin (dB)
					Peak	Average	Peak	Ave.	
2360.66	Hor	1.00	325	9.10	44.27	---	73.96	53.96	-9.69
2373.44	Hor	1.00	263	9.14	44.97	---	73.96	53.96	-8.99
2390.02	Hor	1.00	167	9.18	42.52	---	73.96	53.96	-11.44
2368.24	Ver	1.00	236	9.12	43.79	---	73.96	53.96	-10.17
2382.76	Ver	1.00	1	9.16	45.16	---	73.96	53.96	-8.80
2390.02	Ver	1.00	225	9.18	43.52	---	73.96	53.96	-10.44

Channel 78



This is the hard copy of our bandedge measurement generated by our bandedge testing program. The plot shown above is the bandedge of channel 78.

3. The lobe right by the fundamental side is already 20dB below the highest emission level.
4. The emissions recorded in the restricted band is do comply with the Part 15.209(a) – as below


Radiated Emission					Corrected Amplitude		Class B (3m)		
Frequency (MHz)	Ant. P.	Ant. H. (m)	Table (°)	Factors (dB)	(dBμV/m)		Limit (dBμV/m)		Margin (dB)
					Peak	Average	Peak	Ave.	
2483.50	Hor	1.00	341	9.44	43.44	---	73.96	53.96	-10.52
2493.07	Hor	1.00	327	9.47	44.80	---	73.96	53.96	-9.16
2500.01	Hor	1.00	88	9.49	43.49	---	73.96	53.96	-10.47
2511.15	Hor	1.00	300	9.51	44.01	---	73.96	53.96	-9.95
2490.85	Ver	1.00	171	9.44	43.96	---	73.96	53.96	-10.00
2514.65	Ver	1.00	44	9.52	45.02	---	73.96	53.96	-8.94

IX. Section 15.247(d): Power Spectral Density

9.1 Test Condition & Setup

The tests below are running with the EUT transmitter set at high power in TDD mode. The EUT is needed to force selection of output power level and channel number. While testing, the EUT was set to transmit continuously and to be tested by the contact manner with the spectrum analyzer.

9.2 Test Instruments Configuration



PC to control the EUT at maximal power output and channel number and set antenna kit

9.3 List of Test Instruments

Instrument Name	Model No.	Brand	Serial No.	Next time
Spectrum Analyzer	MS2665C	ANRITSU	6200175476	11/02/05

9.4 Test Result of Power spectral density


The following table shows a summary of the test results of the Power Spectral Density.

<i>Channel</i>	<i>Ppr (dBm)</i>	<i>Cable Loss (dB)</i>	<i>Ppq (dBm)</i>	<i>Limit (dB)</i>	<i>Margin (dB)</i>
CH 01	-23.17	1.00	-22.17	8.00	-30.17
CH 39	-25.30	1.00	-24.30	8.00	-32.30
CH 78	-24.62	1.00	-23.62	8.00	-31.62

Note:

1. The following pages show the results of spectrum reading.
2. Ppr: spectrum read power density (using peak search mode),
Ppq: actual peak power density in the spread spectrum band.
3. $Ppq = Ppr + |\text{Cable Loss}|$

Power Spectral Density for Channel 01



Power Spectral Density for Channel 39



Power Spectral Density for Channel 78

