

MEASUREMENT REPORT
of
2.4GHz RF Keyboard

Applicant : TopSeed Technology Corp.
FCC ID : PTITSJE-2401
EUT : 2.4GHz RF Keyboard
Model : TSJE-2401

Test by :

Training Research Co., Ltd.

TEL : 886-2-26935155 **FAX : 886-2-26934440**

No. 255, Nan-yang Street, Shijr, Taipei Hsien 221, Taiwan

CERTIFICATION


We here by verify that:

The test data, data evaluation, test procedures and equipment configurations shown in this report were made mainly in accordance with the procedures given in ANSI C63.4 (2003) as a reference. All tests were conducted by **Training Research Co., Ltd.**, No. 255, Nan-yang Street, Shijr, Taipei Hsien 221, Taiwan. Also, we attest to the accuracy of each.


We further submit that the energy emitted by the sample EUT tested as described in the report is **in compliance with** the technical requirements set forth in the FCC Rules Part 15 Subpart C Section 15.249.

Applicant : TopSeed Technology Corp.
Applicant address : 9F-3, No. 16, Jain Ba Road, Chung Ho City, Taipei Hsien,
Taiwan 235
Report No. : AA515080413
Test Date : February 26, 2009

Prepared by:


Jack Tsai

Approved by:


Frank Tsai

Conditions of issue :

- (1) **This test report shall not be reproduced except in full, without written approval of TRC. And the test result contained within this report only relate to the sample submitted for testing.**
- (2) **This report must not be used by the client to claim product endorsement by NVLAP or any agency of U.S. Government.**
- (3) **This test report, measurements made by TRC are traceable to the NIST only Conducted and Radiated Method.**



NVLAP LAB CODE 200174-0

Tables of Contents

CHAPTER 1	GENERAL.....	4
1.1	INTRODUCTION	4
1.2	DESCRIPTION OF EUT.....	4
1.3	TEST METHOD	4
1.4	DESCRIPTION OF SUPPORT EQUIPMENT	5
1.5	CONFIGURATION OF SYSTEM UNDER TEST	6
1.6	TEST PROCEDURE.....	8
1.7	LOCATION OF THE TEST SITE.....	8
1.8	GENERAL TEST CONDITION.....	8
CHAPTER 2	CONDUCTED EMISSIONS MEASUREMENTS.....	9
2.1	TEST CONDITION & SETUP.....	9
2.2	LIST OF TEST INSTRUMENTS.....	9
2.3	TEST RESULT OF CONDUCTED EMISSIONS	9
CHAPTER 3	TRANSMITTER DUTY CYCLE MEASUREMENTS	10
3.1	TEST CONDITION AND SETUP.....	10
3.2	LIST OF TEST INSTRUMENTS.....	10
3.3	TEST INSTRUMENTS CONFIGURATION	11
3.4	TEST RESULT	11
CHAPTER 4	RADIATED EMISSIONS MEASUREMENTS	13
4.1	TEST CONDITION & SETUP.....	13
4.2	LIST OF TEST INSTRUMENTS.....	15
4.3	TEST RESULT OF RADIATED EMISSIONS	16
	Fundamental Emissions.....	16
4.4	TEST RESULT OF SPURIOUS RADIATED EMISSIONS	17
	Radiated Emissions of Horizontal for 30MHz to 25GHz [Lowest Channel]	17
	Radiated Emissions of Vertical for 30MHz to 25GHz [Lowest Channel]	17
	Radiated Emissions of Horizontal for 30MHz to 25GHz [Middle Channel].....	18
	Radiated Emissions of Vertical for 30MHz to 25GHz [Middle Channel].....	18
	Radiated Emissions of Horizontal for 30MHz to 25GHz [Highest Channel]	19
	Radiated Emissions of Vertical for 30MHz to 25GHz [Highest Channel]	19
4.5	TEST RESULT OF THE BANDEDGE.....	20
	Lowest.....	21
	Highest.....	22

Chapter 1 General

1.1 Introduction

The following measurement report is submitted on behalf of Applicant in support of a wireless mouse certification in accordance with Part 2 Subpart J and Part 15 Subpart C of the Commission's Rules and Regulations.

1.2 Description of EUT

FCC ID	: PTITSJE-2401
Product Name	: 2.4GHz RF Keyboard
Model	: TSJE-2401
Frequency Range	: 2400MHz ~ 2483.5MHz
Operating Frequency	: 2428MHz ~ 2444MHz
Modulation Skill	: GFSK
Power Type	: Powered by DC 1.5V batteries (AA*4)

1.3 Test method

The fundamental frequency of transmitter emitted is due to test fixture by notebook PC. There are security codes for avoiding the possibility of duplicating codes in adjacent systems. The coding must be matching with the companion receiver.

While testing the EUT was adjusted at a position, which transmits the maximum emission.

Test setting:


- (1) The test fixture is connected to notebook PC and setting test channel, transmission on by wireless of test fixture then EUT is setting test mode for radiated of intentional testing. When EUT is setting finish then test fixture is power off.
- (2) Set different channel (Lowest/Middle/Highest) being tested and repeat the procedures above.
 - (a) Radiated for intentional test:
making EUT to the mode of continuously transmission

1.4 Description of Support Equipment

Notebook PC	:	IBM ThinkPad T43
Model No.	:	2662-8HT
Serial No.	:	FX-V3657
FCC ID	:	N/A, DoC (Declaration of Confirmation) Approved
BSMI	:	3892B564
Power adaptor	:	IBM
Part No.	:	92P1018
Serial No.	:	11S92P1018Z1ZAPU57M9W6 REV: D
BSMI	:	D33030
Power type	:	100 ~ 240VAC / 50 ~ 60Hz, 1.0 ~ 0.4A, Switching
Power cord	:	Primary: Non-shielded, 1.0m length, Plastic hood, No ferrite core Secondary: Shielded, 1.84m length, Plastic hood, ferrite core
Test fixture	:	Cypress MTK
Power type	:	Switching adaptor
Power cord	:	Non-shielded, 183cm long, No ferrite core
Data cable	:	Shielded, 1.50m long, No ferrite core

1.5 Configuration of System Under Test

1.5.1 Radiated of test setup for EUT




Connections of Equipment

Notebook:

*RS232 Port ---

1.5.2 Radiated of test setup for measurement system



1.6 Test Procedure

All measurements contained in this report were performed mainly according to the techniques described in Measurement procedure ANSI C63.4 (2003).

1.7 Location of the Test Site

The radiated emissions measurements required by the rules were performed on the **three-meter, Anechoic Chamber (FCC Registration Number: 93906)** maintained by *Training Research Co., Ltd.* 1F, No. 255, Nan-yang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C. Complete description and measurement data have been placed on file with the commission. The conducted power line emissions tests and other test items were performed in an anechoic chamber also located at Training Research Co., Ltd. 1F, No. 255, Nan-yang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C. *Training Research Co., Ltd.* is listed by the FCC as a facility available to do measurement work for others on a contract basis.

1.8 General Test Condition

The conditions under which the EUT operates were varied to determine their effect on the equipment's emission characteristics. The final configuration of the test system and the mode of operation used during these tests was chosen as that which produced the highest emission levels. However, only those conditions which the EUT was considered likely to encounter in normal use were investigated.

In test, they were set in high power and continuously transmitting mode. The Highest, Middle and Lowest of EUT were all tested. The setting up procedure is recorded on 1.3 Test Method.

Chapter 2 Conducted Emissions Measurements

2.1 Test Condition & Setup

The EUT operates solely by the batteries (AA*4 DC 1.5V batteries).

According to the rule of section 15.207(c), the EUT exempt to the power line conducted test.

2.2 List of Test Instruments

N/A (Not applicable)

2.3 Test Result of Conducted Emissions

N/A (Not applicable)

Chapter 3 Transmitter Duty Cycle Measurements

3.1 Test Condition and Setup

The duty cycle measurements were performed in a shielded enclosure. The EUT was placed on a wooded table which is 0.8 meters height and a bi-log periodic antenna was used distance about 3 meters for receiving. While testing EUT was set to transmit continuously. Various key configurations were also investigated to find the maximum duty cycle.

The resolution bandwidth and video bandwidth of the spectrum analyzer was all set to 1MHz to encompass all significant spectral components during the test. The analyzer operated in linear scale and zero span mode after tuning to the transmitter carrier frequency. The spectrum analyzer measured pulses width. The pulse width was determined by the difference between the two half voltage points on a pulse.

The duty cycle was determined by the following equation:

$$\text{Duty Cycle (\%)} = \frac{\text{Total on interval in a complete pulse train}}{\text{Length of a complete pulse train}} \times 100\%$$


To calculate the actual field intensity, the duty cycle correction factor in decibel is needed for later use and be obtained from following conversion:

$$\text{Duty Cycle Correction Factor (dB)} = 20 \times \log_{10} \text{Duty Cycle}$$

3.2 List of Test Instruments

Instrument Name	Model No.	Brand	Serial No.	<u>Calibration Date</u>
				Next time
EMI Receiver	8546A	HP	3520A00242	04/15/09
RF Filter Section	85460A	HP	3448A00217	04/15/09
Spectrum Analyzer	MS2665C	ANRITSU	6200175476	03/19/09
Spectrum Analyzer	8564E	HP	3720A00840	03/17/09
Microwave Preamplifier	84125C	HP	US36433002	05/05/09
Small Biconical Antenna	UBAA9114 & BBVU9135	SCHWARZECK	127	04/10/09

3.3 Test Instruments Configuration



3.4 Test Result

Following is the test result, which produce maximum duty cycle:

Total on interval in a complete pulse train

$$= 262\mu s * 6$$

Length of a complete pulse train

$$= 9.64ms$$



$$\text{Duty Cycle (\%)} = 1.572ms / 86.70ms * 100\% = 0.018$$

$$\text{Duty Cycle Correction Factor (dB)} = 20 * \text{Log} (0.018) = -34.89$$

Maximum duty cycle according to FCC part 15.35(b): -20dB

A plot is attached on the following page.

Duty Cycle Test Picture



Chapter 4 Radiated Emissions Measurements

4.1 Test Condition & Setup

We'd performed the test by the radiated emission skill: The EUT was placed in an anechoic chamber, and set the EUT transmitting continuously and scanned at 3meter distance to determine its emission characteristics. The physical arrangement of the EUT was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude, directivity, and frequency. The exact system configuration, which produced the highest emissions was noted so it could be reproduced later during the final tests. For the measurement above 1GHz, according to the guidance we'd set the spectrum analyzer's 6dB bandwidth RBW to 1MHz.

This was done to ensure that the final measurements would demonstrate the worst-case interference potential of the EUT.

Final radiation measurements were made on a three-meter, anechoic chamber. The EUT system was placed on a nonconductive turntable, which is 0.8 meters height, top surface 1.0 x 1.5 meter.

The spectrum was examined from 30 MHz to 1000 MHz using an Hewlett Packard 85460A EMI Receiver, SCHWARZECK whole range Small Biconical Antenna (model: UBAA9114 & BBVU9135) is used to measure frequency from 30 MHz to 1GHz. The final test is used the HP 85460A spectrum and 8564E spectrum was examined from 1GHz to 25GHz using an Hewlett Packard Spectrum Analyzer, EMCO/HP Horn Antenna (Model 3115 / 84125-80008) for 1G - 25GHz.

A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each frequency, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. There are two spectrum analyzers use on this testing, HP 85460A for frequency 30MHz to 1000MHz, and 8564E for frequency 1GHz to 25GHz. No post-detector video filters were used in the test. The spectrum analyzer's 6dB bandwidth was set to 120KHz (spectrum was examined from 30 MHz to 1000 MHz), the spectrum analyzer's 6 dB bandwidth was set to 1 MHz (spectrum was examined from 1GHz to 25GHz) and the analyzer was operated in the maximum hold mode. There is a test condition applies in this test item, the test procedure description as the following:

Three channels were tested, one in the top, one in the middle and the other in bottom. The setting up procedure is recorded on <1.3>

With the transmitter operating from a AC source and using the internal of EUT, radiates spurious emissions falling within the restricted bands of 15.209 were measured at operating frequencies corresponding to upper, middle and bottom channels in the 2400 ~ 2483.5 MHz band.

The actual field intensity in decibels referenced to 1 microvolt per meter (dBμV/m) is determined by algebraically adding the measured reading in dBμV, the antenna factor (dB), and cable loss (dB) at the appropriate frequency. Since the EUT was set to transmit continuously, with *duty cycle* is present.

For frequency between 30MHz to 1000MHz

$F_{Ia} \text{ (dB}\mu\text{V/m)} = F_{Ir} \text{ (dB}\mu\text{V)} + \text{Correction Factors} + \text{Duty Cycle}$

F_{Ia} : Actual Field Intensity

F_{Ir} : Reading of the Field Intensity

Correction Factors = Antenna factor + (Cable loss – Amplitude gain) + Switching box loss

For frequency between 1GHz to 25GHz

$F_{Ia} \text{ (dB}\mu\text{V/m)} = F_{Ir} \text{ (dB}\mu\text{V)} + \text{Correction Factor} + \text{Duty Cycle}$

F_{Ia} : Actual Field Intensity

F_{Ir} : Reading of the Field Intensity

Correction Factors = Antenna factor + (Cable loss – Amplitude gain) + Switching box loss

4.2 List of Test Instruments

Instrument Name	Model	Brand	Serial No.	Calibration Date
				Next time
EMI Receiver	8546A	HP	3520A00242	04/15/09
RF Filter Section	85460A	HP	3448A00217	04/15/09
Small Biconical Antenna	UBAA9114 & BBVU9135	SCHWARZECK	127	04/10/09
Pre-amplifier	PA1F	TRC	1FAC	04/10/09
Coaxial Cable (Double shielded, 15 meter)	A30A30-0058-50FS-15M	JYEBAO	SMA-01	04/10/09
Coaxial Cable (1.1 meter)	A30A30-0058-50FS-1M	JYEBAO	SMA-02	04/10/09
Spectrum Analyzer	8564E	HP	3720A00840	03/17/09
Microwave Preamplifier	84125C	HP	US36433002	05/05/09
Horn Antenna	3115	EMCO	9104-3668	08/06/09
Standard Guide Horn Antenna	84125-80008	HP	18-26.5GHz	03/14/09
Standard Guide Horn Antenna	84125-80001	HP	26.5-40GHz	05/12/09
Horn Antenna	1196E (3115)	HP (EMCO)	9704-5178	08/13/09
Pre-amplifier	PA2F	TRC	2F1GZ	04/10/09
Coaxial Cable (3 miter)	A30A30-0058-50FST118	JYEBAO	MSA-05	04/10/09
Coaxial Cable (1 meter)	A30A30-0058-50FST118	JYEBAO	MSA-04	04/10/09

4.3 Test Result of Radiated Emissions

The peak values of fundamental emissions from the EUT at various antenna heights, antenna polarization, EUT orientation, etc. are recorded on the following.

Testing room : Temperature : 25 ° C Humidity : 73 % RH

Fundamental Emissions

Channel	Frequency (MHz)	A. P. (H/V)	A.H. (m)	Table (degree)	Peak (dBμV/m)	Duty Cycle	True Value (dBμV/m)	Limit (dBμV)	Margin (dBμV)
Lowest	2428	H	1.00	7	99.95	-20.00	79.95	94.00	-14.05
		V	1.00	277	97.62	-20.00	77.62	94.00	-16.38
Middle	2436	H	1.00	110	99.14	-20.00	79.14	94.00	-14.86
		V	1.00	202	95.81	-20.00	75.81	94.00	-18.19
Highest	2444	H	1.00	145	99.17	-20.00	79.17	94.00	-14.83
		V	1.00	218	95.00	-20.00	75.00	94.00	-19.00

Note:

1. A. P. means antenna polarization, horizontal and vertical.
2. A. H. means antenna height.
3. Table means turntable turning position.
4. Peak amplitude means the fundamental emission measured.
5. True Value = Peak Value + Duty Cycle
6. Margin = True Value – Limit

4.4 Test Result of Spurious Radiated Emissions

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarization, EUT orientation, etc. are recorded on the following.

Testing room : Temperature : 25 °C Humidity : 73% RH

Radiated Emissions of Horizontal for 30MHz to 25GHz [Lowest Channel]

Radiated Emission				CF	Peak Value	Duty Cycle	True Value	FCC Class B	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Angle	(dB)	(dBμV/m)	(dB)	(dBμV/m)	Limit (Avg.) (dBμV/m)	Margin (dB)
312.51	39.03	1.00	337	-2.74	36.29	---	36.29	46.00	-9.71
340.40	42.92	1.00	317	-2.39	40.53	---	40.53	46.00	-5.47
369.50	41.08	1.00	267	-1.81	39.27	---	39.27	46.00	-6.73
2506.25	40.17	1.00	19	9.50	49.67	-20.00	29.67	53.96	-24.29
4855.73	56.10	1.00	278	3.88	59.98	-20.00	39.98	53.96	-13.98
7283.47	42.78	1.00	216	10.23	53.01	-20.00	33.01	53.96	-20.95
12139.25	45.28	1.00	137	9.58	54.86	-20.00	34.86	53.96	-19.10
19423.75	47.16	1.00	176	1.60	48.76	-20.00	28.76	53.96	-25.20

Radiated Emissions of Vertical for 30MHz to 25GHz [Lowest Channel]

Radiated Emission				CF	Peak Value	Duty Cycle	True Value	FCC Class B	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Angle	(dB)	(dBμV/m)	(dB)	(dBμV/m)	Limit (Avg.) (dBμV/m)	Margin (dB)
89.41	28.34	1.00	33	0.05	28.39	---	28.39	43.50	-15.11
251.89	26.37	1.00	97	-3.29	23.08	---	23.08	46.00	-22.92
307.66	24.74	1.00	307	-2.80	21.94	---	21.94	46.00	-24.06
4856.89	56.26	1.00	196	3.89	60.15	-20.00	40.15	53.96	-13.81
7283.47	47.11	1.00	167	10.23	57.34	-20.00	37.34	53.96	-16.62
9710.83	38.77	1.00	267	11.73	50.50	-20.00	30.50	53.96	-23.46
12142.48	49.10	1.00	228	9.59	58.69	-20.00	38.69	53.96	-15.27
21853.33	46.65	1.00	111	2.89	49.54	-20.00	29.54	53.96	-24.42

Radiated Emissions of Horizontal for 30MHz to 25GHz [Middle Channel]

Radiated Emission				CF	Peak Value	Duty Cycle	True Value	FCC Class B	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Angle	(dB)	(dBμV/m)	(dB)	(dBμV/m)	Limit (Avg.) (dBμV/m)	Margin (dB)
311.30	38.28	1.00	167	-2.76	35.52	---	35.52	46.00	-10.48
340.40	43.60	1.00	187	-2.39	41.21	---	41.21	46.00	-4.79
402.24	35.38	1.00	127	-0.98	34.40	---	34.40	46.00	-11.60
2506.25	41.12	1.00	110	9.05	50.17	-20.00	30.17	53.96	-23.79
4872.88	54.27	1.00	306	3.95	58.22	-20.00	38.22	53.96	-15.74
7306.25	39.77	1.00	138	10.29	50.06	-20.00	30.06	53.96	-23.90
12182.43	42.59	1.00	283	9.72	52.31	-20.00	32.31	53.96	-21.65
19487.50	46.99	1.00	122	1.68	48.67	-20.00	28.67	53.96	-25.29

Radiated Emissions of Vertical for 30MHz to 25GHz [Middle Channel]

Radiated Emission				CF	Peak Value	Duty Cycle	True Value	FCC Class B	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Angle	(dB)	(dBμV/m)	(dB)	(dBμV/m)	Limit (Avg.) (dBμV/m)	Margin (dB)
89.41	29.50	1.00	146	0.05	29.55	---	29.55	43.50	-13.95
306.45	27.50	1.00	245	-3.82	23.68	---	23.68	46.00	-22.32
341.61	25.91	1.00	326	-2.38	23.53	---	23.53	46.00	-22.47
4872.84	57.60	1.00	81	3.95	61.55	-20.00	41.55	53.96	-12.41
7307.48	45.94	1.00	126	10.29	56.23	-20.00	36.23	53.96	-17.73
9747.08	38.27	1.00	218	11.89	50.16	-20.00	30.16	53.96	-23.80
12178.90	48.76	1.00	195	9.71	58.47	-20.00	38.47	53.96	-15.49
21924.17	46.49	1.00	9	3.07	49.56	-20.00	29.56	53.96	-24.40

Radiated Emissions of Horizontal for 30MHz to 25GHz [Highest Channel]

Radiated Emission				CF	Peak Value	Duty Cycle	True Value	FCC Class B	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Angle	(dB)	(dBμV/m)	(dB)	(dBμV/m)	Limit (Avg.) (dBμV/m)	Margin (dB)
312.51	38.09	1.00	165	-2.74	35.35	---	35.35	46.00	-10.65
341.61	41.47	1.00	145	-2.38	39.09	---	39.09	46.00	-6.91
373.14	37.46	1.00	316	-1.72	35.74	---	35.74	46.00	-10.26
2345.83	38.50	1.00	146	9.06	47.56	-20.00	27.56	53.96	-26.40
4888.89	55.11	1.00	327	4.01	59.12	-20.00	39.12	53.96	-14.84
7331.46	40.94	1.00	104	10.34	51.28	-20.00	31.28	53.96	-22.68
12218.12	40.77	1.00	233	9.83	50.60	-20.00	30.60	53.96	-23.36
24442.29	46.82	1.00	66	2.88	49.70	-20.00	29.70	53.96	-24.26

Radiated Emissions of Vertical for 30MHz to 25GHz [Highest Channel]

Radiated Emission				CF	Peak Value	Duty Cycle	True Value	FCC Class B	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Angle	(dB)	(dBμV/m)	(dB)	(dBμV/m)	Limit (Avg.) (dBμV/m)	Margin (dB)
90.62	28.77	1.00	202	-0.02	28.75	---	28.75	43.50	-14.75
306.45	25.25	1.00	229	-2.82	22.43	---	22.43	46.00	-23.57
341.61	24.45	1.00	138	-2.38	22.07	---	22.07	46.00	-23.93
4887.75	56.78	1.00	48	4.00	60.78	-20.00	40.78	53.96	-13.18
7331.47	44.77	1.00	108	10.34	55.11	-20.00	35.11	53.96	-18.85
9777.29	38.27	1.00	74	11.91	50.18	-20.00	30.18	53.96	-23.78
12219.22	45.11	1.00	196	9.83	54.94	-20.00	34.94	53.96	-19.02
24442.29	46.49	1.00	229	2.88	49.37	-20.00	29.37	53.96	-24.59

Note:

1. Margin = Amplitude – limit, *if margin is minus means under limit.*
2. Correction factor = Antenna factor + (Cable Loss – Amplitude gain)
3. Peak Value = Reading Amplitude + Correction Factors
4. True Value = Peak Value + Duty Cycle


4.5 Test Result of the Bandedge

§ 15.249 (c) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

We perform this section by the *radiated manner*, the RBW is set to 100kHz and VBW>RBW. We'd made the observation *up to 10th harmonics and the criterion is all the harmonic/spurious emissions must be 50dB below the highest emission level measured*. If the emissions fall in the restricted bands stated in the Part15.205(a) must also *comply with the radiated emission limits specified in Part15.209(a)*. (Peak mode: RBW=VBW=1MHz, Average mode: RBW=1MHz; VBW=10Hz)

The following pages show our observations referring to the lowest channel and highest channel respectively. Test Condition & Setup: same as 4.1 to 4.2.

Lowest




This is the hard copy of our bandedge measurement generated by our bandedge testing program. The plot shown above is the bandedge of lowest channel.

1. The lobe left by the fundamental side is already 50dB below the highest emission level.
2. The emissions recorded in the restricted band is do comply with the Part 15.209(a) – as below.

<i>Radiated Emission</i>				<i>CF</i>	<i>Peak Value</i>	<i>Duty Cycle</i>	<i>True Value</i>	<i>FCC Class B</i>	
Frequency (MHz)	Ant. P.	Ant. H. (m)	Angle	(dB)	(dBμV/m)	(dB)	(dBμV/m)	Limit (Avg.) (dBμV/m)	Margin (dB)
2377.94	Hor	1.00	204	9.15	57.31	-20.00	37.31	53.96	-16.65
2390.23	Hor	1.00	174	9.18	55.85	-20.00	35.85	53.96	-18.11
2377.56	Ver	1.00	322	9.15	53.31	-20.00	33.31	53.96	-20.65
2390.23	Ver	1.00	322	9.18	53.02	-20.00	33.02	53.96	-20.94

Highest



This is the hard copy of our bandedge measurement generated by our bandedge testing program.

The plot shown above is the bandedge of highest channel.

1. The lobe right by the fundamental side is already 50dB below the highest emission level.
2. The emissions recorded in the restricted band is do comply with the Part 15.209(a) – as below

<i>Radiated Emission</i>				<i>CF</i>	<i>Peak Value</i>	<i>Duty Cycle</i>	<i>True Value</i>	<i>FCC Class B</i>	
Frequency (MHz)	Ant. P.	Ant. H. (m)	Angle	(dB)	(dBμV/m)	(dB)	(dBμV/m)	Limit (Avg.) (dBμV/m)	Margin (dB)
2483.91	Hor	1.00	231	9.44	54.61	-20.00	34.61	53.96	-19.35
2485.13	Hor	1.00	255	9.45	55.78	-20.00	35.78	53.96	-18.18
2500.01	Hor	1.00	253	9.49	50.49	-20.00	30.49	53.96	-23.47
2507.77	Hor	1.00	232	9.50	52.50	-20.00	32.50	53.96	-21.46
2483.44	Ver	1.00	311	9.44	48.44	-20.00	28.44	53.96	-25.52
2485.25	Ver	1.00	192	9.45	49.62	-20.00	29.62	53.96	-24.34
2500.01	Ver	1.00	195	9.49	46.66	-20.00	26.66	53.96	-27.30
2504.32	Ver	1.00	216	9.50	47.50	-20.00	27.50	53.96	-26.46