



RF EXPOSURE REPORT (FOR BLUETOOTH)

REPORT NO.: SA980702L17-1

MODEL NO.: 0251, 2872

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: Wistron Corporation

ADDRESS: 21F, No. 88, Sec. 1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 221, Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang, Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.580
High	2.480	

Maximum measured transmitter power:

	Pout (dBm)	Pout (mW)
Conducted Power	0.17	1.040
EIRP Power	1.99	1.581

***Note:** The antenna is PIFA antenna with 1.82dBi gain

Threshold for no SAR evaluation is 24.580mW

Transmitter power is 1.581mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold