

FCC Radio Test Report

FCC ID: PU5-LN300WG3D

Report No. : BTL-FCCP-18-2102T172A
Equipment : Notebook Computer
Model Name : Lenovo 300w Gen 3xxxxxxx (The "x" in model name can be 0 to 9, A to Z, a to z, "-" or blank, for marketing purpose only)
Brand Name : Lenovo
Applicant : Wistron Corporation
Address : 21F, No. 88, Sec. 1, Hsin Tai Wu Rd., Hsichih Dist, New Taipei City 221, Taiwan

Radio Function : Transmit Simultaneously


FCC Rule Part(s) : 47 CFR FCC Part15, Subpart C (15.247)
47 CFR FCC Part15, Subpart E (15.407)
47 CFR FCC Part 22 Subpart H
47 CFR FCC Part 24 Subpart E
47 CFR FCC Part 27 Subpart D
47 CFR FCC Part 27 Subpart F
47 CFR FCC Part 27 Subpart H
47 CFR FCC Part 27 Subpart L
47 CFR FCC Part 27 Subpart M
47 CFR FCC Part 90 Subpart S

Measurement Procedure(s) : ANSI C63.10-2013
ANSI C63.26-2015
ANSI/TIA-603-E-2016
FCC KDB 971168 D01 Power Meas License Digital Systems v03r01

Date of Receipt : 2021/3/12
Date of Test : 2021/3/12 ~ 2021/6/16
Issued Date : 2021/6/17

The above equipment has been tested and found in compliance with the requirement of the above standards by BTL Inc.

Prepared by 
Peter Chen, Engineer

Approved by : 
Scott Hsu, Manager

**BTL Inc.**

No.18, Ln. 171, Sec. 2, Jiuzong Rd., Neihu Dist., Taipei City 114, Taiwan

Tel: +886-2-2657-3299

Fax: +886-2-2657-3331

Web: www.newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

CONTENTS

1	SUMMARY OF TEST RESULTS	5
1.1	TEST FACILITY	6
1.2	MEASUREMENT UNCERTAINTY	6
1.3	TEST ENVIRONMENT CONDITIONS	6
2	GENERAL INFORMATION	7
2.1	DESCRIPTION OF EUT	7
2.2	TEST MODES	10
2.3	BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.4	SUPPORT UNITS	11
3	RADIATED EMISSIONS TEST	12
3.1	LIMIT	12
3.2	TEST PROCEDURE	13
3.3	DEVIATION FROM TEST STANDARD	13
3.4	TEST SETUP	14
3.5	EUT OPERATING CONDITIONS	15
3.6	TEST RESULT	15
4	LIST OF MEASURING EQUIPMENTS	16
5	EUT TEST PHOTO	17
6	EUT PHOTOS	17
APPENDIX A	RADIATED EMISSIONS	18

REVISION HISTORY

Report No.	Version	Description	Issued Date
BTL-FCCP-18-2102T172A	R00	Original Report.	2021/5/21
BTL-FCCP-18-2102T172A	R01	Revised report to address TCB's comments.	2021/5/31
BTL-FCCP-18-2102T172A	R02	Revised report to address TCB's comments.	2021/6/10
BTL-FCCP-18-2102T172A	R03	Revised report to address TCB's comments.	2021/6/15
BTL-FCCP-18-2102T172A	R04	Revised report to address TCB's comments.	2021/6/17

1 SUMMARY OF TEST RESULTS

Test procedures according to the technical standards.

Standard(s) Section	Description	Test Result	Judgement	Remark
15.205 15.209 15.247(d) 15.407(b) 2.1053 22.917(a) 24.238(a) 27.53(a)(4) 27.53(c)(2) 27.53(f) 27.53(g) 27.53(h) 27.53(m)(4) 90.669	Radiated Emissions	APPENDIX A	Pass	-----

NOTE:

- (1) "N/A" denotes test is not applicable in this Test Report.
- (2) The report format version is TP.1.1.1.

1.1 TEST FACILITY

The test facilities used to collect the test data in this report:

No. 68-1, Ln. 169, Sec. 2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan

The test sites and facilities are covered under FCC RN: 674415 and DN: TW0659.

C05
 CB08
 CB11
 CB15
 CB16

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k = 2$, providing a level of confidence of approximately **95 %**.

The measurement instrumentation uncertainty considerations contained in CISPR 16-4-2. The BTL measurement uncertainty is less than the CISPR 16-4-2 U_{cispr} requirement.

A. Radiated emissions test :

Test Site	Measurement Frequency Range	U,(dB)
CB15	0.03 GHz ~ 0.2 GHz	4.17
	0.2 GHz ~ 1 GHz	4.72
	1 GHz ~ 6 GHz	5.21
	6 GHz ~ 18 GHz	5.51
	18 GHz ~ 26 GHz	3.69
	26 GHz ~ 40 GHz	4.23

NOTE:

Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Environment Condition	Test Voltage	Tested by
Radiated emissions	Refer to data	AC 120V	Jay Kao

2 GENERAL INFORMATION

2.1 DESCRIPTION OF EUT

Equipment	Notebook Computer		
Model Name	Lenovo 300w Gen 3xxxxxxx (The "x" in model name can be 0 to 9, A to Z, a to z, "-" or blank, for marketing purpose only)		
Brand Name	Lenovo		
Model Difference	Different model distribute to different area.		
Power Source	DC voltage supplied from External Power Supply. (Lenovo/ADLX45YLC3D)		
Power Rating	I/P: 100-240V~1.3A 50-60Hz O/P: 20.0V---2.25A 45.0W / 15.0V---3.0A / 9.0V---2.0A / 5.0V---2.0A 10.0W		
Products Covered	1 * Adapter: Lenovo/ADLX45YLC3D		
WIFI+BT Module	Intel® Wi-Fi 6 AX200 / AX200NGW		
WWAN Module	Fibocom / L850-GL		
Operation Frequency	WLAN: 2412 MHz ~ 2472 MHz		
	UNII-1: 5180 MHz ~ 5250 MHz		
	UNII-2A: 5250 MHz ~ 5320 MHz		
	UNII-2C: 5500 MHz ~ 5700 MHz		
	UNII-3: 5745 MHz ~ 5825 MHz		
	Band	UL Frequency (MHz)	DL Frequency (MHz)
	WCDMA V	824 ~ 849	869 ~ 894
	LTE 5	824 ~ 849	869 ~ 894
	LTE 26	824 ~ 849	869 ~ 894
	WCDMA II	1850 ~ 1910	1930 ~ 1990
	LTE 2	1850 ~ 1910	1930 ~ 1990
	WCDMA IV	1710 ~ 1755	2110 ~ 2155
	LTE 4	1710 ~ 1755	2110 ~ 2155
	LTE 7	2500 ~ 2570	2620 ~ 2690
	LTE 12	699 ~ 716	729 ~ 746
LTE 13	777 ~ 787	746 ~ 756	
LTE 17	704 ~ 716	734 ~ 746	
LTE 30	2305 ~ 2315	2350 ~ 2360	
LTE 41	2496 ~ 2690	-	
LTE 66	1710 ~ 1780	2110 ~ 2200	
LTE 26	814 ~ 849	859 ~ 894	
Test Model	Lenovo 300w Gen 3		
Sample Status	Engineering Sample		
EUT Modification(s)	N/A		

NOTE:

- (1) For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

(2) Channel List:

WLAN 2.4 GHz					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	06	2437	11	2462
02	2417	07	2442	12	2467
03	2422	08	2447	13	2472
04	2427	09	2452		
05	2432	10	2457		

WLAN 5 GHz					
UNII-1					
IEEE 802.11a IEEE 802.11n (HT20) IEEE 802.11ac (VHT20) IEEE 802.11ax (HEW20)		IEEE 802.11n (HT40) IEEE 802.11ac (VHT40) IEEE 802.11ax (HEW40)		IEEE 802.11ac (VHT80) IEEE 802.11ax (HEW80)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190	42	5210
40	5200	46	5230		
44	5220				
48	5240				

UNII-2A					
IEEE 802.11a IEEE 802.11n (HT20) IEEE 802.11ac (VHT20) IEEE 802.11ax (HEW20)		IEEE 802.11n (HT40) IEEE 802.11ac (VHT40) IEEE 802.11ax (HEW40)		IEEE 802.11ac (VHT80) IEEE 802.11ax (HEW80)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	54	5270	58	5290
56	5280	62	5310		
60	5300				
64	5320				

UNII-2C					
IEEE 802.11a IEEE 802.11n (HT20) IEEE 802.11ac (VHT20) IEEE 802.11ax (HEW20)		IEEE 802.11n (HT40) IEEE 802.11ac (VHT40) IEEE 802.11ax (HEW40)		IEEE 802.11ac (VHT80) IEEE 802.11ax (HEW80)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	102	5510	106	5530
104	5520	110	5550	122	5610
108	5540	118	5590	138	5690
112	5560	126	5630		
116	5580	134	5670		
120	5600				
124	5620				
128	5640				
132	5660				
136	5680				
140	5700				

UNII-3					
IEEE 802.11a IEEE 802.11n (HT20) IEEE 802.11ac (VHT20) IEEE 802.11ax (HEW20)		IEEE 802.11n (HT40) IEEE 802.11ac (VHT40) IEEE 802.11ax (HEW40)		IEEE 802.11ac (VHT80) IEEE 802.11ax (HEW80)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	151	5755	155	5775
153	5765	159	5795		
157	5785				
161	5805				
165	5825				

802.11ac (VHT160) 802.11ax (HEW160)	
Channel	Frequency (MHz)
50	5250
114	5570

(3) Table for Filed Antenna:

WLAN 2.4 GHz and WLAN 5 GHz						
Antenna	Manufacture	Part Number	Type	Connector	Frequency Range (MHz)	Gain (dBi)
Main	INPAQ Corporation	025.901U1.0001	PIFA	I-PEX	2400-2500	-1.26
					5150-5350	0.41
					5470-5725	0.28
					5725-5850	1.06
Aux	INPAQ Corporation	025.901U2.0001	PIFA	I-PEX	2400-2500	-1.46
					5150-5350	0.65
					5470-5725	-0.25
					5725-5850	0.15

Antenna	Manufacture	Part Number	Type	Connector	Frequency Range (MHz)	Gain (dBi)
Main	AWAN	025.901U3.0001	PIFA	I-PEX	2400-2500	0.93
					5150-5350	0.58
					5470-5725	1.68
					5725-5850	0.86
Aux	AWAN	025.901U4.0001	PIFA	I-PEX	2400-2500	1.52
					5150-5350	0.62
					5470-5725	0.93
					5725-5850	0.93

NOTE: Since the antenna gain of Antenna _ AWAN is the highest one among all, Antenna _ AWAN had used for testing.

WWAN						
Antenna	Manufacture	Parts Number	Type	Connector	Gain (dBi)	Note
Main	INPAQ Corporation	025.901TX.0001	PIFA	I-PEX	-5.74	WCDMA Band V LTE Band 5
					-5.67	LTE Band 26
					0.74	WCDMA Band II LTE Band 2
					-0.22	WCDMA Band IV LTE Band 4
					1.88	LTE Band 7
					-6.73	LTE Band 12
					-5.59	LTE Band 13
					-7.84	LTE Band 17
					2.14	LTE Band 30
					1.95	LTE Band 41
					-0.22	LTE Band 66
Aux	INPAQ Corporation	025.901TY.0001	PIFA	I-PEX	-	RX only

2.2 TEST MODES

The test system was pre-tested based on the consideration of all possible combinations of EUT operation mode as listed in below table.

The worst-cases of WWAN and WLAN are selected by the maximum conducted power.

Simultaneously transmission condition		
Condition	Technology	
1	WWAN (LTE Band 4)_Ch20175	WLAN (2.4 GHz)_IEEE802.11n (HT20)_2472MHz
2	WWAN (LTE Band 4)_Ch20175	WLAN (2.4 GHz)_IEEE802.11ax (HEW20)_2412MHz_26Tone
3	WWAN (LTE Band 4)_Ch20175	WLAN (5 GHz)_IEEE802.11n (HT40)_5670MHz
4	WWAN (LTE Band 4)_Ch20175	WLAN (5 GHz)_IEEE802.11ax (HEW40)_5510MHz_242Tone
5	WWAN (LTE Band 4)_Ch20175	Bluetooth (3 Mbps)_2480MHz

Following mode(s) as (were) found to be the worst case(s) and selected for the final test.


Test Mode	Description
1	Condition 1 @ WLAN (2.4 GHz)_IEEE802.11n (HT20)_2472MHz
2	Condition 1 @ WWAN (LTE Band 4)_Ch20175
3	Condition 2 @ WLAN (2.4 GHz)_IEEE802.11ax (HEW20)_2412MHz_26Tone
4	Condition 2 @ WWAN (LTE Band 4)_Ch20175
5	Condition 3 @ WLAN (5 GHz)_IEEE802.11n (HT40)_5670MHz
6	Condition 3 @ WWAN (LTE Band 4)_Ch20175
7	Condition 4 @ WLAN (5 GHz)_IEEE802.11ax (HEW40)_5510MHz_242Tone
8	Condition 4 @ WWAN (LTE Band 4)_Ch20175

NOTE:

- (1) The highest output powers were set for final test.
- (2) Due to the units and limits of WWAN and WLAN are different, the test mode 1, 3, 5 and 7 is using WLAN Limits for WLAN part as main emission and the test mode 2, 4, 6 and 8 is using WWAN Limits for WWAN part as main emission.

2.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Equipment letters and Cable numbers refer to item numbers described in the tables of clause 2.4.



2.4 SUPPORT UNITS

Item	Equipment	Brand	Model No.	Series No.	Remarks
A	ADP	Lenovo	ADLX45YLC3D	N/A	Supplied by test requester.
B	Screen	ASUS	MX27U	N/A	Furnished by test lab.
C	Mouse	ACER	MP-368	N/A	Furnished by test lab.
D	Earphone	Sony	MDR-E9LP	N/A	Furnished by test lab.
E	USB	Kingston	C7052-322.AOOL F	N/A	Furnished by test lab.

Item	Shielded	Ferrite Core	Length	Cable Type	Remarks
1	N/A	N/A	1.8m	HDMI Cable	Furnished by test lab.

3 RADIATED EMISSIONS TEST

3.1 LIMIT

For WLAN:

In case the emission fall within the restricted band specified on 15.205, then the 15.209 limit in the table below has to be followed.

LIMITS OF RADIATED EMISSIONS MEASUREMENT (9 kHz to 1000 MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS

Frequency (MHz)	EIRP Limit (dBm)	Equivalent Field Strength at 3m (dBµV/m)
5150-5250	-27	68.3
5250-5350	-27	68.3
5470-5725	-27	68.3
5725-5850	-27 (NOTE 2)	68.3
	10 (NOTE 2)	105.3
	15.6 (NOTE 2)	110.9
	27 (NOTE 2)	122.3

For WWAN:

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm.

NOTE:

- (1) The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$

- (2) According to FCC 16-24, All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
- (3) The test result calculated as following:

Measurement Value = Reading Level + Correct Factor
 Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use)
 Margin Level = Measurement Value - Limit Value

Calculation example:

Reading Level		Correct Factor		Measurement Value
19.11	+	2.11	=	21.22

Measurement Value		Limit Value		Margin Level
21.22	-	68.3	=	-47.08

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average

Spectrum Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz~110KHz for QP detector
Start ~ Stop Frequency	110KHz~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

3.2 TEST PROCEDURE


- a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8 m or 1.5 m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- i. For the actual test configuration, please refer to the related Item – EUT TEST PHOTO.

3.3 DEVIATION FROM TEST STANDARD


No deviation.


3.4 TEST SETUP

9 kHz to 30 MHz



30 MHz to 1 GHz





3.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

3.6 TEST RESULT

Please refer to the APPENDIX A.

4 LIST OF MEASURING EQUIPMENTS

Radiated Emissions						
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated Date	Calibrated Until
1	Preamplifier	EMCI	EMC02325B	980217	2021/4/8	2022/4/7
2	Preamplifier	EMCI	EMC012645B	980267	2021/4/8	2022/4/7
3	Preamplifier	EMCI	EMC001340	980555	2021/4/8	2022/4/7
4	Test Cable	EMCI	EMC-SM-SM-100 0	180809	2021/4/8	2022/4/7
5	Test Cable	EMCI	EMC104-SM-SM- 3000	151205	2021/4/8	2022/4/7
6	Test Cable	EMCI	EMC-SM-SM-700 0	180408	2021/4/8	2022/4/7
7	MXE EMI Receiver	Agilent	N9038A	MY554200087	2021/5/27	2022/5/26
8	Signal Analyzer	Agilent	N9010A	MY56480554	2020/8/25	2021/8/24
9	Loop Ant	Electro-Metrics	EMCI-LPA600	274	2021/6/1	2022/5/31
10	Horn Ant	SCHWARZBECK	BBHA 9120D	9120D-1342	2021/6/2	2022/6/1
11	Horn Ant	Schwarzbeck	BBHA 9170	BBHA 9170340	2020/7/9	2021/7/8
12	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	VULB 9168-352	2020/7/24	2021/7/23
13	5dB Attenuator	EMCI	EMCI-N-6-05	AT-N0625	2020/7/24	2021/7/23
14	Measurement Software	EZ	EZ EMC (Version NB-03A1-01)	N/A	N/A	N/A
15	Preamplifier	EMCI	EMC184045SE	980512	2021/5/28	2022/5/27
16	8960 Series 10 Wireless Com Test Set	Agilent	E5515C	GB47390193	2020/7/23	2021/7/22
17	Radio Communication Analyzer (LTE)	Anritsu	MT8820C	6201381608	2021/1/7	2022/1/6
18	Radio Communication Analyzer	Anritsu	MT8821C	6262044728	2020/12/15	2021/12/14

Remark: "N/A" denotes no model name, no serial no. or no calibration specified.
All calibration period of equipment list is one year.

5 EUT TEST PHOTO


Please refer to document Appendix No.: TP-2102T172A-FCCP-2 (APPENDIX-TEST PHOTOS).

6 EUT PHOTOS

Please refer to document Appendix No.: EP-2102T172A-2 (APPENDIX-EUT PHOTOS).

APPENDIX A RADIATED EMISSIONS

Test Mode	1	Test Date	2021/6/16
Test Frequency	WLAN (2.4 GHz)_ IEEE802.11n (HT20)_ 2472MHz	Polarization	Vertical
Temp	23°C	Hum.	57%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4944.000	54.47	-9.71	44.76	74.00	-29.24	peak	
2		4944.000	42.23	-9.71	32.52	54.00	-21.48	AVG	
3		5171.000	55.94	-9.46	46.48	74.00	-27.52	peak	
4	*	5171.000	54.81	-9.46	45.35	54.00	-8.65	AVG	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	1	Test Date	2021/6/16
Test Frequency	WLAN (2.4 GHz)_ IEEE802.11n (HT20)_ 2472MHz	Polarization	Horizontal
Temp	23°C	Hum.	57%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4944.000	53.37	-9.71	43.66	74.00	-30.34	peak	
2		4944.000	42.18	-9.71	32.47	54.00	-21.53	AVG	
3		5171.080	54.88	-9.46	45.42	74.00	-28.58	peak	
4	*	5171.080	53.67	-9.46	44.21	54.00	-9.79	AVG	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	2	Test Date	2021/6/16
Test Frequency	WWAN (LTE Band 4)_ Ch20175	Polarization	Vertical
Temp	23°C	Hum.	57%




No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Over dB	Detector	Comment
1		4944.000	-51.58	0.68	-50.90	-13.00	-37.90	peak	
2	*	5171.110	-39.61	1.79	-37.82	-13.00	-24.82	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	2	Test Date	2021/6/16
Test Frequency	WWAN (LTE Band 4)_ Ch20175	Polarization	Horizontal
Temp	23°C	Hum.	57%




No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Over dB	Detector	Comment
1		4944.000	-52.07	1.89	-50.18	-13.00	-37.18	peak	
2	*	5171.110	-41.40	2.38	-39.02	-13.00	-26.02	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	3	Test Date	2021/6/16
Test Frequency	WLAN (2.4 GHz)_ IEEE802.11ax (HEW20)_ 2412MHz_26Tone	Polarization	Vertical
Temp	23°C	Hum.	57%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4824.000	53.97	-9.86	44.11	74.00	-29.89	peak	
2		4824.000	41.53	-9.86	31.67	54.00	-22.33	AVG	
3		5171.200	55.97	-9.46	46.51	74.00	-27.49	peak	
4	*	5171.200	54.83	-9.46	45.37	54.00	-8.63	AVG	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	3	Test Date	2021/6/16
Test Frequency	WLAN (2.4 GHz)_ IEEE802.11ax (HEW20)_ 2412MHz_26Tone	Polarization	Horizontal
Temp	23°C	Hum.	57%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4824.000	53.24	-9.86	43.38	74.00	-30.62	peak	
2		4824.000	41.84	-9.86	31.98	54.00	-22.02	AVG	
3		5171.200	55.13	-9.46	45.67	74.00	-28.33	peak	
4	*	5171.200	54.33	-9.46	44.87	54.00	-9.13	AVG	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	4	Test Date	2021/6/16
Test Frequency	WWAN (LTE Band 4)_ Ch20175	Polarization	Vertical
Temp	23°C	Hum.	57%




No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Over dB	Detector	Comment
1		4824.000	-51.86	1.66	-50.20	-13.00	-37.20	peak	
2	*	5171.131	-41.11	1.79	-39.32	-13.00	-26.32	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	4	Test Date	2021/6/16
Test Frequency	WWAN (LTE Band 4)_ Ch20175	Polarization	Horizontal
Temp	23°C	Hum.	57%




No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Over dB	Detector	Comment
1		4824.000	-52.30	1.96	-50.34	-13.00	-37.34	peak	
2	*	5171.131	-42.45	2.38	-40.07	-13.00	-27.07	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	5	Test Date	2021/6/16
Test Frequency	WLAN (5 GHz)_ IEEE802.11n (HT40)_ 5670MHz	Polarization	Vertical
Temp	23°C	Hum.	57%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		5171.000	56.75	-9.46	47.29	74.00	-26.71	peak	
2		5171.000	55.53	-9.46	46.07	54.00	-7.93	AVG	
3		11340.00	53.57	5.34	58.91	74.00	-15.09	peak	
4	*	11340.00	41.77	5.34	47.11	54.00	-6.89	AVG	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	5	Test Date	2021/6/16
Test Frequency	WLAN (5 GHz)_ IEEE802.11n (HT40)_ 5670MHz	Polarization	Horizontal
Temp	23°C	Hum.	57%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		5171.100	55.98	-9.46	46.52	74.00	-27.48	peak	
2		5171.100	54.86	-9.46	45.40	54.00	-8.60	AVG	
3		11340.00	52.43	5.34	57.77	74.00	-16.23	peak	
4	*	11340.00	41.54	5.34	46.88	54.00	-7.12	AVG	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	6	Test Date	2021/6/16
Test Frequency	WWAN (LTE Band 4)_ Ch20175	Polarization	Vertical
Temp	23°C	Hum.	57%




No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Over dB	Detector	Comment
1	*	5171.100	-40.05	1.79	-38.26	-13.00	-25.26	peak	
2		11340.00	-52.25	13.21	-39.04	-13.00	-26.04	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	6	Test Date	2021/6/16
Test Frequency	WWAN (LTE Band 4)_ Ch20175	Polarization	Horizontal
Temp	23°C	Hum.	57%




No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Over dB	Detector	Comment
1		5171.100	-42.40	2.38	-40.02	-13.00	-27.02	peak	
2	*	11340.00	-52.13	14.27	-37.86	-13.00	-24.86	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	7	Test Date	2021/6/16
Test Frequency	WLAN (5 GHz)_ IEEE802.11ax (HEW40)_ 5510MHz_242Tone	Polarization	Vertical
Temp	23°C	Hum.	57%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		5171.100	55.57	-9.46	46.11	74.00	-27.89	peak	
2		5171.100	54.51	-9.46	45.05	54.00	-8.95	AVG	
3		11020.00	52.25	6.13	58.38	74.00	-15.62	peak	
4	*	11020.00	41.61	6.13	47.74	54.00	-6.26	AVG	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	7	Test Date	2021/6/16
Test Frequency	WLAN (5 GHz)_ IEEE802.11ax (HEW40)_ 5510MHz_242Tone	Polarization	Horizontal
Temp	23°C	Hum.	57%




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		5171.100	55.70	-9.46	46.24	74.00	-27.76	peak	
2		5171.100	54.49	-9.46	45.03	54.00	-8.97	AVG	
3		11020.00	51.79	6.13	57.92	74.00	-16.08	peak	
4	*	11020.00	41.74	6.13	47.87	54.00	-6.13	AVG	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	8	Test Date	2021/6/16
Test Frequency	WWAN (LTE Band 4)_ Ch20175	Polarization	Vertical
Temp	23°C	Hum.	57%




No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Over dB	Detector	Comment
1	*	5171.130	-39.21	1.79	-37.42	-13.00	-24.42	peak	
2		11020.00	-51.76	13.19	-38.57	-13.00	-25.57	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	8	Test Date	2021/6/16
Test Frequency	WWAN (LTE Band 4)_ Ch20175	Polarization	Horizontal
Temp	23°C	Hum.	57%



No.	Mk.	Freq. MHz	Reading Level dBm	Correct Factor dB	Measure- ment dBm	Limit dBm	Over dB	Detector	Comment
1		5171.130	-41.38	2.38	-39.00	-13.00	-26.00	peak	
2	*	11020.00	-52.84	14.44	-38.40	-13.00	-25.40	peak	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

End of Test Report