



# FCC RADIO TEST REPORT

**FCC ID** : PU5-TP00132B  
**Equipment** : Notebook Computer  
**Brand Name** : Lenovo  
**Model Name** : TP00132B  
**Applicant** : Wistron Corporation  
21F, No. 88, Sec. 1, Hsin Tai Wu Rd., Hsichih Dist,  
New Taipei City 221, Taiwan  
**Manufacturer** : Lenovo PC HK Limited.  
23/F, Lincoln House, Taikoo Place, 979 King's  
Road, Quarry Bay, Hong Kong, China  
**Standard** : FCC 47 CFR Part 2, Part 27(D)

Equipment: Fibocom FM350-GL tested inside of Lenovo Notebook Computer.

The product was received on Jan. 28, 2022 and testing was performed from Feb. 25, 2022 to Mar. 24, 2022. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The test results in this partial report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

**Sporton International Inc. Wensan Laboratory**



## Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
<b>1 General Description .....</b>	<b>5</b>
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	6
1.3 Modification of EUT .....	6
1.4 Testing Site.....	6
1.5 Applied Standards .....	7
<b>2 Test Configuration of Equipment Under Test .....</b>	<b>8</b>
2.1 Test Mode.....	8
2.2 Connection Diagram of Test System.....	8
2.3 Support Unit used in test configuration and system .....	9
2.4 Frequency List of Low/Middle/High Channels .....	9
<b>3 Conducted Test Items.....</b>	<b>10</b>
3.1 Measuring Instruments .....	10
3.2 Conducted Output Power Measurement .....	11
3.3 Effective Isotropic Radiated Power.....	12
<b>4 Radiated Test Items .....</b>	<b>13</b>
4.1 Measuring Instruments .....	13
4.2 Radiated Spurious Emission Measurement .....	15
<b>5 List of Measuring Equipment.....</b>	<b>16</b>
<b>6 Uncertainty of Evaluation .....</b>	<b>18</b>
<b>Appendix A. Test Results of Conducted Test</b>	
<b>Appendix B. Test Results of Radiated Test</b>	
<b>Appendix C. Test Setup Photographs</b>	



### History of this test report

Report No.	Version	Description	Issued Date
FG1N2210D	01	Initial issue of report	Mar. 31, 2022
FG1N2210D	02	Revise Product Feature of Equipment Under Test	Apr. 13, 2022



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046	Conducted Output Power	Reporting only	-
-	-	Peak-to-Average Ratio	-	See Note
3.3	§27.50 (a)(3)	Effective Isotropic Radiated Power	Pass	-
-	§2.1049	Occupied Bandwidth	-	See Note
-	§2.1051 §27.53 (a)(4)	Conducted Band Edge Measurement	-	See Note
-	§2.1051 §27.53 (a)(4)	Conducted Spurious Emission	-	See Note
-	§2.1055 §27.54	Frequency Stability Temperature & Voltage	-	See Note
4.2	§2.1053 §27.53 (a)(4)	Radiated Spurious Emission	Pass	Under limit 16.44 dB at 6931.000 MHz

Note:

- The certified module (model: FM350-GL) which supports normal mode and TX switching mode being integrated into a notebook computer. Spot check on both modes were performed and no degradation occur. Thus the module test results were leveraged in this report and additionally reporting the spot check results in this report.
- In normal mode, Conducted power was verified to be consistent with the original modular approval, so the output power level in the original modular grant is referenced in this report for determining EIRP of this host product, and verified the TX switching mode of Radiated Spurious Emission and Conducted power.

Declaration of Conformity:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers. It's means measurement values may risk exceeding the limit of regulation standards, if measurement uncertainty is include in test results.
- The measurement uncertainty please refer to this report "Uncertainty of Evaluation".

Comments and Explanations:

The product specifications of the EUT presented in the report are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Sheng Kuo  
Report Producer: Vivian Hsu



# 1 General Description

## 1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Notebook Computer
Brand Name	Lenovo
Model Name	TP00132B
FCC ID	PU5-TP00132B
Sample 1	EUT with AVX/ Ethertronics Antenna
Sample 2	EUT with LUXSHARE-ICT Antenna
EUT supports Radios application	WCDMA/HSPA/LTE/5G NR/GNSS
EUT Stage	Production Unit

**Remark:**

1. The above EUT's information was declared by manufacturer.
2. Equipment: Fibocom FM350-GL tested inside of Lenovo Notebook Computer.

WWAN Antenna Information				
Main Antenna	Manufacturer	AVX/ Ethertronics	Peak gain (dBi)	LTE Band 30 : 1.91
	Part number	SA31F29287AA	Type	PIFA
	Manufacturer	LUXSHARE-ICT	Peak gain (dBi)	LTE Band 30 : -1.1
	Part number	SA31F29290AA	Type	PIFA
MIMO 2 Antenna	Manufacturer	AVX/ Ethertronics	Peak gain (dBi)	LTE Band 30: 1.73
	Part number	SA31F29288AA	Type	PIFA
	Manufacturer	LUXSHARE-ICT	Peak gain (dBi)	LTE Band 30: 1.70
	Part number	SA31F29291AA	Type	PIFA

**Remark:** The above EUT's information is declared by manufacturer. Please refer to Comments and Explanations in report summary.

Normal mode		TX switching mode	
	TX/RX		TX/RX
Ant_0(Main)	WCDMA : 2/4/5 LTE : 2/4/5/7/12/13/14/17/25/26/30/38/66/71 NR : 2/5/7/25/30/38/66/71	Ant_0(Main)	WCDMA : 5 LTE : 5/12/13/14/17/26/41/48/71 NR : 5/41/71/77/78
Ant_2(MIMO2)	LTE : 41/48 NR : 41/77/78	Ant_2(MIMO2)	WCDMA : 2/4 LTE : 2/4/7/25/30/38/66 NR : 2/7/25/30/38/66



## 1.2 Product Specification of Equipment Under Test

Product Specification is subject to this standard	
Tx Frequency	2307.5 MHz ~ 2312.5 MHz
Rx Frequency	2352.5 MHz ~ 2357.5 MHz
Bandwidth	5MHz / 10MHz
Maximum Output Power to Antenna	22.23 dBm
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM

## 1.3 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.4 Testing Site

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333
Test Site No.	<b>Sporton Site No.</b>
	TH03-HY (TAF Code: 1190)
Test Engineer	Nina Cheng
Temperature	22~25°C
Relative Humidity	52~54%
Remark	The Conducted test item subcontracted to Sporton International Inc. EMC & Wireless Communications Laboratory.

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010
Test Site No.	<b>Sporton Site No.</b>
	03CH12-HY
Test Engineer	Jack Cheng, Lance Chiang and Chuan Chu
Temperature	21.6~26.2
Relative Humidity	56~68

**Note:** The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW3786



## 1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ ANSI C63.26-2015
- ♦ FCC 47 CFR Part 2, Part 27(D)
- ♦ ANSI / TIA-603-E
- ♦ FCC KDB 971168 Power Meas License Digital Systems D01 v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.


## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Test Items	Band	Bandwidth (MHz)						Modulation				RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H
Max. Output Power	30	-	-	v	v	-	-	v	v	v	v	v	v	v	v	v	v
E.I.R.P	30	-	-	v	v	-	-	v	v	v	v	Max. Power					
Radiated Spurious Emission	30	-	-	v	v	-	-	v				v			v	v	v
Remark	<ol style="list-style-type: none"> <li>The mark "v" means that this configuration is chosen for testing</li> <li>The mark "-" means that this bandwidth is not supported.</li> <li>The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.</li> <li>For radiated measurement, pre-scanned in two samples, sample 1 and sample 2. The worst cases in sample 1 were recorded in this report.</li> <li>For modulation of 256QAM, the maximum power of 256QAM is lower than other modulation (QPSK/16QAM/64QAM), therefore, for Normal Mode, according to engineering evaluation, we choose higher power (QPSK/16QAM/64QAM) to perform all tests and show in the report.</li> <li>All the radiated test cases were performed with Adapter (ADL170SDC3A) and Sample 1.</li> </ol>																

### 2.2 Connection Diagram of Test System







### 2.3 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m
2.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A

### 2.4 Frequency List of Low/Middle/High Channels

LTE Band 30 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	-	27710	-
	Frequency	-	2310	-
5	Channel	27685	27710	27735
	Frequency	2307.5	2310	2312.5


### 3 Conducted Test Items

#### 3.1 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.1 Test Setup

##### 3.1.2 Conducted Output Power



##### 3.1.3 Test Result of Conducted Test

Please refer to Appendix A.



## **3.2 Conducted Output Power Measurement**

### **3.2.1 Description of the Conducted Output Power Measurement**

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

### **3.2.2 Test Procedures**

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.



### 3.3 Effective Isotropic Radiated Power

#### 3.3.1 Description of EIRP Power

For mobile and portable stations transmitting in the 2305-2315 MHz band or the 2350-2360 MHz band, the average EIRP must not exceed 50 milliwatts within any 1 megahertz of authorized bandwidth, *except that* for mobile and portable stations compliant with 3GPP LTE standards or another advanced mobile broadband protocol that avoids concentrating energy at the edge of the operating band the average EIRP must not exceed 250 milliwatts within any 5 megahertz of authorized bandwidth but may exceed 50 milliwatts within any 1 megahertz of authorized bandwidth. For mobile and portable stations using time division duplexing (TDD) technology, the duty cycle must not exceed 38 percent in the 2305-2315 MHz and 2350-2360 MHz bands. Mobile and portable stations using FDD technology are restricted to transmitting in the 2305-2315 MHz band. Power averaging shall not include intervals in which the transmitter is off.

**Remark:** EIRP use worst case measure the total power to cover per 5MHz Power.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$ , where

$P_T$  = transmitter output power in dBm

$G_T$  = gain of the transmitting antenna in dBi

$L_C$  = signal attenuation in the connecting cable between the transmitter and antenna in dB

#### 3.3.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.2.4.5

1. Determine the EIRP by adding the effective antenna gain to the adjusted power level

## 4 Radiated Test Items

### 4.1 Measuring Instruments


See list of measuring instruments of this test report.

#### 4.1.1 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



#### 4.1.2 Test Result of Radiated Test

Please refer to Appendix B.

**Note:**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.



## 4.2 Radiated Spurious Emission Measurement

### 4.2.1 Description of Radiated Spurious Emission Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA-603-E  
The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $70 + 10 \log (P)$  dB.  
The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 4.2.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI / TIA-603-E Section 2.2.12.

1. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
5. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.  
$$\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$$
$$\text{ERP (dBm)} = \text{EIRP} - 2.15$$
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.  
The limit line is derived from  $70 + 10\log(P)$ dB below the transmitter power P(Watts)  
$$= P(\text{W}) - [70 + 10\log(P)] (\text{dB})$$
$$= [30 + 10\log(P)] (\text{dBm}) - [70 + 10\log(P)] (\text{dB})$$
$$= -40\text{dBm}.$$



## 5 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Sep. 07, 2021	Mar. 05, 2022~ Mar. 23, 2022	Sep. 06, 2022	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N -06	37059 & 01	30MHz~1GHz	Oct. 09, 2021	Mar. 05, 2022~ Mar. 23, 2022	Oct. 08, 2022	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D & N-6-06	35414 & AT-N0602	30MHz~1GHz	Oct. 09, 2021	Mar. 05, 2022~ Mar. 23, 2022	Oct. 08, 2022	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1328	1GHz~18GHz	Dec. 03, 2021	Mar. 05, 2022~ Mar. 23, 2022	Dec. 02, 2022	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1212	1GHz~18GHz	May 18, 2021	Mar. 05, 2022~ Mar. 23, 2022	May 17, 2022	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA917025 1	18GHz~40GHz	Nov. 30, 2021	Mar. 05, 2022~ Mar. 23, 2022	Nov. 29, 2022	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA917057 6	18GHz~40GHz	May 21, 2021	Mar. 05, 2022~ Mar. 23, 2022	May 20, 2022	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 24, 2021	Mar. 05, 2022~ Mar. 22, 2022	Mar. 23, 2022	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 23, 2022	Mar. 23, 2022	Mar. 22, 2023	Radiation (03CH12-HY)
Preamplifier	Aglient	8449B	3008A02375	1GHz~26.5GHz	May 25, 2021	Mar. 05, 2022~ Mar. 23, 2022	May 24, 2022	Radiation (03CH12-HY)
Preamplifier	E-INSTRUME NT TECH LTD.	ERA-100M-18 G-56-01-A70	EC1900270	1GHz-18GHz	Dec. 27, 2021	Mar. 05, 2022~ Mar. 23, 2022	Dec. 26, 2022	Radiation (03CH12-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz~40GHz	Dec. 24, 2021	Mar. 05, 2022~ Mar. 23, 2022	Dec. 23, 2022	Radiation (03CH12-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz~44GHz	Oct. 15, 2021	Mar. 05, 2022~ Mar. 23, 2022	Oct. 14, 2022	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0058/126E	30MHz~18GHz	Dec. 10, 2021	Mar. 05, 2022~ Mar. 23, 2022	Dec. 09, 2022	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30MHz~40GHz	Feb. 21, 2022	Mar. 05, 2022~ Mar. 23, 2022	Feb. 20, 2023	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30MHz~40GHz	Feb. 21, 2022	Mar. 05, 2022~ Mar. 07, 2022	Feb. 20, 2023	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803953/2	30MHz~40GHz	Mar. 08, 2022	Mar. 08, 2022~ Mar. 23, 2022	Mar. 07, 2023	Radiation (03CH12-HY)
Filter	Wainwright	WLKS1200-12 SS	SN2	1.2GHz Low Pass Filter	Mar. 17, 2021	Mar. 05, 2022~ Mar. 15, 2022	Mar. 16, 2022	Radiation (03CH12-HY)
Filter	Wainwright	WLKS1200-12 SS	SN2	1.2GHz Low Pass Filter	Mar. 16, 2022	Mar. 16, 2022~ Mar. 23, 2022	Mar. 15, 2023	Radiation (03CH12-HY)
Filter	Wainwright	WHKX12-1080 -1200-15000-6 0SS	SN1	1.2GHz High Pass Filter	Mar. 17, 2021	Mar. 05, 2022~ Mar. 15, 2022	Mar. 16, 2022	Radiation (03CH12-HY)
Filter	Wainwright	WHKX12-1080 -1200-15000-6 0SS	SN1	1.2GHz High Pass Filter	Mar. 16, 2022	Mar. 16, 2022~ Mar. 23, 2022	Mar. 15, 2023	Radiation (03CH12-HY)





Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Filter	Wainwright	WHKX12-2700 -3000-18000-6 0ST	SN2	3GHz High Pass Filter	Jul. 12, 2021	Mar. 05, 2022~ Mar. 23, 2022	Jul. 11, 2022	Radiation (03CH12-HY)
Filter	Wainwright	WHKX8-5872. 5-6750-18000- 40ST	SN2	6.75GHz High Pass Filter	Mar. 17, 2021	Mar. 05, 2022~ Mar. 15, 2022	Mar. 16, 2022	Radiation (03CH12-HY)
Filter	Wainwright	WHKX8-5872. 5-6750-18000- 40ST	SN2	6.75GHz High Pass Filter	Mar. 16, 2022	Mar. 16, 2022~ Mar. 23, 2022	Mar. 15, 2023	Radiation (03CH12-HY)
Hygrometer	TECPEL	DTM-303B	TP140349	N/A	Sep. 30, 2021	Mar. 05, 2022~ Mar. 23, 2022	Sep. 29, 2022	Radiation (03CH12-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Mar. 05, 2022~ Mar. 23, 2022	N/A	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Mar. 05, 2022~ Mar. 23, 2022	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Mar. 05, 2022~ Mar. 23, 2022	N/A	Radiation (03CH12-HY)
Software	Audix	E3 6.2009-8-24	RK-000989	N/A	N/A	Mar. 05, 2022~ Mar. 23, 2022	N/A	Radiation (03CH12-HY)
Radio Communication Analyzer	Anritsu	MT8821C	6201664755	2/3/4G/LTE FDD/TDD with44)/LTE-3C C DLCA/2CC ULCA, CatM1/NB1/NB2	Jul. 21, 2021	Feb. 25, 2022~ Mar. 24, 2022	Jul. 20, 2022	Conducted (TH03-HY)



## 6 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	3.10 dB
---	---------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	3.39 dB
---	---------

### Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.34 dB
---	---------



## Appendix A. Test Results of Conducted Test

### Conducted Output Power (Average power & EIRP)

<Main Antenna>

LTE Band 30 Maximum Average Power [dBm] (GT - LC = 1.91 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
10	1	0	QPSK		21.60		23.79	0.2393
10	1	25			21.88			
10	1	49			21.72			
10	25	0			20.56			
10	25	12			20.55			
10	25	25			20.50			
10	50	0			20.52			
10	1	0	16-QAM	-	21.10	-	23.01	0.2000
10	1	25			20.66			
10	1	49			20.80			
10	25	0			19.67			
10	25	12			19.73			
10	25	25			19.55			
10	50	0			19.68			
10	1	0	64-QAM		19.64		21.99	0.1581
10	1	25			19.58			
10	1	49			20.08			
10	25	0			18.59			
10	25	12			18.71			
10	25	25			18.52			
10	50	0			18.52			
Limit	EIRP < 250mW/5MHz			Result			Pass	



LTE Band 30 Maximum Average Power [dBm] (GT - LC = 1.91 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
5	1	0	QPSK	21.66	21.83	21.82	23.78	0.2388
5	1	12		21.87	21.78	21.82		
5	1	24		21.76	21.76	21.80		
5	12	0		20.60	20.84	20.86		
5	12	7		20.72	20.72	20.81		
5	12	13		20.70	20.62	20.77		
5	25	0		20.73	20.70	20.72		
5	1	0	16-QAM	21.17	21.15	21.22	23.13	0.2056
5	1	12		20.87	21.07	20.98		
5	1	24		20.65	21.15	20.74		
5	12	0		19.68	19.77	19.84		
5	12	7		19.66	19.78	19.81		
5	12	13		19.70	19.60	19.69		
5	25	0		19.74	19.81	19.82		
5	1	0	64-QAM	20.00	20.05	20.08	22.07	0.1611
5	1	12		19.78	19.81	19.82		
5	1	24		20.01	20.16	19.91		
5	12	0		18.66	18.73	18.98		
5	12	7		18.68	18.73	18.74		
5	12	13		18.64	18.56	18.76		
5	25	0		18.71	18.69	18.80		
Limit	EIRP < 250mW/5MHz			Result			Pass	



<MIMO 2 Antenna>

LTE Band 30 Maximum Average Power [dBm] (GT - LC = 1.73 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
10	1	0	QPSK		22.23		23.96	0.2489
10	1	25			22.22			
10	1	49			22.19			
10	25	0			21.24			
10	25	12			21.21			
10	25	25			21.08			
10	50	0			21.22			
10	1	0	16-QAM		21.53		23.26	0.2118
10	1	25			21.51			
10	1	49			21.44			
10	25	0			20.16			
10	25	12			20.22			
10	25	25			20.02			
10	50	0			20.21			
10	1	0	64-QAM		20.46		22.19	0.1656
10	1	25			20.32			
10	1	49			20.32			
10	25	0			19.18			
10	25	12			19.19			
10	25	25			19.08			
10	50	0			19.20			
10	1	0	256-QAM		17.12		19.10	0.0813
10	1	25			17.37			
10	1	49			17.29			
10	25	0			17.09			
10	25	12			17.16			
10	25	25			17.23			
10	50	0			17.19			
Limit	EIRP < 250mW/5MHz			Result			Pass	



LTE Band 30 Maximum Average Power [dBm] (GT - LC = 1.73 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
5	1	0	QPSK	22.13	22.10	22.18	23.94	0.2477
5	1	12		22.08	22.21	22.07		
5	1	24		22.17	22.05	22.14		
5	12	0		21.17	21.14	21.13		
5	12	7		21.09	21.04	21.11		
5	12	13		21.06	20.96	20.96		
5	25	0		21.19	21.19	21.21		
5	1	0	16-QAM	21.47	21.37	21.51	23.24	0.2109
5	1	12		21.39	21.39	21.31		
5	1	24		21.33	21.35	21.31		
5	12	0		20.07	20.01	20.19		
5	12	7		20.06	20.19	20.03		
5	12	13		19.86	19.95	20.01		
5	25	0		20.13	20.13	20.18		
5	1	0	64-QAM	20.27	20.22	20.44	22.17	0.1648
5	1	12		20.14	20.31	20.33		
5	1	24		20.17	20.17	20.22		
5	12	0		19.11	19.18	19.16		
5	12	7		19.10	18.98	19.03		
5	12	13		18.98	18.92	19.02		
5	25	0		19.18	19.20	19.14		
5	1	0	256-QAM	17.16	17.01	16.93	19.11	0.0815
5	1	12		17.28	17.28	17.38		
5	1	24		17.16	17.20	17.24		
5	12	0		16.96	17.08	16.89		
5	12	7		17.02	17.03	17.13		
5	12	13		17.03	17.04	17.23		
5	25	0		17.01	17.01	17.09		
Limit	EIRP < 250mW/5MHz			Result			Pass	



# Appendix B. Test Results of Radiated Test

<Main Antenna>

## LTE Band 30

LTE Band 30 / 5MHz / QPSK									
Channel	Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	4611	-61.68	-40	-21.68	-48.63	-72.90	1.45	12.68	H
	6916	-60.05	-40	-20.05	-54.25	-70.34	1.73	12.02	H
	9221	-58.69	-40	-18.69	-53.97	-68.31	2.16	11.78	H
									H
									H
									H
	4611	-59.45	-40	-19.45	-45.65	-70.67	1.45	12.68	V
	6916	-58.14	-40	-18.14	-51.89	-68.43	1.73	12.02	V
	9221	-57.93	-40	-17.93	-54.21	-67.55	2.16	11.78	V
									V
									V
									V
Middle	4614	-63.04	-40	-23.04	-50.02	-74.26	1.46	12.68	H
	6924	-60.19	-40	-20.19	-54.42	-70.47	1.73	12.01	H
	9234	-58.75	-40	-18.75	-54	-68.35	2.16	11.77	H
									H
									H
									H
	4614	-62.39	-40	-22.39	-48.59	-73.61	1.46	12.68	V
	6924	-60.10	-40	-20.10	-53.88	-70.38	1.73	12.01	V
	9234	-57.70	-40	-17.70	-53.96	-67.30	2.16	11.77	V
									V
									V
									V



Highest	4621	-61.75	-40	-21.75	-48.75	-72.97	1.46	12.68	H
	6931	-57.85	-40	-17.85	-52.12	-68.12	1.73	12.00	H
	9241	-58.64	-40	-18.64	-53.9	-68.24	2.16	11.76	H
									H
									H
									H
									H
	4621	-60.63	-40	-20.63	-46.86	-71.85	1.46	12.68	V
	6931	-56.44	-40	-16.44	-50.25	-66.71	1.73	12.00	V
	9241	-57.14	-40	-17.14	-53.43	-66.74	2.16	11.76	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.





LTE Band 30 / 10MHz / QPSK									
Channel	Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	4611	-62.76	-40	-22.76	-49.71	-73.98	1.45	12.68	H
	6917	-59.95	-40	-19.95	-54.15	-70.23	1.73	12.02	H
	9222	-58.36	-40	-18.36	-53.64	-67.98	2.16	11.78	H
									H
									H
									H
									H
	4611	-63.72	-40	-23.72	-49.88	-74.94	1.45	12.68	V
	6917	-60.06	-40	-20.06	-53.81	-70.34	1.73	12.02	V
	9222	-57.55	-40	-17.55	-53.83	-67.17	2.16	11.78	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



<MIMO 2 Antenna>

**LTE Band 30**

LTE Band 30 / 10MHz / QPSK									
Channel	Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	4611	-62.84	-40	-22.84	-49.79	-74.06	1.45	12.68	H
	6917	-59.80	-40	-19.80	-54.01	-70.09	1.73	12.02	H
	9222	-58.84	-40	-18.84	-54.14	-68.47	2.16	11.78	H
									H
									H
									H
									H
	4611	-62.43	-40	-22.43	-48.59	-73.65	1.45	12.68	V
	6917	-59.95	-40	-19.95	-53.71	-70.24	1.73	12.02	V
	9222	-58.21	-40	-18.21	-54.51	-67.84	2.16	11.78	V
									V
									V
									V
									V

**Remark:** Spurious emissions within 30-1000MHz were found more than 20dB below limit line.