

# 1 Human Exposure Assessment

## 1.1 Maximum Permissible Exposure

### 1.1.1 Limit of Maximum Permissible Exposure

| Limits for Occupational / Controlled Exposure                       |                                   |                                   |                                          |                                                                  |
|---------------------------------------------------------------------|-----------------------------------|-----------------------------------|------------------------------------------|------------------------------------------------------------------|
| Frequency Range (MHz)                                               | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) |
| 0.3-3.0                                                             | 614                               | 1.63                              | (100)*                                   | 6                                                                |
| 3.0-30                                                              | 1842 / f                          | 4.89 / f                          | (900 / f)*                               | 6                                                                |
| 30-300                                                              | 61.4                              | 0.163                             | 1.0                                      | 6                                                                |
| 300-1500                                                            | -                                 | -                                 | F/300                                    | 6                                                                |
| 1500-100,000                                                        | -                                 | -                                 | 5                                        | 6                                                                |
| Limits for General Population / Uncontrolled Exposure               |                                   |                                   |                                          |                                                                  |
| Frequency Range (MHz)                                               | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) |
| 0.3-1.34                                                            | 614                               | 1.63                              | (100)*                                   | 30                                                               |
| 1.34-30                                                             | 824/f                             | 2.19/f                            | (180/f)*                                 | 30                                                               |
| 30-300                                                              | 27.5                              | 0.073                             | 0.2                                      | 30                                                               |
| 300-1500                                                            | -                                 | -                                 | F/1500                                   | 30                                                               |
| 1500-100,000                                                        | -                                 | -                                 | 1.0                                      | 30                                                               |
| Note 1: f = frequency in MHz ; *Plane-wave equivalent power density |                                   |                                   |                                          |                                                                  |
| Note 2: For the applicable limit, see FCC 1.1310                    |                                   |                                   |                                          |                                                                  |

| RF Field Strength Limits for Controlled Use Devices (Controlled Environment)               |                               |                                                 |                                   |                                 |
|--------------------------------------------------------------------------------------------|-------------------------------|-------------------------------------------------|-----------------------------------|---------------------------------|
| Frequency Range (MHz)                                                                      | Electric Field (V/m rms)      | Magnetic Field (A/m rms)                        | Power Density (W/m <sup>2</sup> ) | Averaging Time (minutes)        |
| 0.003-1                                                                                    | 600                           | 4.9                                             | -                                 | 6                               |
| 1-10                                                                                       | 600/ <i>f</i>                 | 4.9/ <i>f</i>                                   | -                                 | 6                               |
| 10-30                                                                                      | 60                            | 4.9/ <i>f</i>                                   | -                                 | 6                               |
| 30-300                                                                                     | 60                            | 0.163                                           | 10*                               | 6                               |
| 300-1500                                                                                   | 3.54 <i>f</i> <sup>0.5</sup>  | 0.0094 <i>f</i> <sup>0.5</sup>                  | <i>f</i> /30                      | 6                               |
| 1500-15000                                                                                 | 137                           | 0.364                                           | 50                                | 6                               |
| 15000-150000                                                                               | 137                           | 0.364                                           | 50                                | 616000/ <i>f</i> <sup>1.2</sup> |
| 150000-300000                                                                              | 0.354 <i>f</i> <sup>0.5</sup> | 9.4 × 10 <sup>-4</sup> <i>f</i> <sup>0.5</sup>  | 3.33 × 10 <sup>-4</sup> <i>f</i>  | 616000/ <i>f</i> <sup>1.2</sup> |
| RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment) |                               |                                                 |                                   |                                 |
| Frequency Range (MHz)                                                                      | Electric Field (V/m rms)      | Magnetic Field (A/m rms)                        | Power Density (W/m <sup>2</sup> ) | Averaging Time (minutes)        |
| 0.003-1                                                                                    | 280                           | 2.19                                            | -                                 | 6                               |
| 1-10                                                                                       | 280/ <i>f</i>                 | 2.19/ <i>f</i>                                  | -                                 | 6                               |
| 10-30                                                                                      | 28                            | 2.19/ <i>f</i>                                  | -                                 | 6                               |
| 30-300                                                                                     | 28                            | 0.073                                           | 2*                                | 6                               |
| 300-1500                                                                                   | 1.585 <i>f</i> <sup>0.5</sup> | 0.0042 <i>f</i> <sup>0.5</sup>                  | <i>f</i> /150                     | 6                               |
| 1500-15000                                                                                 | 61.4                          | 0.163                                           | 10                                | 6                               |
| 15000-150000                                                                               | 61.4                          | 0.163                                           | 10                                | 616000/ <i>f</i> <sup>1.2</sup> |
| 150000-300000                                                                              | 0.158 <i>f</i> <sup>0.5</sup> | 4.21 × 10 <sup>-4</sup> <i>f</i> <sup>0.5</sup> | 6.67 × 10 <sup>-5</sup> <i>f</i>  | 616000/ <i>f</i> <sup>1.2</sup> |
| Note 1: <i>f</i> is frequency in MHz.                                                      |                               |                                                 |                                   |                                 |
| Note 2: For the applicable limit, see IC RSS-102                                           |                               |                                                 |                                   |                                 |

### 1.1.2 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d}$$

**E** = Electric field (V/m)

**G** = EUT Antenna numeric gain (numeric)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**P** = RF output power (W)

**d** = Separation distance between radiator and human body (m)

**1.1.3 Result of Maximum Permissible Exposure (5.8G)**

| Transmitter Chains & Receiver Chains Information                                 |                                              |                                             |                                                   |                       |
|----------------------------------------------------------------------------------|----------------------------------------------|---------------------------------------------|---------------------------------------------------|-----------------------|
| Modulation Mode                                                                  | Number of Transmit Chains (N <sub>TX</sub> ) | Number of Receive Chains (N <sub>RX</sub> ) | Correlation Signals with Multiple N <sub>TX</sub> | RF Output Power (dBm) |
| QPSK                                                                             | 1                                            | 1                                           | Uncorrelated                                      | 10.55                 |
| Note 1: RF output power specifies that Maximum Conducted (Average) Output Power. |                                              |                                             |                                                   |                       |

| Worst Maximum RF Output Power Result                     |                 |                                            |            |            |                              |
|----------------------------------------------------------|-----------------|--------------------------------------------|------------|------------|------------------------------|
| Exposure Environment                                     |                 | General Population / Uncontrolled Exposure |            |            |                              |
| Separation Distance (cm)                                 |                 | 20                                         |            |            |                              |
| Power Level                                              | 1               | RF Output Power (dBm)                      |            |            |                              |
| Modulation Mode                                          | N <sub>TX</sub> | Max. Cond. Power                           | Gain (dBi) | EIRP Power | PD (S) (mW/cm <sup>2</sup> ) |
| QPSK                                                     | 1               | 10.55                                      | 3.20       | 13.75      | 0.00472                      |
| Maximum Permissible Exposure Limit (mW/cm <sup>2</sup> ) |                 |                                            |            |            | 1                            |
| Note 1: N <sub>TX</sub> = Number of Transmit Chains      |                 |                                            |            |            |                              |

**1.1.4 Result of Maximum Permissible Exposure (5.2G)**

| Transmitter Chains & Receiver Chains Information                                 |                                              |                                             |                                                   |                       |
|----------------------------------------------------------------------------------|----------------------------------------------|---------------------------------------------|---------------------------------------------------|-----------------------|
| Modulation Mode                                                                  | Number of Transmit Chains (N <sub>TX</sub> ) | Number of Receive Chains (N <sub>RX</sub> ) | Correlation Signals with Multiple N <sub>TX</sub> | RF Output Power (dBm) |
| QPSK                                                                             | 1                                            | 1                                           | Uncorrelated                                      | 10.77                 |
| Note 1: RF output power specifies that Maximum Conducted (Average) Output Power. |                                              |                                             |                                                   |                       |

| Worst Maximum RF Output Power Result                     |                 |                                            |            |            |                              |
|----------------------------------------------------------|-----------------|--------------------------------------------|------------|------------|------------------------------|
| Exposure Environment                                     |                 | General Population / Uncontrolled Exposure |            |            |                              |
| Separation Distance (cm)                                 |                 | 20                                         |            |            |                              |
| Power Level                                              | 1               | RF Output Power (dBm)                      |            |            |                              |
| Modulation Mode                                          | N <sub>TX</sub> | Max. Cond. Power                           | Gain (dBi) | EIRP Power | PD (S) (mW/cm <sup>2</sup> ) |
| QPSK                                                     | 1               | 10.77                                      | 3.00       | 13.77      | 0.00474                      |
| Maximum Permissible Exposure Limit (mW/cm <sup>2</sup> ) |                 |                                            |            |            | 1                            |
| Note 1: N <sub>TX</sub> = Number of Transmit Chains      |                 |                                            |            |            |                              |