

# EMITECH ATLANTIQUE

15, rue de la Cliae  
Z.I. Angers-Beaucouzé  
49070 BEAUCOUZÉ  
Tél. 02 41 73 26 27  
Fax 02 41 73 26 40  
e-mail : atlantique@emitech.fr

R.C.S. ANGERS 95 B 543  
SIRET 344 545 645 00055

## RA-06-24015-1/A Ed. 0

### FCC CERTIFICATION RADIO Measurement Technical Report

**standard to apply:**  
**FCC Part 15**

**Equipment under test:**  
**HZ WALL MOUNTED TRANSMITTER /ND US**

**FCC ID:**  
**PUDTRANSHZ002**

**Company:**  
**SIMU U.S. Inc.**

**DISTRIBUTION:** Mr SANDERS

**Company:** SIMU U.S. Inc.

**Number of pages: 20 including 5 annexes**

Ed.	Date	Modified pages	Written by Name	Visa	Technical Verification Name	Quality Approval Name
0	10-Mar-06	Creation	L. BERTHAUD	LB	P. BONNENFANT	

Duplication of this document is only permitted for an integral photographic facsimile. It includes the number of pages referenced here above.  
This document is the result of testing a specimen or a sample of the product submitted. It does not imply an assessment of the conformity of the whole manufactured products of the tested sample.

SIEGE SOCIAL : EMITECH S.A.

3, rue des Coudriers – Z.A. de l'Observatoire – 78180 MONTIGNY-LE-BRETONNEUX – Tél. 01 30 57 55 55 – Fax 01 30 43 74 48  
S.A. AU CAPITAL DE 480 000 € - R.C. VERSAILLES B 344 545 645 – SIRET 344 545 645 000 22 – CODE APE 742 C

**PRODUCT:** HZ WALL MOUNTED TRANSMITTER /ND US

**Reference / model:** 2005840

**Serial number:** not communicated

**MANUFACTURER:** not communicated

**COMPANY SUBMITTING THE PRODUCT:**

**Company:** SIMU U.S. Inc.

**Address:** 6100 Broken Sound Parkway N.W.  
Suite 14  
Boca Raton, FL 33487  
UNITED STATES

**Responsible:** Mr SANDERS

**DATE(S) OF TEST:** 30 and 31 January 2006

**TESTING LOCATION:** EMITECH ATLANTIQUE laboratory at ANGERS (49)  
FRANCE  
EMITECH ATLANTIQUE open area test site in LA POUEZE  
(49) FRANCE  
Registration Number by FCC: 101696/FRN: 0006 6490 08

**TESTED BY:** L. BERTHAUD

## CONTENTS

TITLE	PAGE
<b>1. INTRODUCTION.....</b>	<b>4</b>
<b>2. PRODUCT DESCRIPTION .....</b>	<b>4</b>
<b>3. NORMATIVE REFERENCE.....</b>	<b>4</b>
<b>4. TEST METHODOLOGY .....</b>	<b>5</b>
<b>5. TEST UNIT CONFIGURATION .....</b>	<b>5</b>
<b>6. TESTS AND CONCLUSIONS .....</b>	<b>6</b>
<b>7. RADIATED EMISSION LIMITS; GENERAL REQUIREMENTS (TRANSMITTER) .....</b>	<b>7</b>
<b>ANNEX 1: PHOTOS OF THE EQUIPMENT UNDER TEST .....</b>	<b>9</b>
<b>ANNEX 2: OPEN AREA TEST SITE, TEST SET UP .....</b>	<b>12</b>
<b>ANNEX 3: EMISSION BANDWIDTH.....</b>	<b>14</b>
<b>ANNEX 4: DUTY CYCLE DETERMINATION.....</b>	<b>15</b>
<b>ANNEX 5: SHUTT-OFF TIMING.....</b>	<b>20</b>

## 1. INTRODUCTION

This document presents the result of RADIO test carried out on the following equipment:  
HZ WALL MOUNTED TRANSMITTER /ND US in accordance with normative reference.

## 2. PRODUCT DESCRIPTION

ITU Emission code: 500KD1D

Class: B (residential environment)

Intermittent control signals with no continuous transmission, the transmitter operates only when a key is depressed.

Utilization: remote control

Antenna type: internal antenna

Operating frequency: 433.42 MHz

No of channels: 1

Channel spacing: not concerned

Frequency generation:  SAW Resonator  Crystal  Synthesiser

Modulation:  Amplitude (pulsed modulated device)  Digital  Frequency  Phase

Power source: Lithium battery CR2430 (1 × 3 V)

Power level, frequency range and channels characteristics are not user adjustable.

The details pictures of the product and the circuit boards are joined with this file.

## 3. NORMATIVE REFERENCE

The standards and testing methods related throughout this report are those listed below. They are applied on the whole test report even though the extensions (version, date and amendment) are not repeated.

FCC Part 15 (2005) Code of Federal Regulations  
Title 47 - Telecommunication  
Chapter 1 - Federal Communications Commission  
Part 15 - Radio frequency devices  
Subpart C - Intentional Radiators

ANSI C63.4 (03) American National Standard for Methods of measurement of Radio-Noise from low-voltage.  
Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.

#### **4. TEST METHODOLOGY**

Radio performance tests procedures given in part 15:

Paragraph 33: frequency range of radiated measurements

Paragraph 35: measurement detector functions and bandwidths

Paragraph 203: antenna requirement

Paragraph 205: restricted bands of operation

Paragraph 209: radiated emission limits; general requirements

Paragraph 231: periodic operation in the band 40.66 MHz - 40.7 MHz and above 70 MHz  
(subpart C, intentional radiator)

#### **5. TEST UNIT CONFIGURATION**

##### JOINED DOCUMENTATIONS

***“Synoptic”***  
***“Block diagram”***  
***“External photos and Product labeling”***  
***“Assembly of components”***  
***“Internal photos”***  
***“Layout pcb”***  
***“Bill of materials”***  
***“Schematics”***  
***“Product description”***  
***“User guide”***

**6.TESTS AND CONCLUSIONS**

Test procedure	Description of test	Criteria respected ?				Comment
		Yes	No	NAp	NAs	
FCC Part 15.203	ANTENNA REQUIREMENT	X				<i>Note 1</i>
FCC Part 15.205	RESTRICTED BANDS OF OPERATION	X				
FCC Part 15.231	PERIODIC OPERATION IN THE BAND 40.66 – 40.7 MHz and above 70 MHz					
a)		X				<i>Note 2</i>
b)		X				<i>Notes 3 &amp; 5</i>
c)		X				<i>Note 4</i>
d)				X		
e)				X		

NAp: Not Applicable

NAs: Not Asked

Note 1: *internal antenna without connector.*Note 2: *the equipment is manually operated and employ a switch that deactivates automatically the transmitter and ceases transmission within 5 seconds after being released (see annex 5). The transmitter is not activated automatically.*Note 3: *field strength limit of fundamental ( $F = 433.42 \text{ MHz}$ )*

$$41.6667 (F) - 7083.3333 = 10976 \mu\text{V/m} \text{ at } 3 \text{ m} = 80.8 \text{ dB}\mu\text{V/m at } 3 \text{ m.}$$

*The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.*Note 4: *the bandwidth of the emission at 20 dB is 524 kHz (see annex 3), less than 0.25 % of the centre frequency (1.084 MHz).*Note 5: *pulsed modulated device.**\* A duty cycle correction factor has been applied to measures, we use the formulas:*

$$\text{* ON TIME} = N_1 \cdot L_1 + N_2 \cdot L_2 + \dots + N_{n-1} \cdot L_{n-1} + N_n \cdot L_n$$

*(where  $N_1$  is number of type 1 pulse,  $L_1$  is length of type 1 pulse...)**and \* DUTY CYCLE = ON TIME / 100 ms or  $T$  (whichever is less, where  $T$  is the period of the pulse train).**We have found (see annex 4)*

$$N_1 = 6$$

$$L_1 = 2.7 \text{ ms}$$

$$N_2 = 1$$

$$L_2 = 5.1 \text{ ms}$$

$$N_3 = 56$$

$$L_3 = 0.64 \text{ ms}$$

$$\text{So DUTY CYCLE} = \frac{(6 \times 2.7) + (1 \times 5.1) + (56 \times 0.64)}{100} = 57.1\% \text{ which gives a correction}$$

*factor of -4.87 dB.***Conclusion:**

The sample of HZ WALL MOUNTED TRANSMITTER /ND US submitted to the tests complies with the regulations of the standard FCC Part 15 in accordance with the limits or criteria defined in this report.

**7.RADIATED EMISSION LIMITS; GENERAL REQUIREMENTS (TRANSMITTER)****Standard:** FCC Part 15**Test procedure:** paragraph 205 / 209  
Paragraph 231**Test equipment:**

TYPE	BRAND	EMITECH NUMBER
Test receiver	Rohde & Schwarz ESVS 10	1219
Biconical antenna	Hewlet Packard 11966 C	728
Log periodic antenna	Rohde & Schwarz HL 223	1999
Double ridged guide antenna	Electrometrics RGA-60	1204
Spectrum analyzer	Rohde & Schwarz FSP40	4088
Open area test site	EMITECH	1274
Preamplifier 1 to 18 GHz	ALC	2648
High pass filter	Micro-tronics HPM11630	1673

**Test set up:**

The system is tested in an open area test site (OATS).

The test unit is placed on a rotating table, 0.8 m from a ground plane. Zero degree azimuth corresponds to the front of the equipment under test.

**Frequency range:** from 30 MHz to harmonic 10 ( $F_{carrier} \leq 1 \text{ GHz}$ )**Detection mode:** Peak detector**Bandwidth:** 120 kHz ( $F < 1 \text{ GHz}$ )  
1 MHz ( $F > 1 \text{ GHz}$ )**Distance of antenna:** 3 meters**Antenna height:** 1 to 4 meters**Antenna polarization:** vertical and horizontal (only the highest level is recorded)**Equipment under test operating condition:**

The equipment is blocked in continuous transmission mode, modulated by internal data signal.

**Results:**

Ambient temperature (°C): 17.5  
 Relative humidity (%): 42

Power source: we used for power source the internal battery of the equipment and we noted:

Voltage at the beginning of test (V): 3.34  
 Voltage at the end of test (V): 3.22  
 Percentage of the voltage drop during the test (%): -3.6  
 Limits (%): ± 5

The polarity column refers to the antenna polarity at which the maximum emissions level is measured.

Channel	Emission							
FREQUENCIES (MHz)	E.U.T. orientation	Antenna height (cm)	Polarization of antenna H: Horizontal V: Vertical	Azimuth (degrees)	Peak reading (dB $\mu$ V/m)	Calculated average reading (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Difference from limit (dB)
433.479 <sup>(1)</sup>	Z	119	V	287	85.3	80.4	80.8	-0.4
866.96	Z	267	H	11	52.5	47.6	60.8	-13.2
1300.36*	Z	136	V	229	48.4	43.5	54	-10.5
1733.98	Z	159	H	186	47.5	42.6	60.8	-18.2
2167.34	Z	202	V	347	45.8	40.9	60.8	-19.9
2600.87	Z	194	V	0	46.1	41.2	60.8	-19.6
3034.35	Z	138	V	0	47.6	42.7	60.8	-18.1
3467.82	Z	196	H	0	45.9	41	60.8	-19.8
3901.32*	Z	190	H	0	43.8	38.9	54	-15.1
4334.66*	Z	194	H	0	53.1	48.2	54	-5.8

<sup>(1)</sup> fundamental.

E.U.T.: Equipment Under Test

\* restricted band of operation § 15.205.

E.U.T. orientation

X: to put flat

Y: on the edge

Z: up right

Note: 60.8 dB $\mu$ V/m at 3 m (20 dB below the maximum permitted fundamental level corresponding to the tighter limit)

500  $\mu$ V/m at 3 m = 54 dB $\mu$ V/m at 3 m (§ 15.209 limit)

□□□ End of report, 5 annexes to be forwarded □□□