

---

EXHIBIT 14

**RADIATED SPURIOUS EMISSIONS MEASUREMENTS**

Measurements of radiated spurious emissions were performed in accordance with the requirements and conditions of § 24.238 and § 2.1053; requirements, procedures and results are described in this exhibit.

**Requirements**

Broadband PCS equipment operating under the authority of Part 24, Subpart E, must comply with the emissions limits given in § 24.238(a): "On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log (P)$  dB."

Section 2.1053(a) of the FCC Rules specifies that measurements shall be made to detect spurious emissions that may be radiated directly from the cabinet, control circuits, power leads, or intermediate circuit elements under normal conditions of installation and operation. Curves or equivalent data shall be supplied showing the magnitude of each harmonic and other spurious emission. The magnitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be specified. Furthermore, § 2.1057 requires that measurements be made from the lowest radio frequency generated in the equipment up to at least the 10<sup>th</sup> harmonic of the carrier frequency (approximately 20 GHz for PCS 1900 terminals).

Per § 2.1053(a), the allowable field strength of radiated spurious emissions is found by referencing the relative radiated power of each emissions to the rated RF output power of the EUT, assuming that each is radiated from a halfwave dipole antenna. As required by § 24.238(a), spurious emissions must be attenuated by at least  $43+10\log(P)$  dB. For a maximum rated RF output power of 1 W (30 dBm), the required attenuation is thus 43 dBc, corresponding to an absolute level of -13 dBm. Compliance with the -43 dBc (-13 dBm absolute) limit is verified using a substitution method to relate measured spurious emissions to that produced by driving an ideal halfwave dipole at -13 dBm.

Additionally, because Part 24 applies only to PCS transmissions, only transmitter and transmitter-related spurious emissions are subject to the limits given in § 24.238. Radiated spurious emissions from receivers which operate above 960 MHz are not regulated, per § 15.101(b). All other emissions, including those originating from digital control, processing, and other circuitry, and power supplies, and whether radiated or conducted onto the AC powerline, are regulated as unintentional emissions by Part 15 of the FCC rules. In accordance with the guidance given in § 15.101, this category of emissions is subject to the verification process.

---

## Measurement Procedure and Results Summary

Measurements of radiated spurious emissions were performed at and by Criterion Technology of Rollinsville, CO. Criterion Technology is accredited through the national Voluntary Laboratory Accreditation Program (NVLAP) and a description of its open air test site (OATS) has been filed with the FCC. Measurement procedures and results are described in the test report prepared by Criterion Technology, which is on file.

For all radiated and AC powerline conducted emissions measurements, the Core Engine was mounted to a carrier board as Figures E14.1 and E14.2. This carrier board provided a conditioned interface for the DC power and RS-232 signals to the Core Engine. Measurements of unintentional (non transmitter related) emissions, both radiated and AC powerline conducted, were performed to ensure that these emissions from the Core Engine are well below the Class B limits. When incorporated into an OEM product, unintentional emissions from the Core Engine will thus not contribute excessively to the emission from the combined product; Class B performance will also enable the Core Engine to be incorporated into any type of end product. Similarly, measurements of transmitter-related (above 1 GHz) emissions demonstrated that the Core Engine complies with the radiated spurious limits given in § 24.238 without any allowance or need for additional RF shielding from the host product, a requirement for this type of modular device.

Measurements performed by Criterion Technologies were in accordance with the procedures given in ANSI C63.4-1992, *"Method of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz"* over the frequency range of 30 MHz to 20 GHz. For measurements of unintentional emissions below 1 GHz, emissions were measured per standard practice.

For transmitter spurious emissions, peak (versus average) measurements were made, in accordance with FCC practice. Compliance with the 43 dBc (-13 dBm absolute) limit was verified using a substitution method at each frequency where a transmitter spurious emissions was measured.

During the substitution measurements, the EUT was replaced with a horn antenna and signal generator, the latter of which was tuned successively to the frequency of each EUT transmitter spurious emission using a power level chosen to avoid overdriving the measurement system pre-amplifier. At each frequency the "substitution emission" was maximized as during the normal EUT measurement, using the same spectrum analyzer settings, by rotating the turntable containing the substitution (horn) antenna and varying the height of the measurement system receive antenna from 1 to 4 meters. This was performed with both the substitution and measurement system antennas in both the vertical and horizontal polarities.

The (maximized) signals recorded during the substitution measurements were then compensated for the difference between the substitution antenna drive signal and the 43 dBc (-13 dBm) limit, and the difference between the gain of the substitution antenna and that of an ideal  $\lambda/2$  dipole (2.15 dBi). At each measurement frequency, the difference between this adjusted signal level and that from the EUT represents the margin to the Part 24.238 limit of 43 dBc (-13 dBm) into an ideal  $\lambda/2$  dipole.

The results from this substitution measurement indicate that the Core Engine meets the transmitter radiated emissions requirements and limits given in §§ 24.238 and 2.1053. Furthermore, all other emissions, both radiated and conducted, and from all sources excluding the Core Engine transmitter (i.e., receiver, digital, etc.) comply with FCC Part 15, Class B limits.

Representative values for the field strength of non-transmitter (i.e., receiver and unintentional) spurious radiated emissions are presented in Table E14.1. Substitution results indicating the measured margin to the Part 24.238 limit are provided in Table E14.2 for all transmitter spurious emissions.

For both sets of measurements the transmitter was tuned to a mid-band PCS 1900 channel at 1880.0 MHz (channel 661). Similar results were measured with the transmitter tuned to the low (channel 512, 1850.2 MHz) and high (channel 810, 1909.8 MHz) PCS 1900 channels in the licensed PCS spectrum.



Figure E14.1. Radiated Emissions set-up at Criterion Technologies.



Figure E14.2. Radiated Emissions set-up at Criterion Technologies.

Table E14.1. Representative radiated spurious emissions results below 1GHz

| Frequency (MHz) | Field Strength at 10 m (dB $\mu$ V/m) | Limit at 10 m (dB $\mu$ V/m) | Margin (dB) |
|-----------------|---------------------------------------|------------------------------|-------------|
| 32.1571         | 20.40                                 | 29.54                        | 9.14        |
| 39.0079         | 20.13                                 | 29.54                        | 9.41        |
| 48.0053         | 22.49                                 | 29.54                        | 7.51        |
| 48.7489         | 20.60                                 | 29.54                        | 8.94        |
| 50.7949         | 20.69                                 | 29.54                        | 8.85        |
| 52.0000         | 20.60                                 | 29.54                        | 8.94        |
| 56.3060         | 21.21                                 | 29.54                        | 8.33        |
| 60.0011         | 18.96                                 | 29.54                        | 10.58       |
| 65.0000         | 20.95                                 | 29.54                        | 8.59        |
| 78.0000         | 20.83                                 | 29.54                        | 8.71        |
| 82.5517         | 20.21                                 | 29.54                        | 9.33        |
| 84.4998         | 20.39                                 | 29.54                        | 9.15        |
| 90.9595         | 22.29                                 | 33.06                        | 10.77       |
| 104.0000        | 20.72                                 | 33.06                        | 12.34       |
| 112.6323        | 16.93                                 | 33.06                        | 16.13       |
| 117.0000        | 21.11                                 | 33.06                        | 11.95       |
| 130.0000        | 20.34                                 | 33.06                        | 12.72       |
| 137.2939        | 20.83                                 | 33.06                        | 12.23       |
| 143.0000        | 14.77                                 | 33.06                        | 18.29       |
| 156.0000        | 21.62                                 | 33.06                        | 11.44       |
| 169.0000        | 17.45                                 | 33.06                        | 15.61       |
| 175.5009        | 19.17                                 | 33.06                        | 13.89       |
| 188.4979        | 18.22                                 | 33.06                        | 14.84       |
| 195.0000        | 12.94                                 | 33.06                        | 20.12       |
| 208.0000        | 20.70                                 | 33.06                        | 12.36       |
| 221.0000        | 16.59                                 | 33.06                        | 18.97       |
| 224.2504        | 18.90                                 | 33.06                        | 16.66       |
| 233.2482        | 12.62                                 | 33.06                        | 22.94       |
| 234.0000        | 24.01                                 | 33.06                        | 11.55       |
| 247.0000        | 24.01                                 | 33.06                        | 13.91       |
| 269.7525        | 21.80                                 | 33.06                        | 13.76       |
| 273.0000        | 17.01                                 | 33.06                        | 18.55       |
| 276.2469        | 22.64                                 | 33.06                        | 12.92       |
| 279.4952        | 20.58                                 | 33.06                        | 14.98       |
| 286.0000        | 22.52                                 | 33.06                        | 13.04       |
| 299.0000        | 23.86                                 | 33.06                        | 11.70       |
| 308.7507        | 26.11                                 | 33.06                        | 9.45        |
| 312.0000        | 26.73                                 | 33.06                        | 8.83        |
| 325.0000        | 24.64                                 | 33.06                        | 10.92       |
| 338.0000        | 20.41                                 | 33.06                        | 15.15       |
| 351.0000        | 19.78                                 | 33.06                        | 15.78       |
| 364.0000        | 19.85                                 | 33.06                        | 15.71       |

Table E14.2. Representative transmitter radiated spurious emissions results using Substitution Method.

| FREQ  | SUB MEAS<br>TX POWER | SUB ANT<br>GAIN | SUB<br>CORRECTION | EUT MEAS (WORST CASE) |       | RAW SUB MEAS |       | COR RAW SUB MEAS |       | PART 24 MARGIN<br>(WORST CASE) | COMMENTS            |
|-------|----------------------|-----------------|-------------------|-----------------------|-------|--------------|-------|------------------|-------|--------------------------------|---------------------|
|       |                      |                 |                   | AMPLITUDE             | POLAR | VER          | HOR   | VER              | HOR   |                                |                     |
| MHz   | dBm                  | dBi             | dB                | dBuV                  | V,H   | dBuV         | dBuV  | dBuV             | dBuV  | dB                             |                     |
| 1452  | -33.83               | 8.1             | 14.88             | 61.85                 | V     | 77.95        | 76.60 | 92.83            | 91.48 | 31.0                           | TXLO                |
| 1600  | -33.81               | 8.5             | 14.46             | 60.35                 | H     | 79.70        | 78.15 | 94.16            | 92.61 | 32.3                           | RXLO                |
| 1880  | -33.93               | 8.7             | 14.38             | 101.90                | H     | 75.25        | 74.35 | 89.63            | 88.73 | -13.2                          | RF - FUNDAMENTAL    |
| 2904  | -34.54               | 9.0             | 14.69             | 44.05                 | V     | 68.90        | 70.50 | 83.59            | 85.19 | 39.5                           | 2TXLO - NOISE LEVEL |
| 3200  | -34.74               | 8.6             | 15.29             | 45.10                 | H     | 67.20        | 68.30 | 82.49            | 83.59 | 38.5                           | 2RXLO               |
| 3760  | -35.04               | 9.2             | 14.99             | 61.05                 | H     | 64.90        | 65.25 | 79.89            | 80.24 | 19.2                           | 2RF                 |
| 4356  | -35.12               | 10.8            | 13.47             | 50.45                 | V     | 65.25        | 64.20 | 78.72            | 77.67 | 28.3                           | 3TXLO               |
| 4800  | -35.45               | 10.6            | 14.00             | 46.50                 | V     | 63.45        | 61.90 | 77.45            | 75.90 | 31.0                           | 3RXLO               |
| 5640  | -35.54               | 10.3            | 14.39             | 52.05                 | V     | 56.55        | 54.65 | 70.94            | 69.04 | 18.9                           | 3RF                 |
| 5808  | -35.52               | 10.4            | 14.27             | 45.44                 | H     | 59.15        | 58.55 | 73.42            | 72.82 | 27.4                           | 4TXLO - NOISE LEVEL |
| 6400  | -35.84               | 11.1            | 13.89             | 45.40                 | V     | 50.40        | 49.15 | 64.29            | 63.04 | 18.9                           | 4RXLO - NOISE LEVEL |
| 7260  | -35.85               | 11.0            | 14.00             | 46.00                 | V     | 55.80        | 54.05 | 69.80            | 68.05 | 23.8                           | 5TXLO - NOISE LEVEL |
| 7520  | -35.93               | 11.0            | 14.08             | 54.50                 | V     | 56.40        | 55.25 | 70.48            | 69.33 | 16.0                           | 4RF                 |
| 8000  | -36.06               | 11.4            | 13.81             | 44.95                 | H     | 57.55        | 55.50 | 71.36            | 69.31 | 24.4                           | 5RXLO - NOISE LEVEL |
| 9400  | -36.45               | 11.3            | 14.30             | 52.55                 | H     | 52.00        | 52.70 | 66.30            | 67.00 | 14.5                           | 5RF                 |
| 11280 | -36.78               | 12.2            | 13.73             | 46.15                 | H     | 47.95        | 45.80 | 61.68            | 59.53 | 13.4                           | 6RF                 |
| 13160 | -37.45               | 11.6            | 15.00             | 49.00                 | H     | 41.30        | 40.10 | 56.30            | 55.10 | 6.1                            | 7RF - NOISE LEVEL   |