



FCC CFR47 PART 24 SUBPART E

CERTIFICATION REPORT

FOR

CDMA PCS WLL TERMINAL

MODEL: DTT-1900

FCC ID: PUNDTT-1900

REPORT NUMBER: 01U0934-1

ISSUE DATE: AUGUST 30, 2001

Prepared for

DOWTELECOM INC.

**4TH FLOOR, WOOSONG BLDG. 361-10, YATAP-DONG,
BUNDANG-GU, SEONGNAM-SI,
GYUNGGI-DO, KOREA**

Prepared by

COMPLIANCE CERTIFICATION SERVICES, INC.

d.b.a.

COMPLIANCE ENGINEERING SERVICES, INC.

**561F Monterey Road,
Morgan Hill, Ca 95037-9001**

U.S.A.

TEL: (408) 463-0885

FAX: (408) 463-0888

TABLE OF CONTENT

PAGE NO

FCC CERTIFICATION INFORMATION 3

TEST RESULT CERTIFICATION 6

EUT DESCRIPTION..... 7

TEST FACILITY..... 7

ACCREDITATION AND LISTING 7

MEASURING INSTRUMENT CALIBRATION 7

TEST EQUIPMENT LIST..... 8

FCC PART 15 TEST RESULTS 9

 TESTED SYSTEMS DETAILS 9

 CONFIGURATION BLOCK DIAGRAM 10

 EXTERNAL I/O CABLE CONSTRUCTION DESCRIPTION 11

 RADIATED EMISSION 12

 LINE CONDUCTION PLOT 14

 SETUP PHOTOS 15

FCC PART 2 CERTIFICATION TEST RESULTS: 19

 SECTION 2.1046: RF POWER OUTPUT 20

 SECTION 2.1047: MODULATION CHARACTERISTICS 22

 SECTION 2.1049: OCCUPIED BANDWIDTH..... 23

 SECTION 2.1051: SPURIOUS EMISSION AT ANTENNA TERMINAL 25

 SECTION 2.1053: FIELD STRENGTH OF SPURIOUS RADIATION..... 30

 SECTION 2.1055: FREQUENCY STABILITY 33

 SECTION 24.235: FREQUENCY STABILITY 33

 SETUP PHOTOS..... 34

ATTACHMENTS

 EUT PHOTOGRAPHS

 PROPOSED FCC ID LABEL FORMAT

 TECHNICAL DESCRIPTION & TUNE UP PROCEDURE

 REQUEST OF CONFIDENTIALITY LETTER

 INSTALLATION & SERVICE MANUAL

 BLOCK DIAGRAM, SCHEMATIC DIAGRAM & PART LIST

FCC CERTIFICATION INFORMATION

The following information is in accordance with FCC Rules, 47CFR Part2, Subpart J, Sections 2.1033 – 2.1055.

2.1033(c)(1): Applicant: DOWTELECOM INC.
4TH Floor, Woosong Bldg. 361-10, Yatap-Dong
Bundang-Gu, Seongnam-Si,
Gyunggi-Do, Korea

Contact person: Mr. Seoung Chul Ju/Senior Engineer

Telephone number: 482-031-701-8962

2.1033(c)(2) FCC ID: PUNDTT-1900

2.1033(c)(3) Instructions/Installation Manual

Refer to **Attachment:** Installation and Service manual.

2.1033(c)(4) Type of emissions

1M25F9W

2.1033(c)(5) Frequency Range

Transmit: **1850MHz to 1910MHz**

Receive: **1930MHz to 1990MHz**

2.1033(c)(6) Range of Operation Power

< -50dBm, 0.00001WATTS.

25dBm (0.316WATTS)

See Attachment: *Technical Description* section 2.983(d)(3) *Means for variation of operating power.*

2.1033(c)(7) Maximum Power Rating

25dBm, 0.316WATTS.

2.1033(c)(8) Applied voltage and currents into the final transistor elements

See Attachment: *Technical Description* section 2.983(d)(5) *DC voltage and current of final amplifying device.*

2.1033(c)(9) Tune-up/Optimizations Procedure

See Attachment: *Technical Description* section 2.983(d)(9) *Tune-up procedure over the power range.*

2.1033(c)(10) Complete Circuit Diagrams and Functional Diagram

Functional diagram: See Attachment: *Technical Description* section 2.983(d)(12) *Description of modulation system used.*

Complete circuit diagrams: See Attachment: Schematics and parts list.

2.1033(c)(10a) Means for Frequency Stabilization

See Attachment: *Technical Description* section 2.983(d)(10) *Description of frequency determining and stabilizing circuitry..*

2.1033(c)(10b) Means for Suppressing of Spurious radiation.

See Attachment: *Technical Description* section 2.983(d)(11) *Description of circuit emulated for suppression of spurious radiations.*

2.1033(c)(10c) Means for Limiting Modulation.

See Attachment: *Technical Description* section 2.983(d)(12) *Description of modulation system used.*

2.1033(c)(10d) Means for Limiting Power.

See Attachment: *Technical Description* section 2.983(d)(3) *Means for variation of operating power.*

2.1033(c)(11) Equipment Identification

A drawing of the equipment identification nameplate appears under **Attachment:** PROPOSED FCC ID LABEL FORMAT.

2.1033(c)(12) Photographs

Photographs of the equipment, internal and external views, are found in the **Attachment:** Eut Photographs.

2.1033(c)(13) Description of Digital Modulation Techniques

See Attachment: *Technical Description* section 2.983(d)(12) *Description of modulation system used*

2.1033(c)(14) Standard Test Condition

The EUT was operated in Test Mode during testing. See Attachment: *Technical Description* section 2.983(d)(9) *Tune-up procedure over the power range*, for a description of the Test Mode.

TEST RESULT CERTIFICATION

COMPANY NAME: DOWTELECOM INC.
4TH FLOOR, WOOSONG BLDG. 361-10, YATAP-DONG
BUNDANG-GU, SEONGNAM-SI,
GYUNGGI-DO, KOREA

CONTACT PERSON: MR. SEOUNG CHUL JU/ SENIOR ENGINEER

TELEPHONE NO: 482-031-701-8962

EUT DESCRIPTION: CDMA PCS WLL TERMINAL

MODEL NAME: DTT-1900

DATE TESTED: AUGUST 24, 20001

TYPE OF EQUIPMENT	CDMA WIRELESS LOCAL LOOP TERMINAL
AUTHORIZATION PROCEDURE	CERTIFICATION
FCC RULE PARTS	FCC Part 2, 15 & 24
MEASUREMENT PROCEDURE	FCC Part 2, 24, and ANSI C63.4

Compliance Certification Services, Inc. tested the above equipment for compliance with the requirements set forth in FCC Parts 2, 15 and 24. The said equipment, in the configuration described in this report, fulfills the technical characteristics of the specified standard.

Warning : This document reports conditions under which testing was conducted and results of tests performed. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification Services will constitute fraud and shall nullify the document.

Tested By:

PETE KREBILL
ASSOCIATE EMC ENGINEER
COMPLIANCE CERTIFICATION SERVICES

Released For CCS By:

STEVE CHENG
EMC ENGINEERING MANAGER
COMPLIANCE CERTIFICATION SERVICES

EUT DESCRIPTION

The Dowtel DTT-1900 terminal is a CDMA Wireless Local Loop (WLL) terminal. Its basic purpose is for use on a desk. It can be connected to telephones to provide voice communication and or a computer to provide data communication such as fax or modem. It transmits from 1850 MHz to 1910 MHz and receives from 1930 MHz to 1990 MHz. The RF power is rated at 316 mW. The omni-directional dipole antenna has a rated gain of more than 1.5dBi.

TEST FACILITY

The open area test sites and conducted measurement facilities used to collect the radiated data are located at 561F Monterey Road, Morgan Hill, California, USA. The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

ACCREDITATION AND LISTING

The test facilities used to perform radiated and conducted emissions tests are accredited by National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code: 200065-0 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government. In addition, the test facilities are listed with Federal Communications Commission (reference no: 31040/SIT (1300B3) and 31040/SIT (1300F2))

MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

TEST EQUIPMENT LIST

Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
Signal Generator	HP	83732B	US3449059	3/21/01	3/21/02
Spectrum Analyzer	H.P.	8593EM	3710A00205	6/20/01	6/20/02
Pre-Amp	H.P	8449B	3008A00369	5/30/01	5/30/02
Horn Antenna	EMCO	3115	2238	6/20/01	6/20/02
Horn Antenna	EMCO	3115	9001-3245	6/20/01	6/20/02
Horn Antenna	ARA	MWH-1826/B	1013	7/26/01	7/26/02


Name of Equipment	Manufacturer	Model No.	Serial No.	Due Date
Spectrum Analyzer	HP100Hz - 22GHz	8566B	2140A01296	5/4/02
Spectrum Display	HP	85662A	2152A03066	5/10/02
Quasi-Peak Detector	HP9K - 1GHz	85650A	2811A01155	5/4/02
Pre-Amplifier, 25 dB	HP 0.1 - 1300MHz	8447D (P_1M)	2944A06833	11/21/01
Antenna, BiLog	Chase 30 - 2000MHz	CBL6112	2049	12/11/01
LISN	Fisher Cus. Comm.	LISN-50/250-25-2	2023	8/5/02
EMI Test Receiver	Rohde & Schwarz	ESHS 20	827129/006	2/28/02
Horn Antenna(1 - 18GHz)	EMCO	3115	9001-3245	6/20/02
Pre-Amplifier	MITEQ1-26GHz	NSP2600-44	646456	1/3/02
EMC Receiver (9K- 26.5GHz)	HP	8593EM	3710A00205	6/20/02
Horn Antenna,(18 - 26GHz)	Antenna Research Associate	MWH 1826/B	1013	7/26/02
Signal Generator	HP	8640B	2322A22402	4/10/02

FCC PART 15 TEST RESULTS

TESTED SYSTEMS DETAILS

<i>MOUSE</i>	<i>HP</i>	<i>M-S34</i>	<i>LZB75062022</i>	<i>DZL211029</i>
<i>PRINTER</i>	<i>HP</i>	<i>2225C</i>	<i>2930S52614</i>	<i>DSI6XU2225</i>
<i>LAPTOP</i>	<i>IMENTIC</i>	<i>94A2824</i>	<i>H4895AAA</i>	<i>DoC</i>
<i>PHONE</i>	<i>WINTONE</i>	<i>HA178</i>	<i>64489</i>	<i>DoC</i>


CONFIGURATION BLOCK DIAGRAM



EXTERNAL I/O CABLE CONSTRUCTION DESCRIPTION

Cable No	I/O Port	# of I/O Port	Connector Type	Type of Cable	Cable Length	Data Traffic	Bundled	Remark
1	AC	1	US 115V	Un-shielded	2m	No	No	N/A
2	AC	1	US 115V	Un-shielded	2m	No	Yes	Bundled during AC LC only
3	AC	1	US 115V	Un-shielded	2m	No	No	N/A
4	Mouse	1	PS/2	Un-shielded	2m	Yes	No	N/A
5	Serial	1	DB9	Shielded	1m	Yes	No	N/A
6	Parallel	1	DB25	Shielded	2m	Yes	Yes	N/A
7	RJ-11	1	RJ-11	Un-shielded	1m	Yes	No	N/A

RADIATED EMISSION

 <p>FCC, VCCI, CISPR, CE, AUSTEL, NZ UL, CSA, TUV, BSMI, DHHS, NVLAP</p> <p>561F MONTEREY ROAD, SAN JOSE, CA 95037-9001 PHONE: (408) 463-0885 FAX: (408) 463-0888</p> <p>Project #: 01I0934-1 Report #: 010822b Date & Time: 08/22/01 1:30 PM Test Engr: HUE LY VANG</p> <p>Company: ETL INC. EUT Description: PCS WALL TERMINAL Test Configuration: EUT/LAPTOP/MOUSE/PRINTER/ Type of Test: FCC CLASS B Mode of Operation: EUT IS NORMAL OPERATIONS, ALSO DIAL AND REDIAL TO LAPTOP</p>											
Freq. (MHz)	Reading (dBuV)	AF (dB)	Cross (dB)	Pre-amp (dB)	Level (dBuV/m)	Limit FCC B	Margin (dB)	Pol (H/V)	Az (Deg)	Height (Meter)	Mark (P/Q/A)
66.50	44.00	6.98	1.82	29.47	23.33	40.00	-16.67	3mV	180.00	1.00	P
930.00	25.20	21.64	8.45	28.35	26.94	46.00	-19.06	3mV	180.00	1.00	P
36.60	30.00	17.58	1.41	29.49	19.50	40.00	-20.50	3mV	180.00	1.00	P
830.00	25.00	20.70	7.93	28.74	24.89	46.00	-21.11	3mH	180.00	2.00	P
48.00	35.70	10.62	1.56	29.48	18.40	40.00	-21.60	3mH	180.00	2.50	P
555.00	25.00	18.41	6.16	29.36	20.21	46.00	-25.79	3mH	180.00	2.00	P
6 Worst Data											

CONDUCTED EMISSION


CONDUCTED EMISSIONS DATA (115VAC 60Hz)										
Freq. (MHz)	Reading			Class (dB)	Limit QP	FCC_B		Margin		Remark L1/L2
	PK (dBuV)	QP (dBuV)	AV (dBuV)			AV	QP (dB)	AV (dB)		
0.86	36.56	--	--	0.00	48.00	--	-11.44	--	L1	
6.73	40.29	--	--	0.00	48.00	--	-7.71	--	L1	
20.47	37.14	--	--	0.00	48.00	--	-10.86	--	L1	
0.86	39.88	--	--	0.00	48.00	--	-8.12	--	L2	
1.38	41.33	--	--	0.00	48.00	--	-6.67	--	L2	
6.56	42.30	--	--	0.00	48.00	--	-5.70	--	L2	
6 Worst Data										

LINE CONDUCTION PLOT



561 F Monterey Road, Route 2
Morgan Hill, CA 95037-9001 USA
Tel: (408) 463-0885
Fax: (408) 463-0888

Data#: 28 File#: 01I0934.EMI Date: 08-23-2001 Time: 11:18:09
Level (dBuV) Compliance Certification Services



Trace: 24
Project No. : 01i0934-1
Report No. : 010822-wall unit
Test Engr : Hue Ly Vang
Company : BTL INC.
EUT Description : PCS WLL TERMINAL
Model : DTT1900
EUT Config. : EUT
Type of Test : FCC CLASS B
Mode of Operation:
: PEAK: L1(Green), L2(Black)
: 115Vac, 60Hz

SETUP PHOTOS



RADIATION FRONT



RADIATION BACK




LINE CONDUCTION FRONT



LINE CONDUCTION BACK

FCC PART 2 CERTIFICATION TEST RESULTS:

Test Set-up for the following conducted tests:



SECTION 2.1046: RF POWER OUTPUT

Minimum Requirement:

24.232(B); Mobile/Portable stations are limited to 2 Watts EIRP peak power.

Test Procedure conducted:

The EUT was setup to maximum output power (maximum gain) at its lowest channel. The output power was measured using a spectrum analyzer. The measurements are repeated for the highest and a middle channel. The EIRP is then calculated by adding the EUT's antennas gain in dBi to the EUT's power in dBm. The EUT's antenna gain was rated at < 1.5dBi. 1.5dBi is used for calculating EIRP.

Test Procedure radiated:

The EUT was setup to its maximum output power at its lowest channel. The EUT's antenna was attached normally. EIRP was measured using the radiated substitution method. The measurements are repeated for the highest and a middle channel. See the description of the test method in *Field Strength of Spurious Radiations Substitution* section of this report.

Test Result:

Complies.

Calculations and plots are shown below for conducted measurements.

A spreadsheet is shown below for radiated measurements

Conducted measurements:

Channel 25: 25.09dBm + 1.5dBi = 26.59dBm EIRP or 456mW EIRP

Channel 600: 25.03dBm + 1.5dBi = 26.53dBm EIRP or 449.8mW EIRP

Channel 1175: 25.01dBm + 1.5dBi = 26.51dBm EIRP or 407.4mW EIRP




Radiated measurements:

Compliance Certification Services

8/22/01

Pete Krebill

Frequency MHz	SA reading dBuV	Sig Gen dBm	CL dB	Gain dBi	EIRP dBm	Limit dBm	Margin dB
Channel 25							
1805.125	96.86	19.6	0.3	8.8	28.1	33	-4.9
Channel 600							
1880	96.72	19.5	0.3	8.8	28	33	-5
Channel 1175							
1908.75	97.2	19.7	0.3	8.8	28.2	33	-4.8



SECTION 2.1047: MODULATION CHARACTERISTICS

A curve or equivalent data which shows that the equipment will meet the modulation requirements of the rules under which the equipment is to be licensed.

Not applicable. No modulation requirements for PCS. PCS licensees may provide any mobile communications services on their assigned spectrum (FCC 24.3).

SECTION 2.1049: OCCUPIED BANDWIDTH

Minimum requirement:

Section 2.1049(i); transmitters designed for other types of modulation-when modulated by an appropriate signal of sufficient amplitude to be representative of the type of service in which used.




Test Procedure:

The EUT was setup to maximum output power at its lowest channel. The occupied bandwidth was measured using a spectrum analyzer. The measurements are repeated for the highest and a middle channel. The EUT's occupied bandwidth is measured as the width of the signal between two points, one below the carrier center frequency and one above the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

Test Result:

Channel 25: 1.437 MHz
Channel 600: 1.437 MHz
Channel 1175: 1.430 MHz

Plots of the EUT's output bandwidth are shown below.



SECTION 2.1051: SPURIOUS EMISSION AT ANTENNA TERMINAL

Minimum standard:

FCC 24.238(a); On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB. Limit equivalent to -13dBm , calculation shown below.

$$43 + 10 \log (0.316\text{W}) = 38\text{dB}$$
$$25\text{dBm} - 38\text{dB} = -13\text{dBm}$$

FCC 24.238 (b):

Compliance with the out-of-band emissions requirement is based on test being performed with an analyzer resolution bandwidth of 1 MHz. However in the 1 MHz band immediately outside and adjacent to the frequency block a resolution bandwidth of at least 1% of the fundamental emissions bandwidth may be employed.

CDMA:



$0.01 * 1.43\text{MHz} = 14.3 \text{ KHz}$. A RES BW of 30 KHz was used for measurement at the block edges.

Test Procedure:

The EUT was setup to maximum output power at its lowest channel, channel 25 (1851.25MHz). The RES BW of the analyser is set to 1% of the emission bandwidth to show compliance with the -13 dBm limit, in the 1 MHz bands immediately outside and adjacent to the edge of the frequency block. The measurements are repeated for the EUT's highest channel, channel 1175 (1908.75). For the Out-of-Band measurements a 1 MHz RES BW was used to scan from 30 MHz to 20GHz. A display line was placed at -13 dBm to show compliance. The high, lowest and a middle channel were tested for out of band measurements.


Test Results:

Complies. Plots are shown below.




17:16:21 AUG 23, 2001
ETL OUT OF BAND CH25



ACTV DET: PEAK
MEAS DET: PEAK QP AVG



17:18:13 AUG 23, 2001
ETL OUT OF BAND CH25


ACTV DET: PEAK
MEAS DET: PEAK QP AVG






17:22:28 AUG 29, 2001
ETL OUT OF BAND CH1175

ACTV DET: PEAK
MEAS DET: PEAK QP AVG



17:22:39 AUG 29, 2001
ETL OUT OF BAND CH1175


ACTV DET: PEAK
MEAS DET: PEAK QP AVG




**SECTION 2.1053: FIELD STRENGTH OF SPURIOUS RADIATION.
SUBSTITUTION METHOD: (Radiated Emissions)**

Test Set-up:

Radiated BELOW 1GHz



Radiated ABOVE 1 GHz



The actual signal generated by the measured equipment may be determined by means of a substitution measurement in which a known signal source replaces the device to be measured.

The substitution antenna will replace the EUT antenna in the same position and in vertical polarization. The frequency of the signal generator shall be set to the frequencies that were measured on the EUT. The test antenna shall be raised and lowered, if necessary, to ensure that the maximum signal is still being received. The signal generator, output level, shall be adjusted until an equal or a known related level to what was measured from the EUT is obtained in the spectrum analyzer.

The radiated power is equal to the power supplied by the signal generator
The formula, to calculate the true reading, is: True reading = dBm + GdBd - CL

dBm = signal generator output level
GdBd = the gain in dBd of the substitution antenna
CL = the cable loss

The calculated True reading is then compared to the limit and should not exceed the limit. This method must be performed for every emission measured from the EUT. This shall also be repeated for horizontal polarization.

Minimum Requirement:

The magnitude of each spurious and harmonic emissions detected as being radiated from the EUT must be at a level no more than $43 + 10 \log$ (mean output power, watts) dB below the mean power output.

Test procedure:

EUT's antenna port was terminated with a 50-ohm load. The EUT was placed on a wooden table on the outdoor ground plane. The search antenna was placed 1 meter from the EUT. The EUT was setup to its maximum output power at its lowest channel. All spurious emissions were measured. The measurements are repeated for the highest and a middle channel.

Test Result:

Complies. Spreadsheet shown below.

8/23/01
Pete Krebill

Frequency MHz	SA reading dBuV	Sig Gen dBm	CL dB	Gain dBi	Gain dBd	ERP dBm	Limit dBm	Margin dB
Channel 25								
3702	47.76	-59.9	1.5	9	6.8	-54.6	-13	-41.6
5554	40.7	-64.8	2.3	10	7.8	-59.3	-13	-46.3
Channel 600								
3760	45.61	-60.6	1.5	9	6.8	-55.3	-13	-42.3
5640	39.25	-62.7	2.3	10	7.8	-57.2	-13	-44.2
Channel 1175								
3817	48.69	-58.4	1.5	9	6.8	-53.1	-13	-40.1
5726	42.93	-58.5	2.3	10	7.8	-53	-13	-40
Noise floor readings below:								
7405	28	-90	3	10.9	8.7	-84.3	-13	-71.3
9256	31.3	-90	6.2	11	8.8	-87.4	-13	-74.4
11107	30.42	-85.2	6.4	12.2	10	-81.6	-13	-68.6
12959	33.5	-70.2	5.8	11.8	9.6	-66.4	-13	-53.4
14800	34.8	-65.2	8	13.8	11.6	-61.6	-13	-48.6
16661	34.77	-60.2	10	12.5	10.3	-59.9	-13	-46.9
185125	34.98	-53.2	14.6	23.5	21.3	-46.5	-13	-33.5

SECTION 2.1055: FREQUENCY STABILITY

SECTION 24.235: FREQUENCY STABILITY

Minimum standard:

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Procedure frequency/temperature:

The EUT was setup in a temperature chamber. The EUT was setup to its maximum output power at its lowest channel. The temperature was varied in 10 degree steps from -30° C to +50° C. Enough time was allowed for the EUT's temperature to stabilize at each temperature. The block edge emissions were measured at each temperature after the temperature stabilized. The procedure described in the *Spurious Emissions at Antenna Terminal* section for measuring block edge emissions was used.

Test Procedure frequency/voltage AC:

Band edge emissions were measured with the AC voltage to the EUT's SMPS adjusted to 85% and 115% of nominal. The procedure described in the *Spurious Emissions at Antenna Terminal* section of this report for measuring block edge emissions was used.

Test Results:

Block edge measurements were compliant with the FCC 24.238 limits for all of the conditions listed above.


SETUP PHOTOS



ANTENNA CONDUCTED & FREQUENCY STABILITY



EIRP RADIATED



ANTENNA CONDUCTED & FREQUENCY STABILITY



SPURIOUS RADIATED



SUBSTITUTION