



**CFR 47 FCC PART 15 SUBPART C
ISED RSS-247 ISSUE 2**

TEST REPORT

For

Outdoor Plug TCO

MODEL NUMBER: CPLGOD2BLG1

HVIN: CPLGOD2BLG2

REPORT NUMBER: 4790448291-1-RF-2

ISSUE DATE: June 23, 2022

FCC ID:PUU-CPLGOD2BLG2

IC:10798A-CPLGOD2BLG2

Prepared for

GE Lighting

1975 Noble Road Cleveland, Ohio 44112 United States

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.



Revision History

Rev.	Issue Date	Revisions	Revised By
V0	June 23, 2022	Initial Issue	

**Summary of Test Results**

Summary of Test Results			
Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC Part 15.203/15.247 (c) RSS-GEN Clause 6.8	Pass
AC Power Line Conducted Emission	ANSI C63.10-2013, Clause 6.2	FCC Part 15.207 RSS-GEN Clause 8.8	Pass
Conducted Output Power	ANSI C63.10-2013, Clause 11.9.1.3	FCC Part 15.247 (b)(3) RSS-247 Clause 5.4 (d)	Pass
6dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2013, Clause 11.8.1	FCC Part 15.247 (a)(2) RSS-247 Clause 5.2 (a) ISED RSS-Gen Clause 6.7	Pass
Power Spectral Density	ANSI C63.10-2013, Clause 11.10.2	FCC Part 15.247 (e) RSS-247 Clause 5.2 (b)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2013, Clause 11.11	FCC Part 15.247(d) RSS-247 Clause 5.5	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2013, Clause 11.12 & Clause 11.13	FCC Part 15.247 (d) FCC Part 15.205/15.209 RSS-247 Clause 5.5 RSS-GEN Clause 8.9	Pass
Duty Cycle	ANSI C63.10-2013, Clause 11.6	None; for reporting purposes only.	Pass

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C ISED RSS-247 ISSUE 2> when <Accuracy Method> decision rule is applied.

CONTENTS

1. ATTESTATION OF TEST RESULTS	6
2. TEST METHODOLOGY	7
3. FACILITIES AND ACCREDITATION	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	8
4.2. <i>MEASUREMENT UNCERTAINTY</i>	8
5. EQUIPMENT UNDER TEST	9
5.1. <i>DESCRIPTION OF EUT</i>	9
5.2. <i>CHANNEL LIST</i>	9
5.3. <i>MAXIMUM AVERAGE EIRP</i>	9
5.4. <i>TEST CHANNEL CONFIGURATION</i>	9
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER</i>	10
5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	11
5.7. <i>SUPPORT UNITS FOR SYSTEM TEST</i>	12
5.8. <i>SETUP DIAGRAM</i>	12
6. MEASURING EQUIPMENT AND SOFTWARE USED	13
7. ANTENNA PORT TEST RESULTS	16
7.1. <i>CONDUCTED OUTPUT POWER</i>	16
7.2. <i>6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH</i>	18
7.3. <i>POWER SPECTRAL DENSITY</i>	20
7.4. <i>CONDUCTED BAND EDGE AND SPURIOUS EMISSION</i>	21
7.5. <i>DUTY CYCLE</i>	23
8. RADIATED TEST RESULTS	24
8.1. <i>RESTRICTED BANDEDGE</i>	31
8.2. <i>SPURIOUS EMISSIONS(1 GHZ~3 GHZ)</i>	42
8.3. <i>SPURIOUS EMISSIONS(3 GHZ~18 GHZ)</i>	48
8.4. <i>SPURIOUS EMISSIONS(9 KHZ~30 MHZ)</i>	66
8.5. <i>SPURIOUS EMISSIONS(18 GHZ~26 GHZ)</i>	69
8.6. <i>SPURIOUS EMISSIONS(30 MHZ~1 GHZ)</i>	71
9. ANTENNA REQUIREMENT	73
10. AC POWER LINE CONDUCTED EMISSION	74
11. ST DATA	77



11.1.	<i>APPENDIX A: DTS BANDWIDTH</i>	77
11.1.1.	Test Result	77
11.1.2.	Test Graphs	78
11.2.	<i>APPENDIX B: OCCUPIED CHANNEL BANDWIDTH</i>	81
11.2.1.	Test Result	81
11.2.2.	Test Graphs	82
11.3.	<i>APPENDIX C: MAXIMUM AVERAGE CONDUCTED OUTPUT POWER</i>	85
11.3.1.	Test Result	85
11.4.	<i>APPENDIX D: MAXIMUM AVERAGE POWER SPECTRAL DENSITY</i>	86
11.4.1.	Test Result	86
11.4.2.	Test Graphs	87
11.5.	<i>APPENDIX E: BAND EDGE MEASUREMENTS</i>	90
11.5.1.	Test Result	90
11.5.2.	Test Graphs	91
11.6.	<i>APPENDIX F: CONDUCTED SPURIOUS EMISSION</i>	93
11.6.1.	Test Result	93
11.6.2.	Test Graphs	94
11.7.	<i>APPENDIX G: DUTY CYCLE</i>	103
11.7.1.	Test Result	103
11.7.2.	Test Graphs	104



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: GE Lighting
Address: 1975 Noble Road Cleveland, Ohio 44112 United States

Manufacturer Information

Company Name: GE Lighting
Address: 1975 Noble Road Cleveland, Ohio 44112 United States

EUT Information

EUT Name: Outdoor Plug TCO
Model: CPLGOD2BLG1
Sample Received Date: June 13, 2022
Sample Status: Normal
Sample ID: 5051105
Date of Tested: June 13, 2022 to June 23, 2022

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C ISED RSS-247 ISSUE 2	Pass

Prepared By:

Kebo Zhang
Engineer Project Associate

Checked By:

Shawn Wen
Laboratory Leader

Approved By:

Stephen Guo
Laboratory Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, CFR 47 FCC Part 15, ANSI C63.10-2013, ISED RSS-247 Issue 2 and ISED RSS-GEN Issue 5.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p>A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p>ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	---

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.



4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Measurement Frequency Range	K	U(dB)
Conducted emissions from the AC mains power ports	0.009 MHz ~ 0.15 MHz	2	4.00
Conducted emissions from the AC mains power ports	0.15 MHz ~ 30 MHz	2	3.62
Radiated emissions	9kHz ~ 30MHz	2	2.20
Radiated emissions	30 MHz ~ 1 GHz	2	3.16
Radiated emissions	1 GHz ~ 18 GHz	2	5.64

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	Outdoor Plug TCO
Model	CPLGOD2BLG1

Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2412 MHz to 2462 MHz
Type of Modulation:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g/n: OFDM(64-QAM, 16-QAM, QPSK, BPSK)
Data Rate:	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g: Up to 54 Mbps IEEE 802.11n: Up to MCS7
Number of Channels:	IEEE 802.11b/g/n-HT20: 11
Normal Test Voltage:	AC 120 V, 60 Hz

5.2. CHANNEL LIST

Channel List for 802.11b/g/n (20 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452	/	/

5.3. MAXIMUM AVERAGE EIRP

IEEE Std. 802.11	Frequency (MHz)	Channel Number	Maximum Conducted AVG Output Power (dBm)	Maximum AVG EIRP (dBm)
b	2412 ~ 2462	1-11[11]	14.65	16.29
g	2412 ~ 2462	1-11[11]	13.90	15.54
n HT20	2412 ~ 2462	1-11[11]	13.91	15.55

5.4. TEST CHANNEL CONFIGURATION

IEEE Std. 802.11	Test Channel Number	Frequency
b	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
g	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT20	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz



5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band							
Test Software		AmebaZ2_mptool					
Modulation Mode	Transmit Antenna Number	Test Channel					
		NCB: 20MHz			NCB: 40MHz		
		CH 1	CH 6	CH 11	CH 3	CH 6	CH 9
802.11b	1	Default	Default	Default	/		
802.11g	1	Default	Default	Default			
802.11n HT20	1	Default	Default	Default			

WORST-CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst-case data rates as provided by the client were:

- 802.11b mode: 1 Mbps
- 802.11g mode: 6 Mbps
- 802.11n HT20 mode: MCS0

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.



5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2412-2462	PCB IFA antenna	1.64

Test Mode	Transmit and Receive Mode	Description
IEEE 802.11b	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11g	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT20	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.

Note: The value of the antenna gain was declared by customer.

5.7. SUPPORT UNITS FOR SYSTEM TEST

Item	Equipment	Brand Name	Model Name	P/N
1	Laptop	ThinkPad	T460S	SL10K24796 JS
2	UART	/	/	/
3	Light	/	/	/
4	LED light	/	/	/


I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	/	/	1.0	/

ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
1	/	/	/	/

5.8. SETUP DIAGRAM



**6. MEASURING EQUIPMENT AND SOFTWARE USED**

R&S TS 8997 Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Power sensor, Power Meter	R&S	OSP120	100921	Mar.23,2021	Mar.22,2022
Vector Signal Generator	R&S	SMBV100A	261637	Oct.30, 2021	Oct.29, 2022
Signal Generator	R&S	SMB100A	178553	Oct.30, 2021	Oct.29, 2022
Signal Analyzer	R&S	FSV40	101118	Oct.30, 2021	Oct.29, 2022
Software					
Description	Manufacturer	Name		Version	
For R&S TS 8997 Test System	Rohde & Schwarz	EMC 32		10.60.10	
Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Wideband Radio Communication Tester	R&S	CMW500	155523	Oct.30, 2021	Oct.29, 2022
Wireless Connectivity Tester	R&S	CMW270	1201.0002N75-102	Sep.29, 2021	Sep.28, 2022
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Oct.30, 2021	Oct.29, 2022
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Oct.30, 2021	Oct.29, 2022
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Oct.30, 2021	Oct.29, 2022
DC power supply	Keysight	E3642A	MY55159130	Oct.30, 2021	Oct.29, 2022
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Nov.20,2020	Nov.19,2022
Software					
Description	Manufacturer	Name		Version	
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System		2.6.77.0518	
Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Oct.30, 2021	Oct.29, 2022
Two-Line V-Network	R&S	ENV216	101983	Oct.30, 2021	Oct.29, 2022
Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Oct.30, 2021	Oct.29, 2022



Software					
Description		Manufacturer	Name	Version	
Test Software for Conducted Emissions		Farad	EZ-EMC	Ver. UL-3A1	
Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Oct.30, 2021	Oct.29, 2022
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130959	Aug.02, 2021	Aug.01, 2024
Preamplifier	HP	8447D	2944A09099	Oct.30, 2021	Oct.29, 2022
EMI Measurement Receiver	R&S	ESR26	101377	Oct.30, 2021	Oct.29, 2022
Horn Antenna	TDK	HRN-0118	130940	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Oct.30, 2021	Oct.29, 2022
Horn Antenna	Schwarzbeck	BBHA9170	697	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-2	TRS-307-00003	Oct.31, 2021	Oct.30, 2022
Preamplifier	TDK	PA-02-3	TRS-308-00002	Oct.31, 2021	Oct.30, 2022
Loop antenna	Schwarzbeck	1519B	00008	Dec.14, 2021	Dec.13, 2024
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Oct.31, 2021	Oct.30, 2022
Preamplifier	Mini-Circuits	ZX60-83LN-S+	SUP01201941	Oct.31, 2021	Oct.30, 2022
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Oct.31, 2021	Oct.30, 2022
Highpass Filter	Wainwright	WHKX10-5850-6500-1800-40SS	4	Oct.31, 2021	Oct.30, 2022
Band Reject Filter	Wainwright	WRCJV12-5695-5725-5850-5880-40SS	4	Oct.31, 2021	Oct.30, 2022
Band Reject Filter	Wainwright	WRCJV20-5120-5150-5350-5380-60SS	2	Oct.31, 2021	Oct.30, 2022
Band Reject Filter	Wainwright	WRCJV20-5440-5470-5725-5755-60SS	1	Oct.31, 2021	Oct.30, 2022
Band Reject Filter	Wainwright	WRCJV8-2350-2400-	4	Oct.31, 2021	Oct.30, 2022



		2483.5- 2533.5-40SS			
Band Reject Filter	Wainwright	WRCD5- 1879- 1879.85- 1880.15- 1881-40SS	1	Oct.31, 2021	Oct.30, 2022
Notch Filter	Wainwright	WHJ10-882- 980-7000- 40SS	1	Oct.31, 2021	Oct.30, 2022
Software					
Description		Manufacturer	Name	Version	
Test Software for Radiated Emissions		Farad	EZ-EMC	Ver. UL-3A1	
Other Instrument					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Temperature humidity probe	OMEGA	ITHX-SD-5	18470007	Nov. 4, 2021	Nov. 3, 2022
Barometer	Yiyi	Baro	N/A	Nov. 15, 2021	Nov. 14, 2022

7. ANTENNA PORT TEST RESULTS

7.1. CONDUCTED OUTPUT POWER

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3) ISED RSS-247 5.4 (d)	AVG Output Power	1 watt or 30 dBm	2400-2483.5

TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 11.9.2.3.1.

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the average output power, after any corrections for external attenuators and cables.

The test result in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.

TEST SETUP





TEST ENVIRONMENT

Temperature	23,5°C	Relative Humidity	69%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

TEST RESULTS

Please refer to section "Test Data" - Appendix C

7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2) ISED RSS-247 5.2 (a)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	For reporting purposes only.	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.

Connect the EUT to the spectrum analyser and use the following settings:


Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: ≥3 × RBW For 99 % Occupied Bandwidth: ≥3 × RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



TEST SETUP



TEST ENVIRONMENT

Temperature	23.5°C	Relative Humidity	69%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

TEST RESULTS

Please refer to section "Test Data" - Appendix A&B

7.3. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e) ISED RSS-247 5.2 (b)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.5.


Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	power averaging (rms) or sample detector
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x OBW bandwidth
Trace	Average
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT

Temperature	23.5°C	Relative Humidity	69%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

TEST RESULTS

Please refer to section "Test Data" - Appendix D



7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d) ISED RSS-247 5.5	Conducted Bandedge and Spurious Emissions	at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyser and use the following settings for reference level measurement:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.


Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.



TEST SETUP



TEST ENVIRONMENT

Temperature	23.5°C	Relative Humidity	69%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

TEST RESULTS

Please refer to section "Test Data" - Appendix E&F



7.5. DUTY CYCLE


LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	23.5°C	Relative Humidity	69%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

TEST RESULTS

Please refer to section "Test Data" - Appendix G



8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Please refer to ISED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (uA/m)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.



ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

Table 7 – Restricted frequency bands ^{Note 1}		
MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.
²Above 38.6c

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω. For example, the measurement frequency X KHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1G

The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

For Band edge note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Horizontal and Vertical have been tested, only the worst data was recorded in the report.

For Radiate Spurious emission 1GHz-3GHz note:

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
 5. For the transmitting duration, please refer to clause 7.5.
 6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
 7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
4. All modes and channels have been tested, only the worst data was recorded in the report.

For Radiate Spurious emission 3GHz-18GHz note:

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
 5. For the transmitting duration, please refer to clause 7.5.
 6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
 7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

For Radiate Spurious emission 9kHz-30MHz note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes and channels have been tested, only the worst data was recorded in the report.


For Radiate Spurious emission 18GHz-26GHz note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. All modes and channels have been tested, only the worst data was recorded in the report.


For Radiate Spurious emission 30MHz-1GHz note:

1. Result Level = Read Level + Correct Factor.
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.
4. All modes and channels have been tested, only the worst data was recorded in the report.


TEST SETUP



Below 1 GHz and above 30 MHz



Above 1 GHz



TEST ENVIRONMENT


Temperature	26.3°C	Relative Humidity	62%
Atmosphere Pressure	101kPa	Test Voltage	

TEST RESULTS



8.1. RESTRICTED BANDEDGE


Test Mode:	802.11b PK	Channel:	2412
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2379.000	19.11	32.13	51.24	74.00	-22.76	peak
2	2390.000	16.55	32.16	48.71	74.00	-25.29	peak




Test Mode:	802.11b PK	Channel:	2412
Polarity:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	13.84	32.16	46.00	74.00	-28.00	peak




Test Mode:	802.11b PK	Channel:	2462
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	18.24	32.44	50.68	74.00	-23.32	peak
2	2486.800	21.00	32.45	53.45	74.00	-20.55	peak




Test Mode:	802.11g PK	Channel:	2412
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	25.66	32.16	57.82	74.00	-16.18	peak




Test Mode:	802.11g AV	Channel:	2412
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	10.93	32.16	43.09	54.00	-10.91	AVG




Test Mode:	802.11g PK	Channel:	2462
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	34.06	32.44	66.50	74.00	-7.50	peak




Test Mode:	802.11g AV	Channel:	2462
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	14.89	32.44	47.33	54.00	-6.67	AVG




Test Mode:	802.11n HT20 PK	Channel:	2412
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	27.81	32.16	59.97	74.00	-14.03	peak




Test Mode:	802.11n HT20 AV	Channel:	2412
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	13.10	32.16	45.26	54.00	-8.74	AVG




Test Mode:	802.11n HT20 PK	Channel:	2462
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	33.39	32.44	65.83	74.00	-8.17	peak



Test Mode:	802.11n HT20 AV	Channel:	2462
Polarity:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	15.39	32.44	47.83	54.00	-6.17	AVG



8.2. SPURIOUS EMISSIONS(1 GHz~3 GHz)


Test Mode:	802.11b	Channel:	2412
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1008.000	49.80	-15.02	34.78	74.00	-39.22	peak
2	2092.000	51.94	-10.51	41.43	74.00	-32.57	peak
3	2314.000	52.90	-9.31	43.59	74.00	-30.41	peak
4	2396.000	67.63	-8.87	58.76	74.00	-15.24	peak
5	2396.000	31.10	-8.87	22.23	54.00	-31.77	AVG
6	2412.000	57.76	-8.78	48.98	/	/	fundamental
7	2716.000	61.10	-7.74	53.36	74.00	-20.64	peak




Test Mode:	802.11b	Channel:	2412
Polarity:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1008.000	49.56	-15.02	34.54	74.00	-39.46	peak
2	1248.000	45.98	-13.81	32.17	74.00	-41.83	peak
3	1704.000	45.82	-11.91	33.91	74.00	-40.09	peak
4	2092.000	49.20	-10.51	38.69	74.00	-35.31	peak
5	2396.000	57.27	-8.87	48.40	74.00	-25.60	peak
6	2412.000	53.60	-8.78	44.82	/	/	fundamental




Test Mode:	802.11b	Channel:	2437
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1006.000	49.13	-15.03	34.10	74.00	-39.90	peak
2	2116.000	53.46	-10.38	43.08	74.00	-30.92	peak
3	2338.000	52.78	-9.18	43.60	74.00	-30.40	peak
4	2424.000	57.34	-8.72	48.62	74.00	-25.38	peak
5	2437.000	60.23	-8.64	51.59	/	/	fundamental
6	2760.000	59.89	-7.62	52.27	74.00	-21.73	peak




Test Mode:	802.11b	Channel:	2437
Polarity:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1006.000	47.66	-15.03	32.63	74.00	-41.37	peak
2	1512.000	45.77	-12.49	33.28	74.00	-40.72	peak
3	1776.000	45.24	-11.69	33.55	74.00	-40.45	peak
4	2118.000	49.91	-10.36	39.55	74.00	-34.45	peak
5	2437.000	55.24	-8.64	46.60	/	/	fundamental
6	2758.000	52.99	-7.63	45.36	74.00	-28.64	peak




Test Mode:	802.11b	Channel:	2462
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1008.000	48.95	-15.02	33.93	74.00	-40.07	peak
2	1560.000	45.82	-12.35	33.47	74.00	-40.53	peak
3	2148.000	55.95	-10.21	45.74	74.00	-28.26	peak
4	2328.000	51.37	-9.24	42.13	74.00	-31.87	peak
5	2450.000	61.00	-8.57	52.43	74.00	-21.57	peak
6	2462.000	60.95	-8.52	52.43	/	/	fundamental



Test Mode:	802.11b	Channel:	2462
Polarity:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1008.000	48.53	-15.02	33.51	74.00	-40.49	peak
2	1504.000	45.16	-12.52	32.64	74.00	-41.36	peak
3	1768.000	48.28	-11.71	36.57	74.00	-37.43	peak
4	2142.000	51.60	-10.23	41.37	74.00	-32.63	peak
5	2462.000	54.99	-8.52	46.47	/	/	fundamental
6	2782.000	52.98	-7.56	45.42	74.00	-28.58	peak



8.3. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)


Test Mode:	802.11b	Channel:	2412
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	46.74	-0.82	45.92	74.00	-28.08	peak
2	7830.000	38.52	5.72	44.24	74.00	-29.76	peak
3	9150.000	37.02	9.75	46.77	74.00	-27.23	peak
4	11820.000	35.45	16.49	51.94	74.00	-22.06	peak
5	13995.000	32.02	21.07	53.09	74.00	-20.91	peak
6	17385.000	30.64	21.16	51.80	74.00	-22.20	peak




Test Mode:	802.11b	Channel:	2412
Polarity:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	46.54	-0.82	45.72	74.00	-28.28	peak
2	7965.000	38.29	5.76	44.05	74.00	-29.95	peak
3	9345.000	37.42	9.94	47.36	74.00	-26.64	peak
4	11370.000	36.67	15.00	51.67	74.00	-22.33	peak
5	13920.000	31.98	20.87	52.85	74.00	-21.15	peak
6	17985.000	27.96	24.53	52.49	74.00	-21.51	peak




Test Mode:	802.11b	Channel:	2437
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	44.79	-0.58	44.21	74.00	-29.79	peak
2	7305.000	38.16	5.71	43.87	74.00	-30.13	peak
3	9075.000	37.30	9.69	46.99	74.00	-27.01	peak
4	11760.000	36.11	16.32	52.43	74.00	-21.57	peak
5	13950.000	32.28	20.96	53.24	74.00	-20.76	peak
6	18000.000	27.76	24.62	52.38	74.00	-21.62	peak




Test Mode:	802.11b	Channel:	2437
Polarity:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	46.50	-0.58	45.92	74.00	-28.08	peak
2	7305.000	39.24	5.71	44.95	74.00	-29.05	peak
3	9345.000	37.99	9.94	47.93	74.00	-26.07	peak
4	11790.000	35.56	16.40	51.96	74.00	-22.04	peak
5	13965.000	31.46	20.99	52.45	74.00	-21.55	peak
6	18000.000	27.51	24.62	52.13	74.00	-21.87	peak




Test Mode:	802.11b	Channel:	2462
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	44.15	-0.41	43.74	74.00	-30.26	peak
2	7740.000	37.94	5.69	43.63	74.00	-30.37	peak
3	9150.000	36.96	9.75	46.71	74.00	-27.29	peak
4	11835.000	36.44	16.53	52.97	74.00	-21.03	peak
5	13935.000	32.76	20.91	53.67	74.00	-20.33	peak
6	17985.000	28.89	24.53	53.42	74.00	-20.58	peak




Test Mode:	802.11b	Channel:	2462
Polarity:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	45.31	-0.41	44.90	74.00	-29.10	peak
2	7845.000	38.41	5.73	44.14	74.00	-29.86	peak
3	9195.000	37.30	9.80	47.10	74.00	-26.90	peak
4	11835.000	35.62	16.53	52.15	74.00	-21.85	peak
5	13590.000	32.71	20.03	52.74	74.00	-21.26	peak
6	18000.000	27.00	24.62	51.62	74.00	-22.38	peak




Test Mode:	802.11g	Channel:	2412
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4830.000	44.91	-0.76	44.15	74.00	-29.85	peak
2	7755.000	38.63	5.69	44.32	74.00	-29.68	peak
3	8940.000	38.08	9.24	47.32	74.00	-26.68	peak
4	12735.000	34.93	17.37	52.30	74.00	-21.70	peak
5	13920.000	31.87	20.87	52.74	74.00	-21.26	peak
6	18000.000	28.28	24.62	52.90	74.00	-21.10	peak




Test Mode:	802.11g	Channel:	2412
Polarity:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	44.85	-0.88	43.97	74.00	-30.03	peak
2	7890.000	38.50	5.73	44.23	74.00	-29.77	peak
3	9375.000	37.10	9.98	47.08	74.00	-26.92	peak
4	11895.000	35.64	16.70	52.34	74.00	-21.66	peak
5	13785.000	32.34	20.53	52.87	74.00	-21.13	peak
6	17940.000	27.36	24.26	51.62	74.00	-22.38	peak




Test Mode:	802.11g	Channel:	2437
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4860.000	43.02	-0.65	42.37	74.00	-31.63	peak
2	7875.000	38.33	5.72	44.05	74.00	-29.95	peak
3	9195.000	37.36	9.80	47.16	74.00	-26.84	peak
4	11850.000	35.78	16.58	52.36	74.00	-21.64	peak
5	13560.000	32.94	19.96	52.90	74.00	-21.10	peak
6	17910.000	28.74	24.08	52.82	74.00	-21.18	peak




Test Mode:	802.11g	Channel:	2437
Polarity:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4860.000	43.72	-0.65	43.07	74.00	-30.93	peak
2	7305.000	39.22	5.71	44.93	74.00	-29.07	peak
3	9135.000	37.32	9.75	47.07	74.00	-26.93	peak
4	11865.000	35.28	16.61	51.89	74.00	-22.11	peak
5	13530.000	32.78	19.88	52.66	74.00	-21.34	peak
6	17370.000	31.76	21.11	52.87	74.00	-21.13	peak




Test Mode:	802.11g	Channel:	2462
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	42.04	-0.41	41.63	74.00	-32.37	peak
2	7335.000	38.03	5.69	43.72	74.00	-30.28	peak
3	8985.000	37.33	9.51	46.84	74.00	-27.16	peak
4	11520.000	36.07	15.64	51.71	74.00	-22.29	peak
5	13560.000	33.00	19.96	52.96	74.00	-21.04	peak
6	17985.000	28.01	24.53	52.54	74.00	-21.46	peak




Test Mode:	802.11g	Channel:	2462
Polarity:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	43.33	-0.41	42.92	74.00	-31.08	peak
2	7815.000	39.03	5.72	44.75	74.00	-29.25	peak
3	9375.000	37.14	9.98	47.12	74.00	-26.88	peak
4	11760.000	35.83	16.32	52.15	74.00	-21.85	peak
5	13965.000	31.17	20.99	52.16	74.00	-21.84	peak
6	17385.000	30.88	21.16	52.04	74.00	-21.96	peak




Test Mode:	802.11n HT20	Channel:	2412
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	44.39	-0.82	43.57	74.00	-30.43	peak
2	7890.000	38.09	5.73	43.82	74.00	-30.18	peak
3	9270.000	37.21	9.87	47.08	74.00	-26.92	peak
4	11865.000	35.70	16.61	52.31	74.00	-21.69	peak
5	14010.000	31.74	21.05	52.79	74.00	-21.21	peak
6	17670.000	29.65	22.62	52.27	74.00	-21.73	peak




Test Mode:	802.11n HT20	Channel:	2412
Polarity:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4830.000	44.01	-0.76	43.25	74.00	-30.75	peak
2	8985.000	37.33	9.51	46.84	74.00	-27.16	peak
3	11835.000	34.99	16.53	51.52	74.00	-22.48	peak
4	12615.000	35.54	17.18	52.72	74.00	-21.28	peak
5	13965.000	31.24	20.99	52.23	74.00	-21.77	peak
6	17280.000	30.92	20.77	51.69	74.00	-22.31	peak




Test Mode:	802.11n HT20	Channel:	2437
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4860.000	42.60	-0.65	41.95	74.00	-32.05	peak
2	7710.000	38.39	5.69	44.08	74.00	-29.92	peak
3	9195.000	37.09	9.80	46.89	74.00	-27.11	peak
4	11820.000	35.50	16.49	51.99	74.00	-22.01	peak
5	13920.000	31.37	20.87	52.24	74.00	-21.76	peak
6	17280.000	31.04	20.77	51.81	74.00	-22.19	peak




Test Mode:	802.11n HT20	Channel:	2437
Polarity:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4860.000	44.78	-0.65	44.13	74.00	-29.87	peak
2	7290.000	38.60	5.71	44.31	74.00	-29.69	peak
3	9375.000	36.75	9.98	46.73	74.00	-27.27	peak
4	11790.000	35.62	16.40	52.02	74.00	-21.98	peak
5	13950.000	31.18	20.96	52.14	74.00	-21.86	peak
6	18000.000	26.95	24.62	51.57	74.00	-22.43	peak




Test Mode:	802.11n HT20	Channel:	2462
Polarity:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	41.05	-0.41	40.64	74.00	-33.36	peak
2	7875.000	38.34	5.72	44.06	74.00	-29.94	peak
3	9030.000	37.43	9.64	47.07	74.00	-26.93	peak
4	11835.000	35.84	16.53	52.37	74.00	-21.63	peak
5	14070.000	31.84	20.79	52.63	74.00	-21.37	peak
6	17400.000	30.53	21.22	51.75	74.00	-22.25	peak



Test Mode:	802.11n HT20	Channel:	2462
Polarity:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4935.000	41.96	-0.36	41.60	74.00	-32.40	peak
2	7605.000	37.87	5.65	43.52	74.00	-30.48	peak
3	9345.000	36.93	9.94	46.87	74.00	-27.13	peak
4	11835.000	35.31	16.53	51.84	74.00	-22.16	peak
5	13935.000	31.93	20.91	52.84	74.00	-21.16	peak
6	17955.000	27.79	24.34	52.13	74.00	-21.87	peak



8.4. SPURIOUS EMISSIONS(9 kHz~30 MHz)


Test Mode:	802.11b	Channel:	2412
Polarity:	FACE ON TO THE EUT		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.0100	75.72	-101.40	-25.68	47.60	-77.18	-3.90	-73.28	peak
2	0.0131	72.47	-101.38	-28.91	45.25	-80.41	-6.25	-74.16	peak
3	0.0221	69.63	-101.35	-31.72	40.71	-83.22	-10.79	-72.43	peak
4	0.0286	66.96	-101.38	-34.42	38.47	-85.92	-13.03	-72.89	peak
5	0.0551	61.95	-101.50	-39.55	32.78	-91.05	-18.72	-72.33	peak
6	0.0830	60.18	-101.65	-41.47	29.22	-92.97	-22.28	-70.69	peak




Test Mode:	802.11b	Channel:	2412
Polarity:	FACE ON TO THE EUT		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.1554	75.77	-101.65	-25.88	23.77	-77.38	-27.73	-49.65	peak
2	0.1794	72.27	-101.68	-29.41	22.53	-80.91	-28.97	-51.94	peak
3	0.2190	68.27	-101.75	-33.48	20.79	-84.98	-30.71	-54.27	peak
4	0.2298	66.55	-101.77	-35.22	20.37	-86.72	-31.13	-55.59	peak
5	0.2942	62.82	-101.85	-39.03	18.23	-90.53	-33.27	-57.26	peak
6	0.3809	59.91	-101.94	-42.03	15.99	-93.53	-35.51	-58.02	peak



Test Mode:	802.11b	Channel:	2412
Polarity:	FACE ON TO THE EUT		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.5039	64.43	-62.07	2.36	33.56	-49.14	-17.94	-31.20	peak
2	0.8296	63.44	-62.17	1.27	29.23	-50.23	-22.27	-27.96	peak
3	1.6149	57.62	-62.00	-4.38	23.44	-55.88	-28.06	-27.82	peak
4	3.8246	55.20	-61.38	-6.18	29.54	-57.68	-21.96	-35.72	peak
5	11.8513	54.56	-60.88	-6.32	29.54	-57.82	-21.96	-35.86	peak
6	16.3959	54.67	-60.96	-6.29	29.54	-57.79	-21.96	-35.83	peak



8.5. SPURIOUS EMISSIONS(18 GHz~26 GHz)


Test Mode:	802.11b	Channel:	2412
Polarity:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18616.000	50.39	-5.34	45.05	74.00	-28.95	peak
2	19784.000	49.57	-5.28	44.29	74.00	-29.71	peak
3	21544.000	48.76	-4.63	44.13	74.00	-29.87	peak
4	23088.000	48.02	-3.41	44.61	74.00	-29.39	peak
5	24568.000	47.10	-2.33	44.77	74.00	-29.23	peak
6	25728.000	45.61	-0.72	44.89	74.00	-29.11	peak



Test Mode:	802.11b	Channel:	2412
Polarity:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18144.000	50.27	-5.48	44.79	74.00	-29.21	peak
2	19392.000	50.12	-5.57	44.55	74.00	-29.45	peak
3	21600.000	49.52	-4.54	44.98	74.00	-29.02	peak
4	22160.000	49.08	-4.31	44.77	74.00	-29.23	peak
5	23744.000	48.15	-3.20	44.95	74.00	-29.05	peak
6	25000.000	46.86	-2.10	44.76	74.00	-29.24	peak



8.6. SPURIOUS EMISSIONS(30 MHz~1 GHz)


Test Mode:	802.11b	Channel:		2412
Polarity:	Horizontal			



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	120.2100	57.30	-19.85	37.45	43.50	-6.05	QP
2	288.0200	56.59	-16.06	40.53	46.00	-5.47	QP
3	468.4400	52.35	-12.04	40.31	46.00	-5.69	QP
4	540.2199	51.22	-10.49	40.73	46.00	-5.27	QP
5	743.9200	46.74	-7.92	38.82	46.00	-7.18	QP
6	875.8400	46.24	-5.63	40.61	46.00	-5.39	QP



Test Mode:	802.11b	Channel:	2412
Polarity:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	120.2100	57.73	-19.85	37.88	43.50	-5.62	QP
2	203.6300	56.23	-16.70	39.53	43.50	-3.97	QP
3	323.9100	57.03	-14.74	42.29	46.00	-3.71	QP
4	348.1600	56.14	-14.34	41.80	46.00	-4.20	QP
5	468.4400	52.56	-12.04	40.52	46.00	-5.48	QP
6	540.2199	53.11	-10.49	42.62	46.00	-3.38	QP



9. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DESCRIPTION

10. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8


FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP




TEST ENVIRONMENT

Temperature	23.8°C	Relative Humidity	59.7%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz



TEST RESULTS

Test Mode:	802.11b	Channel:	2412
------------	---------	----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1548	32.33	9.50	41.83	65.74	-23.91	QP
2	0.1548	12.83	9.50	22.33	55.74	-33.41	AVG
3	0.1858	40.61	9.56	50.17	64.22	-14.05	QP
4	0.1858	24.23	9.56	33.79	54.22	-20.43	AVG
5	0.2067	41.55	9.59	51.14	63.34	-12.20	QP
6	0.2067	27.39	9.59	36.98	53.34	-16.36	AVG
7	0.5806	37.01	9.50	46.51	56.00	-9.49	QP
8	0.5806	24.54	9.50	34.04	46.00	-11.96	AVG
9	2.7612	30.38	9.62	40.00	56.00	-16.00	QP
10	2.7612	21.74	9.62	31.36	46.00	-14.64	AVG
11	4.7943	30.75	9.45	40.20	56.00	-15.80	QP
12	4.7943	21.45	9.45	30.90	46.00	-15.10	AVG


Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.



Test Mode:	802.11b	Channel:	2412
Line:	Neutral		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.2163	41.23	9.58	50.81	62.96	-12.15	QP
2	0.2163	28.21	9.58	37.79	52.96	-15.17	AVG
3	0.2513	40.81	9.57	50.38	61.71	-11.33	QP
4	0.2513	27.30	9.57	36.87	51.71	-14.84	AVG
5	0.3232	42.90	9.55	52.45	59.62	-7.17	QP
6	0.3232	25.68	9.55	35.23	49.62	-14.39	AVG
7	0.4767	38.57	9.51	48.08	56.40	-8.32	QP
8	0.4767	26.20	9.51	35.71	46.40	-10.69	AVG
9	0.5868	36.63	9.50	46.13	56.00	-9.87	QP
10	0.5868	25.65	9.50	35.15	46.00	-10.85	AVG
11	4.0108	33.84	9.60	43.44	56.00	-12.56	QP
12	4.0108	28.48	9.60	38.08	46.00	-7.92	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.




11. ST DATA

11.1. APPENDIX A: DTS BANDWIDTH



11.1.1. Test Result

Test Mode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	8.52	2407.96	2416.48	0.5	PASS
		2437	9.56	2431.92	2441.48	0.5	PASS
		2462	9.04	2457.44	2466.48	0.5	PASS
11G	Ant1	2412	16.32	2403.80	2420.12	0.5	PASS
		2437	16.32	2428.80	2445.12	0.5	PASS
		2462	16.32	2453.80	2470.12	0.5	PASS
11N20SISO	Ant1	2412	17.76	2403.12	2420.88	0.5	PASS
		2437	17.56	2428.16	2445.72	0.5	PASS
		2462	17.60	2453.16	2470.76	0.5	PASS


11.1.2. Test Graphs




11B_Ant1_2462




11G_Ant1_2462



11N20SISO_Ant1_2412



11N20SISO_Ant1_2437



11N20SISO_Ant1_2462






11.2. APPENDIX B: OCCUPIED CHANNEL BANDWIDTH



11.2.1. Test Result

Test Mode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Verdict
11B	Ant1	2412	13.986	2405.007	2418.993	PASS
		2437	14.026	2429.967	2443.993	PASS
		2462	14.026	2454.967	2468.993	PASS
11G	Ant1	2412	17.502	2403.209	2420.711	PASS
		2437	17.502	2428.209	2445.711	PASS
		2462	17.622	2453.209	2470.831	PASS
11N20SISO	Ant1	2412	18.462	2402.769	2421.231	PASS
		2437	18.541	2427.729	2446.271	PASS
		2462	18.422	2452.809	2471.231	PASS


11.2.2. Test Graphs




11B_Ant1_2462




11G_Ant1_2462



11N20SISO_Ant1_2412



11N20SISO_Ant1_2437



11N20SISO_Ant1_2462



11.3. APPENDIX C: MAXIMUM AVERAGE CONDUCTED OUTPUT POWER

11.3.1. Test Result

Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	14.49	≤30.00	PASS
		2437	14.65	≤30.00	PASS
		2462	14.26	≤30.00	PASS
11G	Ant1	2412	13.75	≤30.00	PASS
		2437	13.90	≤30.00	PASS
		2462	13.41	≤30.00	PASS
11N20SISO	Ant1	2412	13.74	≤30.00	PASS
		2437	13.91	≤30.00	PASS
		2462	13.32	≤30.00	PASS

Note: 1. Conducted Power=Meas. Level+ Correction Factor

2. The Duty Cycle Factor (refer to section 7.1) had already compensated to the test data.




11.4. APPENDIX D: MAXIMUM AVERAGE POWER SPECTRAL DENSITY


11.4.1. Test Result

Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-16.22	≤8.00	PASS
		2437	-16.09	≤8.00	PASS
		2462	-16.6	≤8.00	PASS
11G	Ant1	2412	-17.49	≤8.00	PASS
		2437	-17.13	≤8.00	PASS
		2462	-16.71	≤8.00	PASS
11N20SISO	Ant1	2412	-16.8	≤8.00	PASS
		2437	-16.78	≤8.00	PASS
		2462	-17.05	≤8.00	PASS


Note: The Duty Cycle Factor (refer to section 7.1) is compensated in the graph.

11.4.2. Test Graphs







11G_Ant1_2412




11G_Ant1_2437




11G_Ant1_2462



11N20SISO_Ant1_2412



11N20SISO_Ant1_2437



11N20SISO_Ant1_2462




11.5. APPENDIX E: BAND EDGE MEASUREMENTS


11.5.1. Test Result

Test Mode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	Low	2412	6.58	-42.51	≤-23.42	PASS
		High	2462	4.98	-45.39	≤-25.02	PASS
11G	Ant1	Low	2412	2.42	-33.62	≤-27.58	PASS
		High	2462	2.03	-44.42	≤-27.97	PASS
11N20SISO	Ant1	Low	2412	1.62	-32.48	≤-28.38	PASS
		High	2462	2.08	-44.49	≤-27.92	PASS


11.5.2. Test Graphs






11B_Ant1_Low_2412



11B_Ant1_High_2462




11G_Ant1_Low_2412




**11.6. APPENDIX F: CONDUCTED SPURIOUS EMISSION****11.6.1. Test Result**


Test Mode	Antenna	Channel	FreqRange [Mhz]	Result [dBm]	Limit [dBm]	Verdict	
11B	Ant1	2412	Reference	6.85	---	PASS	
			30~1000	-53.67	≤-23.15	PASS	
			1000~26500	-47.62	≤-23.15	PASS	
		2437	Ant1	Reference	6.72	---	PASS
				30~1000	-53.15	≤-23.28	PASS
				1000~26500	-47.87	≤-23.28	PASS
		2462	Ant1	Reference	5.94	---	PASS
				30~1000	-52.77	≤-24.06	PASS
				1000~26500	-44.08	≤-24.06	PASS
11G	Ant1	2412	Reference	2.77	---	PASS	
			30~1000	-52.35	≤-27.23	PASS	
			1000~26500	-48.93	≤-27.23	PASS	
		2437	Ant1	Reference	3.11	---	PASS
				30~1000	-53.66	≤-26.89	PASS
				1000~26500	-49.13	≤-26.89	PASS
		2462	Ant1	Reference	2.61	---	PASS
				30~1000	-53.88	≤-27.39	PASS
				1000~26500	-47.84	≤-27.39	PASS
11N20SISO	Ant1	2412	Reference	2.79	---	PASS	
			30~1000	-54.03	≤-27.21	PASS	
			1000~26500	-48.77	≤-27.21	PASS	
		2437	Ant1	Reference	3.09	---	PASS
				30~1000	-54.28	≤-26.91	PASS
				1000~26500	-49.41	≤-26.91	PASS
		2462	Ant1	Reference	2.87	---	PASS
				30~1000	-54.41	≤-27.13	PASS
				1000~26500	-47.5	≤-27.13	PASS

11.6.2. Test Graphs







11B_Ant1_2437_0~Reference




11B_Ant1_2437_30~1000




11B_Ant1_2437_1000~26500




11B_Ant1_2462_0~Reference




11B_Ant1_2462_30~1000




11B_Ant1_2462_1000~26500




11G_Ant1_2412_0~Reference




11G_Ant1_2412_30~1000




11G_Ant1_2412_1000~26500




11G_Ant1_2437_0~Reference




11G_Ant1_2437_30~1000




11G_Ant1_2437_1000~26500




11G_Ant1_2462_0~Reference




11G_Ant1_2462_30~1000




11G_Ant1_2462_1000~26500




11N20SISO_Ant1_2412_0~Reference




11N20SISO_Ant1_2412_30~1000




11N20SISO_Ant1_2412_1000~26500




11N20SISO_Ant1_2437_0~Reference




11N20SISO_Ant1_2437_30~100




11N20SISO_Ant1_2437_1000~26500



11N20SISO_Ant1_2462_0~Reference



11N20SISO_Ant1_2462_30~100



11N20SISO_Ant1_2462_1000~26500



11.7. APPENDIX G: DUTY CYCLE

11.7.1. Test Result

Test Mode	On Time (msec)	Period (msec)	Duty Cycle _x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
11B	12.39	12.52	0.9896	98.96	0.05	0.08	0.01
11G	2.05	2.18	0.9404	94.04	0.27	0.49	1
11N20SISO	1.91	2.04	0.9363	93.63	0.29	0.52	1

Note:

Duty Cycle Correction Factor=10log (1/x).

Where: x is Duty Cycle (Linear)




Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.

For 802.11b mode, the duty cycle > 98%, so, VBW=10 Hz has been used to test.



11.7.2. Test Graphs



END OF REPORT