

Applicant: Savant Technologies LLC, dba GE Lighting, a Savant company

Product Name: RTL8721DM Module

Model Number: JXC8721-65

FCC ID: PUU-KEYPADSG2A

## RADIO FREQUENCY EXPOSURE COMPLIANCE RESULT:

Test Standard: FCC CFR 47 § 1.1310 : Radiofrequency radiation exposure limits.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

Note:

(1) Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when a person is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

(2) General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

MPE Calculation Standard:

$$MPE(S) = PG/(4\pi R^2)$$

where: S = power density (in appropriate units, e.g. mW/ cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

**Calculation Result:**

For this EUT, General population/uncontrolled exposure limits applied.

The limit value  $1.0\text{mW/cm}^2$  is available for this EUT.

Modulation	Peak Output Power		Antenna Gain		MPE	Limit	Verdict
	(dBm)	(mW)	(dBi)	(Numeric)	( $\text{mW/cm}^2$ )	( $\text{mW/cm}^2$ )	
BLE	5.586	3.6191	-2.72	0.53456	0.00038	1.0	Compliant
802.11b	12.22	16.6725	-2.72	0.53456	0.00177	1.0	Compliant
802.11g	9.23	8.37529	-2.72	0.53456	0.00089	1.0	Compliant
802.11n20	8.87	7.70903	-2.72	0.53456	0.00082	1.0	Compliant
802.11n40	11.77	15.0314	-2.72	0.53456	0.0016	1.0	Compliant
802.11a	11.06	12.7644	2.15	1.64059	0.00417	1.0	Compliant
802.11n20	11.33	13.5831	2.15	1.64059	0.00443	1.0	Compliant
802.11n40	9.57	9.05733	4.1	2.5704	0.00463	1.0	Compliant

For R = 20cm