

Test report No: RF Exposure

TEST REPORT

Radio Spectrum Matters (RF)

Identification of item tested	Cync dynamic effect indoor strip
Trademark	GE
Model and /or type reference	CSTR16CDID/ENS, CSTR32CDID/ENS
FCC ID	PUU-STR-CDID
Features	Adaptor: CLASS 2 POWER UNIT MODEL NO: XY24SR-240100VQ-UW INPUT: 100-240Vac, 50/60Hz, 0.6A MAX OUTPUT: 24Vdc, 1.0A
Applicant's name / address	Savant Technologies LLC, dba GE Lighting, a Savant Company 1975 Noble Road, Cleveland, OH, 44112, US.
Test method requested, standard	KDB 447498 D01V06 FCC Part 1.1310
Verdict Summary	COMPLIANCE
Tested by (name & signature)	Jazz Liang 
Approved by (name & signature)	Tim Yan 
Date of issue	2024-06-19
Report template No	TRF_EMCC 2017-06- FCC_Exposure

INDEX

	page
General conditions	3
Uncertainty	3
Environmental conditions	3
Possible test case verdicts	3
Definition of symbols used in this test report.....	4
Abbreviations	4
Document History	4
Remarks and Comments	4
1 General Information	5
1.1 General Description of the Item(s)	5
1.2 Test data.....	8
1.3 The environment(s) in which the EUT is intended to be used	8
2 Description of Test Setup	9
2.1 Operating mode(s) used for tests	9
2.2 Support / Auxiliary equipment / unit / software for the EUT.....	9
2.3 Test Configuration / Block diagram used for tests	9
2.4 Measurement procedure	10
3 RF Exposure Evaluation.....	11
3.1 Limits	11
3.2 Test Procedure	12
3.3 Test Result.....	12

GENERAL CONDITIONS

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.
5. This report will not be used for social proof function in China market.

UNCERTAINTY

For all measurements where guidance for the calculation of the instrumentation uncertainty of a measurement is specified in EN 55016-4-2 (CISPR 16-4-2), EN/IEC 61000-4 series or a product standard, the measurement instrumentation uncertainty has been calculated and applied in accordance with these standards.

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	15 °C – 35 °C
Relative Humidity air	30% - 60%
Atmospheric pressure	86 kPa – 106 kPa

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not measured	N/M

DEFINITION OF SYMBOLS USED IN THIS TEST REPORT

<input checked="" type="checkbox"/> Indicates that the listed condition, standard or equipment is applicable for this report/test/EUT.		
<input type="checkbox"/> Indicates that the listed condition, standard or equipment is not applicable for this report/test/EUT.		
Decimal separator used in this report	<input checked="" type="checkbox"/> Comma (,)	<input type="checkbox"/> Point (.)

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	: Equipment Under Test
QP	: Quasi-Peak
CAV	: CISPR Average
AV	: Average
CDN	: Coupling Decoupling Network
SAC	: Semi-Anechoic Chamber
OATS	: Open Area Test Site
BW	: Bandwidth
AM	: Amplitude Modulation
PM	: Pulse Modulation
HCP	: Horizontal Coupling Plane
VCP	: Vertical Coupling Plane
U_N	: Nominal voltage
T_x	: Transmitter
R_x	: Receiver
N/A	: Not Applicable
N/M	: Not Measured

DOCUMENT HISTORY

Report nr.	Date	Description
RF Exposure	2024-06-19	First release.

REMARKS AND COMMENTS

The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).

1 GENERAL INFORMATION

1.1 General Description of the Item(s)

Description of the item	Cync dynamic effect indoor strip
Trademark	GE
Model / Type number	CSTR16CDID/ENS, CSTR32CDID/ENS
FCC ID	PUU-STR-CDID
Ratings	Adaptor: CLASS 2 POWER UNIT MODEL NO: XY24SR-240100VQ-UW INPUT: 100-240Vac, 50/60Hz, 0.6A MAX OUTPUT: 24Vdc, 1.0A
Manufacturer.....	Same as applicant
Factory 1	Dongguan ZOYO Electronics Technology Co., Ltd. NO.11, Nange west Road, Nanya Village, Daojiao Town, Dongguan, Guangdong, China
Factory 2	SILVER AGE VIETNAM TECHNOLOGY COMPANY LIMITED. Lot A2, Gia Le industrial zone, Dong Xuan commune, Dong Hung district, Thai Binh province, VietNam.

Rated power supply	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	<input checked="" type="checkbox"/>	AC: 100-240 V, 50/60 Hz	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	AC:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	<input checked="" type="checkbox"/>	DC: 5 V					
Mounting position.....	<input checked="" type="checkbox"/> Table top equipment						
	<input type="checkbox"/> Wall/Ceiling mounted equipment						
	<input type="checkbox"/> Floor standing equipment						
	<input type="checkbox"/> Hand-held equipment						
	<input type="checkbox"/> Other:						

Based on customer description: Wireless module Characteristic

Wireless module No.....	JXC8720-18
Operating frequency range(s) – Tx :	2412 – 2462 MHz for 2.4G WIFI 2402 – 2480 MHz for Bluetooth
Operating frequency range(s) – Rx :	2412 – 2462 MHz for 2.4G WIFI 2402 – 2480 MHz for Bluetooth
Type of Modulation	WLAN 2.4GHz : IEEE 802.11b: DSSS (CCK, QPSK, BPSK); IEEE 802.11g: OFDM (BPSK, QPSK, 16QAM, 64QAM); IEEE 802.11n HT20: OFDM (BPSK, QPSK, 16QAM, 64QAM) Bluetooth LE:GFSK

Antenna type..... :	Integrate antenna
Antenna gain..... :	0.5 dBi
Operation temperature range	-20 – 40 °C

Antenna List

Antenna Model No.	N/A		
Antenna Manufacturer	N/A		
Antenna Delivery	<input checked="" type="checkbox"/> 1*TX+1*RX	<input type="checkbox"/> 2*TX+2*RX	<input type="checkbox"/> 3*TX+3*RX
Antenna Technology	<input checked="" type="checkbox"/> SISO		
	<input type="checkbox"/> MIMO	<input type="checkbox"/> Basic methodology	
		<input type="checkbox"/> Sectorized antenna systems	
		<input type="checkbox"/> Cross-polarized antennas	
		<input type="checkbox"/> Unequal antenna gains, with equal transmit powers	
		<input type="checkbox"/> Spatial Multiplexing	
		<input type="checkbox"/> Cyclic Delay Diversity (CDD)	
Antenna Type	Integrate antenna		
Antenna Gain			
Antenna Technology	Ant Gain(eth1) (dBi)		
<input checked="" type="checkbox"/> SISO	<input checked="" type="checkbox"/> Ant1	0.5	
	<input type="checkbox"/> Ant2	-	

The radio module (Bluetooth) operating channels are:
 BLE:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464
4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454	-	-
13	2428	27	2456	-	-

The WIFI mode operating channels are:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2412	7	2447
1	2417	8	2452
2	2422	9	2457
3	2427	10	2462
4	2432	-	-
5	2437	-	-
6	2442	-	-

Intended use of the Equipment Under Test (EUT)

The apparatus as supplied for the test is Cync dynamic effect indoor strip which intended for residential use, the product contains electronic circuitry and without earth connection. It contains a Wireless module, so it would be controlled by other Wi-Fi devices through APPs.

Based on customer description, models CSTR16CDID/ENS, CSTR32CDID/ENS are identical except for the length of the LED strip(5m for model CSTR16CDID/ENS, 10m for model CSTR32CDID/ENS).

Hence, model CSTR32CDID/ENS was chosen for full test.

Copy of marking plate:

Refer to document label.

1.2 Test data

Test Location	DEKRA Testing and Certification (Shanghai) Ltd. Guangzhou Branch Block 5, No.3, Qiyun Road, Huangpu District, Guangzhou, Guangdong, China FCC Designation Number: CN1324;
Date of receipt of test item	2024-05-14
Date (s) of performance of tests	2024-05-14 to 2024-05-31
Test sample	Normal sample: CSTR32CDID/ENS (lab no.4918539-1) RF conducted sample: CSTR32CDID/ENS (lab no.4918539-2) RF radiated sample: CSTR32CDID/ENS (lab no.4918539-3)

1.3 The environment(s) in which the EUT is intended to be used

The equipment under test (EUT) is intended to be used in the following environment(s):

<input checked="" type="checkbox"/>	Residential (domestic) environment.
<input checked="" type="checkbox"/>	Commercial and light-industrial environment.
<input type="checkbox"/>	Industrial environment.

2 DESCRIPTION OF TEST SETUP

2.1 Operating mode(s) used for tests

During the tests the following operating mode(s) has(have) been used.

Operating mode	Operating mode description	Used for methods	
		Conducted	Radiated
1	Transmitting at BLE mode	<input checked="" type="checkbox"/>	<input type="checkbox"/>
2	Transmitting at WIFI mode	<input checked="" type="checkbox"/>	<input type="checkbox"/>
3		<input type="checkbox"/>	<input type="checkbox"/>
Supplemental information: ---			

2.2 Support / Auxiliary equipment / unit / software for the EUT

The EUT has been tested with the following auxiliary equipment / unit / software:

Auxiliary equipment / unit / software	Type / Version	Manufacturer	Supplied by
Laptop	Latitude 5488	DELL	DEKRA
AmebaZ2_mptool_1V3 (soft ware)	-	-	Client
Realtek Bluetooth MP Kit Setup Package (soft ware)	-	-	Client
Adaptor Name: CLASS 2 POWER UNIT	XY24SR- 240100VQ-UW	GE Lighting, a Savant Company / XING YUAN ELETRONICS CO.,LTD	Client
Supplemental information: ---			

2.3 Test Configuration / Block diagram used for tests

Refer to Annex 3.

2.4 Measurement procedure

The EUT was controlled by a serial PCB(TUYA) which provided by test lab which connected to laptop through the com port. After connected, run the software “Realtek Bluetooth MP Kit Setup Package” supplied by manufacturer to control the EUT work in required test mode as below table.

RF Mode	Set_channel(MHz)	Set_power in software
BLE_1M	2402	0x2a
	2440	0x2a
	2480	0x2a

The EUT was controlled by a serial PCB(TUYA) which provided by test lab which connected to laptop through the com port. After connected, run the software “AmebaZ2_mptool_1V3” supplied by manufacturer to control the EUT work in required test mode as below table.

RF Mode	Frequency (MHz)	Set_power in software
IEEE 802.11 b/g/n20	2412	100
	2437	100
	2462	100

3 RF EXPOSURE EVALUATION

3.1 Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Power Density: $Pd(W/m^2) = E^2 / 377$

Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

E=Electric Field (V/m)

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

3.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

3.3 Test Result

Test Mode	Frequency Band (MHz)	Conducted RF Power Output (dBm)	Conducted Maximum Power (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit of Power Density S(mW/cm ²)
BLE	2400 ~ 2480	5.9	3.9	0.001	1
2.4GWIFI	2412 ~ 2462	18.66	73.5	0.014	1

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

For example,: EIRP= $P_{out} * G = 3.9$ mW

$$E = 3.9 / (4 * \pi * 20^2) = 0.001 \text{ mW/cm}^2$$

The formula of calculate the simultaneously transmission is

$$\sum (\text{All mode Power Density}) / \text{Limit} \leq 1$$

Calculated:

$$0.001/1 + 0.014/1 = 0.015 \leq 1$$

--- END ---