



FCC RF EXPOSURE REPORT

For

WGZ100 ZigBee to 0-10V Interface

MODEL NUMBER: WGZ100

FCC ID: PUU-WGZ100

REPORT NUMBER: 4788794370.1-4

Prepared for

GE Lighting

1975, Noble Road, East Cleveland, OH, 4412-6300, USA

Prepared by

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch
Building 10, Innovation Technology Park, No. 1, Li Bin Road,
Song Shan Lake Hi-Tech Development Zone, Dongguan, People's Republic of China
Tel: +86 769-22038881
Fax: +86 769 33244054
Website: www.ul.com**



TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	3
2. TEST METHODOLOGY	3
3. FACILITIES AND ACCREDITATION.....	4
4. REQUIREMENT	5



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: GE Lighting
Address: 1975, Noble Road, East Cleveland, OH, 4412-6300, USA

Manufacturer Information

Company Name: LEEDARSON LIGHTING CO., LTD.
Address: Xingtai Industrial Zone, Economic Development Zone, Changtai County, Zhangzhou City, Fujian Province, P.R.China

EUT Information

EUT Name: WGZ100 ZigBee to 0-10V Interface
Model: WGZ100
Brand: /
Sample Received Date: December 7, 2018
Date of Tested: December 10, 2018 ~ December 13, 2018

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47CFR§2.1091	Complies
KDB-447498 D01 V06	

Tested By:

Checked By:

Kebo Zhang
Engineer
Approved By:

Shawn Wen
Laboratory Leader

Stephen Guo
Laboratory Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p>A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p>IC(Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with Industry Canada. The Company Number is 21320.</p> <p>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2 : For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. These measurements below 30MHz had been correlated to measurements performed on an OATS.



4. REQUIREMENT

LIMIT

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/150	30
1500-100,000	--	--	1.0	30

Note 1: f = frequency in MHz, * means Plane-wave equivalent power density

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Note 3: The limit value 1.0mW/cm² is available for this EUT.

MPE CALCULATION METHOD

$$S = PG / (4\pi R^2)$$

where: S = power density (in appropriate units, e.g. mW/ cm²)
P = power input to the antenna (in appropriate units, e.g., mW)
G = power gain of the antenna in the direction of interest relative to an isotropic radiator
R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)



CALCULATED RESULTS

Radio Frequency Radiation Exposure Evaluation

Zigbee (Worst case)						
Operating Mode	Max. Tune up Power		Antenna Gain		Power density	Limit
	(dBm)	(mW)	(dBi)	(num)	(mW/ cm ²)	
Zigbee	20	100	1.95	1.57	0.0312	1

BLE (Worst case)						
Operating Mode	Max. Tune up Power		Antenna Gain		Power density	Limit
	(dBm)	(mW)	(dBi)	(num)	(mW/ cm ²)	
BLE	12	15.84	1.95	1.57	0.0049	1

Note: the calculated distance is 20cm.

END OF REPORT