



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15.247

TEST REPORT

For

JiangSu HuiTong Group Co.,Ltd

24#, 2 block TaoHuawu new district, ZhenJiang City, JiangSu, P.R.C, ZhenJiang, China

FCC ID: PUW-HTMD004A

Report Type: Original Report	Product Type: TL8269 LIGHT MODULE
Test Engineer: <u>Stone Zhang</u>	<i>Stone Zhang</i>
Report Number: <u>RSHA180830006-00A</u>	
Report Date: <u>2018-10-16</u>	
Reviewed By: <u>Oscar Ye</u> RF Leader	<i>Oscar Ye</i>
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	6
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	10
TEST EQUIPMENT LIST	11
FCC §1.1310& §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	12
FCC §15.203 - ANTENNA REQUIREMENT.....	13
APPLICABLE STANDARD	13
ANTENNA CONNECTOR CONSTRUCTION	13
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	14
APPLICABLE STANDARD	14
EUT SETUP	14
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE	14
CORRECTED FACTOR & MARGIN CALCULATION	15
TEST RESULTS SUMMARY	15
TEST DATA	15
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	18
APPLICABLE STANDARD	18
EUT SETUP	18
EMI TEST RECEIVER SETUP.....	19
TEST PROCEDURE	19
CORRECTED AMPLITUDE & MARGIN CALCULATION	19
TEST RESULTS SUMMARY	19
TEST DATA	20
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	28
APPLICABLE STANDARD	28
TEST PROCEDURE	28
TEST DATA	28
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	31
APPLICABLE STANDARD	31

TEST PROCEDURE	31
TEST DATA	31
FCC §15.247(d) – BAND EDGE.....	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST DATA	34
FCC §15.247(e) - POWER SPECTRAL DENSITY	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37
TEST DATA	37

FINAL

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	JiangSu HuiTong Group Co.,Ltd
Tested Model	HTMD-004A
Product Type	TL8269 LIGHT MODULE
Dimension	22 mm(L) × 15 mm(W) × 3.5 mm(H)
Power Supply	DC 3.3V

**All measurement and test data in this report was gathered from production sample serial number: 20180830006. (Assigned by the BACL. The EUT supplied by the applicant was received on 2018-08-30)*

Objective

This report is prepared on behalf of JiangSu HuiTong Group Co.,Ltd in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No related submittal/grant.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB 558074 D01 15.247 Meas Guidance v05.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0℃
Humidity		6%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel list for Zigbee mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
11	2405	19	2445
12	2410	...	...
...	...	...	...
...	...	...	...
...	...	25	2475
18	2440	26	2480

EUT was tested with Channel 11, 18, 25 and 26.

Note: Channel 25 is only tested Band Edge and Maximum Conducted Output Power.

Equipment Modifications


No modification was made to the EUT tested.

EUT Exercise Software

RF test tool: EMI_Test Tool

The worst case was performed as below:

Channel	Power Level
Channel 11	7
Channel 18	7
Channel 25	7
Channel 26	5

Duty Cycle:**Channel 18: 2440MHz**

Channel	Duty Cycle	T(ms)	1/T(kHz)	10log(1/x)
Channel 18	100%	/	/	0

Note: “x” means the Duty Cycle.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	Notebook	GX620	D65874152
DELL	Adapter	LA65NS0-00	DF263
Telink	Burning EVK	TLSR8266	/

External I/O Cable


Cable Description	Length (m)	From Port	To
USB Cable	0.8	Notebook	Burning EVK
Data Cable	0.3	EUT	Burning EVK
Power Cable	1.2	Notebook	Adapter

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions (Below 1GHz):



For Radiated Emissions(Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2017-11-12	2018-11-11
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2016-12-26	2019-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2018-08-15	2019-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2018-08-15	2019-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2018-08-27	2019-08-26
ETS-LINDGREN	Horn Antenna	3115	6229	2016-01-11	2019-01-10
ETS-LINDGREN	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
A.H.Systems, inc	Amplifier	2641-1	466	2018-09-11	2019-09-10
EM Electronics Corporation	Amplifier	EM18G40G	060726	2018-03-22	2019-03-21
MICRO-TRONICS	Band notch Filter	BRM50702	G024	2018-08-05	2019-08-04
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2018-08-15	2019-08-14
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2017-11-12	2018-11-11
Narda	Attenuator/10dB	10dB	010	2018-08-15	2019-08-14
HuiTong	RF Cable	HT0830006	C0830006	Each Time	/
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	834115/007	2017-11-12	2018-11-11
Rohde & Schwarz	LISN	ENV216	3560655016	2017-11-15	2018-11-14
BACL	Auto test Software	BACL-EMC	CE001	/	/
Narda	Attenuator/6dB	10690812-2	26850-6	2018-01-10	2019-01-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2018-08-15	2019-08-14

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310& §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency Range (MHz)	Antenna Gain		Turn-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm²)	MPE Limit (mW/cm²)
		(dBi)	(numeric)	(dBm)	(mW)			
Zigbee	2405~2480	0.00	1.00	7.00	5.01	20	0.001	1.0

Conclusion: The EUT meets exemption requirement - RF exposure evaluation greater than 20cm distance specified in § 2.1091. If the device built into a host as a portable usage, the additional RF exposure evaluation may be required as specified by § 2.1093.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has a PCB antenna and the antenna gain is 0dBi, which was permanently attached, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Corrected Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V)} - \text{Corrected Amplitude (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	48 %
ATM Pressure:	101.2kPa


The testing was performed by Stone Zhang on 2018-10-09.

EUT operation mode: Transmitting in channel 11. (Worst case)

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.265	36.20	QP	9.000	L1	16.03	61.27	25.07	Compliance
0.265	13.70	AV	9.000	L1	16.03	51.27	37.57	Compliance
0.410	29.46	QP	9.000	L1	16.06	57.65	28.19	Compliance
0.410	15.30	AV	9.000	L1	16.06	47.65	32.35	Compliance
1.150	26.35	QP	9.000	L1	15.88	56.00	29.65	Compliance
1.150	19.18	AV	9.000	L1	15.88	46.00	26.82	Compliance
3.400	23.96	QP	9.000	L1	15.85	56.00	32.04	Compliance
3.400	16.02	AV	9.000	L1	15.85	46.00	29.98	Compliance
6.850	24.67	QP	9.000	L1	15.97	60.00	35.33	Compliance
6.850	17.83	AV	9.000	L1	15.97	50.00	32.17	Compliance
21.500	34.73	QP	9.000	L1	16.45	60.00	25.27	Compliance
21.500	26.31	AV	9.000	L1	16.45	50.00	23.69	Compliance

AC 120V/60 Hz, Neutral

Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.230	33.27	QP	9.000	N	16.06	62.45	29.18	Compliance
0.230	11.44	AV	9.000	N	16.06	52.45	41.01	Compliance
0.390	32.03	QP	9.000	N	16.09	58.06	26.03	Compliance
0.390	24.39	AV	9.000	N	16.09	48.06	23.67	Compliance
1.150	26.51	QP	9.000	N	15.94	56.00	29.49	Compliance
1.150	19.24	AV	9.000	N	15.94	46.00	26.76	Compliance
2.800	24.35	QP	9.000	N	15.90	56.00	31.65	Compliance
2.800	15.74	AV	9.000	N	15.90	46.00	30.26	Compliance
6.500	24.44	QP	9.000	N	15.91	60.00	35.56	Compliance
6.500	16.85	AV	9.000	N	15.91	50.00	33.15	Compliance
22.150	32.51	QP	9.000	N	16.19	60.00	27.49	Compliance
22.150	15.43	AV	9.000	N	16.19	50.00	34.57	Compliance

Note:

1) Corrected Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)


2) Margin (dB) = Limit (dBμV) - Corrected Amplitude (dBμV)

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver setup was set with the following configurations:

Frequency Range	RBW	VBW	Detector	Duty Cycle	Measurement method
30 MHz - 1000 MHz	120 kHz	/	QP	/	QP
Above 1GHz	1MHz	3 MHz	PK	/	PK
	1MHz	3 MHz	RMS	≥98%	Ave
	1MHz	1/T	PK	<98%	Ave

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection mode for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V/m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V/m)}$$

Test Results Summary

According to the recorded data in following table, the EUT is compliant with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data**Environmental Conditions**


Temperature:	25 °C
Relative Humidity:	48 %
ATM Pressure:	101.2kPa

The Test was performed by Stone Zhang on 2018-10-12.

EUT operation mode: Transmitting

Spurious Emission Test:**30MHz-1GHz**

(Pre-scan with channel 11, channel 18 and channel 26 of operation in the X,Y and Z axes of orientation, the worst case **channel 11 of operation in X-axis of orientation** was recorded)



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
50.016450	21.58	101.0	V	278.0	-17.5	40.00	18.42
66.650700	22.53	101.0	V	294.0	-17.5	40.00	17.47
99.589700	29.33	101.0	V	242.0	-15.0	43.50	14.17
233.301000	27.93	199.0	H	93.0	-12.2	46.00	18.07
368.338650	23.30	101.0	H	164.0	-8.9	46.00	22.70
530.810650	23.48	101.0	V	242.0	-5.8	46.00	22.52

1GHz-18GHz


(Pre-scan in the X,Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded.)

Note:

1. This test was performed with the 2.4 - 2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) - Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) - Corrected Amplitude (dBμV /m)

Channel 11: 2405MHz


Full Spectrum



Frequency (MHz)	MaxPeak (dBμV /m)	Average (dBμV /m)	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
			Height (cm)	Polar (H/V)				
1595.000000	---	26.46	200.0	V	218.0	-7.2	54.00	27.54
1595.000000	36.56	---	200.0	V	218.0	-7.2	74.00	37.44
3097.800000	---	29.46	100.0	H	348.0	-1.5	54.00	24.54
3097.800000	39.76	---	100.0	H	348.0	-1.5	74.00	34.24
4810.000000	---	37.35	100.0	H	56.0	1.8	54.00	16.65
4810.000000	44.94	---	100.0	H	56.0	1.8	74.00	29.06
7215.000000	---	38.58	200.0	H	334.0	9.2	54.00	15.42
7215.000000	50.25	---	200.0	H	334.0	9.2	74.00	23.75
10571.000000	---	40.47	100.0	V	101.0	12.8	54.00	13.53
10571.000000	51.38	---	100.0	V	101.0	12.8	74.00	22.62
17534.200000	---	47.29	100.0	V	21.0	17.2	54.00	6.71
17534.200000	57.14	---	100.0	V	21.0	17.2	74.00	16.86

Channel 18: 2440MHz


Full Spectrum



Frequency (MHz)	MaxPeak (dBµV /m)	Average (dBµV /m)	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
			Height (cm)	Polar (H/V)				
1268.600000	---	24.15	200.0	V	217.0	-8.9	54.00	29.85
1268.600000	38.24	---	200.0	V	217.0	-8.9	74.00	35.76
3165.800000	---	29.67	100.0	V	153.0	-1.4	54.00	24.33
3165.800000	39.76	---	100.0	V	153.0	-1.4	74.00	34.24
4880.000000	---	36.47	100.0	H	45.0	1.9	54.00	17.53
4880.000000	45.14	---	100.0	H	45.0	1.9	74.00	28.86
7320.000000	---	38.44	150.0	H	143.0	9.3	54.00	15.56
7320.000000	47.90	---	150.0	H	143.0	9.3	74.00	26.10
10407.800000	---	41.05	100.0	V	58.0	12.7	54.00	12.95
10407.800000	52.03	---	100.0	V	58.0	12.7	74.00	21.97
17575.000000	---	46.74	200.0	V	154.0	17.3	54.00	7.26
17575.000000	57.51	---	200.0	V	154.0	17.3	74.00	16.49

Channel 26: 2480MHz

Full Spectrum




Frequency (MHz)	MaxPeak (dBμV /m)	Average (dBμV /m)	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
			Height (cm)	Polar (H/V)				
1595.000000	---	26.23	150.0	V	211.0	-7.2	54.00	27.77
1595.000000	36.21	---	150.0	V	211.0	-7.2	74.00	37.79
3114.800000	---	29.59	200.0	V	131.0	-1.4	54.00	24.41
3114.800000	38.88	---	200.0	V	131.0	-1.4	74.00	35.12
4960.000000	---	35.95	100.0	H	248.0	2.0	54.00	18.05
4960.000000	44.95	---	100.0	H	248.0	2.0	74.00	29.05
7440.000000	---	38.85	150.0	H	74.0	9.6	54.00	15.15
7440.000000	48.50	---	150.0	H	74.0	9.6	74.00	25.50
10367.000000	---	41.30	150.0	H	334.0	12.7	54.00	12.70
10367.000000	51.90	---	150.0	H	334.0	12.7	74.00	22.10
17605.600000	---	47.65	200.0	V	4.0	17.3	54.00	6.35
17605.600000	57.32	---	200.0	V	4.0	17.3	74.00	16.68

18GHz-25GHz


(Pre-scan with channel 11, channel 18 and channel 26 of operation in the X,Y and Z axes of orientation, the worst case channel 11 of operation in X-axis of orientation was recorded)

Horizontal



Date: 12.OCT.2018 18:26:40

Vertical



Date: 12.OCT.2018 18:49:17

Fundamental Test & Restricted Bands Emissions Test:

(Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded.)

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) - Amplifier Factor (dB)


Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)

Margin (dB) = Limit (dBμV/m) - Corrected Amplitude (dBμV /m)


Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
Channel 11: 2405MHz								
2405.000000	101.69	---	150.0	H	66.0	6.1	/	/
2405.000000	---	98.69	150.0	H	66.0	6.1	/	/
2405.000000	99.45	---	200.0	V	284.0	6.1	/	/
2405.000000	---	96.21	200.0	V	284.0	6.1	/	/
2389.742000	49.20	---	100.0	H	351.0	6.0	74.00	24.80
2389.742000	---	38.75	150.0	H	351.0	6.0	54.00	15.25
Channel 18: 2440MHz								
2440.000000	100.64	---	200.0	H	69.0	6.2	/	/
2440.000000	---	97.77	200.0	H	69.0	6.2	/	/
2440.000000	98.57	---	200.0	V	15.0	6.2	/	/
2440.000000	---	95.65	200.0	V	15.0	6.2	/	/
Channel 25: 2475MHz								
2475.000000	101.53	---	150.0	H	351.0	6.3	/	/
2475.000000	---	98.69	150.0	H	351.0	6.3	/	/
2475.000000	99.25	---	150.0	V	104.0	6.3	/	/
2475.000000	---	96.56	150.0	V	104.0	6.3	/	/
2483.500000	54.63	---	150.0	H	178.0	6.3	74.00	19.37
2483.500000	---	49.08	150.0	H	178.0	6.3	54.00	4.92
Channel 26: 2480MHz								
2480.000000	98.71	---	200.0	H	93.0	6.3	/	/
2480.000000	---	95.82	200.0	H	93.0	6.3	/	/
2480.000000	96.58	---	150.0	V	87.0	6.3	/	/
2480.000000	---	93.44	150.0	V	87.0	6.3	/	/
2483.500000	54.40	---	150.0	H	139.0	6.3	74.00	19.60
2483.500000	---	46.91	150.0	H	139.0	6.3	54.00	7.09

Conducted Spurious Emissions at Antenna Port


Channel 11: 2405MHz



Channel 18: 2440MHz



Channel 26: 2480MHz



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	48 %
ATM Pressure:	101.2kPa


The testing was performed by Stone Zhang on 2018-10-12.

Test Result: Pass.


EUT operation mode: Transmitting

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
Channel 11	2405	1.623	≥ 0.5
Channel 18	2440	1.623	≥ 0.5
Channel 26	2480	1.623	≥ 0.5


Channel 11: 2405MHz



Channel 18: 2440MHz



Channel 26: 2480MHz



FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.9.1.1

1. Set the RBW $\geq$ DTS bandwidth.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 3 \times$ RBW
4. Sweep time = auto couple.
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.



Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	48 %
ATM Pressure:	101.2kPa

The testing was performed by Stone Zhang on 2018-10-12.


EUT operation mode: Transmitting

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
Channel 11	2405	6.95	30	Pass
Channel 18	2440	6.60	30	Pass
Channel 25	2475	6.22	30	Pass
Channel 26	2480	3.72	30	Pass


Channel 11: 2405MHz




Channel 18: 2440MHz



Channel 25: 2475MHz



Channel 26: 2480MHz



FCC §15.247(d) – BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2013 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	48 %
ATM Pressure:	101.2kPa

The testing was performed by Stone Zhang on 2018-10-12.


EUT operation mode: Transmitting

Test Result: *Compliance*


Left Side



Right Side for 2475MHz



Right Side for 2480MHz



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.10.2

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	48 %
ATM Pressure:	101.2kPa


The testing was performed by Stone Zhang on 2018-10-12.

EUT operation mode: Transmitting


Test Result: Pass

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
Channel 11	2405	-8.10	≤ 8
Channel 18	2440	-8.50	≤ 8
Channel 26	2480	-8.64	≤ 8


Channel 11: 2405MHz



Channel 18: 2440MHz



Channel 26: 2480MHz



***** END OF REPORT *****