



NVLAP LAB CODE 200707-0



FCC PART 15.235

EMI MEASUREMENT AND TEST REPORT

For

Meisida Electronic Toys Co., Ltd.

Anping Industry Park (Anhai), Fujian, China

FCC ID: PV5MSD09041990

| | |
|--|--|
| Report Type: Original Report | Product Type: CRAZY CRAB R/C CAR |
| Test Engineer: Chris Peng | <i>Chris Peng</i> |
| Report Number: RSZ09061102 | |
| Report Date: 2009-06-30 | |
| Reviewed By: EMC Engineer | <i>Simon Mo</i> |
| Prepared By: | Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 |

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, NIST, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "*" (Rev 2)

TABLE OF CONTENTS

| | |
|--|-----------|
| GENERAL INFORMATION..... | 3 |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) | 3 |
| OBJECTIVE | 3 |
| RELATED SUBMITTAL(S)/GRANT(S)..... | 3 |
| TEST METHODOLOGY | 3 |
| TEST FACILITY | 3 |
| SYSTEM TEST CONFIGURATION..... | 5 |
| JUSTIFICATION | 5 |
| EQUIPMENT MODIFICATIONS | 5 |
| CONFIGURATION OF TEST SETUP | 5 |
| BLOCK DIAGRAM OF TEST SETUP | 5 |
| SUMMARY OF TEST RESULTS | 6 |
| §15.203 - ANTENNA REQUIREMENT..... | 7 |
| STANDARD APPLICABLE | 7 |
| §15.209(A), §15.235(A) & §15.205 - RADIATED EMISSIONS | 8 |
| STANDARD APPLICABLE | 8 |
| MEASUREMENT UNCERTAINTY..... | 8 |
| EUT SETUP | 8 |
| EMI TEST RECEIVER SETUP..... | 9 |
| TEST EQUIPMENT LIST AND DETAILS..... | 9 |
| TEST PROCEDURE | 9 |
| CORRECTED AMPLITUDE & MARGIN CALCULATION | 9 |
| TEST RESULTS SUMMARY | 10 |
| TEST DATA | 10 |
| §15.235(B) - BAND EDGES TESTING | 12 |
| STANDARD APPLICABLE | 12 |
| TEST PROCEDURE | 12 |
| TEST EQUIPMENT LIST AND DETAILS..... | 12 |
| TEST DATA | 12 |

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The *MEISIDA ELECTRONIC TOYS Co., Ltd.*'s product, model number: *MSD0904* (FCC ID: *PV5MSD09041990*) or the "EUT" as referred to in this report is a *CRAZY CRAB R/C CAR*, which measures approximately 32.5cm L x 11.3cm W x 5.0cm H, rated input voltage: DC 9V Battery.

*Note: The fundamental of the EUT was 49.86 MHz

** All measurement and test data in this report was gathered from production sample serial number: 0906047 (Assigned by BACL, Shenzhen). The EUT was received on 2009-06-11.*

Objective

This Type approval report is prepared on behalf of *MEISIDA ELECTRONIC TOYS CO., LTD* in accordance with Part 2, Subpart J, and Part 15, Subparts A, B and C of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules, section 15.203, 15.205, 15.207, 15.209 and 15.235 rules.

Related Submittal(s)/Grant(s)

No Related Submittals.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratory Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratory Corp. (Shenzhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratory Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 21, 2007. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179 and Industrial Canada registration test site No.: 5500A. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



NVLAP LAB CODE 200707-0

The current scope of accreditations can be found at
<http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION


Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

Equipment Modifications


No modifications were made to the unit tested.

Configuration of Test Setup



EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

| FCC Rules | Description of Test | Result |
|-----------------------------------|---------------------|-----------|
| §15.203 | Antenna requirement | Compliant |
| §15.207(a) | Conducted Emissions | N/A * |
| §15.205; §15.209(a) §15.235(a) | Radiated Emissions | Compliant |
| §15.235(b) | Band Edge Testing | Compliant |

Note: * Battery operation.

§15.203 - ANTENNA REQUIREMENT

Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

This product has a permanent antenna, fulfill the requirement of this section.

Result: Compliant.

Please refer to the EUT photos.

§15.209(a), §15.235(a) & §15.205 - RADIATED EMISSIONS

Standard Applicable


CFR47 Part15.205, 15.209, and 15.235

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratory Corp. (Shenzhen) is ± 4.0 dB.

EUT Setup



The radiated emission tests were performed in the chamber B test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC part15.205, 15.209, and 15.235 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 1000 MHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

| <i>Frequency Range</i> | <i>R B/W</i> | <i>Video B/W</i> | <i>IF B/W</i> |
|------------------------|--------------|------------------|---------------|
| 30 – 1000 MHz | 100 kHz | 100 kHz | 120 kHz |

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-------------------|---------|---------------|------------------|----------------------|
| Rohde & Schwarz | EMI Test Receiver | ESCI | 100035 | 2008-11-07 | 2009-11-06 |
| HP | Amplifier | HP8447E | 1937A01046 | 2008-08-02 | 2009-08-02 |
| Sunol Sciences | Broadband Antenna | JB1 | A040904-2 | 2009-05-05 | 2010-05-05 |
| NANYAN | AUDIO GENERATOR | NY2201 | 019596 | 2009-05-05 | 2010-05-05 |

* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All fundamental data was recorded in the Average and Peak detection mode.

All harmonic data was recorded in the Quasi-Peak detection mode.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209 & 15.235, with the worst margin reading of:

11.50 dB at 149.579950 MHz in the Vertical polarization (Transmitting mode).

Test Data

Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 56 % |
| ATM Pressure: | 101.0 kPa |


The testing was performed by Chris Peng on 2009-06-23.

Test Mode: Transmitting (worst case)

Fundamental:

| Freq. (MH) | S.A. Reading (dBμV) | Table Angle Deg | Test Antenna | | Detector (PK//AV) | Ant. Factor (dB/m) | Cable Loss (dB) | Pre- Amp. Gain (dB) | Cord. Amp. (dBμV/m) | FCC Part 15.235/15.209 | | |
|---------------|---------------------------|-----------------------|---------------|----------------|----------------------|--------------------------|-----------------------|------------------------------|---------------------------|------------------------|----------------|---------|
| | | | Height (m) | Polar (H/V) | | | | | | Limit (dBμV/m) | Margin (dB) | Remarks |
| 49.86 | 62.69 | 0 | 1.4 | V | AV | 7.1 | 0.36 | 25.92 | 44.23 | 80 | 35.77 | Fund. |
| 49.86 | 62.39 | 0 | 1.1 | H | AV | 7.1 | 0.36 | 25.92 | 43.93 | 80 | 36.07 | Fund. |
| 49.86 | 76.95 | 0 | 1.4 | V | PK | 7.1 | 0.36 | 25.92 | 58.49 | 100 | 41.51 | Fund. |
| 49.86 | 75.82 | 0 | 1.1 | H | PK | 7.1 | 0.36 | 25.92 | 57.36 | 100 | 42.64 | Fund. |

Test Mode: Transmitting (worst case)



| Frequency (MHz) | Corrected Amplitude (dB μ V/m) | Antenna Height (cm) | Antenna Polarity (H/V) | Turntable Position (deg) | Correction Factor (dB) | FCC Limit (dB μ V/m) | Margin (dB) |
|-----------------|------------------------------------|---------------------|------------------------|--------------------------|------------------------|--------------------------|-------------|
| 149.579950 | 32.0 | 106.0 | V | 249.0 | -18.4 | 43.5 | 11.5 |
| 99.717325 | 31.8 | 108.0 | V | 105.0 | -20.2 | 43.5 | 11.7 |
| 349.023300 | 30.0 | 143.0 | V | 91.0 | -13.2 | 46.0 | 16.0 |
| 199.435225 | 26.5 | 103.0 | V | 249.0 | -16.9 | 43.5 | 17.0 |
| 299.156925 | 28.4 | 186.0 | V | 156.0 | -14.6 | 46.0 | 17.6 |

§15.235(b) - BAND EDGES TESTING

Standard Applicable

The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the unmodulated carrier or to the general limits in §15.209, whichever permits the higher emission levels. The field strength of any emissions removed by more than 10 kHz from the band edges shall not exceed the general radiated emission limits in §15.209. All signals exceeding 20 microvolts/meter at 3 meters shall be reported in the application for certification.

Test Procedure

With the EUT's antenna attached, the EUT's radiated emission power was received by the test antenna which was connected to the test receiver setup with the START and STOP frequencies set to the EUT's operation band.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-------------------|--------|---------------|------------------|----------------------|
| Rohde & Schwarz | EMI Test Receiver | ESCI | 100224 | 2008-11-07 | 2009-11-06 |
| NANYAN | AUDIO GENERATOR | NY2201 | 019596 | 2009-05-05 | 2010-05-05 |

* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

| | |
|--------------------|----------|
| Temperature: | 25 °C |
| Relative Humidity: | 56 % |
| ATM Pressure: | 101.0kPa |


The testing was performed by Chris Peng on 2009-06-15.

Test Mode: Transmitting

Result: Compliant.

Please refer to the plot attached.

Plot of Band Edge



Bandedge

Date: 15.JUN.2009 23:22:03

***** END OF REPORT *****